
pyTelegramBotAPI

Release 4.4.1

coder2020official

Apr 17, 2022

CONTENTS

1	TeleBot	1
1.1	Chats	1
1.2	Some features:	1
1.3	Content	1
2	Indices and tables	133
	Python Module Index	135
	Index	137

TELEBOT

TeleBot is synchronous and asynchronous implementation of [Telegram Bot API](#).

1.1 Chats

English chat: [Private chat](#)

Russian chat: [@pytelegrambotapi_talks_ru](#)

News: [@pyTelegramBotAPI](#)

Pypi: [Pypi](#)

Source: [Github repository](#)

1.2 Some features:

Easy to learn and use.

Easy to understand.

Both sync and async.

Examples on features.

States

And more...

1.3 Content

1.3.1 Installation Guide

Using PIP

```
$ pip install pyTelegramBotAPI
```

Using pipenv

```
$ pipenv install pyTelegramBotAPI
```

By cloning repository

```
$ git clone https://github.com/eternnoir/pyTelegramBotAPI.git
$ cd pyTelegramBotAPI
$ python setup.py install
```

Directly using pip

```
$ pip install git+https://github.com/eternnoir/pyTelegramBotAPI.git
```

It is generally recommended to use the first option.

While the API is production-ready, it is still under development and it has regular updates, do not forget to update it regularly by calling:

```
$ pip install pytelegrambotapi --upgrade
```

1.3.2 Quick start

Synchronous TeleBot

```
#!/usr/bin/python

# This is a simple echo bot using the decorator mechanism.
# It echoes any incoming text messages.

import telebot

API_TOKEN = '<api_token>'

bot = telebot.TeleBot(API_TOKEN)

# Handle '/start' and '/help'
@bot.message_handler(commands=['help', 'start'])
def send_welcome(message):
    bot.reply_to(message, """\
Hi there, I am EchoBot.
I am here to echo your kind words back to you. Just say anything nice and I'll say the
↳ exact same thing to you!\
""")

# Handle all other messages with content_type 'text' (content_types defaults to ['text'])
@bot.message_handler(func=lambda message: True)
```

(continues on next page)

(continued from previous page)

```
def echo_message(message):
    bot.reply_to(message, message.text)

bot.infinity_polling()
```

Asynchronous TeleBot

```
#!/usr/bin/python

# This is a simple echo bot using the decorator mechanism.
# It echoes any incoming text messages.

from telebot.async_telebot import AsyncTeleBot
bot = AsyncTeleBot('TOKEN')

# Handle '/start' and '/help'
@bot.message_handler(commands=['help', 'start'])
async def send_welcome(message):
    await bot.reply_to(message, """\
Hi there, I am EchoBot.
I am here to echo your kind words back to you. Just say anything nice and I'll say the
↪ exact same thing to you!\
""")

# Handle all other messages with content_type 'text' (content_types defaults to ['text'])
@bot.message_handler(func=lambda message: True)
async def echo_message(message):
    await bot.reply_to(message, message.text)

import asyncio
asyncio.run(bot.polling())
```

1.3.3 Types of API

```
class telebot.types.Animation(file_id, file_unique_id, width=None, height=None, duration=None,
                             thumb=None, file_name=None, mime_type=None, file_size=None,
                             **kwargs)
```

Bases: `telebot.types.JsonDeserializable`

classmethod `de_json(json_string)`

Returns an instance of this class from the given json dict or string.

This function must be overridden by subclasses. :return: an instance of this class created from the given json dict or string.

```
class telebot.types.Audio(file_id, file_unique_id, duration, performer=None, title=None, file_name=None,
                           mime_type=None, file_size=None, thumb=None, **kwargs)
    Bases: telebot.types.JsonDeserializable

    classmethod de_json(json_string)
        Returns an instance of this class from the given json dict or string.

        This function must be overridden by subclasses. :return: an instance of this class created from the given
        json dict or string.

class telebot.types.BotCommand(command, description)
    Bases: telebot.types.JsonSerializable, telebot.types.JsonDeserializable

    classmethod de_json(json_string)
        Returns an instance of this class from the given json dict or string.

        This function must be overridden by subclasses. :return: an instance of this class created from the given
        json dict or string.

    to_dict()

    to_json()
        Returns a JSON string representation of this class.

        This function must be overridden by subclasses. :return: a JSON formatted string.

class telebot.types.BotCommandScope(type='default', chat_id=None, user_id=None)
    Bases: abc.ABC, telebot.types.JsonSerializable

    to_json()
        Returns a JSON string representation of this class.

        This function must be overridden by subclasses. :return: a JSON formatted string.

class telebot.types.BotCommandScopeAllChatAdministrators
    Bases: telebot.types.BotCommandScope

class telebot.types.BotCommandScopeAllGroupChats
    Bases: telebot.types.BotCommandScope

class telebot.types.BotCommandScopeAllPrivateChats
    Bases: telebot.types.BotCommandScope

class telebot.types.BotCommandScopeChat(chat_id=None)
    Bases: telebot.types.BotCommandScope

class telebot.types.BotCommandScopeChatAdministrators(chat_id=None)
    Bases: telebot.types.BotCommandScope

class telebot.types.BotCommandScopeChatMember(chat_id=None, user_id=None)
    Bases: telebot.types.BotCommandScope

class telebot.types.BotCommandScopeDefault
    Bases: telebot.types.BotCommandScope

class telebot.types.CallbackQuery(id, from_user, data, chat_instance, message=None,
                                    inline_message_id=None, game_short_name=None, **kwargs)
    Bases: telebot.types.JsonDeserializable
```


classmethod `de_json(json_string)`

Returns an instance of this class from the given json dict or string.

This function must be overridden by subclasses. :return: an instance of this class created from the given json dict or string.

class `telebot.types.Chat(id, type, title=None, username=None, first_name=None, last_name=None, photo=None, bio=None, has_private_forwards=None, description=None, invite_link=None, pinned_message=None, permissions=None, slow_mode_delay=None, message_auto_delete_time=None, has_protected_content=None, sticker_set_name=None, can_set_sticker_set=None, linked_chat_id=None, location=None, **kwargs)`

Bases: `telebot.types.JsonDeserializable`

classmethod `de_json(json_string)`

Returns an instance of this class from the given json dict or string.

This function must be overridden by subclasses. :return: an instance of this class created from the given json dict or string.

class `telebot.types.ChatInviteLink(invite_link, creator, creates_join_request, is_primary, is_revoked, name=None, expire_date=None, member_limit=None, pending_join_request_count=None, **kwargs)`

Bases: `telebot.types.JsonSerializable`, `telebot.types.JsonDeserializable`, `telebot.types.Dictionaryable`

classmethod `de_json(json_string)`

Returns an instance of this class from the given json dict or string.

This function must be overridden by subclasses. :return: an instance of this class created from the given json dict or string.

to_dict()

Returns a DICT with class field values

This function must be overridden by subclasses. :return: a DICT

to_json()

Returns a JSON string representation of this class.

This function must be overridden by subclasses. :return: a JSON formatted string.

class `telebot.types.ChatJoinRequest(chat, from_user, date, bio=None, invite_link=None, **kwargs)`

Bases: `telebot.types.JsonDeserializable`

classmethod `de_json(json_string)`

Returns an instance of this class from the given json dict or string.

This function must be overridden by subclasses. :return: an instance of this class created from the given json dict or string.

class `telebot.types.ChatLocation(location, address, **kwargs)`

Bases: `telebot.types.JsonSerializable`, `telebot.types.JsonDeserializable`, `telebot.types.Dictionaryable`

classmethod `de_json(json_string)`

Returns an instance of this class from the given json dict or string.

This function must be overridden by subclasses. :return: an instance of this class created from the given json dict or string.

to_dict()

Returns a DICT with class field values

This function must be overridden by subclasses. :return: a DICT

to_json()

Returns a JSON string representation of this class.

This function must be overridden by subclasses. :return: a JSON formatted string.

```
class telebot.types.ChatMember(user, status, custom_title=None, is_anonymous=None,  
                                can_be_edited=None, can_post_messages=None,  
                                can_edit_messages=None, can_delete_messages=None,  
                                can_restrict_members=None, can_promote_members=None,  
                                can_change_info=None, can_invite_users=None, can_pin_messages=None,  
                                is_member=None, can_send_messages=None,  
                                can_send_media_messages=None, can_send_polls=None,  
                                can_send_other_messages=None, can_add_web_page_previews=None,  
                                can_manage_chat=None, can_manage_voice_chats=None,  
                                until_date=None, **kwargs)
```

Bases: [telebot.types.JsonDeserializable](#)

classmethod de_json(json_string)

Returns an instance of this class from the given json dict or string.

This function must be overridden by subclasses. :return: an instance of this class created from the given json dict or string.

```
class telebot.types.ChatMemberAdministrator(user, status, custom_title=None, is_anonymous=None,  
                                              can_be_edited=None, can_post_messages=None,  
                                              can_edit_messages=None, can_delete_messages=None,  
                                              can_restrict_members=None,  
                                              can_promote_members=None, can_change_info=None,  
                                              can_invite_users=None, can_pin_messages=None,  
                                              is_member=None, can_send_messages=None,  
                                              can_send_media_messages=None, can_send_polls=None,  
                                              can_send_other_messages=None,  
                                              can_add_web_page_previews=None,  
                                              can_manage_chat=None, can_manage_voice_chats=None,  
                                              until_date=None, **kwargs)
```

Bases: [telebot.types.ChatMember](#)

```
class telebot.types.ChatMemberBanned(user, status, custom_title=None, is_anonymous=None,  
                                       can_be_edited=None, can_post_messages=None,  
                                       can_edit_messages=None, can_delete_messages=None,  
                                       can_restrict_members=None, can_promote_members=None,  
                                       can_change_info=None, can_invite_users=None,  
                                       can_pin_messages=None, is_member=None,  
                                       can_send_messages=None, can_send_media_messages=None,  
                                       can_send_polls=None, can_send_other_messages=None,  
                                       can_add_web_page_previews=None, can_manage_chat=None,  
                                       can_manage_voice_chats=None, until_date=None, **kwargs)
```

Bases: [telebot.types.ChatMember](#)

```
class telebot.types.ChatMemberLeft(user, status, custom_title=None, is_anonymous=None,
    can_be_edited=None, can_post_messages=None,
    can_edit_messages=None, can_delete_messages=None,
    can_restrict_members=None, can_promote_members=None,
    can_change_info=None, can_invite_users=None,
    can_pin_messages=None, is_member=None,
    can_send_messages=None, can_send_media_messages=None,
    can_send_polls=None, can_send_other_messages=None,
    can_add_web_page_previews=None, can_manage_chat=None,
    can_manage_voice_chats=None, until_date=None, **kwargs)
```

Bases: [telebot.types.ChatMember](#)

```
class telebot.types.ChatMemberMember(user, status, custom_title=None, is_anonymous=None,
    can_be_edited=None, can_post_messages=None,
    can_edit_messages=None, can_delete_messages=None,
    can_restrict_members=None, can_promote_members=None,
    can_change_info=None, can_invite_users=None,
    can_pin_messages=None, is_member=None,
    can_send_messages=None, can_send_media_messages=None,
    can_send_polls=None, can_send_other_messages=None,
    can_add_web_page_previews=None, can_manage_chat=None,
    can_manage_voice_chats=None, until_date=None, **kwargs)
```

Bases: [telebot.types.ChatMember](#)

```
class telebot.types.ChatMemberOwner(user, status, custom_title=None, is_anonymous=None,
    can_be_edited=None, can_post_messages=None,
    can_edit_messages=None, can_delete_messages=None,
    can_restrict_members=None, can_promote_members=None,
    can_change_info=None, can_invite_users=None,
    can_pin_messages=None, is_member=None,
    can_send_messages=None, can_send_media_messages=None,
    can_send_polls=None, can_send_other_messages=None,
    can_add_web_page_previews=None, can_manage_chat=None,
    can_manage_voice_chats=None, until_date=None, **kwargs)
```

Bases: [telebot.types.ChatMember](#)

```
class telebot.types.ChatMemberRestricted(user, status, custom_title=None, is_anonymous=None,
    can_be_edited=None, can_post_messages=None,
    can_edit_messages=None, can_delete_messages=None,
    can_restrict_members=None, can_promote_members=None,
    can_change_info=None, can_invite_users=None,
    can_pin_messages=None, is_member=None,
    can_send_messages=None, can_send_media_messages=None,
    can_send_polls=None, can_send_other_messages=None,
    can_add_web_page_previews=None, can_manage_chat=None,
    can_manage_voice_chats=None, until_date=None, **kwargs)
```

Bases: [telebot.types.ChatMember](#)

```
class telebot.types.ChatMemberUpdated(chat, from_user, date, old_chat_member, new_chat_member,
    invite_link=None, **kwargs)
```

Bases: [telebot.types.JsonDeserializable](#)

```
classmethod de_json(json_string)
```

Returns an instance of this class from the given json dict or string.

This function must be overridden by subclasses. :return: an instance of this class created from the given json dict or string.

property difference: Dict[str, List]

Get the difference between *old_chat_member* and *new_chat_member* as a dict in the following format { 'parameter': [old_value, new_value]} E.g { 'status': ['member', 'kicked'], 'until_date': [None, 1625055092]}

```
class telebot.types.ChatPermissions(can_send_messages=None, can_send_media_messages=None,
                                     can_send_polls=None, can_send_other_messages=None,
                                     can_add_web_page_previews=None, can_change_info=None,
                                     can_invite_users=None, can_pin_messages=None, **kwargs)
```

Bases: [telebot.types.JsonDeserializable](#), [telebot.types.JsonSerializable](#), [telebot.types.Dictionaryable](#)

classmethod de_json(json_string)

Returns an instance of this class from the given json dict or string.

This function must be overridden by subclasses. :return: an instance of this class created from the given json dict or string.

to_dict()

Returns a DICT with class field values

This function must be overridden by subclasses. :return: a DICT

to_json()

Returns a JSON string representation of this class.

This function must be overridden by subclasses. :return: a JSON formatted string.

```
class telebot.types.ChatPhoto(small_file_id, small_file_unique_id, big_file_id, big_file_unique_id,
                              **kwargs)
```

Bases: [telebot.types.JsonDeserializable](#)

classmethod de_json(json_string)

Returns an instance of this class from the given json dict or string.

This function must be overridden by subclasses. :return: an instance of this class created from the given json dict or string.

```
class telebot.types.ChosenInlineResult(result_id, from_user, query, location=None,
                                       inline_message_id=None, **kwargs)
```

Bases: [telebot.types.JsonDeserializable](#)

classmethod de_json(json_string)

Returns an instance of this class from the given json dict or string.

This function must be overridden by subclasses. :return: an instance of this class created from the given json dict or string.

```
class telebot.types.Contact(phone_number, first_name, last_name=None, user_id=None, vcard=None,
                            **kwargs)
```

Bases: [telebot.types.JsonDeserializable](#)

classmethod de_json(json_string)

Returns an instance of this class from the given json dict or string.

This function must be overridden by subclasses. :return: an instance of this class created from the given json dict or string.

class telebot.types.Dice(value, emoji, ***kwargs*)

Bases: [telebot.types.JsonSerializable](#), [telebot.types.Dictionaryable](#), [telebot.types.JsonDeserializable](#)

classmethod de_json(json_string)

Returns an instance of this class from the given json dict or string.

This function must be overridden by subclasses. :return: an instance of this class created from the given json dict or string.

to_dict()

Returns a DICT with class field values

This function must be overridden by subclasses. :return: a DICT

to_json()

Returns a JSON string representation of this class.

This function must be overridden by subclasses. :return: a JSON formatted string.

class telebot.types.Dictionaryable

Bases: object

Subclasses of this class are guaranteed to be able to be converted to dictionary. All subclasses of this class must override to_dict.

to_dict()

Returns a DICT with class field values

This function must be overridden by subclasses. :return: a DICT

class telebot.types.Document(file_id, file_unique_id, thumb=None, file_name=None, mime_type=None, file_size=None, ***kwargs*)

Bases: [telebot.types.JsonDeserializable](#)

classmethod de_json(json_string)

Returns an instance of this class from the given json dict or string.

This function must be overridden by subclasses. :return: an instance of this class created from the given json dict or string.

class telebot.types.File(file_id, file_unique_id, file_size, file_path, ***kwargs*)

Bases: [telebot.types.JsonDeserializable](#)

classmethod de_json(json_string)

Returns an instance of this class from the given json dict or string.

This function must be overridden by subclasses. :return: an instance of this class created from the given json dict or string.

class telebot.types.ForceReply(selective: Optional[bool] = None, input_field_placeholder: Optional[str] = None)

Bases: [telebot.types.JsonSerializable](#)

to_json()

Returns a JSON string representation of this class.

This function must be overridden by subclasses. :return: a JSON formatted string.

```
class telebot.types.Game(title, description, photo, text=None, text_entities=None, animation=None,
                        **kwargs)
    Bases: telebot.types.JsonDeserializable
    classmethod de_json(json_string)
        Returns an instance of this class from the given json dict or string.
        This function must be overridden by subclasses. :return: an instance of this class created from the given
        json dict or string.
    classmethod parse_entities(message_entity_array)
    classmethod parse_photo(photo_size_array)

class telebot.types.GameHighScore(position, user, score, **kwargs)
    Bases: telebot.types.JsonDeserializable
    classmethod de_json(json_string)
        Returns an instance of this class from the given json dict or string.
        This function must be overridden by subclasses. :return: an instance of this class created from the given
        json dict or string.

class telebot.types.GroupChat(id, title, **kwargs)
    Bases: telebot.types.JsonDeserializable
    classmethod de_json(json_string)
        Returns an instance of this class from the given json dict or string.
        This function must be overridden by subclasses. :return: an instance of this class created from the given
        json dict or string.

class telebot.types.InlineKeyboardButton(text, url=None, callback_data=None,
                                         switch_inline_query=None,
                                         switch_inline_query_current_chat=None,
                                         callback_game=None, pay=None, login_url=None, **kwargs)
    Bases: telebot.types.Dictionaryable, telebot.types.JsonSerializable, telebot.types.JsonDeserializable
    classmethod de_json(json_string)
        Returns an instance of this class from the given json dict or string.
        This function must be overridden by subclasses. :return: an instance of this class created from the given
        json dict or string.
    to_dict()
        Returns a DICT with class field values
        This function must be overridden by subclasses. :return: a DICT
    to_json()
        Returns a JSON string representation of this class.
        This function must be overridden by subclasses. :return: a JSON formatted string.

class telebot.types.InlineKeyboardMarkup(keyboard=None, row_width=3)
    Bases: telebot.types.Dictionaryable, telebot.types.JsonSerializable, telebot.types.JsonDeserializable
```

add(*args, row_width=None)

This method adds buttons to the keyboard without exceeding row_width.

E.g. `InlineKeyboardMarkup.add("A", "B", "C")` yields the json result: `{keyboard: [[["A"], ["B"], ["C"]]]}` when row_width is set to 1. When row_width is set to 2, the result: `{keyboard: [[["A", "B"], ["C"]]]}` See <https://core.telegram.org/bots/api#inlinekeyboardmarkup>

Parameters

- **args** – Array of `InlineKeyboardButton` to append to the keyboard
- **row_width** – width of row

Returns self, to allow function chaining.

classmethod de_json(json_string)

Returns an instance of this class from the given json dict or string.

This function must be overridden by subclasses. :return: an instance of this class created from the given json dict or string.

max_row_keys = 8

row(*args)

Adds a list of `InlineKeyboardButton` to the keyboard. This method does not consider row_width.

`InlineKeyboardMarkup.row("A").row("B", "C").to_json()` outputs: `{keyboard: [[["A"], ["B", "C"]]]}` See <https://core.telegram.org/bots/api#inlinekeyboardmarkup>

Parameters args – Array of `InlineKeyboardButton` to append to the keyboard

Returns self, to allow function chaining.

to_dict()

Returns a DICT with class field values

This function must be overridden by subclasses. :return: a DICT

to_json()

Converts this object to its json representation following the Telegram API guidelines described here: <https://core.telegram.org/bots/api#inlinekeyboardmarkup> :return:

class telebot.types.InlineQuery(id, from_user, query, offset, chat_type=None, location=None, **kwargs)

Bases: `telebot.types.JsonDeserializable`

classmethod de_json(json_string)

Returns an instance of this class from the given json dict or string.

This function must be overridden by subclasses. :return: an instance of this class created from the given json dict or string.

class telebot.types.InlineQueryResultArticle(id, title, input_message_content, reply_markup=None, url=None, hide_url=None, description=None, thumb_url=None, thumb_width=None, thumb_height=None)

Bases: `telebot.types.InlineQueryResultBase`

to_dict()

Returns a DICT with class field values

This function must be overridden by subclasses. :return: a DICT

```
class telebot.types.InlineQueryResultAudio(id, audio_url, title, caption=None, caption_entities=None,  
                                           parse_mode=None, performer=None,  
                                           audio_duration=None, reply_markup=None,  
                                           input_message_content=None)
```

Bases: [telebot.types.InlineQueryResultBase](#)

```
to_dict()
```

Returns a DICT with class field values

This function must be overridden by subclasses. :return: a DICT

```
class telebot.types.InlineQueryResultBase(type, id, title=None, caption=None,  
                                           input_message_content=None, reply_markup=None,  
                                           caption_entities=None, parse_mode=None)
```

Bases: [abc.ABC](#), [telebot.types.Dictionaryable](#), [telebot.types.JsonSerializable](#)

```
to_dict()
```

Returns a DICT with class field values

This function must be overridden by subclasses. :return: a DICT

```
to_json()
```

Returns a JSON string representation of this class.

This function must be overridden by subclasses. :return: a JSON formatted string.

```
class telebot.types.InlineQueryResultCachedAudio(id, audio_file_id, caption=None,  
                                                  caption_entities=None, parse_mode=None,  
                                                  reply_markup=None,  
                                                  input_message_content=None)
```

Bases: [telebot.types.InlineQueryResultCachedBase](#)

```
class telebot.types.InlineQueryResultCachedBase
```

Bases: [abc.ABC](#), [telebot.types.JsonSerializable](#)

```
to_json()
```

Returns a JSON string representation of this class.

This function must be overridden by subclasses. :return: a JSON formatted string.

```
class telebot.types.InlineQueryResultCachedDocument(id, document_file_id, title, description=None,  
                                                    caption=None, caption_entities=None,  
                                                    parse_mode=None, reply_markup=None,  
                                                    input_message_content=None)
```

Bases: [telebot.types.InlineQueryResultCachedBase](#)

```
class telebot.types.InlineQueryResultCachedGif(id, gif_file_id, title=None, description=None,  
                                                caption=None, caption_entities=None,  
                                                parse_mode=None, reply_markup=None,  
                                                input_message_content=None)
```

Bases: [telebot.types.InlineQueryResultCachedBase](#)

```
class telebot.types.InlineQueryResultCachedMpeg4Gif(id, mpeg4_file_id, title=None,  
                                                    description=None, caption=None,  
                                                    caption_entities=None, parse_mode=None,  
                                                    reply_markup=None,  
                                                    input_message_content=None)
```

Bases: [telebot.types.InlineQueryResultCachedBase](#)


```
class telebot.types.InlineQueryResultCachedPhoto(id, photo_file_id, title=None, description=None,
                                                caption=None, caption_entities=None,
                                                parse_mode=None, reply_markup=None,
                                                input_message_content=None)
```

Bases: [telebot.types.InlineQueryResultCachedBase](#)

```
class telebot.types.InlineQueryResultCachedSticker(id, sticker_file_id, reply_markup=None,
                                                    input_message_content=None)
```

Bases: [telebot.types.InlineQueryResultCachedBase](#)

```
class telebot.types.InlineQueryResultCachedVideo(id, video_file_id, title, description=None,
                                                  caption=None, caption_entities=None,
                                                  parse_mode=None, reply_markup=None,
                                                  input_message_content=None)
```

Bases: [telebot.types.InlineQueryResultCachedBase](#)

```
class telebot.types.InlineQueryResultCachedVoice(id, voice_file_id, title, caption=None,
                                                  caption_entities=None, parse_mode=None,
                                                  reply_markup=None,
                                                  input_message_content=None)
```

Bases: [telebot.types.InlineQueryResultCachedBase](#)

```
class telebot.types.InlineQueryResultContact(id, phone_number, first_name, last_name=None,
                                              vcard=None, reply_markup=None,
                                              input_message_content=None, thumb_url=None,
                                              thumb_width=None, thumb_height=None)
```

Bases: [telebot.types.InlineQueryResultBase](#)

to_dict()

Returns a DICT with class field values

This function must be overridden by subclasses. :return: a DICT

```
class telebot.types.InlineQueryResultDocument(id, title, document_url, mime_type, caption=None,
                                              caption_entities=None, parse_mode=None,
                                              description=None, reply_markup=None,
                                              input_message_content=None, thumb_url=None,
                                              thumb_width=None, thumb_height=None)
```

Bases: [telebot.types.InlineQueryResultBase](#)

to_dict()

Returns a DICT with class field values

This function must be overridden by subclasses. :return: a DICT

```
class telebot.types.InlineQueryResultGame(id, game_short_name, reply_markup=None)
```

Bases: [telebot.types.InlineQueryResultBase](#)

to_dict()

Returns a DICT with class field values

This function must be overridden by subclasses. :return: a DICT

```
class telebot.types.InlineQueryResultGif(id, gif_url, thumb_url, gif_width=None, gif_height=None,
                                          title=None, caption=None, caption_entities=None,
                                          reply_markup=None, input_message_content=None,
                                          gif_duration=None, parse_mode=None,
                                          thumb_mime_type=None)
```

Bases: *telebot.types.InlineQueryResultBase*

to_dict()

Returns a DICT with class field values

This function must be overridden by subclasses. :return: a DICT

```
class telebot.types.InlineQueryResultLocation(id, title, latitude, longitude, horizontal_accuracy,
                                              live_period=None, reply_markup=None,
                                              input_message_content=None, thumb_url=None,
                                              thumb_width=None, thumb_height=None,
                                              heading=None, proximity_alert_radius=None)
```

Bases: *telebot.types.InlineQueryResultBase*

to_dict()

Returns a DICT with class field values

This function must be overridden by subclasses. :return: a DICT

```
class telebot.types.InlineQueryResultMpeg4Gif(id, mpeg4_url, thumb_url, mpeg4_width=None,
                                              mpeg4_height=None, title=None, caption=None,
                                              caption_entities=None, parse_mode=None,
                                              reply_markup=None, input_message_content=None,
                                              mpeg4_duration=None, thumb_mime_type=None)
```

Bases: *telebot.types.InlineQueryResultBase*

to_dict()

Returns a DICT with class field values

This function must be overridden by subclasses. :return: a DICT

```
class telebot.types.InlineQueryResultPhoto(id, photo_url, thumb_url, photo_width=None,
                                              photo_height=None, title=None, description=None,
                                              caption=None, caption_entities=None, parse_mode=None,
                                              reply_markup=None, input_message_content=None)
```

Bases: *telebot.types.InlineQueryResultBase*

to_dict()

Returns a DICT with class field values

This function must be overridden by subclasses. :return: a DICT

```
class telebot.types.InlineQueryResultVenue(id, title, latitude, longitude, address, foursquare_id=None,
                                              foursquare_type=None, reply_markup=None,
                                              input_message_content=None, thumb_url=None,
                                              thumb_width=None, thumb_height=None,
                                              google_place_id=None, google_place_type=None)
```

Bases: *telebot.types.InlineQueryResultBase*

to_dict()

Returns a DICT with class field values

This function must be overridden by subclasses. :return: a DICT

```
class telebot.types.InlineQueryResultVideo(id, video_url, mime_type, thumb_url, title, caption=None,
                                              caption_entities=None, parse_mode=None,
                                              video_width=None, video_height=None,
                                              video_duration=None, description=None,
                                              reply_markup=None, input_message_content=None)
```

Bases: *telebot.types.InlineQueryResultBase*

to_dict()

Returns a DICT with class field values

This function must be overridden by subclasses. :return: a DICT

```
class telebot.types.InlineQueryResultVoice(id, voice_url, title, caption=None, caption_entities=None,
                                           parse_mode=None, voice_duration=None,
                                           reply_markup=None, input_message_content=None)
```

Bases: *telebot.types.InlineQueryResultBase*

to_dict()

Returns a DICT with class field values

This function must be overridden by subclasses. :return: a DICT

```
class telebot.types.InputContactMessageContent(phone_number, first_name, last_name=None,
                                                vcard=None)
```

Bases: *telebot.types.Dictionaryable*

to_dict()

Returns a DICT with class field values

This function must be overridden by subclasses. :return: a DICT

```
class telebot.types.InputInvoiceMessageContent(title, description, payload, provider_token, currency,
                                                prices, max_tip_amount=None,
                                                suggested_tip_amounts=None, provider_data=None,
                                                photo_url=None, photo_size=None,
                                                photo_width=None, photo_height=None,
                                                need_name=None, need_phone_number=None,
                                                need_email=None, need_shipping_address=None,
                                                send_phone_number_to_provider=None,
                                                send_email_to_provider=None, is_flexible=None)
```

Bases: *telebot.types.Dictionaryable*

to_dict()

Returns a DICT with class field values

This function must be overridden by subclasses. :return: a DICT

```
class telebot.types.InputLocationMessageContent(latitude, longitude, horizontal_accuracy=None,
                                                  live_period=None, heading=None,
                                                  proximity_alert_radius=None)
```

Bases: *telebot.types.Dictionaryable*

to_dict()

Returns a DICT with class field values

This function must be overridden by subclasses. :return: a DICT

```
class telebot.types.InputMedia(type, media, caption=None, parse_mode=None, caption_entities=None)
```

Bases: *telebot.types.Dictionaryable*, *telebot.types.JsonSerializable*

convert_input_media()

to_dict()

Returns a DICT with class field values

This function must be overridden by subclasses. :return: a DICT

to_json()

Returns a JSON string representation of this class.

This function must be overridden by subclasses. :return: a JSON formatted string.

class telebot.types.**InputMediaAnimation**(*media, thumb=None, caption=None, parse_mode=None, width=None, height=None, duration=None*)

Bases: [telebot.types.InputMedia](#)

to_dict()

Returns a DICT with class field values

This function must be overridden by subclasses. :return: a DICT

class telebot.types.**InputMediaAudio**(*media, thumb=None, caption=None, parse_mode=None, duration=None, performer=None, title=None*)

Bases: [telebot.types.InputMedia](#)

to_dict()

Returns a DICT with class field values

This function must be overridden by subclasses. :return: a DICT

class telebot.types.**InputMediaDocument**(*media, thumb=None, caption=None, parse_mode=None, disable_content_type_detection=None*)

Bases: [telebot.types.InputMedia](#)

to_dict()

Returns a DICT with class field values

This function must be overridden by subclasses. :return: a DICT

class telebot.types.**InputMediaPhoto**(*media, caption=None, parse_mode=None*)

Bases: [telebot.types.InputMedia](#)

to_dict()

Returns a DICT with class field values

This function must be overridden by subclasses. :return: a DICT

class telebot.types.**InputMediaVideo**(*media, thumb=None, caption=None, parse_mode=None, width=None, height=None, duration=None, supports_streaming=None*)

Bases: [telebot.types.InputMedia](#)

to_dict()

Returns a DICT with class field values

This function must be overridden by subclasses. :return: a DICT

class telebot.types.**InputTextMessageContent**(*message_text, parse_mode=None, entities=None, disable_web_page_preview=None*)

Bases: [telebot.types.Dictionaryable](#)

to_dict()

Returns a DICT with class field values

This function must be overridden by subclasses. :return: a DICT

class telebot.types.**InputVenueMessageContent**(*latitude, longitude, title, address, foursquare_id=None, foursquare_type=None, google_place_id=None, google_place_type=None*)

Bases: [telebot.types.Dictionaryable](#)

to_dict()

Returns a DICT with class field values

This function must be overridden by subclasses. :return: a DICT

class telebot.types.**Invoice**(*title, description, start_parameter, currency, total_amount, **kwargs*)

Bases: [telebot.types.JsonDeserializable](#)

classmethod **de_json**(*json_string*)

Returns an instance of this class from the given json dict or string.

This function must be overridden by subclasses. :return: an instance of this class created from the given json dict or string.

class telebot.types.**JsonDeserializable**

Bases: object

Subclasses of this class are guaranteed to be able to be created from a json-style dict or json formatted string. All subclasses of this class must override `de_json`.

static **check_json**(*json_type, dict_copy=True*)

Checks whether `json_type` is a dict or a string. If it is already a dict, it is returned as-is. If it is not, it is converted to a dict by means of `json.loads(json_type)`

Parameters

- **json_type** – input json or parsed dict
- **dict_copy** – if dict is passed and it is changed outside - should be True!

Returns Dictionary parsed from json or original dict

classmethod **de_json**(*json_string*)

Returns an instance of this class from the given json dict or string.

This function must be overridden by subclasses. :return: an instance of this class created from the given json dict or string.

class telebot.types.**JsonSerializable**

Bases: object

Subclasses of this class are guaranteed to be able to be converted to JSON format. All subclasses of this class must override `to_json`.

to_json()

Returns a JSON string representation of this class.

This function must be overridden by subclasses. :return: a JSON formatted string.

```
class telebot.types.KeyboardButton(text: str, request_contact: Optional[bool] = None, request_location:
    Optional[bool] = None, request_poll:
    Optional[telebot.types.KeyboardButtonPollType] = None)
```

Bases: [telebot.types.Dictionaryable](#), [telebot.types.JsonSerializable](#)

to_dict()

Returns a DICT with class field values

This function must be overridden by subclasses. :return: a DICT

to_json()

Returns a JSON string representation of this class.

This function must be overridden by subclasses. :return: a JSON formatted string.

```
class telebot.types.KeyboardButtonPollType(type="")
```

Bases: [telebot.types.Dictionaryable](#)

to_dict()

Returns a DICT with class field values

This function must be overridden by subclasses. :return: a DICT

```
class telebot.types.LabeledPrice(label, amount)
```

Bases: [telebot.types.JsonSerializable](#)

to_dict()

to_json()

Returns a JSON string representation of this class.

This function must be overridden by subclasses. :return: a JSON formatted string.

```
class telebot.types.Location(longitude, latitude, horizontal_accuracy=None, live_period=None,
    heading=None, proximity_alert_radius=None, **kwargs)
```

Bases: [telebot.types.JsonDeserializable](#), [telebot.types.JsonSerializable](#), [telebot.types.Dictionaryable](#)

classmethod de_json(json_string)

Returns an instance of this class from the given json dict or string.

This function must be overridden by subclasses. :return: an instance of this class created from the given json dict or string.

to_dict()

Returns a DICT with class field values

This function must be overridden by subclasses. :return: a DICT

to_json()

Returns a JSON string representation of this class.

This function must be overridden by subclasses. :return: a JSON formatted string.

```
class telebot.types.LoginUrl(url, forward_text=None, bot_username=None, request_write_access=None,
    **kwargs)
```

Bases: [telebot.types.Dictionaryable](#), [telebot.types.JsonSerializable](#), [telebot.types.JsonDeserializable](#)

classmethod `de_json(json_string)`

Returns an instance of this class from the given json dict or string.

This function must be overridden by subclasses. :return: an instance of this class created from the given json dict or string.

to_dict()

Returns a DICT with class field values

This function must be overridden by subclasses. :return: a DICT

to_json()

Returns a JSON string representation of this class.

This function must be overridden by subclasses. :return: a JSON formatted string.

class `telebot.types.MaskPosition(point, x_shift, y_shift, scale, **kwargs)`

Bases: `telebot.types.Dictionaryable`, `telebot.types.JsonDeserializable`, `telebot.types.JsonSerializable`

classmethod `de_json(json_string)`

Returns an instance of this class from the given json dict or string.

This function must be overridden by subclasses. :return: an instance of this class created from the given json dict or string.

to_dict()

Returns a DICT with class field values

This function must be overridden by subclasses. :return: a DICT

to_json()

Returns a JSON string representation of this class.

This function must be overridden by subclasses. :return: a JSON formatted string.

class `telebot.types.Message(message_id, from_user, date, chat, content_type, options, json_string)`

Bases: `telebot.types.JsonDeserializable`

classmethod `de_json(json_string)`

Returns an instance of this class from the given json dict or string.

This function must be overridden by subclasses. :return: an instance of this class created from the given json dict or string.

property `html_caption`

property `html_text`

classmethod `parse_chat(chat)`

classmethod `parse_entities(message_entity_array)`

classmethod `parse_photo(photo_size_array)`

class `telebot.types.MessageAutoDeleteTimerChanged(message_auto_delete_time, **kwargs)`

Bases: `telebot.types.JsonDeserializable`

classmethod `de_json(json_string)`

Returns an instance of this class from the given json dict or string.

This function must be overridden by subclasses. :return: an instance of this class created from the given json dict or string.

class `telebot.types.MessageEntity`(*type, offset, length, url=None, user=None, language=None, **kwargs*)

Bases: `telebot.types.Dictionaryable`, `telebot.types.JsonSerializable`, `telebot.types.JsonDeserializable`

classmethod `de_json(json_string)`

Returns an instance of this class from the given json dict or string.

This function must be overridden by subclasses. :return: an instance of this class created from the given json dict or string.

to_dict()

Returns a DICT with class field values

This function must be overridden by subclasses. :return: a DICT

to_json()

Returns a JSON string representation of this class.

This function must be overridden by subclasses. :return: a JSON formatted string.

static `to_list_of_dicts(entity_list)` → Optional[List[Dict]]

class `telebot.types.MessageID`(*message_id, **kwargs*)

Bases: `telebot.types.JsonDeserializable`

classmethod `de_json(json_string)`

Returns an instance of this class from the given json dict or string.

This function must be overridden by subclasses. :return: an instance of this class created from the given json dict or string.

class `telebot.types.OrderInfo`(*name=None, phone_number=None, email=None, shipping_address=None, **kwargs*)

Bases: `telebot.types.JsonDeserializable`

classmethod `de_json(json_string)`

Returns an instance of this class from the given json dict or string.

This function must be overridden by subclasses. :return: an instance of this class created from the given json dict or string.

class `telebot.types.PhotoSize`(*file_id, file_unique_id, width, height, file_size=None, **kwargs*)

Bases: `telebot.types.JsonDeserializable`

classmethod `de_json(json_string)`

Returns an instance of this class from the given json dict or string.

This function must be overridden by subclasses. :return: an instance of this class created from the given json dict or string.

class `telebot.types.Poll`(*question, options, poll_id=None, total_voter_count=None, is_closed=None, is_anonymous=None, poll_type=None, allows_multiple_answers=None, correct_option_id=None, explanation=None, explanation_entities=None, open_period=None, close_date=None, **kwargs*)

Bases: `telebot.types.JsonDeserializable`

add(*option*)

classmethod de_json(*json_string*)

Returns an instance of this class from the given json dict or string.

This function must be overridden by subclasses. :return: an instance of this class created from the given json dict or string.

class `telebot.types.PollAnswer`(*poll_id, user, option_ids, **kwargs*)

Bases: `telebot.types.JsonSerializable`, `telebot.types.JsonDeserializable`, `telebot.types.Dictionaryable`

classmethod de_json(*json_string*)

Returns an instance of this class from the given json dict or string.

This function must be overridden by subclasses. :return: an instance of this class created from the given json dict or string.

to_dict()

Returns a DICT with class field values

This function must be overridden by subclasses. :return: a DICT

to_json()

Returns a JSON string representation of this class.

This function must be overridden by subclasses. :return: a JSON formatted string.

class `telebot.types.PollOption`(*text, voter_count=0, **kwargs*)

Bases: `telebot.types.JsonDeserializable`

classmethod de_json(*json_string*)

Returns an instance of this class from the given json dict or string.

This function must be overridden by subclasses. :return: an instance of this class created from the given json dict or string.

class `telebot.types.PreCheckoutQuery`(*id, from_user, currency, total_amount, invoice_payload, shipping_option_id=None, order_info=None, **kwargs*)

Bases: `telebot.types.JsonDeserializable`

classmethod de_json(*json_string*)

Returns an instance of this class from the given json dict or string.

This function must be overridden by subclasses. :return: an instance of this class created from the given json dict or string.

class `telebot.types.ProximityAlertTriggered`(*traveler, watcher, distance, **kwargs*)

Bases: `telebot.types.JsonDeserializable`

classmethod de_json(*json_string*)

Returns an instance of this class from the given json dict or string.

This function must be overridden by subclasses. :return: an instance of this class created from the given json dict or string.

```
class telebot.types.ReplyKeyboardMarkup(resize_keyboard: Optional[bool] = None, one_time_keyboard: Optional[bool] = None, selective: Optional[bool] = None, row_width: int = 3, input_field_placeholder: Optional[str] = None)
```

Bases: [telebot.types.JsonSerializable](#)

```
add(*args, row_width=None)
```

This function adds strings to the keyboard, while not exceeding row_width. E.g. ReplyKeyboardMarkup#add("A", "B", "C") yields the json result {keyboard: [["A"], ["B"], ["C"]]} when row_width is set to 1. When row_width is set to 2, the following is the result of this function: {keyboard: [["A", "B"], ["C"]]} See <https://core.telegram.org/bots/api#replykeyboardmarkup>

Parameters

- **args** – KeyboardButton to append to the keyboard
- **row_width** – width of row

Returns self, to allow function chaining.

```
max_row_keys = 12
```

```
row(*args)
```

Adds a list of KeyboardButton to the keyboard. This function does not consider row_width. ReplyKeyboardMarkup#row("A")#row("B", "C")#to_json() outputs '{keyboard: [["A"], ["B", "C"]]}'. See <https://core.telegram.org/bots/api#replykeyboardmarkup>

Parameters **args** – strings

Returns self, to allow function chaining.

```
to_json()
```

Converts this object to its json representation following the Telegram API guidelines described here: <https://core.telegram.org/bots/api#replykeyboardmarkup> :return:

```
class telebot.types.ReplyKeyboardRemove(selective=None)
```

Bases: [telebot.types.JsonSerializable](#)

```
to_json()
```

Returns a JSON string representation of this class.

This function must be overridden by subclasses. :return: a JSON formatted string.

```
class telebot.types.ShippingAddress(country_code, state, city, street_line1, street_line2, post_code, **kwargs)
```

Bases: [telebot.types.JsonDeserializable](#)

```
classmethod de_json(json_string)
```

Returns an instance of this class from the given json dict or string.

This function must be overridden by subclasses. :return: an instance of this class created from the given json dict or string.

```
class telebot.types.ShippingOption(id, title)
```

Bases: [telebot.types.JsonSerializable](#)

```
add_price(*args)
```

Add LabeledPrice to ShippingOption

Parameters **args** – LabeledPrices

to_json()

Returns a JSON string representation of this class.

This function must be overridden by subclasses. :return: a JSON formatted string.

class telebot.types.**ShippingQuery**(*id, from_user, invoice_payload, shipping_address, **kwargs*)

Bases: [telebot.types.JsonDeserializable](#)

classmethod **de_json**(*json_string*)

Returns an instance of this class from the given json dict or string.

This function must be overridden by subclasses. :return: an instance of this class created from the given json dict or string.

class telebot.types.**Sticker**(*file_id, file_unique_id, width, height, is_animated, is_video, thumb=None, emoji=None, set_name=None, mask_position=None, file_size=None, **kwargs*)

Bases: [telebot.types.JsonDeserializable](#)

classmethod **de_json**(*json_string*)

Returns an instance of this class from the given json dict or string.

This function must be overridden by subclasses. :return: an instance of this class created from the given json dict or string.

class telebot.types.**StickerSet**(*name, title, is_animated, is_video, contains_masks, stickers, thumb=None, **kwargs*)

Bases: [telebot.types.JsonDeserializable](#)

classmethod **de_json**(*json_string*)

Returns an instance of this class from the given json dict or string.

This function must be overridden by subclasses. :return: an instance of this class created from the given json dict or string.

class telebot.types.**SuccessfulPayment**(*currency, total_amount, invoice_payload, shipping_option_id=None, order_info=None, telegram_payment_charge_id=None, provider_payment_charge_id=None, **kwargs*)

Bases: [telebot.types.JsonDeserializable](#)

classmethod **de_json**(*json_string*)

Returns an instance of this class from the given json dict or string.

This function must be overridden by subclasses. :return: an instance of this class created from the given json dict or string.

class telebot.types.**Update**(*update_id, message, edited_message, channel_post, edited_channel_post, inline_query, chosen_inline_result, callback_query, shipping_query, pre_checkout_query, poll, poll_answer, my_chat_member, chat_member, chat_join_request*)

Bases: [telebot.types.JsonDeserializable](#)

classmethod **de_json**(*json_string*)

Returns an instance of this class from the given json dict or string.

This function must be overridden by subclasses. :return: an instance of this class created from the given json dict or string.

```
class telebot.types.User(id, is_bot, first_name, last_name=None, username=None, language_code=None,
                        can_join_groups=None, can_read_all_group_messages=None,
                        supports_inline_queries=None, **kwargs)
```

Bases: [telebot.types.JsonDeserializable](#), [telebot.types.Dictionaryable](#), [telebot.types.JsonSerializable](#)

```
classmethod de_json(json_string)
```

Returns an instance of this class from the given json dict or string.

This function must be overridden by subclasses. :return: an instance of this class created from the given json dict or string.

property full_name

```
to_dict()
```

Returns a DICT with class field values

This function must be overridden by subclasses. :return: a DICT

```
to_json()
```

Returns a JSON string representation of this class.

This function must be overridden by subclasses. :return: a JSON formatted string.

```
class telebot.types.UserProfilePhotos(total_count, photos=None, **kwargs)
```

Bases: [telebot.types.JsonDeserializable](#)

```
classmethod de_json(json_string)
```

Returns an instance of this class from the given json dict or string.

This function must be overridden by subclasses. :return: an instance of this class created from the given json dict or string.

```
class telebot.types.Venue(location, title, address, foursquare_id=None, foursquare_type=None,
                        google_place_id=None, google_place_type=None, **kwargs)
```

Bases: [telebot.types.JsonDeserializable](#)

```
classmethod de_json(json_string)
```

Returns an instance of this class from the given json dict or string.

This function must be overridden by subclasses. :return: an instance of this class created from the given json dict or string.

```
class telebot.types.Video(file_id, file_unique_id, width, height, duration, thumb=None, file_name=None,
                        mime_type=None, file_size=None, **kwargs)
```

Bases: [telebot.types.JsonDeserializable](#)

```
classmethod de_json(json_string)
```

Returns an instance of this class from the given json dict or string.

This function must be overridden by subclasses. :return: an instance of this class created from the given json dict or string.

```
class telebot.types.VideoNote(file_id, file_unique_id, length, duration, thumb=None, file_size=None,
                        **kwargs)
```

Bases: [telebot.types.JsonDeserializable](#)

classmethod `de_json(json_string)`

Returns an instance of this class from the given json dict or string.

This function must be overridden by subclasses. :return: an instance of this class created from the given json dict or string.

class `telebot.types.Voice(file_id, file_unique_id, duration, mime_type=None, file_size=None, **kwargs)`

Bases: `telebot.types.JsonDeserializable`

classmethod `de_json(json_string)`

Returns an instance of this class from the given json dict or string.

This function must be overridden by subclasses. :return: an instance of this class created from the given json dict or string.

class `telebot.types.VoiceChatEnded(duration, **kwargs)`

Bases: `telebot.types.JsonDeserializable`

classmethod `de_json(json_string)`

Returns an instance of this class from the given json dict or string.

This function must be overridden by subclasses. :return: an instance of this class created from the given json dict or string.

class `telebot.types.VoiceChatParticipantsInvited(users=None, **kwargs)`

Bases: `telebot.types.JsonDeserializable`

classmethod `de_json(json_string)`

Returns an instance of this class from the given json dict or string.

This function must be overridden by subclasses. :return: an instance of this class created from the given json dict or string.

class `telebot.types.VoiceChatScheduled(start_date, **kwargs)`

Bases: `telebot.types.JsonDeserializable`

classmethod `de_json(json_string)`

Returns an instance of this class from the given json dict or string.

This function must be overridden by subclasses. :return: an instance of this class created from the given json dict or string.

class `telebot.types.VoiceChatStarted`

Bases: `telebot.types.JsonDeserializable`

classmethod `de_json(json_string)`

Returns an instance of this class from the given json dict or string.

This function must be overridden by subclasses. :return: an instance of this class created from the given json dict or string.

class `telebot.types.WebhookInfo(url, has_custom_certificate, pending_update_count, ip_address=None, last_error_date=None, last_error_message=None, max_connections=None, allowed_updates=None, **kwargs)`

Bases: `telebot.types.JsonDeserializable`

classmethod `de_json(json_string)`

Returns an instance of this class from the given json dict or string.

This function must be overridden by subclasses. :return: an instance of this class created from the given json dict or string.

1.3.4 TeleBot version

TeleBot methods

class telebot.**ExceptionHandler**

Bases: object

Class for handling exceptions while Polling

handle(*exception*)

class telebot.**Handler**(*callback, *args, **kwargs*)

Bases: object

Class for (next step|reply) handlers

telebot.**REPLY_MARKUP_TYPES**

telebot

Type Module

alias of Union[telebot.types.InlineKeyboardMarkup, telebot.types.ReplyKeyboardMarkup, telebot.types.ReplyKeyboardRemove, telebot.types.ForceReply]

class telebot.**TeleBot**(*token, parse_mode=None, threaded=True, skip_pending=False, num_threads=2, next_step_backend=None, reply_backend=None, exception_handler=None, last_update_id=0, suppress_middleware_exceptions=False, state_storage=<telebot.storage.memory_storage.StateMemoryStorage object>, use_class_middlewares=False*)

Bases: object

This is the main synchronous class for Bot.

It allows you to add handlers for different kind of updates.

Usage:

```
from telebot import TeleBot
bot = TeleBot('token') # get token from @BotFather
```

See more examples in examples/ directory: <https://github.com/eternnoir/pyTelegramBotAPI/tree/master/examples>

add_callback_query_handler(*handler_dict*)

Adds a callback request handler Note that you should use register_callback_query_handler to add callback_query_handler to the bot.

Parameters *handler_dict* –

Returns

add_channel_post_handler(*handler_dict*)

Adds channel post handler Note that you should use register_channel_post_handler to add channel_post_handler to the bot.

Parameters *handler_dict* –

Returns

add_chat_join_request_handler(handler_dict)

Adds a chat_join_request handler. Note that you should use register_chat_join_request_handler to add chat_join_request_handler to the bot.

Parameters handler_dict –

Returns

add_chat_member_handler(handler_dict)

Adds a chat_member handler. Note that you should use register_chat_member_handler to add chat_member_handler to the bot.

Parameters handler_dict –

Returns

add_chosen_inline_handler(handler_dict)

Description: TBD Note that you should use register_chosen_inline_handler to add chosen_inline_handler to the bot.

Parameters handler_dict –

Returns

add_custom_filter(custom_filter: Union[telebot.custom_filters.SimpleCustomFilter, telebot.custom_filters.AdvancedCustomFilter])

Create custom filter.

Parameters

- **custom_filter** – Class with check(message) method.
- **custom_filter** – Custom filter class with key.

add_data(user_id: int, chat_id: Optional[int] = None, **kwargs)

Add data to states.

Parameters

- **user_id** –
- **chat_id** –

add_edited_channel_post_handler(handler_dict)

Adds the edit channel post handler Note that you should use register_edited_channel_post_handler to add edited_channel_post_handler to the bot.

Parameters handler_dict –

Returns

add_edited_message_handler(handler_dict)

Adds the edit message handler Note that you should use register_edited_message_handler to add edited_message_handler to the bot.

Parameters handler_dict –

Returns

add_inline_handler(handler_dict)

Adds inline call handler Note that you should use register_inline_handler to add inline_handler to the bot.

Parameters handler_dict –

Returns**add_message_handler**(*handler_dict*)

Adds a message handler Note that you should use `register_message_handler` to add `message_handler` to the bot.

Parameters **handler_dict** –**Returns****add_middleware_handler**(*handler, update_types=None*)

Add middleware handler.

Parameters

- **handler** –
- **update_types** –

Returns**add_my_chat_member_handler**(*handler_dict*)

Adds a `my_chat_member` handler. Note that you should use `register_my_chat_member_handler` to add `my_chat_member_handler` to the bot.

Parameters **handler_dict** –**Returns****add_poll_answer_handler**(*handler_dict*)

Adds a `poll_answer` request handler. Note that you should use `register_poll_answer_handler` to add `poll_answer_handler` to the bot.

Parameters **handler_dict** –**Returns****add_poll_handler**(*handler_dict*)

Adds a poll request handler Note that you should use `register_poll_handler` to add `poll_handler` to the bot.

Parameters **handler_dict** –**Returns****add_pre_checkout_query_handler**(*handler_dict*)

Adds a pre-checkout request handler Note that you should use `register_pre_checkout_query_handler` to add `pre_checkout_query_handler` to the bot.

Parameters **handler_dict** –**Returns****add_shipping_query_handler**(*handler_dict*)

Adds a shipping request handler. Note that you should use `register_shipping_query_handler` to add `shipping_query_handler` to the bot.

Parameters **handler_dict** –**Returns****add_sticker_to_set**(*user_id: int, name: str, emojis: str, png_sticker: Optional[Union[Any, str]] = None, tgs_sticker: Optional[Union[Any, str]] = None, webm_sticker: Optional[Union[Any, str]] = None, mask_position: Optional[telebot.types.MaskPosition] = None*) → bool

Use this method to add a new sticker to a set created by the bot. It's required to pass *png_sticker* or *tgs_sticker*. Returns True on success.

Telegram documentation: <https://core.telegram.org/bots/api#addstickertoset>

Parameters

- **user_id** –
- **name** –
- **emojis** –
- **png_sticker** – Required if *tgs_sticker* is None
- **tgs_sticker** – Required if *png_sticker* is None
- **webm_sticker** –
- **mask_position** –

Returns

answer_callback_query(*callback_query_id: int, text: Optional[str] = None, show_alert: Optional[bool] = None, url: Optional[str] = None, cache_time: Optional[int] = None*) → bool

Use this method to send answers to callback queries sent from inline keyboards. The answer will be displayed to the user as a notification at the top of the chat screen or as an alert.

Telegram documentation: <https://core.telegram.org/bots/api#answercallbackquery>

Parameters

- **callback_query_id** –
- **text** –
- **show_alert** –
- **url** –
- **cache_time** –

Returns

answer_inline_query(*inline_query_id: str, results: List[Any], cache_time: Optional[int] = None, is_personal: Optional[bool] = None, next_offset: Optional[str] = None, switch_pm_text: Optional[str] = None, switch_pm_parameter: Optional[str] = None*) → bool

Use this method to send answers to an inline query. On success, True is returned. No more than 50 results per query are allowed.

Telegram documentation: <https://core.telegram.org/bots/api#answerinlinequery>

Parameters

- **inline_query_id** – Unique identifier for the answered query
- **results** – Array of results for the inline query
- **cache_time** – The maximum amount of time in seconds that the result of the inline query may be cached on the server.
- **is_personal** – Pass True, if results may be cached on the server side only for the user that sent the query.

- **next_offset** – Pass the offset that a client should send in the next query with the same text to receive more results.
- **switch_pm_parameter** – If passed, clients will display a button with specified text that switches the user to a private chat with the bot and sends the bot a start message with the parameter switch_pm_parameter
- **switch_pm_text** – Parameter for the start message sent to the bot when user presses the switch button

Returns True means success.

answer_pre_checkout_query(*pre_checkout_query_id: int, ok: bool, error_message: Optional[str] = None*) → bool

Response to a request for pre-inspection.

Telegram documentation: <https://core.telegram.org/bots/api#answerprecheckoutquery>

Parameters

- **pre_checkout_query_id** –
- **ok** –
- **error_message** –

Returns

answer_shipping_query(*shipping_query_id: str, ok: bool, shipping_options: Optional[List[telebot.types.ShippingOption]] = None, error_message: Optional[str] = None*) → bool

Asks for an answer to a shipping question.

Telegram documentation: <https://core.telegram.org/bots/api#answershippingquery>

Parameters

- **shipping_query_id** –
- **ok** –
- **shipping_options** –
- **error_message** –

Returns

approve_chat_join_request(*chat_id: Union[str, int], user_id: Union[int, str]*) → bool

Use this method to approve a chat join request. The bot must be an administrator in the chat for this to work and must have the can_invite_users administrator right. Returns True on success.

Telegram documentation: <https://core.telegram.org/bots/api#approvechatjoinrequest>

Parameters

- **chat_id** – Unique identifier for the target chat or username of the target supergroup (in the format @supergroupusername)
- **user_id** – Unique identifier of the target user

Returns True on success.

ban_chat_member(*chat_id: Union[int, str], user_id: int, until_date: Optional[Union[int, datetime.datetime]] = None, revoke_messages: Optional[bool] = None*) → bool

Use this method to ban a user in a group, a supergroup or a channel. In the case of supergroups and channels, the user will not be able to return to the chat on their own using invite links, etc., unless unbanned first. Returns True on success.

Telegram documentation: <https://core.telegram.org/bots/api#banchatmember>

Parameters

- **chat_id** – Int or string : Unique identifier for the target group or username of the target supergroup
- **user_id** – Int : Unique identifier of the target user
- **until_date** – Date when the user will be unbanned, unix time. If user is banned for more than 366 days or less than 30 seconds from the current time they are considered to be banned forever
- **revoke_messages** – Bool: Pass True to delete all messages from the chat for the user that is being removed. If False, the user will be able to see messages in the group that were sent before the user was removed. Always True for supergroups and channels.

Returns boolean

ban_chat_sender_chat(*chat_id: Union[int, str], sender_chat_id: Union[int, str]*) → bool

Use this method to ban a channel chat in a supergroup or a channel. The owner of the chat will not be able to send messages and join live streams on behalf of the chat, unless it is unbanned first. The bot must be an administrator in the supergroup or channel for this to work and must have the appropriate administrator rights. Returns True on success.

Telegram documentation: <https://core.telegram.org/bots/api#banchatsenderchat>

Parameters

- **chat_id** – Unique identifier for the target chat or username of the target channel (in the format @channelusername)
- **sender_chat_id** – Unique identifier of the target sender chat

Returns True on success.

callback_query_handler(*func, **kwargs*)

Callback request handler decorator

Parameters

- **func** –
- **kwargs** –

Returns

channel_post_handler(*commands=None, regexp=None, func=None, content_types=None, **kwargs*)

Channel post handler decorator

Parameters

- **commands** –
- **regexp** –
- **func** –
- **content_types** –
- **kwargs** –

Returns**chat_join_request_handler**(*func=None, **kwargs*)

chat_join_request handler

Parameters

- **func** –
- **kwargs** –

Returns**chat_member_handler**(*func=None, **kwargs*)

chat_member handler.

Parameters

- **func** –
- **kwargs** –

Returns**static check_commands_input**(*commands, method_name*)**static check_regex_input**(*regex, method_name*)**chosen_inline_handler**(*func, **kwargs*)

Description: TBD

Parameters

- **func** –
- **kwargs** –

Returns**clear_reply_handlers**(*message: telebot.types.Message*) → None

Clears all callback functions registered by register_for_reply() and register_for_reply_by_message_id().

Parameters **message** – The message for which we want to clear reply handlers**clear_reply_handlers_by_message_id**(*message_id: int*) → None

Clears all callback functions registered by register_for_reply() and register_for_reply_by_message_id().

Parameters **message_id** – The message id for which we want to clear reply handlers**clear_step_handler**(*message: telebot.types.Message*) → None

Clears all callback functions registered by register_next_step_handler().

Parameters **message** – The message for which we want to handle new message after that in same chat.**clear_step_handler_by_chat_id**(*chat_id: Union[int, str]*) → None

Clears all callback functions registered by register_next_step_handler().

Parameters **chat_id** – The chat for which we want to clear next step handlers

close() → bool

Use this method to close the bot instance before moving it from one local server to another. You need to delete the webhook before calling this method to ensure that the bot isn't launched again after server restart. The method will return error 429 in the first 10 minutes after the bot is launched. Returns True on success.

Telegram documentation: <https://core.telegram.org/bots/api#close>

copy_message(*chat_id: Union[int, str], from_chat_id: Union[int, str], message_id: int, caption: Optional[str] = None, parse_mode: Optional[str] = None, caption_entities: Optional[List[telebot.types.MessageEntity]] = None, disable_notification: Optional[bool] = None, protect_content: Optional[bool] = None, reply_to_message_id: Optional[int] = None, allow_sending_without_reply: Optional[bool] = None, reply_markup: Optional[Union[telebot.types.InlineKeyboardMarkup, telebot.types.ReplyKeyboardMarkup, telebot.types.ReplyKeyboardRemove, telebot.types.ForceReply]] = None, timeout: Optional[int] = None*) → int

Use this method to copy messages of any kind.

Telegram documentation: <https://core.telegram.org/bots/api#copymessage>

Parameters

- **chat_id** – which chat to forward
- **from_chat_id** – which chat message from
- **message_id** – message id
- **caption** –
- **parse_mode** –
- **caption_entities** –
- **disable_notification** –
- **protect_content** –
- **reply_to_message_id** –
- **allow_sending_without_reply** –
- **reply_markup** –
- **timeout** –

Returns API reply.

create_chat_invite_link(*chat_id: Union[int, str], name: Optional[str] = None, expire_date: Optional[Union[int, datetime.datetime]] = None, member_limit: Optional[int] = None, creates_join_request: Optional[bool] = None*) → *telebot.types.ChatInviteLink*

Use this method to create an additional invite link for a chat. The bot must be an administrator in the chat for this to work and must have the appropriate admin rights.

Telegram documentation: <https://core.telegram.org/bots/api#createchatinvitelink>

Parameters

- **chat_id** – Id: Unique identifier for the target chat or username of the target channel (in the format @channelusername)
- **name** – Invite link name; 0-32 characters
- **expire_date** – Point in time (Unix timestamp) when the link will expire

- **member_limit** – Maximum number of users that can be members of the chat simultaneously
- **creates_join_request** – True, if users joining the chat via the link need to be approved by chat administrators. If True, member_limit can't be specified

Returns

create_new_sticker_set(*user_id: int, name: str, title: str, emojis: str, png_sticker: Optional[Union[Any, str]] = None, tgs_sticker: Optional[Union[Any, str]] = None, webm_sticker: Optional[Union[Any, str]] = None, contains_masks: Optional[bool] = None, mask_position: Optional[telebot.types.MaskPosition] = None*) → bool

Use this method to create new sticker set owned by a user. The bot will be able to edit the created sticker set. Returns True on success.

Telegram documentation: <https://core.telegram.org/bots/api#createnewstickerset>

Parameters

- **user_id** –
- **name** –
- **title** –
- **emojis** –
- **png_sticker** –
- **tgs_sticker** –
- **webm_sticker** –
- **contains_masks** –
- **mask_position** –

Returns

decline_chat_join_request(*chat_id: Union[str, int], user_id: Union[int, str]*) → bool

Use this method to decline a chat join request. The bot must be an administrator in the chat for this to work and must have the can_invite_users administrator right. Returns True on success.

Telegram documentation: <https://core.telegram.org/bots/api#declinechatjoinrequest>

Parameters

- **chat_id** – Unique identifier for the target chat or username of the target supergroup (in the format @supergroupusername)
- **user_id** – Unique identifier of the target user

Returns True on success.

delete_chat_photo(*chat_id: Union[int, str]*) → bool

Use this method to delete a chat photo. Photos can't be changed for private chats. The bot must be an administrator in the chat for this to work and must have the appropriate admin rights. Returns True on success. Note: In regular groups (non-supergroups), this method will only work if the 'All Members Are Admins' setting is off in the target group.

Telegram documentation: <https://core.telegram.org/bots/api#deletechatphoto>

Parameters **chat_id** – Int or Str: Unique identifier for the target chat or username of the target channel (in the format @channelusername)

delete_chat_sticker_set(*chat_id: Union[int, str]*) → bool

Use this method to delete a group sticker set from a supergroup. The bot must be an administrator in the chat for this to work and must have the appropriate admin rights. Use the field `can_set_sticker_set` optionally returned in `getChat` requests to check if the bot can use this method. Returns True on success.

Telegram documentation: <https://core.telegram.org/bots/api#deletechatstickerset>

Parameters **chat_id** – Unique identifier for the target chat or username of the target supergroup (in the format `@supergroupusername`)

Returns API reply.

delete_message(*chat_id: Union[int, str], message_id: int, timeout: Optional[int] = None*) → bool

Use this method to delete message. Returns True on success.

Telegram documentation: <https://core.telegram.org/bots/api#deletemessage>

Parameters

- **chat_id** – in which chat to delete
- **message_id** – which message to delete
- **timeout** –

Returns API reply.

delete_my_commands(*scope: Optional[telebot.types.BotCommandScope] = None, language_code: Optional[str] = None*) → bool

Use this method to delete the list of the bot's commands for the given scope and user language. After deletion, higher level commands will be shown to affected users. Returns True on success.

Telegram documentation: <https://core.telegram.org/bots/api#deletemycommands>

Parameters

- **scope** – The scope of users for which the commands are relevant. Defaults to `BotCommandScopeDefault`.
- **language_code** – A two-letter ISO 639-1 language code. If empty, commands will be applied to all users from the given scope, for whose language there are no dedicated commands

delete_state(*user_id: int, chat_id: Optional[int] = None*) → None

Delete the current state of a user.

Parameters

- **user_id** –
- **chat_id** –

Returns

delete_sticker_from_set(*sticker: str*) → bool

Use this method to delete a sticker from a set created by the bot. Returns True on success.

Telegram documentation: <https://core.telegram.org/bots/api#deletestickerfromset>

Parameters **sticker** –

Returns

delete_webhook(*drop_pending_updates=None, timeout=None*)

Use this method to remove webhook integration if you decide to switch back to getUpdates.

Telegram documentation: <https://core.telegram.org/bots/api#deletewebhook>

Parameters

- **drop_pending_updates** – Pass True to drop all pending updates
- **timeout** – Integer. Request connection timeout

Returns bool

disable_save_next_step_handlers()

Disable saving next step handlers (by default saving disable)

This function is left to keep backward compatibility whose purpose was to disable file saving capability for handlers. For the same purpose, MemoryHandlerBackend is reassigned as a new next_step_backend backend instead of FileHandlerBackend.

Most probably this function should be deprecated in future major releases

disable_save_reply_handlers()

Disable saving next step handlers (by default saving disable)

This function is left to keep backward compatibility whose purpose was to disable file saving capability for handlers. For the same purpose, MemoryHandlerBackend is reassigned as a new reply_backend backend instead of FileHandlerBackend.

Most probably this function should be deprecated in future major releases

download_file(*file_path: str*) → bytes

edit_chat_invite_link(*chat_id: Union[int, str], invite_link: Optional[str] = None, name: Optional[str] = None, expire_date: Optional[Union[int, datetime.datetime]] = None, member_limit: Optional[int] = None, creates_join_request: Optional[bool] = None*) → *telebot.types.ChatInviteLink*

Use this method to edit a non-primary invite link created by the bot. The bot must be an administrator in the chat for this to work and must have the appropriate admin rights.

Telegram documentation: <https://core.telegram.org/bots/api#editchatinvitelink>

Parameters

- **chat_id** – Id: Unique identifier for the target chat or username of the target channel (in the format @channelusername)
- **name** – Invite link name; 0-32 characters
- **invite_link** – The invite link to edit
- **expire_date** – Point in time (Unix timestamp) when the link will expire
- **member_limit** – Maximum number of users that can be members of the chat simultaneously
- **creates_join_request** – True, if users joining the chat via the link need to be approved by chat administrators. If True, member_limit can't be specified

Returns


```
edit_message_caption(caption: str, chat_id: Optional[Union[int, str]] = None, message_id: Optional[int]
    = None, inline_message_id: Optional[str] = None, parse_mode: Optional[str] =
    None, caption_entities: Optional[List[telebot.types.MessageEntity]] = None,
    reply_markup: Optional[Union[telebot.types.InlineKeyboardMarkup,
    telebot.types.ReplyKeyboardMarkup, telebot.types.ReplyKeyboardRemove,
    telebot.types.ForceReply]] = None) → Union[telebot.types.Message, bool]
```

Use this method to edit captions of messages.

Telegram documentation: <https://core.telegram.org/bots/api#editmessagecaption>

Parameters

- **caption** –
- **chat_id** –
- **message_id** –
- **inline_message_id** –
- **parse_mode** –
- **caption_entities** –
- **reply_markup** –

Returns

```
edit_message_live_location(latitude: float, longitude: float, chat_id: Optional[Union[int, str]] = None,
    message_id: Optional[int] = None, inline_message_id: Optional[str] =
    None, reply_markup:
    Optional[Union[telebot.types.InlineKeyboardMarkup,
    telebot.types.ReplyKeyboardMarkup, telebot.types.ReplyKeyboardRemove,
    telebot.types.ForceReply]] = None, timeout: Optional[int] = None,
    horizontal_accuracy: Optional[float] = None, heading: Optional[int] =
    None, proximity_alert_radius: Optional[int] = None) →
    telebot.types.Message
```

Use this method to edit live location.

Telegram documentation: <https://core.telegram.org/bots/api#editmessagelivelocation>

Parameters

- **latitude** –
- **longitude** –
- **chat_id** –
- **message_id** –
- **reply_markup** –
- **timeout** –
- **inline_message_id** –
- **horizontal_accuracy** –
- **heading** –
- **proximity_alert_radius** –

Returns

```
edit_message_media(media: Any, chat_id: Optional[Union[int, str]] = None, message_id: Optional[int] =  
    None, inline_message_id: Optional[str] = None, reply_markup:  
    Optional[Union[telebot.types.InlineKeyboardMarkup,  
        telebot.types.ReplyKeyboardMarkup, telebot.types.ReplyKeyboardRemove,  
        telebot.types.ForceReply]] = None) → Union[telebot.types.Message, bool]
```

Use this method to edit animation, audio, document, photo, or video messages. If a message is a part of a message album, then it can be edited only to a photo or a video. Otherwise, message type can be changed arbitrarily. When inline message is edited, new file can't be uploaded. Use previously uploaded file via its file_id or specify a URL.

Telegram documentation: <https://core.telegram.org/bots/api#editmessagemedia>

Parameters

- **media** –
- **chat_id** –
- **message_id** –
- **inline_message_id** –
- **reply_markup** –

Returns

```
edit_message_reply_markup(chat_id: Optional[Union[int, str]] = None, message_id: Optional[int] =  
    None, inline_message_id: Optional[str] = None, reply_markup:  
    Optional[Union[telebot.types.InlineKeyboardMarkup,  
        telebot.types.ReplyKeyboardMarkup, telebot.types.ReplyKeyboardRemove,  
        telebot.types.ForceReply]] = None) → Union[telebot.types.Message, bool]
```

Use this method to edit only the reply markup of messages.

Telegram documentation: <https://core.telegram.org/bots/api#editmessagereplymarkup>

Parameters

- **chat_id** –
- **message_id** –
- **inline_message_id** –
- **reply_markup** –

Returns

```
edit_message_text(text: str, chat_id: Optional[Union[int, str]] = None, message_id: Optional[int] =  
    None, inline_message_id: Optional[str] = None, parse_mode: Optional[str] = None,  
    entities: Optional[List[telebot.types.MessageEntity]] = None,  
    disable_web_page_preview: Optional[bool] = None, reply_markup:  
    Optional[Union[telebot.types.InlineKeyboardMarkup,  
        telebot.types.ReplyKeyboardMarkup, telebot.types.ReplyKeyboardRemove,  
        telebot.types.ForceReply]] = None) → Union[telebot.types.Message, bool]
```

Use this method to edit text and game messages.

Telegram documentation: <https://core.telegram.org/bots/api#editmessagetext>

Parameters

- **text** –
- **chat_id** –

- **message_id** –
- **inline_message_id** –
- **parse_mode** –
- **entities** –
- **disable_web_page_preview** –
- **reply_markup** –

Returns

edited_channel_post_handler(*commands=None, regexp=None, func=None, content_types=None, **kwargs*)

Edit channel post handler decorator

Parameters

- **commands** –
- **regexp** –
- **func** –
- **content_types** –
- **kwargs** –

Returns

edited_message_handler(*commands=None, regexp=None, func=None, content_types=None, chat_types=None, **kwargs*)

Edit message handler decorator

Parameters

- **commands** –
- **regexp** –
- **func** –
- **content_types** –
- **chat_types** – list of chat types
- **kwargs** –

Returns

enable_save_next_step_handlers(*delay=120, filename='./handler-saves/step.save'*)

Enable saving next step handlers (by default saving disabled)

This function explicitly assigns `FileHandlerBackend` (instead of `Saver`) just to keep backward compatibility whose purpose was to enable file saving capability for handlers. And the same implementation is now available with `FileHandlerBackend`

Most probably this function should be deprecated in future major releases

Parameters

- **delay** – Delay between changes in handlers and saving
- **filename** – Filename of save file

enable_save_reply_handlers(*delay=120, filename='./handler-saves/reply.save'*)

Enable saving reply handlers (by default saving disable)

This function explicitly assigns FileHandlerBackend (instead of Saver) just to keep backward compatibility whose purpose was to enable file saving capability for handlers. And the same implementation is now available with FileHandlerBackend

Most probably this function should be deprecated in future major releases

Parameters

- **delay** – Delay between changes in handlers and saving
- **filename** – Filename of save file

enable_saving_states(*filename='./state-save/states.pkl'*)

Enable saving states (by default saving disabled)

Parameters filename – Filename of saving file

export_chat_invite_link(*chat_id: Union[int, str]*) → str

Use this method to export an invite link to a supergroup or a channel. The bot must be an administrator in the chat for this to work and must have the appropriate admin rights.

Telegram documentation: <https://core.telegram.org/bots/api#exportchatinviolink>

Parameters chat_id – Id: Unique identifier for the target chat or username of the target channel (in the format @channelusername)

Returns exported invite link as String on success.

forward_message(*chat_id: Union[int, str], from_chat_id: Union[int, str], message_id: int, disable_notification: Optional[bool] = None, protect_content: Optional[bool] = None, timeout: Optional[int] = None*) → *telebot.types.Message*

Use this method to forward messages of any kind.

Telegram documentation: <https://core.telegram.org/bots/api#forwardmessage>

Parameters

- **disable_notification** –
- **chat_id** – which chat to forward
- **from_chat_id** – which chat message from
- **message_id** – message id
- **protect_content** – Protects the contents of the forwarded message from forwarding and saving
- **timeout** –

Returns API reply.

get_chat(*chat_id: Union[int, str]*) → *telebot.types.Chat*

Use this method to get up to date information about the chat (current name of the user for one-on-one conversations, current username of a user, group or channel, etc.). Returns a Chat object on success.

Telegram documentation: <https://core.telegram.org/bots/api#getchat>

Parameters chat_id –

Returns API reply.

get_chat_administrators(*chat_id: Union[int, str]*) → List[*telebot.types.ChatMember*]

Use this method to get a list of administrators in a chat. On success, returns an Array of ChatMember objects that contains information about all chat administrators except other bots.

Telegram documentation: <https://core.telegram.org/bots/api#getchatadministrators>

Parameters **chat_id** – Unique identifier for the target chat or username of the target supergroup or channel (in the format @channelusername)

Returns API reply.

get_chat_member(*chat_id: Union[int, str], user_id: int*) → *telebot.types.ChatMember*

Use this method to get information about a member of a chat. Returns a ChatMember object on success.

Telegram documentation: <https://core.telegram.org/bots/api#getchatmember>

Parameters

- **chat_id** –
- **user_id** –

Returns API reply.

get_chat_member_count(*chat_id: Union[int, str]*) → int

Use this method to get the number of members in a chat. Returns Int on success.

Telegram documentation: <https://core.telegram.org/bots/api#getchatmembercount>

Parameters **chat_id** –

Returns API reply.

get_chat_members_count(*chat_id: Union[int, str]*) → int

This function is deprecated. Use *get_chat_member_count* instead

get_file(*file_id: str*) → *telebot.types.File*

Use this method to get basic info about a file and prepare it for downloading. For the moment, bots can download files of up to 20MB in size. On success, a File object is returned. It is guaranteed that the link will be valid for at least 1 hour. When the link expires, a new one can be requested by calling *get_file* again.

Telegram documentation: <https://core.telegram.org/bots/api#getfile>

Parameters **file_id** – File identifier

get_file_url(*file_id: str*) → str

Get a valid URL for downloading a file.

Parameters **file_id** – File identifier to get download URL for.

get_game_high_scores(*user_id: int, chat_id: Optional[Union[int, str]] = None, message_id: Optional[int] = None, inline_message_id: Optional[str] = None*) → List[*telebot.types.GameHighScore*]

Gets top points and game play.

Telegram documentation: <https://core.telegram.org/bots/api#getgamehighscores>

Parameters

- **user_id** –
- **chat_id** –
- **message_id** –

- **inline_message_id** –

Returns

get_me() → *telebot.types.User*

Returns basic information about the bot in form of a User object.

Telegram documentation: <https://core.telegram.org/bots/api#getme>

get_my_commands(*scope: Optional[telebot.types.BotCommandScope] = None, language_code: Optional[str] = None*) → List[*telebot.types.BotCommand*]

Use this method to get the current list of the bot's commands. Returns List of BotCommand on success.

Telegram documentation: <https://core.telegram.org/bots/api#getmycommands>

Parameters

- **scope** – The scope of users for which the commands are relevant. Defaults to BotCommandScopeDefault.
- **language_code** – A two-letter ISO 639-1 language code. If empty, commands will be applied to all users from the given scope, for whose language there are no dedicated commands

get_state(*user_id: int, chat_id: Optional[int] = None*) → Optional[Union[int, str]]

Get current state of a user.

Parameters

- **user_id** –
- **chat_id** –

Returns state of a user

get_sticker_set(*name: str*) → *telebot.types.StickerSet*

Use this method to get a sticker set. On success, a StickerSet object is returned.

Telegram documentation: <https://core.telegram.org/bots/api#getstickerset>

Parameters **name** –

Returns

get_updates(*offset: Optional[int] = None, limit: Optional[int] = None, timeout: Optional[int] = 20, allowed_updates: Optional[List[str]] = None, long_polling_timeout: int = 20*) → List[*telebot.types.Update*]

Use this method to receive incoming updates using long polling (wiki). An Array of Update objects is returned.

Telegram documentation: <https://core.telegram.org/bots/api#getupdates>

Parameters

- **allowed_updates** – Array of string. List the types of updates you want your bot to receive.
- **offset** – Integer. Identifier of the first update to be returned.
- **limit** – Integer. Limits the number of updates to be retrieved.
- **timeout** – Integer. Request connection timeout
- **long_polling_timeout** – Timeout in seconds for long polling.

Returns array of Updates

get_user_profile_photos(*user_id: int, offset: Optional[int] = None, limit: Optional[int] = None*) → *telebot.types.UserProfilePhotos*

Retrieves the user profile photos of the person with 'user_id'

Telegram documentation: <https://core.telegram.org/bots/api#getuserprofilephotos>

Parameters

- **user_id** – Integer - Unique identifier of the target user
- **offset** –
- **limit** –

Returns API reply.

get_webhook_info(*timeout: Optional[int] = None*)

Use this method to get current webhook status. Requires no parameters. If the bot is using getUpdates, will return an object with the url field empty.

Telegram documentation: <https://core.telegram.org/bots/api#getwebhookinfo>

Parameters **timeout** – Integer. Request connection timeout

Returns On success, returns a WebhookInfo object.

infinity_polling(*timeout: int = 20, skip_pending: bool = False, long_polling_timeout: int = 20, logger_level=40, allowed_updates: Optional[List[str]] = None, *args, **kwargs*)

Wrap polling with infinite loop and exception handling to avoid bot stops polling.

Parameters

- **timeout** – Request connection timeout
- **long_polling_timeout** – Timeout in seconds for long polling (see API docs)
- **skip_pending** – skip old updates
- **logger_level** – Custom logging level for infinity_polling logging. Use logger levels from logging as a value. None/NOTSET = no error logging
- **allowed_updates** – A list of the update types you want your bot to receive. For example, specify ["message", "edited_channel_post", "callback_query"] to only receive updates of these types. See util.update_types for a complete list of available update types. Specify an empty list to receive all update types except chat_member (default). If not specified, the previous setting will be used.

Please note that this parameter doesn't affect updates created before the call to the get_updates, so unwanted updates may be received for a short period of time.

inline_handler(*func, **kwargs*)

Inline call handler decorator

Parameters

- **func** –
- **kwargs** –

Returns

kick_chat_member(*chat_id: Union[int, str], user_id: int, until_date: Optional[Union[int, datetime.datetime]] = None, revoke_messages: Optional[bool] = None*) → bool

This function is deprecated. Use *ban_chat_member* instead

leave_chat(*chat_id: Union[int, str]*) → bool

Use this method for your bot to leave a group, supergroup or channel. Returns True on success.

Telegram documentation: <https://core.telegram.org/bots/api#leavechat>

Parameters **chat_id** –

Returns API reply.

load_next_step_handlers(*filename='./.handler-saves/step.save', del_file_after_loading=True*)

Load next step handlers from save file

This function is left to keep backward compatibility whose purpose was to load handlers from file with the help of FileHandlerBackend and is only recommended to use if next_step_backend was assigned as FileHandlerBackend before entering this function

Most probably this function should be deprecated in future major releases

Parameters

- **filename** – Filename of the file where handlers was saved
- **del_file_after_loading** – Is passed True, after loading save file will be deleted

load_reply_handlers(*filename='./.handler-saves/reply.save', del_file_after_loading=True*)

Load reply handlers from save file

This function is left to keep backward compatibility whose purpose was to load handlers from file with the help of FileHandlerBackend and is only recommended to use if reply_backend was assigned as FileHandlerBackend before entering this function

Most probably this function should be deprecated in future major releases

Parameters

- **filename** – Filename of the file where handlers was saved
- **del_file_after_loading** – Is passed True, after loading save file will be deleted

log_out() → bool

Use this method to log out from the cloud Bot API server before launching the bot locally. You MUST log out the bot before running it locally, otherwise there is no guarantee that the bot will receive updates. After a successful call, you can immediately log in on a local server, but will not be able to log in back to the cloud Bot API server for 10 minutes. Returns True on success.

Telegram documentation: <https://core.telegram.org/bots/api#logout>

message_handler(*commands=None, regexp=None, func=None, content_types=None, chat_types=None, **kwargs*)

Message handler decorator. This decorator can be used to decorate functions that must handle certain types of messages. All message handlers are tested in the order they were added.

Example:

```
bot = TeleBot('TOKEN')

# Handles all messages which text matches regexp.
@bot.message_handler(regexp='someregexp')
def command_help(message):
    bot.send_message(message.chat.id, 'Did someone call for help?')

# Handles messages in private chat
```

(continues on next page)

(continued from previous page)

```

@bot.message_handler(chat_types=['private']) # You can add more chat types
def command_help(message):
    bot.send_message(message.chat.id, 'Private chat detected, sir!')

# Handle all sent documents of type 'text/plain'.
@bot.message_handler(func=lambda message: message.document.mime_type == 'text/
↳ plain',
    content_types=['document'])
def command_handle_document(message):
    bot.send_message(message.chat.id, 'Document received, sir!')

# Handle all other messages.
@bot.message_handler(func=lambda message: True, content_types=['audio', 'photo',
↳ 'voice', 'video', 'document',
    'text', 'location', 'contact', 'sticker'])
def default_command(message):
    bot.send_message(message.chat.id, "This is the default command handler.")

```

Parameters

- **commands** – Optional list of strings (commands to handle).
- **regexp** – Optional regular expression.
- **func** – Optional lambda function. The lambda receives the message to test as the first parameter. It must return True if the command should handle the message.
- **content_types** – Supported message content types. Must be a list. Defaults to ['text'].
- **chat_types** – list of chat types

middleware_handler(update_types=None)

Middleware handler decorator.

This decorator can be used to decorate functions that must be handled as middlewares before entering any other message handlers. But, be careful and check type of the update inside the handler if more than one update_type is given.

Example:

```

bot = TeleBot('TOKEN')

# Print post message text before entering to any post_channel handlers
@bot.middleware_handler(update_types=['channel_post', 'edited_channel_post'])
def print_channel_post_text(bot_instance, channel_post):
    print(channel_post.text)

# Print update id before entering to any handlers
@bot.middleware_handler()
def print_channel_post_text(bot_instance, update):
    print(update.update_id)

```

Parameters **update_types** – Optional list of update types that can be passed into the middleware handler.

my_chat_member_handler(*func=None, **kwargs*)

my_chat_member handler.

Parameters

- **func** –
- **kwargs** –

Returns

pin_chat_message(*chat_id: Union[int, str], message_id: int, disable_notification: Optional[bool] = False*)
→ bool

Use this method to pin a message in a supergroup. The bot must be an administrator in the chat for this to work and must have the appropriate admin rights. Returns True on success.

Telegram documentation: <https://core.telegram.org/bots/api#pinchatmessage>

Parameters

- **chat_id** – Int or Str: Unique identifier for the target chat or username of the target channel (in the format @channelusername)
- **message_id** – Int: Identifier of a message to pin
- **disable_notification** – Bool: Pass True, if it is not necessary to send a notification to all group members about the new pinned message

Returns

poll_answer_handler(*func=None, **kwargs*)

Poll_answer request handler

Parameters

- **func** –
- **kwargs** –

Returns

poll_handler(*func, **kwargs*)

Poll request handler

Parameters

- **func** –
- **kwargs** –

Returns

polling(*non_stop: bool = False, skip_pending=False, interval: int = 0, timeout: int = 20, long_polling_timeout: int = 20, allowed_updates: Optional[List[str]] = None, none_stop: Optional[bool] = None*)

This function creates a new Thread that calls an internal `__retrieve_updates` function. This allows the bot to retrieve Updates automatically and notify listeners and message handlers accordingly.

Warning: Do not call this function more than once!

Always get updates.

Parameters

- **interval** – Delay between two update retrivals

- **non_stop** – Do not stop polling when an ApiException occurs.
- **timeout** – Request connection timeout
- **skip_pending** – skip old updates
- **long_polling_timeout** – Timeout in seconds for long polling (see API docs)
- **allowed_updates** – A list of the update types you want your bot to receive. For example, specify ["message", "edited_channel_post", "callback_query"] to only receive updates of these types. See util.update_types for a complete list of available update types. Specify an empty list to receive all update types except chat_member (default). If not specified, the previous setting will be used.

Please note that this parameter doesn't affect updates created before the call to the get_updates, so unwanted updates may be received for a short period of time.

- **none_stop** – Deprecated, use non_stop. Old typo f***up compatibility

Returns

pre_checkout_query_handler(*func*, ***kwargs*)

Pre-checkout request handler

Parameters

- **func** –
- **kwargs** –

Returns

process_middlewarees(*update*)

process_new_callback_query(*new_callback_querys*)

process_new_channel_posts(*channel_post*)

process_new_chat_join_request(*chat_join_request*)

process_new_chat_member(*chat_members*)

process_new_chosen_inline_query(*new_chosen_inline_querys*)

process_new_edited_channel_posts(*edited_channel_post*)

process_new_edited_messages(*edited_message*)

process_new_inline_query(*new_inline_querys*)

process_new_messages(*new_messages*)

process_new_my_chat_member(*my_chat_members*)

process_new_poll(*polls*)

process_new_poll_answer(*poll_answers*)

process_new_pre_checkout_query(*pre_checkout_querys*)

process_new_shipping_query(*new_shipping_querys*)

process_new_updates(updates)

Processes new updates. Just pass list of subclasses of Update to this method.

Parameters **updates** – List of Update objects

promote_chat_member(chat_id: Union[int, str], user_id: int, can_change_info: Optional[bool] = None, can_post_messages: Optional[bool] = None, can_edit_messages: Optional[bool] = None, can_delete_messages: Optional[bool] = None, can_invite_users: Optional[bool] = None, can_restrict_members: Optional[bool] = None, can_pin_messages: Optional[bool] = None, can_promote_members: Optional[bool] = None, is_anonymous: Optional[bool] = None, can_manage_chat: Optional[bool] = None, can_manage_voice_chats: Optional[bool] = None) → bool

Use this method to promote or demote a user in a supergroup or a channel. The bot must be an administrator in the chat for this to work and must have the appropriate admin rights. Pass False for all boolean parameters to demote a user.

Telegram documentation: <https://core.telegram.org/bots/api#promotechatmember>

Parameters

- **chat_id** – Unique identifier for the target chat or username of the target channel (in the format @channelusername)
- **user_id** – Int : Unique identifier of the target user
- **can_change_info** – Bool: Pass True, if the administrator can change chat title, photo and other settings
- **can_post_messages** – Bool : Pass True, if the administrator can create channel posts, channels only
- **can_edit_messages** – Bool : Pass True, if the administrator can edit messages of other users, channels only
- **can_delete_messages** – Bool : Pass True, if the administrator can delete messages of other users
- **can_invite_users** – Bool : Pass True, if the administrator can invite new users to the chat
- **can_restrict_members** – Bool: Pass True, if the administrator can restrict, ban or unban chat members
- **can_pin_messages** – Bool: Pass True, if the administrator can pin messages, supergroups only
- **can_promote_members** – Bool: Pass True, if the administrator can add new administrators with a subset of his own privileges or demote administrators that he has promoted, directly or indirectly (promoted by administrators that were appointed by him)
- **is_anonymous** – Bool: Pass True, if the administrator's presence in the chat is hidden
- **can_manage_chat** – Bool: Pass True, if the administrator can access the chat event log, chat statistics, message statistics in channels, see channel members, see anonymous administrators in supergroups and ignore slow mode. Implied by any other administrator privilege
- **can_manage_voice_chats** – Bool: Pass True, if the administrator can manage voice chats For now, bots can use this privilege only for passing to other administrators.

Returns True on success.

register_callback_query_handler(*callback, func, pass_bot=False, **kwargs*)

Registers callback query handler.

Parameters

- **callback** – function to be called
- **func** –
- **pass_bot** – Pass TeleBot to handler.

Returns decorated function

register_channel_post_handler(*callback, content_types=None, commands=None, regexp=None, func=None, pass_bot=False, **kwargs*)

Registers channel post message handler.

Parameters

- **callback** – function to be called
- **content_types** – list of content_types
- **commands** – list of commands
- **regexp** –
- **func** –
- **pass_bot** – Pass TeleBot to handler.

Returns decorated function

register_chat_join_request_handler(*callback, func=None, pass_bot=False, **kwargs*)

Registers chat join request handler.

Parameters

- **callback** – function to be called
- **func** –
- **pass_bot** – Pass TeleBot to handler.

Returns decorated function

register_chat_member_handler(*callback, func=None, pass_bot=False, **kwargs*)

Registers chat member handler.

Parameters

- **callback** – function to be called
- **func** –
- **pass_bot** – Pass TeleBot to handler.

Returns decorated function

register_chosen_inline_handler(*callback, func, pass_bot=False, **kwargs*)

Registers chosen inline handler.

Parameters

- **callback** – function to be called
- **func** –

- **pass_bot** – Pass TeleBot to handler.

Returns decorated function

register_edited_channel_post_handler(*callback, content_types=None, commands=None, regexp=None, func=None, pass_bot=False, **kwargs*)

Registers edited channel post message handler.

Parameters

- **callback** – function to be called
- **content_types** – list of content_types
- **commands** – list of commands
- **regexp** –
- **func** –
- **pass_bot** – Pass TeleBot to handler.

Returns decorated function

register_edited_message_handler(*callback, content_types=None, commands=None, regexp=None, func=None, chat_types=None, pass_bot=False, **kwargs*)

Registers edited message handler.

Parameters

- **callback** – function to be called
- **content_types** – list of content_types
- **commands** – list of commands
- **regexp** –
- **func** –
- **chat_types** – True for private chat
- **pass_bot** – Pass TeleBot to handler.

Returns decorated function

register_for_reply(*message: telebot.types.Message, callback: Callable, *args, **kwargs*) → None

Registers a callback function to be notified when a reply to *message* arrives.

Warning: In case *callback* as lambda function, saving reply handlers will not work.

Parameters

- **message** – The message for which we are awaiting a reply.
- **callback** – The callback function to be called when a reply arrives. Must accept one *message* parameter, which will contain the replied message.

register_for_reply_by_message_id(*message_id: int, callback: Callable, *args, **kwargs*) → None

Registers a callback function to be notified when a reply to *message* arrives.

Warning: In case *callback* as lambda function, saving reply handlers will not work.

Parameters

- **message_id** – The id of the message for which we are awaiting a reply.

- **callback** – The callback function to be called when a reply arrives. Must accept one *message* parameter, which will contain the replied message.

register_inline_handler(*callback, func, pass_bot=False, **kwargs*)

Registers inline handler.

Parameters

- **callback** – function to be called
- **func** –
- **pass_bot** – Pass TeleBot to handler.

Returns decorated function

register_message_handler(*callback, content_types=None, commands=None, regexp=None, func=None, chat_types=None, pass_bot=False, **kwargs*)

Registers message handler.

Parameters

- **callback** – function to be called
- **content_types** – list of content_types
- **commands** – list of commands
- **regexp** –
- **func** –
- **chat_types** – True for private chat
- **pass_bot** – Pass TeleBot to handler.

Returns decorated function

register_middleware_handler(*callback, update_types=None*)

Middleware handler decorator.

This function will create a decorator that can be used to decorate functions that must be handled as middlewares before entering any other message handlers. But, be careful and check type of the update inside the handler if more than one update_type is given

Example:

```
bot = TeleBot('TOKEN')
```

```
bot.register_middleware_handler(print_channel_post_text, update_types=['channel_post',
'edited_channel_post'])
```

Parameters

- **callback** –
- **update_types** – Optional list of update types that can be passed into the middleware handler.

register_my_chat_member_handler(*callback, func=None, pass_bot=False, **kwargs*)

Registers my chat member handler.

Parameters

- **callback** – function to be called
- **func** –

- **pass_bot** – Pass TeleBot to handler.

Returns decorated function

register_next_step_handler(*message*: [telebot.types.Message](#), *callback*: *Callable*, **args*, ***kwargs*) → None

Registers a callback function to be notified when new message arrives after *message*.

Warning: In case *callback* as lambda function, saving next step handlers will not work.

Parameters

- **message** – The message for which we want to handle new message in the same chat.
- **callback** – The callback function which next new message arrives.
- **args** – Args to pass in callback func
- **kwargs** – Args to pass in callback func

register_next_step_handler_by_chat_id(*chat_id*: *Union[int, str]*, *callback*: *Callable*, **args*, ***kwargs*) → None

Registers a callback function to be notified when new message arrives after *message*.

Warning: In case *callback* as lambda function, saving next step handlers will not work.

Parameters

- **chat_id** – The chat for which we want to handle new message.
- **callback** – The callback function which next new message arrives.
- **args** – Args to pass in callback func
- **kwargs** – Args to pass in callback func

register_poll_answer_handler(*callback*, *func*, *pass_bot=False*, ***kwargs*)

Registers poll answer handler.

Parameters

- **callback** – function to be called
- **func** –
- **pass_bot** – Pass TeleBot to handler.

Returns decorated function

register_poll_handler(*callback*, *func*, *pass_bot=False*, ***kwargs*)

Registers poll handler.

Parameters

- **callback** – function to be called
- **func** –
- **pass_bot** – Pass TeleBot to handler.

Returns decorated function

register_pre_checkout_query_handler(*callback*, *func*, *pass_bot=False*, ***kwargs*)

Registers pre-checkout request handler.

Parameters

- **callback** – function to be called

- **func** –
- **pass_bot** – Pass TeleBot to handler.

Returns decorated function

register_shipping_query_handler(*callback, func, pass_bot=False, **kwargs*)

Registers shipping query handler.

Parameters

- **callback** – function to be called
- **func** –
- **pass_bot** – Pass TeleBot to handler.

Returns decorated function

remove_webhook()

reply_to(*message: telebot.types.Message, text: str, **kwargs*) → *telebot.types.Message*

Convenience function for *send_message(message.chat.id, text, reply_to_message_id=message.message_id, **kwargs)*

Parameters

- **message** –
- **text** –
- **kwargs** –

Returns

reset_data(*user_id: int, chat_id: Optional[int] = None*)

Reset data for a user in chat.

Parameters

- **user_id** –
- **chat_id** –

restrict_chat_member(*chat_id: Union[int, str], user_id: int, until_date: Optional[Union[int, datetime.datetime]] = None, can_send_messages: Optional[bool] = None, can_send_media_messages: Optional[bool] = None, can_send_polls: Optional[bool] = None, can_send_other_messages: Optional[bool] = None, can_add_web_page_previews: Optional[bool] = None, can_change_info: Optional[bool] = None, can_invite_users: Optional[bool] = None, can_pin_messages: Optional[bool] = None*) → bool

Use this method to restrict a user in a supergroup. The bot must be an administrator in the supergroup for this to work and must have the appropriate admin rights. Pass True for all boolean parameters to lift restrictions from a user.

Telegram documentation: <https://core.telegram.org/bots/api#restrictchatmember>

Parameters

- **chat_id** – Int or String : Unique identifier for the target group or username of the target supergroup or channel (in the format @channelusername)
- **user_id** – Int : Unique identifier of the target user

- **until_date** – Date when restrictions will be lifted for the user, unix time. If user is restricted for more than 366 days or less than 30 seconds from the current time, they are considered to be restricted forever
- **can_send_messages** – Pass True, if the user can send text messages, contacts, locations and venues
- **can_send_media_messages** – Pass True, if the user can send audios, documents, photos, videos, video notes and voice notes, implies can_send_messages
- **can_send_polls** – Pass True, if the user is allowed to send polls, implies can_send_messages
- **can_send_other_messages** – Pass True, if the user can send animations, games, stickers and use inline bots, implies can_send_media_messages
- **can_add_web_page_previews** – Pass True, if the user may add web page previews to their messages, implies can_send_media_messages
- **can_change_info** – Pass True, if the user is allowed to change the chat title, photo and other settings. Ignored in public supergroups
- **can_invite_users** – Pass True, if the user is allowed to invite new users to the chat, implies can_invite_users
- **can_pin_messages** – Pass True, if the user is allowed to pin messages. Ignored in public supergroups

Returns True on success

retrieve_data(*user_id: int, chat_id: Optional[int] = None*) → Optional[Union[int, str]]

revoke_chat_invite_link(*chat_id: Union[int, str], invite_link: str*) → *telebot.types.ChatInviteLink*

Use this method to revoke an invite link created by the bot. Note: If the primary link is revoked, a new link is automatically generated. The bot must be an administrator in the chat for this to work and must have the appropriate admin rights.

Telegram documentation: <https://core.telegram.org/bots/api#revokechatinvitelink>

Parameters

- **chat_id** – Id: Unique identifier for the target chat or username of the target channel (in the format @channelusername)
- **invite_link** – The invite link to revoke

Returns

send_animation(*chat_id: Union[int, str], animation: Union[Any, str], duration: Optional[int] = None, width: Optional[int] = None, height: Optional[int] = None, thumb: Optional[Union[Any, str]] = None, caption: Optional[str] = None, parse_mode: Optional[str] = None, caption_entities: Optional[List[telebot.types.MessageEntity]] = None, disable_notification: Optional[bool] = None, protect_content: Optional[bool] = None, reply_to_message_id: Optional[int] = None, allow_sending_without_reply: Optional[bool] = None, reply_markup: Optional[Union[telebot.types.InlineKeyboardMarkup, telebot.types.ReplyKeyboardMarkup, telebot.types.ReplyKeyboardRemove, telebot.types.ForceReply]] = None, timeout: Optional[int] = None*) → *telebot.types.Message*

Use this method to send animation files (GIF or H.264/MPEG-4 AVC video without sound).

Telegram documentation: <https://core.telegram.org/bots/api#sendanimation>

Parameters

- **chat_id** – Integer : Unique identifier for the message recipient — User or GroupChat id
- **animation** – InputFile or String : Animation to send. You can either pass a file_id as String to resend an animation that is already on the Telegram server
- **duration** – Integer : Duration of sent video in seconds
- **width** – Integer : Video width
- **height** – Integer : Video height
- **thumb** – InputFile or String : Thumbnail of the file sent
- **caption** – String : Animation caption (may also be used when resending animation by file_id).
- **parse_mode** –
- **protect_content** –
- **reply_to_message_id** –
- **reply_markup** –
- **disable_notification** –
- **timeout** –
- **caption_entities** –
- **allow_sending_without_reply** –

Returns

send_audio(*chat_id: Union[int, str], audio: Union[Any, str], caption: Optional[str] = None, duration: Optional[int] = None, performer: Optional[str] = None, title: Optional[str] = None, reply_to_message_id: Optional[int] = None, reply_markup: Optional[Union[telebot.types.InlineKeyboardMarkup, telebot.types.ReplyKeyboardMarkup, telebot.types.ReplyKeyboardRemove, telebot.types.ForceReply]] = None, parse_mode: Optional[str] = None, disable_notification: Optional[bool] = None, timeout: Optional[int] = None, thumb: Optional[Union[Any, str]] = None, caption_entities: Optional[List[telebot.types.MessageEntity]] = None, allow_sending_without_reply: Optional[bool] = None, protect_content: Optional[bool] = None*) → *telebot.types.Message*

Use this method to send audio files, if you want Telegram clients to display them in the music player. Your audio must be in the .mp3 format.

Telegram documentation: <https://core.telegram.org/bots/api#sendaudio>

Parameters

- **chat_id** – Unique identifier for the message recipient
- **audio** – Audio file to send.
- **caption** –
- **duration** – Duration of the audio in seconds
- **performer** – Performer
- **title** – Track name
- **reply_to_message_id** – If the message is a reply, ID of the original message
- **reply_markup** –

- **parse_mode** –
- **disable_notification** –
- **timeout** –
- **thumb** –
- **caption_entities** –
- **allow_sending_without_reply** –
- **protect_content** –

Returns Message

send_chat_action(*chat_id: Union[int, str], action: str, timeout: Optional[int] = None*) → bool

Use this method when you need to tell the user that something is happening on the bot's side. The status is set for 5 seconds or less (when a message arrives from your bot, Telegram clients clear its typing status).

Telegram documentation: <https://core.telegram.org/bots/api#sendchataction>

Parameters

- **chat_id** –
- **action** – One of the following strings: 'typing', 'upload_photo', 'record_video', 'upload_video', 'record_audio', 'upload_audio', 'upload_document', 'find_location', 'record_video_note', 'upload_video_note'.
- **timeout** –

Returns API reply. :type: boolean

send_contact(*chat_id: Union[int, str], phone_number: str, first_name: str, last_name: Optional[str] = None, vcard: Optional[str] = None, disable_notification: Optional[bool] = None, reply_to_message_id: Optional[int] = None, reply_markup: Optional[Union[telebot.types.InlineKeyboardMarkup, telebot.types.ReplyKeyboardMarkup, telebot.types.ReplyKeyboardRemove, telebot.types.ForceReply]] = None, timeout: Optional[int] = None, allow_sending_without_reply: Optional[bool] = None, protect_content: Optional[bool] = None*) → *telebot.types.Message*

Use this method to send phone contacts.

Telegram documentation: <https://core.telegram.org/bots/api#sendcontact>

Parameters

- **chat_id** – Integer or String : Unique identifier for the target chat or username of the target channel
- **phone_number** – String : Contact's phone number
- **first_name** – String : Contact's first name
- **last_name** – String : Contact's last name
- **vcard** – String : Additional data about the contact in the form of a vCard, 0-2048 bytes
- **disable_notification** –
- **reply_to_message_id** –
- **reply_markup** –
- **timeout** –
- **allow_sending_without_reply** –

- **protect_content** –

Returns

send_dice(*chat_id: Union[int, str], emoji: Optional[str] = None, disable_notification: Optional[bool] = None, reply_to_message_id: Optional[int] = None, reply_markup: Optional[Union[telebot.types.InlineKeyboardMarkup, telebot.types.ReplyKeyboardMarkup, telebot.types.ReplyKeyboardRemove, telebot.types.ForceReply]] = None, timeout: Optional[int] = None, allow_sending_without_reply: Optional[bool] = None, protect_content: Optional[bool] = None*) → *telebot.types.Message*

Use this method to send dices.

Telegram documentation: <https://core.telegram.org/bots/api#senddice>

Parameters

- **chat_id** –
- **emoji** –
- **disable_notification** –
- **reply_to_message_id** –
- **reply_markup** –
- **timeout** –
- **allow_sending_without_reply** –
- **protect_content** –

Returns

Message

send_document(*chat_id: Union[int, str], document: Union[Any, str], reply_to_message_id: Optional[int] = None, caption: Optional[str] = None, reply_markup: Optional[Union[telebot.types.InlineKeyboardMarkup, telebot.types.ReplyKeyboardMarkup, telebot.types.ReplyKeyboardRemove, telebot.types.ForceReply]] = None, parse_mode: Optional[str] = None, disable_notification: Optional[bool] = None, timeout: Optional[int] = None, thumb: Optional[Union[Any, str]] = None, caption_entities: Optional[List[telebot.types.MessageEntity]] = None, allow_sending_without_reply: Optional[bool] = None, visible_file_name: Optional[str] = None, disable_content_type_detection: Optional[bool] = None, data: Optional[Union[Any, str]] = None, protect_content: Optional[bool] = None*) → *telebot.types.Message*

Use this method to send general files.

Telegram documentation: <https://core.telegram.org/bots/api#senddocument>

Parameters

- **chat_id** – Unique identifier for the target chat or username of the target channel (in the format @channelusername)
- **document** – (document) File to send. Pass a file_id as String to send a file that exists on the Telegram servers (recommended), pass an HTTP URL as a String for Telegram to get a file from the Internet, or upload a new one using multipart/form-data
- **reply_to_message_id** – If the message is a reply, ID of the original message
- **caption** – Document caption (may also be used when resending documents by file_id), 0-1024 characters after entities parsing
- **reply_markup** –

- **parse_mode** – Mode for parsing entities in the document caption
- **disable_notification** – Sends the message silently. Users will receive a notification with no sound.
- **timeout** –
- **thumb** – InputFile or String : Thumbnail of the file sent; can be ignored if thumbnail generation for the file is supported server-side. The thumbnail should be in JPEG format and less than 200 kB in size. A thumbnail's width and height should not exceed 320. Ignored if the file is not uploaded using multipart/form-data. Thumbnails can't be reused and can be only uploaded as a new file, so you can pass "attach://<file_attach_name>" if the thumbnail was uploaded using multipart/form-data under <file_attach_name>
- **caption_entities** –
- **allow_sending_without_reply** –
- **visible_file_name** – allows to define file name that will be visible in the Telegram instead of original file name
- **disable_content_type_detection** – Disables automatic server-side content type detection for files uploaded using multipart/form-data
- **data** – function typo miss compatibility: do not use it
- **protect_content** –

Returns API reply.

```
send_game(chat_id: Union[int, str], game_short_name: str, disable_notification: Optional[bool] = None,
reply_to_message_id: Optional[int] = None, reply_markup:
Optional[Union[telebot.types.InlineKeyboardMarkup, telebot.types.ReplyKeyboardMarkup,
telebot.types.ReplyKeyboardRemove, telebot.types.ForceReply]] = None, timeout: Optional[int]
= None, allow_sending_without_reply: Optional[bool] = None, protect_content: Optional[bool]
= None) → telebot.types.Message
```

Used to send the game.

Telegram documentation: <https://core.telegram.org/bots/api#sendgame>

Parameters

- **chat_id** –
- **game_short_name** –
- **disable_notification** –
- **reply_to_message_id** –
- **reply_markup** –
- **timeout** –
- **allow_sending_without_reply** –
- **protect_content** –

Returns

```
send_invoice(chat_id: Union[int, str], title: str, description: str, invoice_payload: str, provider_token: str,
currency: str, prices: List[telebot.types.LabeledPrice], start_parameter: Optional[str] =
None, photo_url: Optional[str] = None, photo_size: Optional[int] = None, photo_width:
Optional[int] = None, photo_height: Optional[int] = None, need_name: Optional[bool] =
None, need_phone_number: Optional[bool] = None, need_email: Optional[bool] = None,
need_shipping_address: Optional[bool] = None, send_phone_number_to_provider:
Optional[bool] = None, send_email_to_provider: Optional[bool] = None, is_flexible:
Optional[bool] = None, disable_notification: Optional[bool] = None, reply_to_message_id:
Optional[int] = None, reply_markup: Optional[Union[telebot.types.InlineKeyboardMarkup,
telebot.types.ReplyKeyboardMarkup, telebot.types.ReplyKeyboardRemove,
telebot.types.ForceReply]] = None, provider_data: Optional[str] = None, timeout:
Optional[int] = None, allow_sending_without_reply: Optional[bool] = None,
max_tip_amount: Optional[int] = None, suggested_tip_amounts: Optional[List[int]] = None,
protect_content: Optional[bool] = None) → telebot.types.Message
```

Sends invoice.

Telegram documentation: <https://core.telegram.org/bots/api#sendinvoice>

Parameters

- **chat_id** – Unique identifier for the target private chat
- **title** – Product name
- **description** – Product description
- **invoice_payload** – Bot-defined invoice payload, 1-128 bytes. This will not be displayed to the user, use for your internal processes.
- **provider_token** – Payments provider token, obtained via @Botfather
- **currency** – Three-letter ISO 4217 currency code, see <https://core.telegram.org/bots/payments#supported-currencies>
- **prices** – Price breakdown, a list of components (e.g. product price, tax, discount, delivery cost, delivery tax, bonus, etc.)
- **start_parameter** – Unique deep-linking parameter that can be used to generate this invoice when used as a start parameter
- **photo_url** – URL of the product photo for the invoice. Can be a photo of the goods or a marketing image for a service. People like it better when they see what they are paying for.
- **photo_size** – Photo size
- **photo_width** – Photo width
- **photo_height** – Photo height
- **need_name** – Pass True, if you require the user's full name to complete the order
- **need_phone_number** – Pass True, if you require the user's phone number to complete the order
- **need_email** – Pass True, if you require the user's email to complete the order
- **need_shipping_address** – Pass True, if you require the user's shipping address to complete the order
- **is_flexible** – Pass True, if the final price depends on the shipping method
- **send_phone_number_to_provider** – Pass True, if user's phone number should be sent to provider

- **send_email_to_provider** – Pass True, if user’s email address should be sent to provider
- **disable_notification** – Sends the message silently. Users will receive a notification with no sound.
- **reply_to_message_id** – If the message is a reply, ID of the original message
- **reply_markup** – A JSON-serialized object for an inline keyboard. If empty, one ‘Pay total price’ button will be shown. If not empty, the first button must be a Pay button
- **provider_data** – A JSON-serialized data about the invoice, which will be shared with the payment provider. A detailed description of required fields should be provided by the payment provider.
- **timeout** –
- **allow_sending_without_reply** –
- **max_tip_amount** – The maximum accepted amount for tips in the smallest units of the currency
- **suggested_tip_amounts** – A JSON-serialized array of suggested amounts of tips in the smallest units of the currency. At most 4 suggested tip amounts can be specified. The suggested tip amounts must be positive, passed in a strictly increased order and must not exceed max_tip_amount.
- **protect_content** –

Returns

send_location(*chat_id: Union[int, str], latitude: float, longitude: float, live_period: Optional[int] = None, reply_to_message_id: Optional[int] = None, reply_markup: Optional[Union[telebot.types.InlineKeyboardMarkup, telebot.types.ReplyKeyboardMarkup, telebot.types.ReplyKeyboardRemove, telebot.types.ForceReply]] = None, disable_notification: Optional[bool] = None, timeout: Optional[int] = None, horizontal_accuracy: Optional[float] = None, heading: Optional[int] = None, proximity_alert_radius: Optional[int] = None, allow_sending_without_reply: Optional[bool] = None, protect_content: Optional[bool] = None*) → *telebot.types.Message*

Use this method to send point on the map.

Telegram documentation: <https://core.telegram.org/bots/api#sendlocation>

Parameters

- **chat_id** –
- **latitude** –
- **longitude** –
- **live_period** –
- **reply_to_message_id** –
- **reply_markup** –
- **disable_notification** –
- **timeout** –
- **horizontal_accuracy** –
- **heading** –
- **proximity_alert_radius** –

- **allow_sending_without_reply** –
- **protect_content** –

Returns API reply.

send_media_group(*chat_id: Union[int, str], media: List[Union[telebot.types.InputMediaAudio, telebot.types.InputMediaDocument, telebot.types.InputMediaPhoto, telebot.types.InputMediaVideo]], disable_notification: Optional[bool] = None, protect_content: Optional[bool] = None, reply_to_message_id: Optional[int] = None, timeout: Optional[int] = None, allow_sending_without_reply: Optional[bool] = None*) → List[*telebot.types.Message*]

Send a group of photos or videos as an album. On success, an array of the sent Messages is returned.

Telegram documentation: <https://core.telegram.org/bots/api#sendmediagroup>

Parameters

- **chat_id** –
- **media** –
- **disable_notification** –
- **protect_content** –
- **reply_to_message_id** –
- **timeout** –
- **allow_sending_without_reply** –

Returns

send_message(*chat_id: Union[int, str], text: str, parse_mode: Optional[str] = None, entities: Optional[List[telebot.types.MessageEntity]] = None, disable_web_page_preview: Optional[bool] = None, disable_notification: Optional[bool] = None, protect_content: Optional[bool] = None, reply_to_message_id: Optional[int] = None, allow_sending_without_reply: Optional[bool] = None, reply_markup: Optional[Union[telebot.types.InlineKeyboardMarkup, telebot.types.ReplyKeyboardMarkup, telebot.types.ReplyKeyboardRemove, telebot.types.ForceReply]] = None, timeout: Optional[int] = None*) → *telebot.types.Message*

Use this method to send text messages.

Warning: Do not send more than about 4000 characters each message, otherwise you'll risk an HTTP 414 error. If you must send more than 4000 characters, use the *split_string* or *smart_split* function in *util.py*.

Telegram documentation: <https://core.telegram.org/bots/api#sendmessage>

Parameters

- **chat_id** – Unique identifier for the target chat or username of the target channel (in the format @channelusername)
- **text** – Text of the message to be sent
- **parse_mode** – Send Markdown or HTML, if you want Telegram apps to show bold, italic, fixed-width text or inline URLs in your bot's message.
- **entities** – List of special entities that appear in message text, which can be specified instead of *parse_mode*
- **disable_web_page_preview** – Disables link previews for links in this message

- **disable_notification** – Sends the message silently. Users will receive a notification with no sound.
- **protect_content** – If True, the message content will be hidden for all users except for the target user
- **reply_to_message_id** – If the message is a reply, ID of the original message
- **allow_sending_without_reply** – Pass True, if the message should be sent even if the specified replied-to message is not found
- **reply_markup** – Additional interface options. A JSON-serialized object for an inline keyboard, custom reply keyboard, instructions to remove reply keyboard or to force a reply from the user.
- **timeout** –

Returns API reply.

send_photo(*chat_id: Union[int, str], photo: Union[Any, str], caption: Optional[str] = None, parse_mode: Optional[str] = None, caption_entities: Optional[List[telebot.types.MessageEntity]] = None, disable_notification: Optional[bool] = None, protect_content: Optional[bool] = None, reply_to_message_id: Optional[int] = None, allow_sending_without_reply: Optional[bool] = None, reply_markup: Optional[Union[telebot.types.InlineKeyboardMarkup, telebot.types.ReplyKeyboardMarkup, telebot.types.ReplyKeyboardRemove, telebot.types.ForceReply]] = None, timeout: Optional[int] = None*) → *telebot.types.Message*

Use this method to send photos. On success, the sent Message is returned.

Telegram documentation: <https://core.telegram.org/bots/api#sendphoto>

Parameters

- **chat_id** –
- **photo** –
- **caption** –
- **parse_mode** –
- **caption_entities** –
- **disable_notification** –
- **protect_content** –
- **reply_to_message_id** –
- **allow_sending_without_reply** –
- **reply_markup** –
- **timeout** –

Returns Message

```
send_poll(chat_id: Union[int, str], question: str, options: List[str], is_anonymous: Optional[bool] = None,
           type: Optional[str] = None, allows_multiple_answers: Optional[bool] = None,
           correct_option_id: Optional[int] = None, explanation: Optional[str] = None,
           explanation_parse_mode: Optional[str] = None, open_period: Optional[int] = None,
           close_date: Optional[Union[int, datetime.datetime]] = None, is_closed: Optional[bool] = None,
           disable_notification: Optional[bool] = False, reply_to_message_id: Optional[int] = None,
           reply_markup: Optional[Union[telebot.types.InlineKeyboardMarkup,
           telebot.types.ReplyKeyboardMarkup, telebot.types.ReplyKeyboardRemove,
           telebot.types.ForceReply]] = None, allow_sending_without_reply: Optional[bool] = None,
           timeout: Optional[int] = None, explanation_entities:
           Optional[List[telebot.types.MessageEntity]] = None, protect_content: Optional[bool] = None)
           → telebot.types.Message
```

Sends a poll.

Telegram documentation: <https://core.telegram.org/bots/api#sendpoll>

Parameters

- **chat_id** –
- **question** –
- **options** – array of str with answers
- **is_anonymous** –
- **type** –
- **allows_multiple_answers** –
- **correct_option_id** –
- **explanation** –
- **explanation_parse_mode** –
- **open_period** –
- **close_date** –
- **is_closed** –
- **disable_notification** –
- **reply_to_message_id** –
- **allow_sending_without_reply** –
- **reply_markup** –
- **timeout** –
- **explanation_entities** –
- **protect_content** –

Returns

```
send_sticker(chat_id: Union[int, str], sticker: Union[Any, str], reply_to_message_id: Optional[int] =
              None, reply_markup: Optional[Union[telebot.types.InlineKeyboardMarkup,
              telebot.types.ReplyKeyboardMarkup, telebot.types.ReplyKeyboardRemove,
              telebot.types.ForceReply]] = None, disable_notification: Optional[bool] = None, timeout:
              Optional[int] = None, allow_sending_without_reply: Optional[bool] = None,
              protect_content: Optional[bool] = None, data: Optional[Union[Any, str]] = None) →
              telebot.types.Message
```

Use this method to send .webp stickers.

Telegram documentation: <https://core.telegram.org/bots/api#sendsticker>

Parameters

- **chat_id** –
- **sticker** –
- **data** –
- **reply_to_message_id** –
- **reply_markup** –
- **disable_notification** – to disable the notification
- **timeout** – timeout
- **allow_sending_without_reply** –
- **protect_content** –
- **data** – function typo miss compatibility: do not use it

Returns API reply.

send_venue(*chat_id: Union[int, str], latitude: float, longitude: float, title: str, address: str, foursquare_id: Optional[str] = None, foursquare_type: Optional[str] = None, disable_notification: Optional[bool] = None, reply_to_message_id: Optional[int] = None, reply_markup: Optional[Union[telebot.types.InlineKeyboardMarkup, telebot.types.ReplyKeyboardMarkup, telebot.types.ReplyKeyboardRemove, telebot.types.ForceReply]] = None, timeout: Optional[int] = None, allow_sending_without_reply: Optional[bool] = None, google_place_id: Optional[str] = None, google_place_type: Optional[str] = None, protect_content: Optional[bool] = None*) → *telebot.types.Message*

Use this method to send information about a venue.

Telegram documentation: <https://core.telegram.org/bots/api#sendvenue>

Parameters

- **chat_id** – Integer or String : Unique identifier for the target chat or username of the target channel
- **latitude** – Float : Latitude of the venue
- **longitude** – Float : Longitude of the venue
- **title** – String : Name of the venue
- **address** – String : Address of the venue
- **foursquare_id** – String : Foursquare identifier of the venue
- **foursquare_type** – Foursquare type of the venue, if known. (For example, “arts_entertainment/default”, “arts_entertainment/aquarium” or “food/icecream”.)
- **disable_notification** –
- **reply_to_message_id** –
- **reply_markup** –
- **timeout** –
- **allow_sending_without_reply** –

- **google_place_id** –
- **google_place_type** –
- **protect_content** –

Returns

send_video(*chat_id: Union[int, str], video: Union[Any, str], duration: Optional[int] = None, width: Optional[int] = None, height: Optional[int] = None, thumb: Optional[Union[Any, str]] = None, caption: Optional[str] = None, parse_mode: Optional[str] = None, caption_entities: Optional[List[telebot.types.MessageEntity]] = None, supports_streaming: Optional[bool] = None, disable_notification: Optional[bool] = None, protect_content: Optional[bool] = None, reply_to_message_id: Optional[int] = None, allow_sending_without_reply: Optional[bool] = None, reply_markup: Optional[Union[telebot.types.InlineKeyboardMarkup, telebot.types.ReplyKeyboardMarkup, telebot.types.ReplyKeyboardRemove, telebot.types.ForceReply]] = None, timeout: Optional[int] = None, data: Optional[Union[Any, str]] = None*) → *telebot.types.Message*

Use this method to send video files, Telegram clients support mp4 videos (other formats may be sent as Document).

Telegram documentation: <https://core.telegram.org/bots/api#sendvideo>

Parameters

- **chat_id** – Unique identifier for the target chat or username of the target channel (in the format @channelusername)
- **video** – Video to send. You can either pass a file_id as String to resend a video that is already on the Telegram servers, or upload a new video file using multipart/form-data.
- **duration** – Duration of sent video in seconds
- **width** – Video width
- **height** – Video height
- **thumb** – Thumbnail of the file sent; can be ignored if thumbnail generation for the file is supported server-side. The thumbnail should be in JPEG format and less than 200 kB in size. A thumbnail's width and height should not exceed 320. Ignored if the file is not uploaded using multipart/form-data. Thumbnails can't be reused and can be only uploaded as a new file, so you can pass "attach://<file_attach_name>" if the thumbnail was uploaded using multipart/form-data under <file_attach_name>.
- **caption** – Video caption (may also be used when resending videos by file_id), 0-1024 characters after entities parsing
- **parse_mode** – Mode for parsing entities in the video caption
- **caption_entities** –
- **supports_streaming** – Pass True, if the uploaded video is suitable for streaming
- **disable_notification** – Sends the message silently. Users will receive a notification with no sound.
- **protect_content** –
- **reply_to_message_id** – If the message is a reply, ID of the original message
- **allow_sending_without_reply** –
- **reply_markup** –
- **timeout** –

- **data** – function typo miss compatibility: do not use it

send_video_note(*chat_id: Union[int, str], data: Union[Any, str], duration: Optional[int] = None, length: Optional[int] = None, reply_to_message_id: Optional[int] = None, reply_markup: Optional[Union[telebot.types.InlineKeyboardMarkup, telebot.types.ReplyKeyboardMarkup, telebot.types.ReplyKeyboardRemove, telebot.types.ForceReply]] = None, disable_notification: Optional[bool] = None, timeout: Optional[int] = None, thumb: Optional[Union[Any, str]] = None, allow_sending_without_reply: Optional[bool] = None, protect_content: Optional[bool] = None*) → *telebot.types.Message*

As of v.4.0, Telegram clients support rounded square mp4 videos of up to 1 minute long. Use this method to send video messages.

Telegram documentation: <https://core.telegram.org/bots/api#sendvideonote>

Parameters

- **chat_id** – Integer : Unique identifier for the message recipient — User or GroupChat id
- **data** – InputFile or String : Video note to send. You can either pass a file_id as String to resend a video that is already on the Telegram server
- **duration** – Integer : Duration of sent video in seconds
- **length** – Integer : Video width and height, Can't be None and should be in range of (0, 640)
- **reply_to_message_id** –
- **reply_markup** –
- **disable_notification** –
- **timeout** –
- **thumb** – InputFile or String : Thumbnail of the file sent
- **allow_sending_without_reply** –
- **protect_content** –

Returns

send_voice(*chat_id: Union[int, str], voice: Union[Any, str], caption: Optional[str] = None, duration: Optional[int] = None, reply_to_message_id: Optional[int] = None, reply_markup: Optional[Union[telebot.types.InlineKeyboardMarkup, telebot.types.ReplyKeyboardMarkup, telebot.types.ReplyKeyboardRemove, telebot.types.ForceReply]] = None, parse_mode: Optional[str] = None, disable_notification: Optional[bool] = None, timeout: Optional[int] = None, caption_entities: Optional[List[telebot.types.MessageEntity]] = None, allow_sending_without_reply: Optional[bool] = None, protect_content: Optional[bool] = None*) → *telebot.types.Message*

Use this method to send audio files, if you want Telegram clients to display the file as a playable voice message.

Telegram documentation: <https://core.telegram.org/bots/api#sendvoice>

Parameters

- **chat_id** – Unique identifier for the message recipient.
- **voice** –
- **caption** –

- **duration** – Duration of sent audio in seconds
- **reply_to_message_id** –
- **reply_markup** –
- **parse_mode** –
- **disable_notification** –
- **timeout** –
- **caption_entities** –
- **allow_sending_without_reply** –
- **protect_content** –

Returns Message

set_chat_administrator_custom_title(*chat_id: Union[int, str], user_id: int, custom_title: str*) → bool

Use this method to set a custom title for an administrator in a supergroup promoted by the bot.

Telegram documentation: <https://core.telegram.org/bots/api#setchatadministratorcustomtitle>

Parameters

- **chat_id** – Unique identifier for the target chat or username of the target supergroup (in the format @supergroupusername)
- **user_id** – Unique identifier of the target user
- **custom_title** – New custom title for the administrator; 0-16 characters, emoji are not allowed

Returns True on success.

set_chat_description(*chat_id: Union[int, str], description: Optional[str] = None*) → bool

Use this method to change the description of a supergroup or a channel. The bot must be an administrator in the chat for this to work and must have the appropriate admin rights.

Telegram documentation: <https://core.telegram.org/bots/api#setchatdescription>

Parameters

- **chat_id** – Int or Str: Unique identifier for the target chat or username of the target channel (in the format @channelusername)
- **description** – Str: New chat description, 0-255 characters

Returns True on success.

set_chat_permissions(*chat_id: Union[int, str], permissions: telebot.types.ChatPermissions*) → bool

Use this method to set default chat permissions for all members. The bot must be an administrator in the group or a supergroup for this to work and must have the can_restrict_members admin rights.

Telegram documentation: <https://core.telegram.org/bots/api#setchatpermissions>

Parameters

- **chat_id** – Unique identifier for the target chat or username of the target supergroup (in the format @supergroupusername)
- **permissions** – New default chat permissions

Returns True on success

set_chat_photo(*chat_id: Union[int, str], photo: Any*) → bool

Use this method to set a new profile photo for the chat. Photos can't be changed for private chats. The bot must be an administrator in the chat for this to work and must have the appropriate admin rights. Returns True on success. Note: In regular groups (non-supergroups), this method will only work if the 'All Members Are Admins' setting is off in the target group.

Telegram documentation: <https://core.telegram.org/bots/api#setchatphoto>

Parameters

- **chat_id** – Int or Str: Unique identifier for the target chat or username of the target channel (in the format @channelusername)
- **photo** – InputFile: New chat photo, uploaded using multipart/form-data

Returns

set_chat_sticker_set(*chat_id: Union[int, str], sticker_set_name: str*) → *telebot.types.StickerSet*

Use this method to set a new group sticker set for a supergroup. The bot must be an administrator in the chat for this to work and must have the appropriate admin rights. Use the field `can_set_sticker_set` optionally returned in `getChat` requests to check if the bot can use this method. Returns True on success.

Telegram documentation: <https://core.telegram.org/bots/api#setchatstickerset>

Parameters

- **chat_id** – Unique identifier for the target chat or username of the target supergroup (in the format @supergroupusername)
- **sticker_set_name** – Name of the sticker set to be set as the group sticker set

Returns API reply.

set_chat_title(*chat_id: Union[int, str], title: str*) → bool

Use this method to change the title of a chat. Titles can't be changed for private chats. The bot must be an administrator in the chat for this to work and must have the appropriate admin rights. Returns True on success. Note: In regular groups (non-supergroups), this method will only work if the 'All Members Are Admins' setting is off in the target group.

Telegram documentation: <https://core.telegram.org/bots/api#setchattitle>

Parameters

- **chat_id** – Int or Str: Unique identifier for the target chat or username of the target channel (in the format @channelusername)
- **title** – New chat title, 1-255 characters

Returns

set_game_score(*user_id: Union[int, str], score: int, force: Optional[bool] = None, chat_id: Optional[Union[int, str]] = None, message_id: Optional[int] = None, inline_message_id: Optional[str] = None, disable_edit_message: Optional[bool] = None*) → Union[*telebot.types.Message*, bool]

Sets the value of points in the game to a specific user.

Telegram documentation: <https://core.telegram.org/bots/api#setgamecore>

Parameters

- **user_id** –
- **score** –

- **force** –
- **chat_id** –
- **message_id** –
- **inline_message_id** –
- **disable_edit_message** –

Returns

set_my_commands(*commands*: List[telebot.types.BotCommand], *scope*: Optional[telebot.types.BotCommandScope] = None, *language_code*: Optional[str] = None) → bool

Use this method to change the list of the bot's commands.

Telegram documentation: <https://core.telegram.org/bots/api#setmycommands>

Parameters

- **commands** – List of BotCommand. At most 100 commands can be specified.
- **scope** – The scope of users for which the commands are relevant. Defaults to BotCommandScopeDefault.
- **language_code** – A two-letter ISO 639-1 language code. If empty, commands will be applied to all users from the given scope, for whose language there are no dedicated commands

Returns

set_state(*user_id*: int, *state*: Union[int, str], *chat_id*: Optional[int] = None) → None

Sets a new state of a user.

Parameters

- **user_id** –
- **state** – new state. can be string or integer.
- **chat_id** –

set_sticker_position_in_set(*sticker*: str, *position*: int) → bool

Use this method to move a sticker in a set created by the bot to a specific position . Returns True on success.

Telegram documentation: <https://core.telegram.org/bots/api#setstickerpositioninset>

Parameters

- **sticker** –
- **position** –

Returns

set_sticker_set_thumb(*name*: str, *user_id*: int, *thumb*: Optional[Union[Any, str]] = None)

Use this method to set the thumbnail of a sticker set. Animated thumbnails can be set for animated sticker sets only. Returns True on success.

Telegram documentation: <https://core.telegram.org/bots/api#setstickersetthumb>

Parameters

- **name** – Sticker set name
- **user_id** – User identifier

- **thumb** –

set_update_listener(*listener*)

set_webhook(*url=None, certificate=None, max_connections=None, allowed_updates=None, ip_address=None, drop_pending_updates=None, timeout=None*)

Use this method to specify a url and receive incoming updates via an outgoing webhook. Whenever there is an update for the bot, we will send an HTTPS POST request to the specified url, containing a JSON-serialized Update. In case of an unsuccessful request, we will give up after a reasonable amount of attempts. Returns True on success.

Telegram documentation: <https://core.telegram.org/bots/api#setwebhook>

Parameters

- **url** – HTTPS url to send updates to. Use an empty string to remove webhook integration
- **certificate** – Upload your public key certificate so that the root certificate in use can be checked. See our self-signed guide for details.
- **max_connections** – Maximum allowed number of simultaneous HTTPS connections to the webhook for update delivery, 1-100. Defaults to 40. Use lower values to limit the load on your bot's server, and higher values to increase your bot's throughput.
- **allowed_updates** – A JSON-serialized list of the update types you want your bot to receive. For example, specify ["message", "edited_channel_post", "callback_query"] to only receive updates of these types. See Update for a complete list of available update types. Specify an empty list to receive all updates regardless of type (default). If not specified, the previous setting will be used.
- **ip_address** – The fixed IP address which will be used to send webhook requests instead of the IP address resolved through DNS
- **drop_pending_updates** – Pass True to drop all pending updates
- **timeout** – Integer. Request connection timeout

Returns API reply.

setup_middleware(*middleware: telebot.handler_backends.BaseMiddleware*)

Register middleware

Parameters **middleware** – Subclass of *telebot.handler_backends.BaseMiddleware*

Returns None

shipping_query_handler(*func, **kwargs*)

Shipping request handler

Parameters

- **func** –
- **kwargs** –

Returns

stop_bot()

stop_message_live_location(*chat_id: Optional[Union[int, str]] = None, message_id: Optional[int] = None, inline_message_id: Optional[str] = None, reply_markup: Optional[Union[telebot.types.InlineKeyboardMarkup, telebot.types.ReplyKeyboardMarkup, telebot.types.ReplyKeyboardRemove, telebot.types.ForceReply]] = None, timeout: Optional[int] = None*) → *telebot.types.Message*

Use this method to stop updating a live location message sent by the bot or via the bot (for inline bots) before `live_period` expires

Telegram documentation: <https://core.telegram.org/bots/api#stopmessagelivelocation>

Parameters

- **chat_id** –
- **message_id** –
- **inline_message_id** –
- **reply_markup** –
- **timeout** –

Returns

stop_poll(*chat_id: Union[int, str], message_id: int, reply_markup: Optional[Union[telebot.types.InlineKeyboardMarkup, telebot.types.ReplyKeyboardMarkup, telebot.types.ReplyKeyboardRemove, telebot.types.ForceReply]] = None*) → *telebot.types.Poll*

Stops a poll.

Telegram documentation: <https://core.telegram.org/bots/api#stoppoll>

Parameters

- **chat_id** –
- **message_id** –
- **reply_markup** –

Returns

stop_polling()

unban_chat_member(*chat_id: Union[int, str], user_id: int, only_if_banned: Optional[bool] = False*) → bool

Use this method to unban a previously kicked user in a supergroup or channel. The user will not return to the group or channel automatically, but will be able to join via link, etc. The bot must be an administrator for this to work. By default, this method guarantees that after the call the user is not a member of the chat, but will be able to join it. So if the user is a member of the chat they will also be removed from the chat. If you don't want this, use the parameter `only_if_banned`.

Telegram documentation: <https://core.telegram.org/bots/api#unbanchatmember>

Parameters

- **chat_id** – Unique identifier for the target group or username of the target supergroup or channel (in the format `@username`)
- **user_id** – Unique identifier of the target user
- **only_if_banned** – Do nothing if the user is not banned

Returns True on success

unban_chat_sender_chat(*chat_id: Union[int, str], sender_chat_id: Union[int, str]*) → bool

Use this method to unban a previously banned channel chat in a supergroup or channel. The bot must be an administrator for this to work and must have the appropriate administrator rights. Returns True on success.

Telegram documentation: <https://core.telegram.org/bots/api#unbanchatsenderchat>

Params**Parameters**

- **chat_id** – Unique identifier for the target chat or username of the target channel (in the format @channelusername)
- **sender_chat_id** – Unique identifier of the target sender chat

Returns True on success.

unpin_all_chat_messages(*chat_id: Union[int, str]*) → bool

Use this method to unpin all pinned messages in a supergroup chat. The bot must be an administrator in the chat for this to work and must have the appropriate admin rights. Returns True on success.

Telegram documentation: <https://core.telegram.org/bots/api#unpinallchatmessages>

Parameters **chat_id** – Int or Str: Unique identifier for the target chat or username of the target channel (in the format @channelusername)

Returns

unpin_chat_message(*chat_id: Union[int, str], message_id: Optional[int] = None*) → bool

Use this method to unpin specific pinned message in a supergroup chat. The bot must be an administrator in the chat for this to work and must have the appropriate admin rights. Returns True on success.

Telegram documentation: <https://core.telegram.org/bots/api#unpinchatmessage>

Parameters

- **chat_id** – Int or Str: Unique identifier for the target chat or username of the target channel (in the format @channelusername)
- **message_id** – Int: Identifier of a message to unpin

Returns

upload_sticker_file(*user_id: int, png_sticker: Union[Any, str]*) → *telebot.types.File*

Use this method to upload a .png file with a sticker for later use in `createNewStickerSet` and `addStickerToSet` methods (can be used multiple times). Returns the uploaded File on success.

Telegram documentation: <https://core.telegram.org/bots/api#uploadstickerfile>

Parameters

- **user_id** –
- **png_sticker** –

Returns

property user: *telebot.types.User*

The User object representing this bot. Equivalent to `bot.get_me()` but the result is cached so only one API call is needed

custom_filters file**class telebot.custom_filters.AdvancedCustomFilter**

Bases: `abc.ABC`

Simple Custom Filter base class. Create child class with `check()` method. Accepts two parameters, returns bool: True - filter passed, False - filter failed. message: Message class text: Filter value given in handler

check(*message*, *text*)

Perform a check.

class telebot.custom_filters.ChatFilter

Bases: `telebot.custom_filters.AdvancedCustomFilter`

Check whether chat_id corresponds to given chat_id.

Example: `@bot.message_handler(chat_id=[99999])`

check(*message*, *text*)

Perform a check.

key = `'chat_id'`

class telebot.custom_filters.ForwardFilter

Bases: `telebot.custom_filters.SimpleCustomFilter`

Check whether message was forwarded from channel or group.

Example:

`@bot.message_handler(is_forwarded=True)`

check(*message*)

Perform a check.

key = `'is_forwarded'`

class telebot.custom_filters.IsAdminFilter(*bot*)

Bases: `telebot.custom_filters.SimpleCustomFilter`

Check whether the user is administrator / owner of the chat.

Example: `@bot.message_handler(chat_types=['supergroup'], is_chat_admin=True)`

check(*message*)

Perform a check.

key = `'is_chat_admin'`

class telebot.custom_filters.IsDigitFilter

Bases: `telebot.custom_filters.SimpleCustomFilter`

Filter to check whether the string is made up of only digits.

Example: `@bot.message_handler(is_digit=True)`

check(*message*)

Perform a check.

key = `'is_digit'`

class telebot.custom_filters.IsReplyFilterBases: *telebot.custom_filters.SimpleCustomFilter*

Check whether message is a reply.

Example:

@bot.message_handler(is_reply=True)

check(*message*)

Perform a check.

key = 'is_reply'**class telebot.custom_filters.LanguageFilter**Bases: *telebot.custom_filters.AdvancedCustomFilter*

Check users language_code.

Example:

@bot.message_handler(language_code=['ru'])

check(*message*, *text*)

Perform a check.

key = 'language_code'**class telebot.custom_filters.SimpleCustomFilter**

Bases: abc.ABC

Simple Custom Filter base class. Create child class with check() method. Accepts only message, returns bool value, that is compared with given in handler.

check(*message*)

Perform a check.

class telebot.custom_filters.StateFilter(*bot*)Bases: *telebot.custom_filters.AdvancedCustomFilter*

Filter to check state.

Example: @bot.message_handler(state=1)

check(*message*, *text*)

Perform a check.

key = 'state'**class telebot.custom_filters.TextContainsFilter**Bases: *telebot.custom_filters.AdvancedCustomFilter*

Filter to check Text message. key: text

Example: # Will respond if any message.text contains word 'account'
@bot.message_handler(text_contains=['account'])**check**(*message*, *text*)

Perform a check.

key = 'text_contains'

```
class telebot.custom_filters.TextFilter(equals: Optional[str] = None, contains: Optional[Union[list, tuple]] = None, starts_with: Optional[Union[str, list, tuple]] = None, ends_with: Optional[Union[str, list, tuple]] = None, ignore_case: bool = False)
```

Bases: object

Advanced text filter to check (types.Message, types.CallbackQuery, types.InlineQuery, types.Poll)

example of usage is in examples/custom_filters/advanced_text_filter.py

```
check(obj: Union[telebot.types.Message, telebot.types.CallbackQuery, telebot.types.InlineQuery, telebot.types.Poll])
```

```
class telebot.custom_filters.TextMatchFilter
```

Bases: *telebot.custom_filters.AdvancedCustomFilter*

Filter to check Text message. key: text

Example: @bot.message_handler(text=['account'])

```
check(message, text)
```

Perform a check.

```
key = 'text'
```

```
class telebot.custom_filters.TextStartsFilter
```

Bases: *telebot.custom_filters.AdvancedCustomFilter*

Filter to check whether message starts with some text.

Example: # Will work if message.text starts with 'Sir'. @bot.message_handler(text_startswith='Sir')

```
check(message, text)
```

Perform a check.

```
key = 'text_startswith'
```

Synchronous storage for states

```
class telebot.storage.StateContext(obj, chat_id, user_id)
```

Bases: object

Class for data.

```
class telebot.storage.StateMemoryStorage
```

Bases: *telebot.storage.base_storage.StateStorageBase*

```
delete_state(chat_id, user_id)
```

Delete state for a particular user.

```
get_data(chat_id, user_id)
```

Get data for a user in a particular chat.

```
get_interactive_data(chat_id, user_id)
```

```
get_state(chat_id, user_id)
```

```
reset_data(chat_id, user_id)
```

Reset data for a particular user in a chat.

save(*chat_id, user_id, data*)

set_data(*chat_id, user_id, key, value*)

Set data for a user in a particular chat.

set_state(*chat_id, user_id, state*)

Set state for a particular user.

! Note that you should create a record if it does not exist, and if a record with state already exists, you need to update a record.

class telebot.storage.StatePickleStorage(*file_path='./state-save/states.pkl'*)

Bases: [telebot.storage.base_storage.StateStorageBase](#)

convert_old_to_new()

Use this function to convert old storage to new storage. This function is for people who was using pickle storage that was in version <=4.3.1.

create_dir()

Create directory .save-handlers.

delete_state(*chat_id, user_id*)

Delete state for a particular user.

get_data(*chat_id, user_id*)

Get data for a user in a particular chat.

get_interactive_data(*chat_id, user_id*)

get_state(*chat_id, user_id*)

read()

reset_data(*chat_id, user_id*)

Reset data for a particular user in a chat.

save(*chat_id, user_id, data*)

set_data(*chat_id, user_id, key, value*)

Set data for a user in a particular chat.

set_state(*chat_id, user_id, state*)

Set state for a particular user.

! Note that you should create a record if it does not exist, and if a record with state already exists, you need to update a record.

update_data()

class telebot.storage.StateRedisStorage(*host='localhost', port=6379, db=0, password=None, prefix='telebot_'*)

Bases: [telebot.storage.base_storage.StateStorageBase](#)

This class is for Redis storage. This will work only for states. To use it, just pass this class to: TeleBot(storage=StateRedisStorage())

delete_record(*key*)

Function to delete record from database. It has nothing to do with states. Made for backend compatibility

delete_state(*chat_id, user_id*)

Delete state for a particular user in a chat.

get_data(*chat_id, user_id*)

Get data of particular user in a particular chat.

get_interactive_data(*chat_id, user_id*)

Get Data in interactive way. You can use with() with this function.

get_record(*key*)

Function to get record from database. It has nothing to do with states. Made for backend compatibility

get_state(*chat_id, user_id*)

Get state of a user in a chat.

get_value(*chat_id, user_id, key*)

Get value for a data of a user in a chat.

reset_data(*chat_id, user_id*)

Reset data of a user in a chat.

save(*chat_id, user_id, data*)

set_data(*chat_id, user_id, key, value*)

Set data without interactive data.

set_record(*key, value*)

Function to set record to database. It has nothing to do with states. Made for backend compatibility

set_state(*chat_id, user_id, state*)

Set state for a particular user in a chat.

class telebot.storage.StateStorageBase

Bases: object

delete_state(*chat_id, user_id*)

Delete state for a particular user.

get_data(*chat_id, user_id*)

Get data for a user in a particular chat.

get_state(*chat_id, user_id*)

reset_data(*chat_id, user_id*)

Reset data for a particular user in a chat.

save(*chat_id, user_id, data*)

set_data(*chat_id, user_id, key, value*)

Set data for a user in a particular chat.

set_state(*chat_id, user_id, state*)

Set state for a particular user.

! Note that you should create a record if it does not exist, and if a record with state already exists, you need to update a record.

handler_backends file**class** telebot.handler_backends.**BaseMiddleware**

Bases: object

Base class for middleware. Your middlewares should be inherited from this class.

post_process(*message, data, exception*)**pre_process**(*message, data*)**class** telebot.handler_backends.**CancelUpdate**

Bases: object

Class for canceling updates. Just return instance of this class in middleware to skip update. Update will skip handler and execution of post_process in middlewares.

class telebot.handler_backends.**FileHandlerBackend**(*handlers=None,*
filename='./handler-saves/handlers.save',
delay=120)Bases: [telebot.handler_backends.HandlerBackend](#)**clear_handlers**(*handler_group_id*)**static dump_handlers**(*handlers, filename, file_mode='wb'*)**get_handlers**(*handler_group_id*)**load_handlers**(*filename=None, del_file_after_loading=True*)**register_handler**(*handler_group_id, handler*)**static return_load_handlers**(*filename, del_file_after_loading=True*)**save_handlers**()**start_save_timer**()**class** telebot.handler_backends.**HandlerBackend**(*handlers=None*)

Bases: object

Class for saving (next step|reply) handlers

clear_handlers(*handler_group_id*)**get_handlers**(*handler_group_id*)**register_handler**(*handler_group_id, handler*)**class** telebot.handler_backends.**MemoryHandlerBackend**(*handlers=None*)Bases: [telebot.handler_backends.HandlerBackend](#)**clear_handlers**(*handler_group_id*)**get_handlers**(*handler_group_id*)**load_handlers**(*filename, del_file_after_loading*)**register_handler**(*handler_group_id, handler*)

```
class telebot.handler_backends.RedisHandlerBackend(handlers=None, host='localhost', port=6379,
                                                    db=0, prefix='telebot', password=None)
```

Bases: `telebot.handler_backends.HandlerBackend`

```
clear_handlers(handler_group_id)
```

```
get_handlers(handler_group_id)
```

```
register_handler(handler_group_id, handler)
```

```
class telebot.handler_backends.SkipHandler
```

Bases: `object`

Class for skipping handlers. Just return instance of this class in middleware to skip handler. Update will go to `post_process`, but will skip execution of handler.

```
class telebot.handler_backends.State
```

Bases: `object`

```
class telebot.handler_backends.StatesGroup
```

Bases: `object`

1.3.5 AsyncTeleBot

AsyncTeleBot methods

```
class telebot.async_telebot.AsyncTeleBot(token: str, parse_mode: typing.Optional[str] = None,
                                           offset=None, exception_handler=None,
                                           state_storage=<telebot.asyncio_storage.memory_storage.StateMemoryStorage
                                           object>)
```

Bases: `object`

This is the main asynchronous class for Bot.

It allows you to add handlers for different kind of updates.

Usage:

```
from telebot.async_telebot import AsyncTeleBot
bot = AsyncTeleBot('token') # get token from @BotFather
```

See more examples in `examples/` directory: <https://github.com/eternnoir/pyTelegramBotAPI/tree/master/examples>

```
add_callback_query_handler(handler_dict)
```

Adds a callback request handler. Note that you should use `register_callback_query_handler` to add `callback_query_handler`.

Parameters `handler_dict` –

Returns

```
add_channel_post_handler(handler_dict)
```

Adds channel post handler. Note that you should use `register_channel_post_handler` to add `channel_post_handler`.

Parameters `handler_dict` –

Returns

add_chat_join_request_handler(handler_dict)

Adds a chat_join_request handler. Note that you should use register_chat_join_request_handler to add chat_join_request_handler.

Parameters handler_dict –

Returns

add_chat_member_handler(handler_dict)

Adds a chat_member handler. Note that you should use register_chat_member_handler to add chat_member_handler.

Parameters handler_dict –

Returns

add_chosen_inline_handler(handler_dict)

Description: TBD Note that you should use register_chosen_inline_handler to add chosen_inline_handler.

Parameters handler_dict –

Returns

add_custom_filter(custom_filter)

Create custom filter.

custom_filter: Class with check(message) method.

async add_data(user_id: int, chat_id: Optional[int] = None, **kwargs)

Add data to states.

Parameters

- user_id –
- chat_id –

add_edited_channel_post_handler(handler_dict)

Adds the edit channel post handler. Note that you should use register_edited_channel_post_handler to add edited_channel_post_handler.

Parameters handler_dict –

Returns

add_edited_message_handler(handler_dict)

Adds the edit message handler. Note that you should use register_edited_message_handler to add edited_message_handler.

Parameters handler_dict –

Returns

add_inline_handler(handler_dict)

Adds inline call handler. Note that you should use register_inline_handler to add inline_handler.

Parameters handler_dict –

Returns

add_message_handler(handler_dict)

Adds a message handler. Note that you should use register_message_handler to add message_handler.

Parameters handler_dict –

Returns**add_my_chat_member_handler**(*handler_dict*)

Adds a my_chat_member handler. Note that you should use register_my_chat_member_handler to add my_chat_member_handler.

Parameters *handler_dict* –**Returns****add_poll_answer_handler**(*handler_dict*)

Adds a poll_answer request handler. Note that you should use register_poll_answer_handler to add poll_answer_handler.

Parameters *handler_dict* –**Returns****add_poll_handler**(*handler_dict*)

Adds a poll request handler. Note that you should use register_poll_handler to add poll_handler.

Parameters *handler_dict* –**Returns****add_pre_checkout_query_handler**(*handler_dict*)

Adds a pre-checkout request handler. Note that you should use register_pre_checkout_query_handler to add pre_checkout_query_handler.

Parameters *handler_dict* –**Returns****add_shipping_query_handler**(*handler_dict*)

Adds a shipping request handler. Note that you should use register_shipping_query_handler to add shipping_query_handler.

Parameters *handler_dict* –**Returns**

async add_sticker_to_set(*user_id: int, name: str, emojis: str, png_sticker: Optional[Union[Any, str]] = None, tgs_sticker: Optional[Union[Any, str]] = None, webm_sticker: Optional[Union[Any, str]] = None, mask_position: Optional[telebot.types.MaskPosition] = None*) → bool

Use this method to add a new sticker to a set created by the bot. It's required to pass *png_sticker* or *tgs_sticker*. Returns True on success.

Telegram documentation: <https://core.telegram.org/bots/api#addstickertoset>

Parameters

- **user_id** –
- **name** –
- **emojis** –
- **png_sticker** – Required if *tgs_sticker* is None
- **tgs_sticker** – Required if *png_sticker* is None
- **mask_position** –

Webm_sticker

Returns

async answer_callback_query(*callback_query_id: int, text: Optional[str] = None, show_alert: Optional[bool] = None, url: Optional[str] = None, cache_time: Optional[int] = None*) → bool

Use this method to send answers to callback queries sent from inline keyboards. The answer will be displayed to the user as a notification at the top of the chat screen or as an alert.

Telegram documentation: <https://core.telegram.org/bots/api#answercallbackquery>

Parameters

- **callback_query_id** –
- **text** –
- **show_alert** –
- **url** –
- **cache_time** –

Returns

async answer_inline_query(*inline_query_id: str, results: List[Any], cache_time: Optional[int] = None, is_personal: Optional[bool] = None, next_offset: Optional[str] = None, switch_pm_text: Optional[str] = None, switch_pm_parameter: Optional[str] = None*) → bool

Use this method to send answers to an inline query. On success, True is returned. No more than 50 results per query are allowed.

Telegram documentation: <https://core.telegram.org/bots/api#answerinlinequery>

Parameters

- **inline_query_id** – Unique identifier for the answered query
- **results** – Array of results for the inline query
- **cache_time** – The maximum amount of time in seconds that the result of the inline query may be cached on the server.
- **is_personal** – Pass True, if results may be cached on the server side only for the user that sent the query.
- **next_offset** – Pass the offset that a client should send in the next query with the same text to receive more results.
- **switch_pm_parameter** – If passed, clients will display a button with specified text that switches the user to a private chat with the bot and sends the bot a start message with the parameter switch_pm_parameter
- **switch_pm_text** – Parameter for the start message sent to the bot when user presses the switch button

Returns True means success.

async answer_pre_checkout_query(*pre_checkout_query_id: int, ok: bool, error_message: Optional[str] = None*) → bool

Response to a request for pre-inspection.

Telegram documentation: <https://core.telegram.org/bots/api#answerprecheckoutquery>

Parameters

- **pre_checkout_query_id** –
- **ok** –
- **error_message** –

Returns

async answer_shipping_query(*shipping_query_id: str, ok: bool, shipping_options: Optional[List[telebot.types.ShippingOption]] = None, error_message: Optional[str] = None*) → bool

Asks for an answer to a shipping question.

Telegram documentation: <https://core.telegram.org/bots/api#answershippingquery>

Parameters

- **shipping_query_id** –
- **ok** –
- **shipping_options** –
- **error_message** –

Returns

async approve_chat_join_request(*chat_id: Union[str, int], user_id: Union[int, str]*) → bool

Use this method to approve a chat join request. The bot must be an administrator in the chat for this to work and must have the can_invite_users administrator right. Returns True on success.

Telegram documentation: <https://core.telegram.org/bots/api#approvechatjoinrequest>

Parameters

- **chat_id** – Unique identifier for the target chat or username of the target supergroup (in the format @supergroupusername)
- **user_id** – Unique identifier of the target user

Returns True on success.

async ban_chat_member(*chat_id: Union[int, str], user_id: int, until_date: Optional[Union[int, datetime.datetime]] = None, revoke_messages: Optional[bool] = None*) → bool

Use this method to ban a user in a group, a supergroup or a channel. In the case of supergroups and channels, the user will not be able to return to the chat on their own using invite links, etc., unless unbanned first. Returns True on success.

Telegram documentation: <https://core.telegram.org/bots/api#banchatmember>

Parameters

- **chat_id** – Int or string : Unique identifier for the target group or username of the target supergroup
- **user_id** – Int : Unique identifier of the target user
- **until_date** – Date when the user will be unbanned, unix time. If user is banned for more than 366 days or less than 30 seconds from the current time they are considered to be banned forever
- **revoke_messages** – Bool: Pass True to delete all messages from the chat for the user that is being removed. If False, the user will be able to see messages in the group that were sent before the user was removed. Always True for supergroups and channels.

Returns boolean

async ban_chat_sender_chat(*chat_id: Union[int, str], sender_chat_id: Union[int, str]*) → bool

Use this method to ban a channel chat in a supergroup or a channel. The owner of the chat will not be able to send messages and join live streams on behalf of the chat, unless it is unbanned first. The bot must be an administrator in the supergroup or channel for this to work and must have the appropriate administrator rights. Returns True on success.

Telegram documentation: <https://core.telegram.org/bots/api#banchat senderchat>

Parameters

- **chat_id** – Unique identifier for the target chat or username of the target channel (in the format @channelusername)
- **sender_chat_id** – Unique identifier of the target sender chat

Returns True on success.

callback_query_handler(*func, **kwargs*)

Callback request handler decorator.

Parameters

- **func** –
- **kwargs** –

Returns

channel_post_handler(*commands=None, regexp=None, func=None, content_types=None, **kwargs*)

Channel post handler decorator.

Parameters

- **commands** –
- **regexp** –
- **func** –
- **content_types** –
- **kwargs** –

Returns

chat_join_request_handler(*func=None, **kwargs*)

chat_join_request handler.

Parameters

- **func** –
- **kwargs** –

Returns

chat_member_handler(*func=None, **kwargs*)

chat_member handler.

Parameters

- **func** –
- **kwargs** –

Returns

chosen_inline_handler(*func*, ***kwargs*)

Description: TBD

Parameters

- **func** –
- **kwargs** –

Returns

async close() → bool

Use this method to close the bot instance before moving it from one local server to another. You need to delete the webhook before calling this method to ensure that the bot isn't launched again after server restart. The method will return error 429 in the first 10 minutes after the bot is launched. Returns True on success.

Telegram documentation: <https://core.telegram.org/bots/api#close>

async close_session()

Closes existing session of aiohttp. Use this function if you stop polling.

async copy_message(*chat_id: Union[int, str]*, *from_chat_id: Union[int, str]*, *message_id: int*, *caption: Optional[str] = None*, *parse_mode: Optional[str] = None*, *caption_entities: Optional[List[telebot.types.MessageEntity]] = None*, *disable_notification: Optional[bool] = None*, *protect_content: Optional[bool] = None*, *reply_to_message_id: Optional[int] = None*, *allow_sending_without_reply: Optional[bool] = None*, *reply_markup: Optional[Union[telebot.types.InlineKeyboardMarkup, telebot.types.ReplyKeyboardMarkup, telebot.types.ReplyKeyboardRemove, telebot.types.ForceReply]] = None*, *timeout: Optional[int] = None*) → int

Use this method to copy messages of any kind.

Telegram documentation: <https://core.telegram.org/bots/api#copymessage>

Parameters

- **chat_id** – which chat to forward
- **from_chat_id** – which chat message from
- **message_id** – message id
- **caption** –
- **parse_mode** –
- **caption_entities** –
- **disable_notification** –
- **reply_to_message_id** –
- **allow_sending_without_reply** –
- **reply_markup** –
- **timeout** –
- **protect_content** –

Returns API reply.

```
async create_chat_invite_link(chat_id: Union[int, str], name: Optional[str] = None, expire_date:
                             Optional[Union[int, datetime.datetime]] = None, member_limit:
                             Optional[int] = None, creates_join_request: Optional[bool] = None)
    → telebot.types.ChatInviteLink
```

Use this method to create an additional invite link for a chat. The bot must be an administrator in the chat for this to work and must have the appropriate admin rights.

Telegram documentation: <https://core.telegram.org/bots/api#createchatinvitelink>

Parameters

- **chat_id** – Id: Unique identifier for the target chat or username of the target channel (in the format @channelusername)
- **name** – Invite link name; 0-32 characters
- **expire_date** – Point in time (Unix timestamp) when the link will expire
- **member_limit** – Maximum number of users that can be members of the chat simultaneously
- **creates_join_request** – True, if users joining the chat via the link need to be approved by chat administrators. If True, member_limit can't be specified

Returns

```
async create_new_sticker_set(user_id: int, name: str, title: str, emojis: str, png_sticker:
                             Optional[Union[Any, str]] = None, tgs_sticker: Optional[Union[Any,
                             str]] = None, webm_sticker: Optional[Union[Any, str]] = None,
                             contains_masks: Optional[bool] = None, mask_position:
                             Optional[telebot.types.MaskPosition] = None) → bool
```

Use this method to create new sticker set owned by a user. The bot will be able to edit the created sticker set. Returns True on success.

Telegram documentation: <https://core.telegram.org/bots/api#createnewstickerset>

Parameters

- **user_id** –
- **name** –
- **title** –
- **emojis** –
- **png_sticker** –
- **tgs_sticker** –
- **contains_masks** –
- **mask_position** –

Webm_sticker

Returns

```
async decline_chat_join_request(chat_id: Union[str, int], user_id: Union[int, str]) → bool
```

Use this method to decline a chat join request. The bot must be an administrator in the chat for this to work and must have the can_invite_users administrator right. Returns True on success.

Telegram documentation: <https://core.telegram.org/bots/api#declinechatjoinrequest>

Parameters

- **chat_id** – Unique identifier for the target chat or username of the target supergroup (in the format @supergroupusername)
- **user_id** – Unique identifier of the target user

Returns True on success.

async delete_chat_photo(*chat_id: Union[int, str]*) → bool

Use this method to delete a chat photo. Photos can't be changed for private chats. The bot must be an administrator in the chat for this to work and must have the appropriate admin rights. Returns True on success. Note: In regular groups (non-supergroups), this method will only work if the 'All Members Are Admins' setting is off in the target group.

Telegram documentation: <https://core.telegram.org/bots/api#deletechatphoto>

Parameters **chat_id** – Int or Str: Unique identifier for the target chat or username of the target channel (in the format @channelusername)

async delete_chat_sticker_set(*chat_id: Union[int, str]*) → bool

Use this method to delete a group sticker set from a supergroup. The bot must be an administrator in the chat for this to work and must have the appropriate admin rights. Use the field `can_set_sticker_set` optionally returned in `getChat` requests to check if the bot can use this method. Returns True on success.

Telegram documentation: <https://core.telegram.org/bots/api#deletechatstickerset>

Parameters **chat_id** – Unique identifier for the target chat or username of the target supergroup (in the format @supergroupusername)

Returns API reply.

async delete_message(*chat_id: Union[int, str], message_id: int, timeout: Optional[int] = None*) → bool

Use this method to delete message. Returns True on success.

Telegram documentation: <https://core.telegram.org/bots/api#deletemessage>

Parameters

- **chat_id** – in which chat to delete
- **message_id** – which message to delete
- **timeout** –

Returns API reply.

async delete_my_commands(*scope: Optional[telebot.types.BotCommandScope] = None, language_code: Optional[int] = None*) → bool

Use this method to delete the list of the bot's commands for the given scope and user language. After deletion, higher level commands will be shown to affected users. Returns True on success.

Telegram documentation: <https://core.telegram.org/bots/api#deletemycommands>

Parameters

- **scope** – The scope of users for which the commands are relevant. `async` defaults to `BotCommandScopeasync` default.
- **language_code** – A two-letter ISO 639-1 language code. If empty, commands will be applied to all users from the given scope, for whose language there are no dedicated commands

async delete_state(*user_id: int, chat_id: Optional[int] = None*)

Delete the current state of a user.

Parameters

- **user_id** –
- **chat_id** –

Returns

async delete_sticker_from_set(*sticker: str*) → bool

Use this method to delete a sticker from a set created by the bot. Returns True on success.

Telegram documentation: <https://core.telegram.org/bots/api#deletestickerfromset>

Parameters sticker –**Returns**

async delete_webhook(*drop_pending_updates=None, timeout=None*)

Use this method to remove webhook integration if you decide to switch back to getUpdates.

Telegram documentation: <https://core.telegram.org/bots/api#deletewebhook>

Parameters

- **drop_pending_updates** – Pass True to drop all pending updates
- **timeout** – Integer. Request connection timeout

Returns bool

async download_file(*file_path: str*) → bytes

async edit_chat_invite_link(*chat_id: Union[int, str], invite_link: Optional[str] = None, name: Optional[str] = None, expire_date: Optional[Union[int, datetime.datetime]] = None, member_limit: Optional[int] = None, creates_join_request: Optional[bool] = None*) → *telebot.types.ChatInviteLink*

Use this method to edit a non-primary invite link created by the bot. The bot must be an administrator in the chat for this to work and must have the appropriate admin rights.

Telegram documentation: <https://core.telegram.org/bots/api#editchatinvitelink>

Parameters

- **chat_id** – Id: Unique identifier for the target chat or username of the target channel (in the format @channelusername)
- **name** – Invite link name; 0-32 characters
- **invite_link** – The invite link to edit
- **expire_date** – Point in time (Unix timestamp) when the link will expire
- **member_limit** – Maximum number of users that can be members of the chat simultaneously
- **creates_join_request** – True, if users joining the chat via the link need to be approved by chat administrators. If True, member_limit can't be specified

Returns

```

async edit_message_caption(caption: str, chat_id: Optional[Union[int, str]] = None, message_id:
    Optional[int] = None, inline_message_id: Optional[str] = None,
    parse_mode: Optional[str] = None, caption_entities:
    Optional[List[telebot.types.MessageEntity]] = None, reply_markup:
    Optional[Union[telebot.types.InlineKeyboardMarkup,
        telebot.types.ReplyKeyboardMarkup, telebot.types.ReplyKeyboardRemove,
        telebot.types.ForceReply]] = None) → Union[telebot.types.Message, bool]

```

Use this method to edit captions of messages.

Telegram documentation: <https://core.telegram.org/bots/api#editmessagecaption>

Parameters

- **caption** –
- **chat_id** –
- **message_id** –
- **inline_message_id** –
- **parse_mode** –
- **caption_entities** –
- **reply_markup** –

Returns

```

async edit_message_live_location(latitude: float, longitude: float, chat_id: Optional[Union[int, str]]
    = None, message_id: Optional[int] = None, inline_message_id:
    Optional[str] = None, reply_markup:
    Optional[Union[telebot.types.InlineKeyboardMarkup,
        telebot.types.ReplyKeyboardMarkup,
        telebot.types.ReplyKeyboardRemove, telebot.types.ForceReply]] =
    None, timeout: Optional[int] = None, horizontal_accuracy:
    Optional[float] = None, heading: Optional[int] = None,
    proximity_alert_radius: Optional[int] = None) →
    telebot.types.Message

```

Use this method to edit live location.

Telegram documentation: <https://core.telegram.org/bots/api#editmessagelivelocation>

Parameters

- **latitude** –
- **longitude** –
- **chat_id** –
- **message_id** –
- **reply_markup** –
- **timeout** –
- **inline_message_id** –
- **horizontal_accuracy** –
- **heading** –
- **proximity_alert_radius** –

Returns

async edit_message_media(*media: Any, chat_id: Optional[Union[int, str]] = None, message_id: Optional[int] = None, inline_message_id: Optional[str] = None, reply_markup: Optional[Union[telebot.types.InlineKeyboardMarkup, telebot.types.ReplyKeyboardMarkup, telebot.types.ReplyKeyboardRemove, telebot.types.ForceReply]] = None*) → Union[*telebot.types.Message*, bool]

Use this method to edit animation, audio, document, photo, or video messages. If a message is a part of a message album, then it can be edited only to a photo or a video. Otherwise, message type can be changed arbitrarily. When inline message is edited, new file can't be uploaded. Use previously uploaded file via its file_id or specify a URL.

Telegram documentation: <https://core.telegram.org/bots/api#editmessagemedia>

Parameters

- **media** –
- **chat_id** –
- **message_id** –
- **inline_message_id** –
- **reply_markup** –

Returns

async edit_message_reply_markup(*chat_id: Optional[Union[int, str]] = None, message_id: Optional[int] = None, inline_message_id: Optional[str] = None, reply_markup: Optional[Union[telebot.types.InlineKeyboardMarkup, telebot.types.ReplyKeyboardMarkup, telebot.types.ReplyKeyboardRemove, telebot.types.ForceReply]] = None*) → Union[*telebot.types.Message*, bool]

Use this method to edit only the reply markup of messages.

Telegram documentation: <https://core.telegram.org/bots/api#editmessagereplymarkup>

Parameters

- **chat_id** –
- **message_id** –
- **inline_message_id** –
- **reply_markup** –

Returns

async edit_message_text(*text: str, chat_id: Optional[Union[int, str]] = None, message_id: Optional[int] = None, inline_message_id: Optional[str] = None, parse_mode: Optional[str] = None, entities: Optional[List[telebot.types.MessageEntity]] = None, disable_web_page_preview: Optional[bool] = None, reply_markup: Optional[Union[telebot.types.InlineKeyboardMarkup, telebot.types.ReplyKeyboardMarkup, telebot.types.ReplyKeyboardRemove, telebot.types.ForceReply]] = None*) → Union[*telebot.types.Message*, bool]

Use this method to edit text and game messages.

Telegram documentation: <https://core.telegram.org/bots/api#editmessagetext>

Parameters

- **text** –
- **chat_id** –
- **message_id** –
- **inline_message_id** –
- **parse_mode** –
- **entities** –
- **disable_web_page_preview** –
- **reply_markup** –

Returns

edited_channel_post_handler(*commands=None, regexp=None, func=None, content_types=None, **kwargs*)

Edit channel post handler decorator.

Parameters

- **commands** –
- **regexp** –
- **func** –
- **content_types** –
- **kwargs** –

Returns

edited_message_handler(*commands=None, regexp=None, func=None, content_types=None, chat_types=None, **kwargs*)

Edit message handler decorator.

Parameters

- **commands** –
- **regexp** –
- **func** –
- **content_types** –
- **chat_types** – list of chat types
- **kwargs** –

Returns

enable_saving_states(*filename='./.state-save/states.pkl'*)

Enable saving states (by default saving disabled)

Parameters **filename** – Filename of saving file

async export_chat_invite_link(*chat_id: Union[int, str]*) → str

Use this method to export an invite link to a supergroup or a channel. The bot must be an administrator in the chat for this to work and must have the appropriate admin rights.

Telegram documentation: <https://core.telegram.org/bots/api#exportchatinviolink>

Parameters **chat_id** – Id: Unique identifier for the target chat or username of the target channel (in the format @channelusername)

Returns exported invite link as String on success.

async forward_message(*chat_id: Union[int, str], from_chat_id: Union[int, str], message_id: int, disable_notification: Optional[bool] = None, protect_content: Optional[bool] = None, timeout: Optional[int] = None*) → *telebot.types.Message*

Use this method to forward messages of any kind.

Telegram documentation: <https://core.telegram.org/bots/api#forwardmessage>

Parameters

- **disable_notification** –
- **chat_id** – which chat to forward
- **from_chat_id** – which chat message from
- **message_id** – message id
- **protect_content** –
- **timeout** –

Returns API reply.

async get_chat(*chat_id: Union[int, str]*) → *telebot.types.Chat*

Use this method to get up to date information about the chat (current name of the user for one-on-one conversations, current username of a user, group or channel, etc.). Returns a Chat object on success.

Telegram documentation: <https://core.telegram.org/bots/api#getchat>

Parameters **chat_id** –

Returns

async get_chat_administrators(*chat_id: Union[int, str]*) → List[*telebot.types.ChatMember*]

Use this method to get a list of administrators in a chat. On success, returns an Array of ChatMember objects that contains information about all chat administrators except other bots.

Telegram documentation: <https://core.telegram.org/bots/api#getchatadministrators>

Parameters **chat_id** – Unique identifier for the target chat or username of the target supergroup or channel (in the format @channelusername)

Returns API reply.

async get_chat_member(*chat_id: Union[int, str], user_id: int*) → *telebot.types.ChatMember*

Use this method to get information about a member of a chat. Returns a ChatMember object on success.

Telegram documentation: <https://core.telegram.org/bots/api#getchatmember>

Parameters

- **chat_id** –
- **user_id** –

Returns API reply.

async get_chat_member_count(*chat_id: Union[int, str]*) → int

Use this method to get the number of members in a chat. Returns Int on success.

Telegram documentation: <https://core.telegram.org/bots/api#getchatmemberscount>

Parameters **chat_id** –

Returns

async get_chat_members_count(*chat_id: Union[int, str]*) → int

This function is deprecated. Use *get_chat_member_count* instead

async get_file(*file_id: str*) → *telebot.types.File*

Use this method to get basic info about a file and prepare it for downloading. For the moment, bots can download files of up to 20MB in size. On success, a File object is returned. It is guaranteed that the link will be valid for at least 1 hour. When the link expires, a new one can be requested by calling *get_file* again.

Telegram documentation: <https://core.telegram.org/bots/api#getfile>

Parameters **file_id** –

async get_file_url(*file_id: str*) → str

async get_game_high_scores(*user_id: int, chat_id: Optional[Union[int, str]] = None, message_id: Optional[int] = None, inline_message_id: Optional[str] = None*) → List[*telebot.types.GameHighScore*]

Gets top points and game play.

Telegram documentation: <https://core.telegram.org/bots/api#getgamehighscores>

Parameters

- **user_id** –
- **chat_id** –
- **message_id** –
- **inline_message_id** –

Returns

async get_me() → *telebot.types.User*

Returns basic information about the bot in form of a User object.

Telegram documentation: <https://core.telegram.org/bots/api#getme>

async get_my_commands(*scope: Optional[telebot.types.BotCommandScope], language_code: Optional[str]*) → List[*telebot.types.BotCommand*]

Use this method to get the current list of the bot's commands. Returns List of BotCommand on success.

Telegram documentation: <https://core.telegram.org/bots/api#getmycommands>

Parameters

- **scope** – The scope of users for which the commands are relevant. *async* defaults to BotCommandScopeAsyncDefault.
- **language_code** – A two-letter ISO 639-1 language code. If empty, commands will be applied to all users from the given scope, for whose language there are no dedicated commands

async get_state(*user_id, chat_id: Optional[int] = None*)

Get current state of a user.

Parameters

- **user_id** –
- **chat_id** –

Returns state of a user

async `get_sticker_set(name: str) → telebot.types.StickerSet`

Use this method to get a sticker set. On success, a StickerSet object is returned.

Telegram documentation: <https://core.telegram.org/bots/api#getstickerset>

Parameters **name** –

Returns

async `get_updates(offset: Optional[int] = None, limit: Optional[int] = None, timeout: Optional[int] = None, allowed_updates: Optional[List] = None, request_timeout: Optional[int] = None) → List[telebot.types.Update]`

async `get_user_profile_photos(user_id: int, offset: Optional[int] = None, limit: Optional[int] = None) → telebot.types.UserProfilePhotos`

Retrieves the user profile photos of the person with ‘user_id’

Telegram documentation: <https://core.telegram.org/bots/api#getuserprofilephotos>

Parameters

- **user_id** –
- **offset** –
- **limit** –

Returns API reply.

async `get_webhook_info(timeout=None)`

Use this method to get current webhook status. Requires no parameters. If the bot is using getUpdates, will return an object with the url field empty.

Telegram documentation: <https://core.telegram.org/bots/api#getwebhookinfo>

Parameters **timeout** – Integer. Request connection timeout

Returns On success, returns a WebhookInfo object.

async `infinity_polling(timeout: int = 20, skip_pending: bool = False, request_timeout: int = 20, logger_level=40, allowed_updates: Optional[List[str]] = None, *args, **kwargs)`

Wrap polling with infinite loop and exception handling to avoid bot stops polling.

Parameters

- **timeout** – Request connection timeout
- **request_timeout** – Timeout in seconds for long polling (see API docs)
- **skip_pending** – skip old updates
- **logger_level** – Custom logging level for infinity_polling logging. Use logger levels from logging as a value. None/NOTSET = no error logging
- **allowed_updates** – A list of the update types you want your bot to receive. For example, specify [“message”, “edited_channel_post”, “callback_query”] to only receive updates of these types. See util.update_types for a complete list of available update types. Specify an empty list to receive all update types except chat_member (default). If not specified, the previous setting will be used.

Please note that this parameter doesn’t affect updates created before the call to the get_updates, so unwanted updates may be received for a short period of time.

inline_handler(*func*, ***kwargs*)

Inline call handler decorator.

Parameters

- **func** –
- **kwargs** –

Returns

async kick_chat_member(*chat_id: Union[int, str]*, *user_id: int*, *until_date: Optional[Union[int, datetime.datetime]] = None*, *revoke_messages: Optional[bool] = None*) → bool

This function is deprecated. Use `ban_chat_member` instead

async leave_chat(*chat_id: Union[int, str]*) → bool

Use this method for your bot to leave a group, supergroup or channel. Returns True on success.

Telegram documentation: <https://core.telegram.org/bots/api#leavechat>

Parameters chat_id –

Returns

async log_out() → bool

Use this method to log out from the cloud Bot API server before launching the bot locally. You MUST log out the bot before running it locally, otherwise there is no guarantee that the bot will receive updates. After a successful call, you can immediately log in on a local server, but will not be able to log in back to the cloud Bot API server for 10 minutes. Returns True on success.

Telegram documentation: <https://core.telegram.org/bots/api#logout>

message_handler(*commands=None*, *regexp=None*, *func=None*, *content_types=None*, *chat_types=None*, ***kwargs*)

Message handler decorator. This decorator can be used to decorate functions that must handle certain types of messages. All message handlers are tested in the order they were added.

Example:

```
bot = TeleBot('TOKEN')

# Handles all messages which text matches regexp.
@bot.message_handler(regexp='someregexp')
async def command_help(message):
    bot.send_message(message.chat.id, 'Did someone call for help?')

# Handles messages in private chat
@bot.message_handler(chat_types=['private']) # You can add more chat types
async def command_help(message):
    bot.send_message(message.chat.id, 'Private chat detected, sir!')

# Handle all sent documents of type 'text/plain'.
@bot.message_handler(func=lambda message: message.document.mime_type == 'text/
plain',
    content_types=['document'])
async def command_handle_document(message):
    bot.send_message(message.chat.id, 'Document received, sir!')
```

(continues on next page)

(continued from previous page)

```
# Handle all other messages.
@bot.message_handler(func=lambda message: True, content_types=['audio', 'photo',
↳ 'voice', 'video', 'document',
  'text', 'location', 'contact', 'sticker'])
async def async_default_command(message):
    bot.send_message(message.chat.id, "This is the async default command.")
↳ handler.")
```

Parameters

- **commands** – Optional list of strings (commands to handle).
- **regexp** – Optional regular expression.
- **func** – Optional lambda function. The lambda receives the message to test as the first parameter. It must return True if the command should handle the message.
- **content_types** – Supported message content types. Must be a list. async defaults to ['text'].
- **chat_types** – list of chat types

my_chat_member_handler(*func=None, **kwargs*)

my_chat_member handler.

Parameters

- **func** –
- **kwargs** –

Returns

async pin_chat_message(*chat_id: Union[int, str], message_id: int, disable_notification: Optional[bool] = False*) → bool

Use this method to pin a message in a supergroup. The bot must be an administrator in the chat for this to work and must have the appropriate admin rights. Returns True on success.

Telegram documentation: <https://core.telegram.org/bots/api#pinchatmessage>

Parameters

- **chat_id** – Int or Str: Unique identifier for the target chat or username of the target channel (in the format @channelusername)
- **message_id** – Int: Identifier of a message to pin
- **disable_notification** – Bool: Pass True, if it is not necessary to send a notification to all group members about the new pinned message

Returns

poll_answer_handler(*func=None, **kwargs*)

Poll_answer request handler.

Parameters

- **func** –
- **kwargs** –

Returns

poll_handler(*func*, ***kwargs*)

Poll request handler.

Parameters

- **func** –
- **kwargs** –

Returns

async polling(*non_stop*: bool = False, *skip_pending*=False, *interval*: int = 0, *timeout*: int = 20, *request_timeout*: int = 20, *allowed_updates*: Optional[List[str]] = None, *none_stop*: Optional[bool] = None)

This allows the bot to retrieve Updates automatically and notify listeners and message handlers accordingly.

Warning: Do not call this function more than once!

Always get updates.

Parameters

- **interval** – Delay between two update retrivals
- **non_stop** – Do not stop polling when an ApiException occurs.
- **timeout** – Request connection timeout
- **skip_pending** – skip old updates
- **request_timeout** – Timeout in seconds for a request.
- **allowed_updates** – A list of the update types you want your bot to receive. For example, specify ["message", "edited_channel_post", "callback_query"] to only receive updates of these types. See util.update_types for a complete list of available update types. Specify an empty list to receive all update types except chat_member (default). If not specified, the previous setting will be used.

Please note that this parameter doesn't affect updates created before the call to the get_updates, so unwanted updates may be received for a short period of time.

- **none_stop** – Deprecated, use non_stop. Old typo f***up compatibility

Returns

pre_checkout_query_handler(*func*, ***kwargs*)

Pre-checkout request handler.

Parameters

- **func** –
- **kwargs** –

Returns

async process_chat_join_request(*chat_join_request*)

async process_middlewarees(*update_type*)

async process_new_callback_query(*new_callback_queries*)

async process_new_channel_posts(*channel_post*)

async process_new_chat_member(*chat_members*)

async process_new_chosen_inline_query(*new_chosen_inline_queries*)

async process_new_edited_channel_posts(*edited_channel_post*)

async process_new_edited_messages(*edited_message*)

async process_new_inline_query(*new_inline_queries*)

async process_new_messages(*new_messages*)

async process_new_my_chat_member(*my_chat_members*)

async process_new_poll(*polls*)

async process_new_poll_answer(*poll_answers*)

async process_new_pre_checkout_query(*pre_checkout_queries*)

async process_new_shipping_query(*new_shipping_queries*)

async process_new_updates(*updates*)

Process new updates. Just pass list of updates - each update should be instance of Update object.

Parameters updates – list of updates

async promote_chat_member(*chat_id: Union[int, str], user_id: int, can_change_info: Optional[bool] = None, can_post_messages: Optional[bool] = None, can_edit_messages: Optional[bool] = None, can_delete_messages: Optional[bool] = None, can_invite_users: Optional[bool] = None, can_restrict_members: Optional[bool] = None, can_pin_messages: Optional[bool] = None, can_promote_members: Optional[bool] = None, is_anonymous: Optional[bool] = None, can_manage_chat: Optional[bool] = None, can_manage_voice_chats: Optional[bool] = None*) → bool

Use this method to promote or demote a user in a supergroup or a channel. The bot must be an administrator in the chat for this to work and must have the appropriate admin rights. Pass False for all boolean parameters to demote a user.

Telegram documentation: <https://core.telegram.org/bots/api#promotechatmember>

Parameters

- **chat_id** – Unique identifier for the target chat or username of the target channel (in the format @channelusername)
- **user_id** – Int : Unique identifier of the target user
- **can_change_info** – Bool: Pass True, if the administrator can change chat title, photo and other settings
- **can_post_messages** – Bool : Pass True, if the administrator can create channel posts, channels only
- **can_edit_messages** – Bool : Pass True, if the administrator can edit messages of other users, channels only
- **can_delete_messages** – Bool : Pass True, if the administrator can delete messages of other users
- **can_invite_users** – Bool : Pass True, if the administrator can invite new users to the chat

- **can_restrict_members** – Bool: Pass True, if the administrator can restrict, ban or unban chat members
- **can_pin_messages** – Bool: Pass True, if the administrator can pin messages, supergroups only
- **can_promote_members** – Bool: Pass True, if the administrator can add new administrators with a subset of his own privileges or demote administrators that he has promoted, directly or indirectly (promoted by administrators that were appointed by him)
- **is_anonymous** – Bool: Pass True, if the administrator's presence in the chat is hidden
- **can_manage_chat** – Bool: Pass True, if the administrator can access the chat event log, chat statistics, message statistics in channels, see channel members, see anonymous administrators in supergroups and ignore slow mode. Implied by any other administrator privilege
- **can_manage_voice_chats** – Bool: Pass True, if the administrator can manage voice chats For now, bots can use this privilege only for passing to other administrators.

Returns True on success.

register_callback_query_handler(*callback, func, pass_bot=False, **kwargs*)

Registers callback query handler.

Parameters

- **pass_bot** –
- **callback** – function to be called
- **func** –

Returns decorated function

register_channel_post_handler(*callback, content_types=None, commands=None, regexp=None, func=None, pass_bot=False, **kwargs*)

Registers channel post message handler.

Parameters

- **pass_bot** –
- **callback** – function to be called
- **content_types** – list of content_types
- **commands** – list of commands
- **regexp** –
- **func** –

Returns decorated function

register_chat_join_request_handler(*callback, func=None, pass_bot=False, **kwargs*)

Registers chat join request handler.

Parameters

- **pass_bot** –
- **callback** – function to be called
- **func** –

Returns decorated function

register_chat_member_handler(*callback, func=None, pass_bot=False, **kwargs*)

Registers chat member handler.

Parameters

- **pass_bot** –
- **callback** – function to be called
- **func** –

Returns decorated function

register_chosen_inline_handler(*callback, func, pass_bot=False, **kwargs*)

Registers chosen inline handler.

Parameters

- **pass_bot** –
- **callback** – function to be called
- **func** –

Returns decorated function

register_edited_channel_post_handler(*callback, content_types=None, commands=None, regexp=None, func=None, pass_bot=False, **kwargs*)

Registers edited channel post message handler.

Parameters

- **pass_bot** –
- **callback** – function to be called
- **content_types** – list of content_types
- **commands** – list of commands
- **regexp** –
- **func** –

Returns decorated function

register_edited_message_handler(*callback, content_types=None, commands=None, regexp=None, func=None, chat_types=None, pass_bot=False, **kwargs*)

Registers edited message handler.

Parameters

- **pass_bot** –
- **callback** – function to be called
- **content_types** – list of content_types
- **commands** – list of commands
- **regexp** –
- **func** –
- **chat_types** – True for private chat

Returns decorated function

register_inline_handler(*callback, func, pass_bot=False, **kwargs*)

Registers inline handler.

Parameters

- **pass_bot** –
- **callback** – function to be called
- **func** –

Returns decorated function

register_message_handler(*callback, content_types=None, commands=None, regexp=None, func=None, chat_types=None, pass_bot=False, **kwargs*)

Registers message handler.

Parameters

- **callback** – function to be called
- **content_types** – list of content_types
- **commands** – list of commands
- **regexp** –
- **func** –
- **chat_types** – True for private chat
- **pass_bot** – True if you want to get TeleBot instance in your handler

Returns decorated function

register_my_chat_member_handler(*callback, func=None, pass_bot=False, **kwargs*)

Registers my chat member handler.

Parameters

- **pass_bot** –
- **callback** – function to be called
- **func** –

Returns decorated function

register_poll_answer_handler(*callback, func, pass_bot=False, **kwargs*)

Registers poll answer handler.

Parameters

- **pass_bot** –
- **callback** – function to be called
- **func** –

Returns decorated function

register_poll_handler(*callback, func, pass_bot=False, **kwargs*)

Registers poll handler.

Parameters

- **pass_bot** –

- **callback** – function to be called
- **func** –

Returns decorated function

register_pre_checkout_query_handler(*callback, func, pass_bot=False, **kwargs*)

Registers pre-checkout request handler.

Parameters

- **pass_bot** –
- **callback** – function to be called
- **func** –

Returns decorated function

register_shipping_query_handler(*callback, func, pass_bot=False, **kwargs*)

Registers shipping query handler.

Parameters

- **pass_bot** –
- **callback** – function to be called
- **func** –

Returns decorated function

async remove_webhook()

Alternative for delete_webhook but uses set_webhook

async reply_to(*message: telebot.types.Message, text: str, **kwargs*) → *telebot.types.Message*

Convenience function for *send_message(message.chat.id, text, reply_to_message_id=message.message_id, **kwargs)*

Parameters

- **message** –
- **text** –
- **kwargs** –

Returns

async reset_data(*user_id: int, chat_id: Optional[int] = None*)

Reset data for a user in chat.

Parameters

- **user_id** –
- **chat_id** –

async restrict_chat_member(*chat_id: Union[int, str], user_id: int, until_date: Optional[Union[int, datetime.datetime]] = None, can_send_messages: Optional[bool] = None, can_send_media_messages: Optional[bool] = None, can_send_polls: Optional[bool] = None, can_send_other_messages: Optional[bool] = None, can_add_web_page_previews: Optional[bool] = None, can_change_info: Optional[bool] = None, can_invite_users: Optional[bool] = None, can_pin_messages: Optional[bool] = None*) → bool

Use this method to restrict a user in a supergroup. The bot must be an administrator in the supergroup for this to work and must have the appropriate admin rights. Pass True for all boolean parameters to lift restrictions from a user.

Telegram documentation: <https://core.telegram.org/bots/api#restrictchatmember>

Parameters

- **chat_id** – Int or String : Unique identifier for the target group or username of the target supergroup or channel (in the format @channelusername)
- **user_id** – Int : Unique identifier of the target user
- **until_date** – Date when restrictions will be lifted for the user, unix time. If user is restricted for more than 366 days or less than 30 seconds from the current time, they are considered to be restricted forever
- **can_send_messages** – Pass True, if the user can send text messages, contacts, locations and venues
- **can_send_media_messages** – Pass True, if the user can send audios, documents, photos, videos, video notes and voice notes, implies can_send_messages
- **can_send_polls** – Pass True, if the user is allowed to send polls, implies can_send_messages
- **can_send_other_messages** – Pass True, if the user can send animations, games, stickers and use inline bots, implies can_send_media_messages
- **can_add_web_page_previews** – Pass True, if the user may add web page previews to their messages, implies can_send_media_messages
- **can_change_info** – Pass True, if the user is allowed to change the chat title, photo and other settings. Ignored in public supergroups
- **can_invite_users** – Pass True, if the user is allowed to invite new users to the chat, implies can_invite_users
- **can_pin_messages** – Pass True, if the user is allowed to pin messages. Ignored in public supergroups

Returns True on success

retrieve_data(*user_id: int, chat_id: Optional[int] = None*)

async revoke_chat_invite_link(*chat_id: Union[int, str], invite_link: str*) → *telebot.types.ChatInviteLink*

Use this method to revoke an invite link created by the bot. Note: If the primary link is revoked, a new link is automatically generated. The bot must be an administrator in the chat for this to work and must have the appropriate admin rights.

Telegram documentation: <https://core.telegram.org/bots/api#revokechatinvitelink>

Parameters

- **chat_id** – Id: Unique identifier for the target chat or username of the target channel(in the format @channelusername)
- **invite_link** – The invite link to revoke

Returns API reply.

```
async send_animation(chat_id: Union[int, str], animation: Union[Any, str], duration: Optional[int] =
    None, width: Optional[int] = None, height: Optional[int] = None, thumb:
    Optional[Union[Any, str]] = None, caption: Optional[str] = None, parse_mode:
    Optional[str] = None, caption_entities:
    Optional[List[telebot.types.MessageEntity]] = None, disable_notification:
    Optional[bool] = None, protect_content: Optional[bool] = None,
    reply_to_message_id: Optional[int] = None, allow_sending_without_reply:
    Optional[bool] = None, reply_markup:
    Optional[Union[telebot.types.InlineKeyboardMarkup,
    telebot.types.ReplyKeyboardMarkup, telebot.types.ReplyKeyboardRemove,
    telebot.types.ForceReply]] = None, timeout: Optional[int] = None) →
    telebot.types.Message
```

Use this method to send animation files (GIF or H.264/MPEG-4 AVC video without sound).

Telegram documentation: <https://core.telegram.org/bots/api#sendanimation>

Parameters

- **chat_id** – Integer : Unique identifier for the message recipient — User or GroupChat id
- **animation** – InputFile or String : Animation to send. You can either pass a file_id as String to resend an animation that is already on the Telegram server
- **duration** – Integer : Duration of sent video in seconds
- **width** – Integer : Video width
- **height** – Integer : Video height
- **thumb** – InputFile or String : Thumbnail of the file sent
- **caption** – String : Animation caption (may also be used when resending animation by file_id).
- **parse_mode** –
- **protect_content** –
- **reply_to_message_id** –
- **reply_markup** –
- **disable_notification** –
- **timeout** –
- **caption_entities** –
- **allow_sending_without_reply** –

Returns

```
async send_audio(chat_id: Union[int, str], audio: Union[Any, str], caption: Optional[str] = None,
    duration: Optional[int] = None, performer: Optional[str] = None, title: Optional[str] =
    None, reply_to_message_id: Optional[int] = None, reply_markup:
    Optional[Union[telebot.types.InlineKeyboardMarkup,
    telebot.types.ReplyKeyboardMarkup, telebot.types.ReplyKeyboardRemove,
    telebot.types.ForceReply]] = None, parse_mode: Optional[str] = None,
    disable_notification: Optional[bool] = None, timeout: Optional[int] = None, thumb:
    Optional[Union[Any, str]] = None, caption_entities:
    Optional[List[telebot.types.MessageEntity]] = None, allow_sending_without_reply:
    Optional[bool] = None, protect_content: Optional[bool] = None) →
    telebot.types.Message
```

Use this method to send audio files, if you want Telegram clients to display them in the music player. Your audio must be in the .mp3 format.

Telegram documentation: <https://core.telegram.org/bots/api#sendaudio>

Parameters

- **chat_id** – Unique identifier for the message recipient
- **audio** – Audio file to send.
- **caption** –
- **duration** – Duration of the audio in seconds
- **performer** – Performer
- **title** – Track name
- **reply_to_message_id** – If the message is a reply, ID of the original message
- **reply_markup** –
- **parse_mode** –
- **disable_notification** –
- **timeout** –
- **thumb** –
- **caption_entities** –
- **allow_sending_without_reply** –
- **protect_content** –

Returns Message

async send_chat_action(*chat_id: Union[int, str], action: str, timeout: Optional[int] = None*) → bool

Use this method when you need to tell the user that something is happening on the bot's side. The status is set for 5 seconds or less (when a message arrives from your bot, Telegram clients clear its typing status).

Telegram documentation: <https://core.telegram.org/bots/api#sendchataction>

Parameters

- **chat_id** –
- **action** – One of the following strings: 'typing', 'upload_photo', 'record_video', 'upload_video', 'record_audio', 'upload_audio', 'upload_document', 'find_location', 'record_video_note', 'upload_video_note'.
- **timeout** –

Returns API reply. :type: boolean

async send_contact(*chat_id: Union[int, str], phone_number: str, first_name: str, last_name: Optional[str] = None, vcard: Optional[str] = None, disable_notification: Optional[bool] = None, reply_to_message_id: Optional[int] = None, reply_markup: Optional[Union[telebot.types.InlineKeyboardMarkup, telebot.types.ReplyKeyboardMarkup, telebot.types.ReplyKeyboardRemove, telebot.types.ForceReply]] = None, timeout: Optional[int] = None, allow_sending_without_reply: Optional[bool] = None, protect_content: Optional[bool] = None*) → *telebot.types.Message*

Use this method to send phone contacts.

Telegram documentation: <https://core.telegram.org/bots/api#sendcontact>

Parameters

- **chat_id** – Integer or String : Unique identifier for the target chat or username of the target channel
- **phone_number** – String : Contact's phone number
- **first_name** – String : Contact's first name
- **last_name** – String : Contact's last name
- **vcard** – String : Additional data about the contact in the form of a vCard, 0-2048 bytes
- **disable_notification** –
- **reply_to_message_id** –
- **reply_markup** –
- **timeout** –
- **allow_sending_without_reply** –
- **protect_content** –

```
async send_dice(chat_id: Union[int, str], emoji: Optional[str] = None, disable_notification:
Optional[bool] = None, reply_to_message_id: Optional[int] = None, reply_markup:
Optional[Union[telebot.types.InlineKeyboardMarkup,
telebot.types.ReplyKeyboardMarkup, telebot.types.ReplyKeyboardRemove,
telebot.types.ForceReply]] = None, timeout: Optional[int] = None,
allow_sending_without_reply: Optional[bool] = None, protect_content: Optional[bool]
= None) → telebot.types.Message
```

Use this method to send dices.

Telegram documentation: <https://core.telegram.org/bots/api#senddice>

Parameters

- **chat_id** –
- **emoji** –
- **disable_notification** –
- **reply_to_message_id** –
- **reply_markup** –
- **timeout** –
- **allow_sending_without_reply** –
- **protect_content** –

Returns Message

```

async send_document(chat_id: Union[int, str], document: Union[Any, str], reply_to_message_id:
    Optional[int] = None, caption: Optional[str] = None, reply_markup:
    Optional[Union[telebot.types.InlineKeyboardMarkup,
    telebot.types.ReplyKeyboardMarkup, telebot.types.ReplyKeyboardRemove,
    telebot.types.ForceReply]] = None, parse_mode: Optional[str] = None,
    disable_notification: Optional[bool] = None, timeout: Optional[int] = None, thumb:
    Optional[Union[Any, str]] = None, caption_entities:
    Optional[List[telebot.types.MessageEntity]] = None, allow_sending_without_reply:
    Optional[bool] = None, visible_file_name: Optional[str] = None,
    disable_content_type_detection: Optional[bool] = None, data:
    Optional[Union[Any, str]] = None, protect_content: Optional[bool] = None) →
    telebot.types.Message

```

Use this method to send general files.

Telegram documentation: <https://core.telegram.org/bots/api#senddocument>

Parameters

- **chat_id** – Unique identifier for the target chat or username of the target channel (in the format @channelusername)
- **document** – (document) File to send. Pass a file_id as String to send a file that exists on the Telegram servers (recommended), pass an HTTP URL as a String for Telegram to get a file from the Internet, or upload a new one using multipart/form-data
- **reply_to_message_id** – If the message is a reply, ID of the original message
- **caption** – Document caption (may also be used when resending documents by file_id), 0-1024 characters after entities parsing
- **reply_markup** –
- **parse_mode** – Mode for parsing entities in the document caption
- **disable_notification** – Sends the message silently. Users will receive a notification with no sound.
- **timeout** –
- **thumb** – InputFile or String : Thumbnail of the file sent; can be ignored if thumbnail generation for the file is supported server-side. The thumbnail should be in JPEG format and less than 200 kB in size. A thumbnail's width and height should not exceed 320. Ignored if the file is not uploaded using multipart/form-data. Thumbnails can't be reused and can be only uploaded as a new file, so you can pass "attach://<file_attach_name>" if the thumbnail was uploaded using multipart/form-data under <file_attach_name>
- **caption_entities** –
- **allow_sending_without_reply** –
- **visible_file_name** – allows to async define file name that will be visible in the Telegram instead of original file name
- **disable_content_type_detection** – Disables automatic server-side content type detection for files uploaded using multipart/form-data
- **data** – function typo compatibility: do not use it
- **protect_content** –

Returns API reply.

```
async send_game(chat_id: Union[int, str], game_short_name: str, disable_notification: Optional[bool] =
    None, reply_to_message_id: Optional[int] = None, reply_markup:
    Optional[Union[telebot.types.InlineKeyboardMarkup,
    telebot.types.ReplyKeyboardMarkup, telebot.types.ReplyKeyboardRemove,
    telebot.types.ForceReply]] = None, timeout: Optional[int] = None,
    allow_sending_without_reply: Optional[bool] = None, protect_content: Optional[bool]
    = None) → telebot.types.Message
```

Used to send the game.

Telegram documentation: <https://core.telegram.org/bots/api#sendgame>

Parameters

- **chat_id** –
- **game_short_name** –
- **disable_notification** –
- **reply_to_message_id** –
- **reply_markup** –
- **timeout** –
- **allow_sending_without_reply** –
- **protect_content** –

Returns

```
async send_invoice(chat_id: Union[int, str], title: str, description: str, invoice_payload: str,
    provider_token: str, currency: str, prices: List[telebot.types.LabeledPrice],
    start_parameter: Optional[str] = None, photo_url: Optional[str] = None, photo_size:
    Optional[int] = None, photo_width: Optional[int] = None, photo_height:
    Optional[int] = None, need_name: Optional[bool] = None, need_phone_number:
    Optional[bool] = None, need_email: Optional[bool] = None,
    need_shipping_address: Optional[bool] = None, send_phone_number_to_provider:
    Optional[bool] = None, send_email_to_provider: Optional[bool] = None, is_flexible:
    Optional[bool] = None, disable_notification: Optional[bool] = None,
    reply_to_message_id: Optional[int] = None, reply_markup:
    Optional[Union[telebot.types.InlineKeyboardMarkup,
    telebot.types.ReplyKeyboardMarkup, telebot.types.ReplyKeyboardRemove,
    telebot.types.ForceReply]] = None, provider_data: Optional[str] = None, timeout:
    Optional[int] = None, allow_sending_without_reply: Optional[bool] = None,
    max_tip_amount: Optional[int] = None, suggested_tip_amounts: Optional[List[int]]
    = None, protect_content: Optional[bool] = None) → telebot.types.Message
```

Sends invoice.

Telegram documentation: <https://core.telegram.org/bots/api#sendinvoice>

Parameters

- **chat_id** – Unique identifier for the target private chat
- **title** – Product name
- **description** – Product description
- **invoice_payload** – Bot-async defined invoice payload, 1-128 bytes. This will not be displayed to the user, use for your internal processes.
- **provider_token** – Payments provider token, obtained via @Botfather

- **currency** – Three-letter ISO 4217 currency code, see <https://core.telegram.org/bots/payments#supported-currencies>
- **prices** – Price breakdown, a list of components (e.g. product price, tax, discount, delivery cost, delivery tax, bonus, etc.)
- **start_parameter** – Unique deep-linking parameter that can be used to generate this invoice when used as a start parameter
- **photo_url** – URL of the product photo for the invoice. Can be a photo of the goods or a marketing image for a service. People like it better when they see what they are paying for.
- **photo_size** – Photo size
- **photo_width** – Photo width
- **photo_height** – Photo height
- **need_name** – Pass True, if you require the user's full name to complete the order
- **need_phone_number** – Pass True, if you require the user's phone number to complete the order
- **need_email** – Pass True, if you require the user's email to complete the order
- **need_shipping_address** – Pass True, if you require the user's shipping address to complete the order
- **is_flexible** – Pass True, if the final price depends on the shipping method
- **send_phone_number_to_provider** – Pass True, if user's phone number should be sent to provider
- **send_email_to_provider** – Pass True, if user's email address should be sent to provider
- **disable_notification** – Sends the message silently. Users will receive a notification with no sound.
- **reply_to_message_id** – If the message is a reply, ID of the original message
- **reply_markup** – A JSON-serialized object for an inline keyboard. If empty, one 'Pay total price' button will be shown. If not empty, the first button must be a Pay button
- **provider_data** – A JSON-serialized data about the invoice, which will be shared with the payment provider. A detailed description of required fields should be provided by the payment provider.
- **timeout** –
- **allow_sending_without_reply** –
- **max_tip_amount** – The maximum accepted amount for tips in the smallest units of the currency
- **suggested_tip_amounts** – A JSON-serialized array of suggested amounts of tips in the smallest units of the currency. At most 4 suggested tip amounts can be specified. The suggested tip amounts must be positive, passed in a strictly increased order and must not exceed max_tip_amount.
- **protect_content** –

Returns

```
async send_location(chat_id: Union[int, str], latitude: float, longitude: float, live_period: Optional[int]
                    = None, reply_to_message_id: Optional[int] = None, reply_markup:
                    Optional[Union[telebot.types.InlineKeyboardMarkup,
                    telebot.types.ReplyKeyboardMarkup, telebot.types.ReplyKeyboardRemove,
                    telebot.types.ForceReply]] = None, disable_notification: Optional[bool] = None,
                    timeout: Optional[int] = None, horizontal_accuracy: Optional[float] = None,
                    heading: Optional[int] = None, proximity_alert_radius: Optional[int] = None,
                    allow_sending_without_reply: Optional[bool] = None, protect_content:
                    Optional[bool] = None) → telebot.types.Message
```

Use this method to send point on the map.

Telegram documentation: <https://core.telegram.org/bots/api#sendlocation>

Parameters

- **chat_id** –
- **latitude** –
- **longitude** –
- **live_period** –
- **reply_to_message_id** –
- **reply_markup** –
- **disable_notification** –
- **timeout** –
- **horizontal_accuracy** –
- **heading** –
- **proximity_alert_radius** –
- **allow_sending_without_reply** –
- **protect_content** –

Returns API reply.

```
async send_media_group(chat_id: Union[int, str], media: List[Union[telebot.types.InputMediaAudio,
                    telebot.types.InputMediaDocument, telebot.types.InputMediaPhoto,
                    telebot.types.InputMediaVideo]], disable_notification: Optional[bool] = None,
                    protect_content: Optional[bool] = None, reply_to_message_id: Optional[int] =
                    None, timeout: Optional[int] = None, allow_sending_without_reply:
                    Optional[bool] = None) → List[telebot.types.Message]
```

send a group of photos or videos as an album. On success, an array of the sent Messages is returned.

Telegram documentation: <https://core.telegram.org/bots/api#sendmediagroup>

Parameters

- **chat_id** –
- **media** –
- **disable_notification** –
- **reply_to_message_id** –
- **timeout** –
- **allow_sending_without_reply** –

- **protect_content** –

Returns

async send_message(*chat_id: Union[int, str], text: str, parse_mode: Optional[str] = None, entities: Optional[List[telebot.types.MessageEntity]] = None, disable_web_page_preview: Optional[bool] = None, disable_notification: Optional[bool] = None, protect_content: Optional[bool] = None, reply_to_message_id: Optional[int] = None, allow_sending_without_reply: Optional[bool] = None, reply_markup: Optional[Union[telebot.types.InlineKeyboardMarkup, telebot.types.ReplyKeyboardMarkup, telebot.types.ReplyKeyboardRemove, telebot.types.ForceReply]] = None, timeout: Optional[int] = None*) → *telebot.types.Message*

Use this method to send text messages.

Warning: Do not send more than about 4000 characters each message, otherwise you'll risk an HTTP 414 error. If you must send more than 4000 characters, use the *split_string* or *smart_split* function in *util.py*.

Telegram documentation: <https://core.telegram.org/bots/api#sendmessage>

Parameters

- **chat_id** –
- **text** –
- **disable_web_page_preview** –
- **reply_to_message_id** –
- **reply_markup** –
- **parse_mode** –
- **disable_notification** – Boolean, Optional. Sends the message silently.
- **timeout** –
- **entities** –
- **allow_sending_without_reply** –
- **protect_content** –

Returns API reply.

async send_photo(*chat_id: Union[int, str], photo: Union[Any, str], caption: Optional[str] = None, parse_mode: Optional[str] = None, caption_entities: Optional[List[telebot.types.MessageEntity]] = None, disable_notification: Optional[bool] = None, protect_content: Optional[bool] = None, reply_to_message_id: Optional[int] = None, allow_sending_without_reply: Optional[bool] = None, reply_markup: Optional[Union[telebot.types.InlineKeyboardMarkup, telebot.types.ReplyKeyboardMarkup, telebot.types.ReplyKeyboardRemove, telebot.types.ForceReply]] = None, timeout: Optional[int] = None*) → *telebot.types.Message*

Use this method to send photos.

Telegram documentation: <https://core.telegram.org/bots/api#sendphoto>

Parameters

- **chat_id** –
- **photo** –

- `caption` –
- `parse_mode` –
- `disable_notification` –
- `reply_to_message_id` –
- `reply_markup` –
- `timeout` –
- `caption_entities` –
- `allow_sending_without_reply` –
- `protect_content` –

Returns API reply.

```
async send_poll(chat_id: Union[int, str], question: str, options: List[str], is_anonymous: Optional[bool]
               = None, type: Optional[str] = None, allows_multiple_answers: Optional[bool] = None,
               correct_option_id: Optional[int] = None, explanation: Optional[str] = None,
               explanation_parse_mode: Optional[str] = None, open_period: Optional[int] = None,
               close_date: Optional[Union[int, datetime.datetime]] = None, is_closed: Optional[bool]
               = None, disable_notification: Optional[bool] = False, reply_to_message_id:
               Optional[int] = None, reply_markup:
               Optional[Union[telebot.types.InlineKeyboardMarkup,
                             telebot.types.ReplyKeyboardMarkup, telebot.types.ReplyKeyboardRemove,
                             telebot.types.ForceReply]] = None, allow_sending_without_reply: Optional[bool] =
               None, timeout: Optional[int] = None, explanation_entities:
               Optional[List[telebot.types.MessageEntity]] = None, protect_content: Optional[bool] =
               None) → telebot.types.Message
```

Send polls.

Telegram documentation: <https://core.telegram.org/bots/api#sendpoll>

Parameters

- `chat_id` –
- `question` –
- `options` – array of str with answers
- `is_anonymous` –
- `type` –
- `allows_multiple_answers` –
- `correct_option_id` –
- `explanation` –
- `explanation_parse_mode` –
- `open_period` –
- `close_date` –
- `is_closed` –
- `disable_notification` –
- `reply_to_message_id` –

- **allow_sending_without_reply** –
- **reply_markup** –
- **timeout** –
- **explanation_entities** –
- **protect_content** –

Returns

async send_sticker(*chat_id: Union[int, str], sticker: Union[Any, str], reply_to_message_id: Optional[int] = None, reply_markup: Optional[Union[telebot.types.InlineKeyboardMarkup, telebot.types.ReplyKeyboardMarkup, telebot.types.ReplyKeyboardRemove, telebot.types.ForceReply]] = None, disable_notification: Optional[bool] = None, timeout: Optional[int] = None, allow_sending_without_reply: Optional[bool] = None, protect_content: Optional[bool] = None, data: Optional[Union[Any, str]] = None*) → *telebot.types.Message*

Use this method to send .webp stickers.

Telegram documentation: <https://core.telegram.org/bots/api#sendsticker>

Parameters

- **chat_id** –
- **sticker** –
- **reply_to_message_id** –
- **reply_markup** –
- **disable_notification** – to disable the notification
- **timeout** – timeout
- **allow_sending_without_reply** –
- **protect_content** –
- **data** – deprecated, for backward compatibility

Returns API reply.

async send_venue(*chat_id: Union[int, str], latitude: float, longitude: float, title: str, address: str, foursquare_id: Optional[str] = None, foursquare_type: Optional[str] = None, disable_notification: Optional[bool] = None, reply_to_message_id: Optional[int] = None, reply_markup: Optional[Union[telebot.types.InlineKeyboardMarkup, telebot.types.ReplyKeyboardMarkup, telebot.types.ReplyKeyboardRemove, telebot.types.ForceReply]] = None, timeout: Optional[int] = None, allow_sending_without_reply: Optional[bool] = None, google_place_id: Optional[str] = None, google_place_type: Optional[str] = None, protect_content: Optional[bool] = None*) → *telebot.types.Message*

Use this method to send information about a venue.

Telegram documentation: <https://core.telegram.org/bots/api#sendvenue>

Parameters

- **chat_id** – Integer or String : Unique identifier for the target chat or username of the target channel
- **latitude** – Float : Latitude of the venue

- **longitude** – Float : Longitude of the venue
- **title** – String : Name of the venue
- **address** – String : Address of the venue
- **foursquare_id** – String : Foursquare identifier of the venue
- **foursquare_type** – Foursquare type of the venue, if known. (For example, “arts_entertainment/async default”, “arts_entertainment/aquarium” or “food/icecream”.)
- **disable_notification** –
- **reply_to_message_id** –
- **reply_markup** –
- **timeout** –
- **allow_sending_without_reply** –
- **google_place_id** –
- **google_place_type** –
- **protect_content** –

Returns

async send_video(*chat_id: Union[int, str], video: Union[Any, str], duration: Optional[int] = None, width: Optional[int] = None, height: Optional[int] = None, thumb: Optional[Union[Any, str]] = None, caption: Optional[str] = None, parse_mode: Optional[str] = None, caption_entities: Optional[List[telebot.types.MessageEntity]] = None, supports_streaming: Optional[bool] = None, disable_notification: Optional[bool] = None, protect_content: Optional[bool] = None, reply_to_message_id: Optional[int] = None, allow_sending_without_reply: Optional[bool] = None, reply_markup: Optional[Union[telebot.types.InlineKeyboardMarkup, telebot.types.ReplyKeyboardMarkup, telebot.types.ReplyKeyboardRemove, telebot.types.ForceReply]] = None, timeout: Optional[int] = None, data: Optional[Union[Any, str]] = None*) → *telebot.types.Message*

Use this method to send video files, Telegram clients support mp4 videos (other formats may be sent as Document).

Telegram documentation: <https://core.telegram.org/bots/api#sendvideo>

Parameters

- **chat_id** – Unique identifier for the target chat or username of the target channel (in the format @channelusername)
- **video** – Video to send. You can either pass a `file_id` as String to resend a video that is already on the Telegram servers, or upload a new video file using multipart/form-data.
- **duration** – Duration of sent video in seconds
- **width** – Video width
- **height** – Video height
- **thumb** – Thumbnail of the file sent; can be ignored if thumbnail generation for the file is supported server-side. The thumbnail should be in JPEG format and less than 200 kB in size. A thumbnail’s width and height should not exceed 320. Ignored if the file is not uploaded using multipart/form-data. Thumbnails can’t be reused and can be only uploaded as a new file, so you can pass “attach://<file_attach_name>” if the thumbnail was uploaded using multipart/form-data under <file_attach_name>.

- **caption** – Video caption (may also be used when resending videos by file_id), 0-1024 characters after entities parsing
- **parse_mode** – Mode for parsing entities in the video caption
- **caption_entities** –
- **supports_streaming** – Pass True, if the uploaded video is suitable for streaming
- **disable_notification** – Sends the message silently. Users will receive a notification with no sound.
- **protect_content** –
- **reply_to_message_id** – If the message is a reply, ID of the original message
- **allow_sending_without_reply** –
- **reply_markup** –
- **timeout** –
- **data** – deprecated, for backward compatibility

```

async send_video_note(chat_id: Union[int, str], data: Union[Any, str], duration: Optional[int] = None,
    length: Optional[int] = None, reply_to_message_id: Optional[int] = None,
    reply_markup: Optional[Union[telebot.types.InlineKeyboardMarkup,
    telebot.types.ReplyKeyboardMarkup, telebot.types.ReplyKeyboardRemove,
    telebot.types.ForceReply]] = None, disable_notification: Optional[bool] = None,
    timeout: Optional[int] = None, thumb: Optional[Union[Any, str]] = None,
    allow_sending_without_reply: Optional[bool] = None, protect_content:
    Optional[bool] = None) → telebot.types.Message

```

As of v.4.0, Telegram clients support rounded square mp4 videos of up to 1 minute long. Use this method to send video messages.

Telegram documentation: <https://core.telegram.org/bots/api#sendvideonote>

Parameters

- **chat_id** – Integer : Unique identifier for the message recipient — User or GroupChat id
- **data** – InputFile or String : Video note to send. You can either pass a file_id as String to resend a video that is already on the Telegram server
- **duration** – Integer : Duration of sent video in seconds
- **length** – Integer : Video width and height, Can't be None and should be in range of (0, 640)
- **reply_to_message_id** –
- **reply_markup** –
- **disable_notification** –
- **timeout** –
- **thumb** – InputFile or String : Thumbnail of the file sent
- **allow_sending_without_reply** –
- **protect_content** –

Returns

```
async send_voice(chat_id: Union[int, str], voice: Union[Any, str], caption: Optional[str] = None,
                  duration: Optional[int] = None, reply_to_message_id: Optional[int] = None,
                  reply_markup: Optional[Union[telebot.types.InlineKeyboardMarkup,
                  telebot.types.ReplyKeyboardMarkup, telebot.types.ReplyKeyboardRemove,
                  telebot.types.ForceReply]] = None, parse_mode: Optional[str] = None,
                  disable_notification: Optional[bool] = None, timeout: Optional[int] = None,
                  caption_entities: Optional[List[telebot.types.MessageEntity]] = None,
                  allow_sending_without_reply: Optional[bool] = None, protect_content: Optional[bool]
                  = None) → telebot.types.Message
```

Use this method to send audio files, if you want Telegram clients to display the file as a playable voice message.

Telegram documentation: <https://core.telegram.org/bots/api#sendvoice>

Parameters

- **chat_id** – Unique identifier for the message recipient.
- **voice** –
- **caption** –
- **duration** – Duration of sent audio in seconds
- **reply_to_message_id** –
- **reply_markup** –
- **parse_mode** –
- **disable_notification** –
- **timeout** –
- **caption_entities** –
- **allow_sending_without_reply** –
- **protect_content** –

Returns Message

```
async set_chat_administrator_custom_title(chat_id: Union[int, str], user_id: int, custom_title: str)
                                         → bool
```

Use this method to set a custom title for an administrator in a supergroup promoted by the bot.

Telegram documentation: <https://core.telegram.org/bots/api#setchatadministratorcustomtitle>

Parameters

- **chat_id** – Unique identifier for the target chat or username of the target supergroup (in the format @supergroupusername)
- **user_id** – Unique identifier of the target user
- **custom_title** – New custom title for the administrator; 0-16 characters, emoji are not allowed

Returns True on success.

```
async set_chat_description(chat_id: Union[int, str], description: Optional[str] = None) → bool
```

Use this method to change the description of a supergroup or a channel. The bot must be an administrator in the chat for this to work and must have the appropriate admin rights.

Telegram documentation: <https://core.telegram.org/bots/api#setchatdescription>

Parameters

- **chat_id** – Int or Str: Unique identifier for the target chat or username of the target channel (in the format @channelusername)
- **description** – Str: New chat description, 0-255 characters

Returns True on success.

async set_chat_permissions(*chat_id: Union[int, str]*, *permissions: telebot.types.ChatPermissions*) → bool

Use this method to set async default chat permissions for all members. The bot must be an administrator in the group or a supergroup for this to work and must have the can_restrict_members admin rights.

Telegram documentation: <https://core.telegram.org/bots/api#setchatpermissions>

Parameters

- **chat_id** – Unique identifier for the target chat or username of the target supergroup (in the format @supergroupusername)
- **permissions** – New async default chat permissions

Returns True on success

async set_chat_photo(*chat_id: Union[int, str]*, *photo: Any*) → bool

Use this method to set a new profile photo for the chat. Photos can't be changed for private chats. The bot must be an administrator in the chat for this to work and must have the appropriate admin rights. Returns True on success. Note: In regular groups (non-supergroups), this method will only work if the 'All Members Are Admins' setting is off in the target group.

Telegram documentation: <https://core.telegram.org/bots/api#setchatphoto>

Parameters

- **chat_id** – Int or Str: Unique identifier for the target chat or username of the target channel (in the format @channelusername)
- **photo** – InputFile: New chat photo, uploaded using multipart/form-data

Returns

async set_chat_sticker_set(*chat_id: Union[int, str]*, *sticker_set_name: str*) → *telebot.types.StickerSet*

Use this method to set a new group sticker set for a supergroup. The bot must be an administrator in the chat for this to work and must have the appropriate admin rights. Use the field can_set_sticker_set optionally returned in getChat requests to check if the bot can use this method. Returns True on success.

Telegram documentation: <https://core.telegram.org/bots/api#setchatstickerset>

Parameters

- **chat_id** – Unique identifier for the target chat or username of the target supergroup (in the format @supergroupusername)
- **sticker_set_name** – Name of the sticker set to be set as the group sticker set

Returns API reply.

async set_chat_title(*chat_id: Union[int, str]*, *title: str*) → bool

Use this method to change the title of a chat. Titles can't be changed for private chats. The bot must be an administrator in the chat for this to work and must have the appropriate admin rights. Returns True on success. Note: In regular groups (non-supergroups), this method will only work if the 'All Members Are Admins' setting is off in the target group.

Telegram documentation: <https://core.telegram.org/bots/api#setchattitle>

Parameters

- **chat_id** – Int or Str: Unique identifier for the target chat or username of the target channel (in the format @channelusername)
- **title** – New chat title, 1-255 characters

Returns

async set_game_score(*user_id: Union[int, str], score: int, force: Optional[bool] = None, chat_id: Optional[Union[int, str]] = None, message_id: Optional[int] = None, inline_message_id: Optional[str] = None, disable_edit_message: Optional[bool] = None*) → Union[*telebot.types.Message*, bool]

Sets the value of points in the game to a specific user.

Telegram documentation: <https://core.telegram.org/bots/api#setgamescore>

Parameters

- **user_id** –
- **score** –
- **force** –
- **chat_id** –
- **message_id** –
- **inline_message_id** –
- **disable_edit_message** –

Returns

async set_my_commands(*commands: List[telebot.types.BotCommand], scope: Optional[telebot.types.BotCommandScope] = None, language_code: Optional[str] = None*) → bool

Use this method to change the list of the bot's commands.

Telegram documentation: <https://core.telegram.org/bots/api#setmycommands>

Parameters

- **commands** – List of BotCommand. At most 100 commands can be specified.
- **scope** – The scope of users for which the commands are relevant. `async` defaults to BotCommandScopeAsync default.
- **language_code** – A two-letter ISO 639-1 language code. If empty, commands will be applied to all users from the given scope, for whose language there are no dedicated commands

Returns

async set_state(*user_id: int, state: str, chat_id: Optional[int] = None*)

Sets a new state of a user.

Parameters

- **user_id** –
- **chat_id** –
- **state** – new state. can be string or integer.

async set_sticker_position_in_set(*sticker: str, position: int*) → bool

Use this method to move a sticker in a set created by the bot to a specific position . Returns True on success.

Telegram documentation: <https://core.telegram.org/bots/api#setstickerpositioninset>

Parameters

- **sticker** –
- **position** –

Returns

async set_sticker_set_thumb(*name: str, user_id: int, thumb: Optional[Union[Any, str]] = None*)

Use this method to set the thumbnail of a sticker set. Animated thumbnails can be set for animated sticker sets only. Returns True on success.

Telegram documentation: <https://core.telegram.org/bots/api#setstickersetthumb>

Parameters

- **name** – Sticker set name
- **user_id** – User identifier
- **thumb** – A PNG image with the thumbnail, must be up to 128 kilobytes in size and have width and height exactly 100px, or a TGS animation with the thumbnail up to 32 kilobytes in size; see https://core.telegram.org/animated_stickers#technical-requirements

set_update_listener(*func*)

Update listener is a function that gets any update.

Parameters **func** – function that should get update.

async set_webhook(*url=None, certificate=None, max_connections=None, allowed_updates=None, ip_address=None, drop_pending_updates=None, timeout=None*)

Use this method to specify a url and receive incoming updates via an outgoing webhook. Whenever there is an update for the bot, we will send an HTTPS POST request to the specified url, containing a JSON-serialized Update. In case of an unsuccessful request, we will give up after a reasonable amount of attempts. Returns True on success.

Telegram documentation: <https://core.telegram.org/bots/api#setwebhook>

Parameters

- **url** – HTTPS url to send updates to. Use an empty string to remove webhook integration
- **certificate** – Upload your public key certificate so that the root certificate in use can be checked. See our self-signed guide for details.
- **max_connections** – Maximum allowed number of simultaneous HTTPS connections to the webhook for update delivery, 1-100. Defaults to 40. Use lower values to limit the load on your bot's server, and higher values to increase your bot's throughput.
- **allowed_updates** – A JSON-serialized list of the update types you want your bot to receive. For example, specify ["message", "edited_channel_post", "callback_query"] to only receive updates of these types. See Update for a complete list of available update types. Specify an empty list to receive all updates regardless of type (default). If not specified, the previous setting will be used.
- **ip_address** – The fixed IP address which will be used to send webhook requests instead of the IP address resolved through DNS
- **drop_pending_updates** – Pass True to drop all pending updates

- **timeout** – Integer. Request connection timeout

Returns**setup_middleware**(*middleware*)

Setup middleware.

Parameters **middleware** – Middleware-class.**Returns****shipping_query_handler**(*func, **kwargs*)

Shipping request handler.

Parameters

- **func** –
- **kwargs** –

Returns**async skip_updates**()

Skip existing updates. Only last update will remain on server.

async stop_message_live_location(*chat_id: Optional[Union[int, str]] = None, message_id: Optional[int] = None, inline_message_id: Optional[str] = None, reply_markup: Optional[Union[telebot.types.InlineKeyboardMarkup, telebot.types.ReplyKeyboardMarkup, telebot.types.ReplyKeyboardRemove, telebot.types.ForceReply]] = None, timeout: Optional[int] = None*) → *telebot.types.Message*

Use this method to stop updating a live location message sent by the bot or via the bot (for inline bots) before live_period expires.

Telegram documentation: <https://core.telegram.org/bots/api#stopmessagelivelocation>**Parameters**

- **chat_id** –
- **message_id** –
- **inline_message_id** –
- **reply_markup** –
- **timeout** –

Returns**async stop_poll**(*chat_id: Union[int, str], message_id: int, reply_markup: Optional[Union[telebot.types.InlineKeyboardMarkup, telebot.types.ReplyKeyboardMarkup, telebot.types.ReplyKeyboardRemove, telebot.types.ForceReply]] = None*) → *telebot.types.Poll*

Stops poll.

Telegram documentation: <https://core.telegram.org/bots/api#stoppoll>**Parameters**

- **chat_id** –
- **message_id** –

- **reply_markup** –

Returns

async unban_chat_member(*chat_id: Union[int, str], user_id: int, only_if_banned: Optional[bool] = False*) → bool

Use this method to unban a previously kicked user in a supergroup or channel. The user will not return to the group or channel automatically, but will be able to join via link, etc. The bot must be an administrator for this to work. By async default, this method guarantees that after the call the user is not a member of the chat, but will be able to join it. So if the user is a member of the chat they will also be removed from the chat. If you don't want this, use the parameter `only_if_banned`.

Telegram documentation: <https://core.telegram.org/bots/api#unbanchatmember>

Parameters

- **chat_id** – Unique identifier for the target group or username of the target supergroup or channel (in the format @username)
- **user_id** – Unique identifier of the target user
- **only_if_banned** – Do nothing if the user is not banned

Returns True on success

async unban_chat_sender_chat(*chat_id: Union[int, str], sender_chat_id: Union[int, str]*) → bool

Use this method to unban a previously banned channel chat in a supergroup or channel. The bot must be an administrator for this to work and must have the appropriate administrator rights. Returns True on success.

Telegram documentation: <https://core.telegram.org/bots/api#unbanchatsenderchat>

Params

Parameters

- **chat_id** – Unique identifier for the target chat or username of the target channel (in the format @channelusername)
- **sender_chat_id** – Unique identifier of the target sender chat

Returns True on success.

async unpin_all_chat_messages(*chat_id: Union[int, str]*) → bool

Use this method to unpin a all pinned messages in a supergroup chat. The bot must be an administrator in the chat for this to work and must have the appropriate admin rights. Returns True on success.

Telegram documentation: <https://core.telegram.org/bots/api#unpinallchatmessages>

Parameters **chat_id** – Int or Str: Unique identifier for the target chat or username of the target channel (in the format @channelusername)

Returns

async unpin_chat_message(*chat_id: Union[int, str], message_id: Optional[int] = None*) → bool

Use this method to unpin specific pinned message in a supergroup chat. The bot must be an administrator in the chat for this to work and must have the appropriate admin rights. Returns True on success.

Telegram documentation: <https://core.telegram.org/bots/api#unpinchatmessage>

Parameters

- **chat_id** – Int or Str: Unique identifier for the target chat or username of the target channel (in the format @channelusername)
- **message_id** – Int: Identifier of a message to unpin

Returns

async upload_sticker_file(*user_id: int, png_sticker: Union[Any, str]*) → *telebot.types.File*

Use this method to upload a .png file with a sticker for later use in `createNewStickerSet` and `addStickerToSet` methods (can be used multiple times). Returns the uploaded File on success.

Telegram documentation: <https://core.telegram.org/bots/api#uploadstickerfile>

Parameters

- **user_id** –
- **png_sticker** –

Returns

class telebot.async_telebot.**ExceptionHandler**

Bases: object

Class for handling exceptions while Polling

handle(*exception*)

class telebot.async_telebot.**Handler**(*callback, *args, **kwargs*)

Bases: object

Class for (next step|reply) handlers

telebot.async_telebot.**REPLY_MARKUP_TYPES**

telebot

Type Module

alias of Union[*telebot.types.InlineKeyboardMarkup*, *telebot.types.ReplyKeyboardMarkup*, *telebot.types.ReplyKeyboardRemove*, *telebot.types.ForceReply*]

Asyncio filters

class telebot.asyncio_filters.**AdvancedCustomFilter**

Bases: abc.ABC

Simple Custom Filter base class. Create child class with `check()` method. Accepts two parameters, returns bool: True - filter passed, False - filter failed. message: Message class text: Filter value given in handler

async check(*message, text*)

Perform a check.

class telebot.asyncio_filters.**ChatFilter**

Bases: *telebot.asyncio_filters.AdvancedCustomFilter*

Check whether chat_id corresponds to given chat_id.

Example: `@bot.message_handler(chat_id=[99999])`

async check(*message, text*)

Perform a check.

key = 'chat_id'

class telebot.asyncio_filters.ForwardFilterBases: *telebot.asyncio_filters.SimpleCustomFilter*

Check whether message was forwarded from channel or group.

Example:

@bot.message_handler(is_forwarded=True)

async check(message)

Perform a check.

key = 'is_forwarded'**class telebot.asyncio_filters.IsAdminFilter(bot)**Bases: *telebot.asyncio_filters.SimpleCustomFilter*

Check whether the user is administrator / owner of the chat.

Example: @bot.message_handler(chat_types=['supergroup'], is_chat_admin=True)

async check(message)

Perform a check.

key = 'is_chat_admin'**class telebot.asyncio_filters.IsDigitFilter**Bases: *telebot.asyncio_filters.SimpleCustomFilter*

Filter to check whether the string is made up of only digits.

Example: @bot.message_handler(is_digit=True)

async check(message)

Perform a check.

key = 'is_digit'**class telebot.asyncio_filters.IsReplyFilter**Bases: *telebot.asyncio_filters.SimpleCustomFilter*

Check whether message is a reply.

Example:

@bot.message_handler(is_reply=True)

async check(message)

Perform a check.

key = 'is_reply'**class telebot.asyncio_filters.LanguageFilter**Bases: *telebot.asyncio_filters.AdvancedCustomFilter*

Check users language_code.

Example:

@bot.message_handler(language_code=['ru'])

async check(message, text)

Perform a check.

key = 'language_code'

class telebot.asyncio_filters.SimpleCustomFilter

Bases: abc.ABC

Simple Custom Filter base class. Create child class with check() method. Accepts only message, returns bool value, that is compared with given in handler.

async check(message)

Perform a check.

class telebot.asyncio_filters.StateFilter(bot)

Bases: *telebot.asyncio_filters.AdvancedCustomFilter*

Filter to check state.

Example: @bot.message_handler(state=1)

async check(message, text)

Perform a check.

key = 'state'

class telebot.asyncio_filters.TextContainsFilter

Bases: *telebot.asyncio_filters.AdvancedCustomFilter*

Filter to check Text message. key: text

Example: # Will respond if any message.text contains word 'account'
@bot.message_handler(text_contains=['account'])

async check(message, text)

Perform a check.

key = 'text_contains'

class telebot.asyncio_filters.TextFilter(equals: Optional[str] = None, contains: Optional[Union[list, tuple]] = None, starts_with: Optional[Union[str, list, tuple]] = None, ends_with: Optional[Union[str, list, tuple]] = None, ignore_case: bool = False)

Bases: object

Advanced text filter to check (types.Message, types.CallbackQuery, types.InlineQuery, types.Poll)

example of usage is in examples/custom_filters/advanced_text_filter.py

async check(obj: Union[telebot.types.Message, telebot.types.CallbackQuery, telebot.types.InlineQuery, telebot.types.Poll])

class telebot.asyncio_filters.TextMatchFilter

Bases: *telebot.asyncio_filters.AdvancedCustomFilter*

Filter to check Text message. key: text

Example: @bot.message_handler(text=['account'])

async check(message, text)

Perform a check.

key = 'text'

class telebot.asyncio_filters.TextStartsFilterBases: [telebot.asyncio_filters.AdvancedCustomFilter](#)

Filter to check whether message starts with some text.

Example: # Will work if message.text starts with 'Sir'. @bot.message_handler(text_startswith='Sir')

async check(*message, text*)

Perform a check.

key = 'text_startswith'**Asynchronous storage for states****class telebot.asyncio_storage.StateContext**(*obj, chat_id, user_id*)

Bases: object

Class for data.

class telebot.asyncio_storage.StateMemoryStorageBases: [telebot.asyncio_storage.base_storage.StateStorageBase](#)**async delete_state**(*chat_id, user_id*)

Delete state for a particular user.

async get_data(*chat_id, user_id*)

Get data for a user in a particular chat.

get_interactive_data(*chat_id, user_id*)**async get_state**(*chat_id, user_id*)**async reset_data**(*chat_id, user_id*)

Reset data for a particular user in a chat.

async save(*chat_id, user_id, data*)**async set_data**(*chat_id, user_id, key, value*)

Set data for a user in a particular chat.

async set_state(*chat_id, user_id, state*)

Set state for a particular user.

! Note that you should create a record if it does not exist, and if a record with state already exists, you need to update a record.

class telebot.asyncio_storage.StatePickleStorage(*file_path='./.state-save/states.pkl'*)Bases: [telebot.asyncio_storage.base_storage.StateStorageBase](#)**async convert_old_to_new**()**create_dir**()

Create directory .save-handlers.

async delete_state(*chat_id, user_id*)

Delete state for a particular user.

async get_data(*chat_id, user_id*)

Get data for a user in a particular chat.

get_interactive_data(*chat_id, user_id*)

async get_state(*chat_id, user_id*)

read()

async reset_data(*chat_id, user_id*)

Reset data for a particular user in a chat.

async save(*chat_id, user_id, data*)

async set_data(*chat_id, user_id, key, value*)

Set data for a user in a particular chat.

async set_state(*chat_id, user_id, state*)

Set state for a particular user.

! Note that you should create a record if it does not exist, and if a record with state already exists, you need to update a record.

update_data()

class telebot.asyncio_storage.StateRedisStorage(*host='localhost', port=6379, db=0, password=None, prefix='telebot_'*)

Bases: [telebot.asyncio_storage.base_storage.StateStorageBase](#)

This class is for Redis storage. This will work only for states. To use it, just pass this class to: TeleBot(storage=StateRedisStorage())

async delete_record(*key*)

Function to delete record from database. It has nothing to do with states. Made for backend compatibility

async delete_state(*chat_id, user_id*)

Delete state for a particular user in a chat.

async get_data(*chat_id, user_id*)

Get data of particular user in a particular chat.

get_interactive_data(*chat_id, user_id*)

Get Data in interactive way. You can use with() with this function.

async get_record(*key*)

Function to get record from database. It has nothing to do with states. Made for backend compatibility

async get_state(*chat_id, user_id*)

Get state of a user in a chat.

async get_value(*chat_id, user_id, key*)

Get value for a data of a user in a chat.

async reset_data(*chat_id, user_id*)

Reset data of a user in a chat.

async save(*chat_id, user_id, data*)

async set_data(*chat_id, user_id, key, value*)

Set data without interactive data.

async set_record(*key, value*)

Function to set record to database. It has nothing to do with states. Made for backend compatibility

async set_state(*chat_id, user_id, state*)

Set state for a particular user in a chat.

class telebot.asyncio_storage.**StateStorageBase**

Bases: object

async delete_state(*chat_id, user_id*)

Delete state for a particular user.

async get_data(*chat_id, user_id*)

Get data for a user in a particular chat.

async get_state(*chat_id, user_id*)

async reset_data(*chat_id, user_id*)

Reset data for a particular user in a chat.

async save(*chat_id, user_id, data*)

async set_data(*chat_id, user_id, key, value*)

Set data for a user in a particular chat.

async set_state(*chat_id, user_id, state*)

Set state for a particular user.

! Note that you should create a record if it does not exist, and if a record with state already exists, you need to update a record.

Asyncio handler backends

class telebot.asyncio_handler_backends.**BaseMiddleware**

Bases: object

Base class for middleware. Your middlewares should be inherited from this class.

async post_process(*message, data, exception*)

async pre_process(*message, data*)

class telebot.asyncio_handler_backends.**CancelUpdate**

Bases: object

Class for canceling updates. Just return instance of this class in middleware to skip update. Update will skip handler and execution of post_process in middlewares.

class telebot.asyncio_handler_backends.**SkipHandler**

Bases: object

Class for skipping handlers. Just return instance of this class in middleware to skip handler. Update will go to post_process, but will skip execution of handler.

class telebot.asyncio_handler_backends.**State**

Bases: object

class telebot.asyncio_handler_backends.**StatesGroup**

Bases: object

1.3.6 Callback data factory

callback_data file

class telebot.callback_data.CallbackData(*parts, prefix: str, sep=':')

Bases: object

Callback data factory This class will help you to work with CallbackQuery

filter(**config) → telebot.callback_data.CallbackDataFilter

Generate filter

Parameters **config** – specified named parameters will be checked with CallbackQuery.data

Returns CallbackDataFilter class

new(*args, **kwargs) → str

Generate callback data

Parameters

- **args** – positional parameters of CallbackData instance parts
- **kwargs** – named parameters

Returns str

parse(callback_data: str) → Dict[str, str]

Parse data from the callback data

Parameters **callback_data** – string, use to telebot.types.CallbackQuery to parse it from string to a dict

Returns dict parsed from callback data

class telebot.callback_data.CallbackDataFilter(factory, config: Dict[str, str])

Bases: object

check(query)

Checks if query.data appropriates to specified config

Parameters **query** – telebot.types.CallbackQuery

Returns bool

1.3.7 Utils

util file

class telebot.util.AsyncTask(target, *args, **kwargs)

Bases: object

wait()

class telebot.util.CustomRequestResponse(json_text, status_code=200, reason="")

Bases: object

json()

`telebot.util.OrEvent(*events)`

`class telebot.util.ThreadPool(telebot, num_threads=2)`

Bases: `object`

`clear_exceptions()`

`close()`

`on_exception(worker_thread, exc_info)`

`put(func, *args, **kwargs)`

`raise_exceptions()`

`class telebot.util.WorkerThread(exception_callback=None, queue=None, name=None)`

Bases: `threading.Thread`

`clear_exceptions()`

`count = 0`

`put(task, *args, **kwargs)`

`raise_exceptions()`

`run()`

Method representing the thread's activity.

You may override this method in a subclass. The standard `run()` method invokes the callable object passed to the object's constructor as the target argument, if any, with sequential and keyword arguments taken from the `args` and `kwargs` arguments, respectively.

`stop()`

`telebot.util.antiflood(function, *args, **kwargs)`

Use this function inside loops in order to avoid getting `TooManyRequests` error. Example:

```
from telebot.util import antiflood
for chat_id in chat_id_list:
    msg = antiflood(bot.send_message, chat_id, text)
```

Parameters

- **function** –
- **args** –
- **kwargs** –

Returns `None`

`telebot.util.async_dec()`

`telebot.util.chunks(lst, n)`

Yield successive `n`-sized chunks from `lst`.

`telebot.util.deprecated(warn: bool = True, alternative: Optional[Callable] = None)`

Use this decorator to mark functions as deprecated. When the function is used, an info (or warning if *warn* is True) is logged.

Parameters

- **warn** – If True a warning is logged else an info
- **alternative** – The new function to use instead

`telebot.util.escape(text: str) → str`

Replaces the following chars in *text* ('&' with '&', '<' with '<' and '>' with '>').

Parameters *text* – the text to escape

Returns the escaped text

`telebot.util.extract_arguments(text: str) → str`

Returns the argument after the command.

Examples: `extract_arguments("/get name")`: 'name' `extract_arguments("/get")`: '' `extract_arguments("/get@botName name")`: 'name'

Parameters *text* – String to extract the arguments from a command

Returns the arguments if *text* is a command (according to `is_command`), else None.

`telebot.util.extract_command(text: str) → Optional[str]`

Extracts the command from *text* (minus the '/') if *text* is a command (see `is_command`). If *text* is not a command, this function returns None.

Examples: `extract_command('/help')`: 'help' `extract_command('/help@BotName')`: 'help' `extract_command('/search black eyed peas')`: 'search' `extract_command('Good day to you')`: None

Parameters *text* – String to extract the command from

Returns the command if *text* is a command (according to `is_command`), else None.

`telebot.util.generate_random_token()`

`telebot.util.is_bytes(var)`

`telebot.util.is_command(text: str) → bool`

Checks if *text* is a command. Telegram chat commands start with the '/' character.

Parameters *text* – Text to check.

Returns True if *text* is a command, else False.

`telebot.util.is_dict(var)`

`telebot.util.is_pil_image(var)`

`telebot.util.is_string(var)`

`telebot.util.or_clear(self)`

`telebot.util.or_set(self)`

`telebot.util.orify(e, changed_callback)`

`telebot.util.per_thread(key, construct_value, reset=False)`

`telebot.util.pil_image_to_file(image, extension='JPEG', quality='web_low')`

`telebot.util.quick_markup(values: Dict[str, Dict[str, Any]], row_width: int = 2) → telebot.types.InlineKeyboardMarkup`

Returns a reply markup from a dict in this format: `{'text': kwargs}` This is useful to avoid always typing `'btn1 = InlineKeyboardButton(...)'` `'btn2 = InlineKeyboardButton(...)'`

Example:

```
quick_markup({
    'Twitter': {'url': 'https://twitter.com'},
    'Facebook': {'url': 'https://facebook.com'},
    'Back': {'callback_data': 'whatever'}
}, row_width=2):
    # returns an InlineKeyboardMarkup with two buttons in a row, one leading to
    ↪ Twitter, the other to facebook
    # and a back button below

# kwargs can be:
{
    'url': None,
    'callback_data': None,
    'switch_inline_query': None,
    'switch_inline_query_current_chat': None,
    'callback_game': None,
    'pay': None,
    'login_url': None
}
```

Parameters

- **values** – a dict containing all buttons to create in this format: `{text: kwargs} {str:}`
- **row_width** – int row width

Returns `InlineKeyboardMarkup`

`telebot.util.smart_split(text: str, chars_per_string: int = 4096) → List[str]`

Splits one string into multiple strings, with a maximum amount of `chars_per_string` characters per string. This is very useful for splitting one giant message into multiples. If `chars_per_string > 4096`: `chars_per_string = 4096`. Splits by `'n'`, `'.` or `' '` in exactly this priority.

Parameters

- **text** – The text to split
- **chars_per_string** – The number of maximum characters per part the text is split to.

Returns The splitted text as a list of strings.

`telebot.util.split_string(text: str, chars_per_string: int) → List[str]`

Splits one string into multiple strings, with a maximum amount of `chars_per_string` characters per string. This is very useful for splitting one giant message into multiples.

Parameters

- **text** – The text to split
- **chars_per_string** – The number of characters per line the text is split into.

Returns The splitted text as a list of strings.

`telebot.util.user_link(user: telebot.types.User, include_id: bool = False) → str`

Returns an HTML user link. This is useful for reports. Attention: Don't forget to set `parse_mode` to 'HTML'!

Example: `bot.send_message(your_user_id, user_link(message.from_user) + ' started the bot!', parse_mode='HTML')`

Parameters

- **user** – the user (not the `user_id`)
- **include_id** – include the `user_id`

Returns HTML user link

`telebot.util.webhook_google_functions(bot, request)`

A webhook endpoint for Google Cloud Functions FaaS.

INDICES AND TABLES

- `genindex`
- `modindex`
- `search`

PYTHON MODULE INDEX

t

- telebot, [26](#)
- telebot.async_telebot, [79](#)
- telebot.asyncio_filters, [122](#)
- telebot.asyncio_handler_backends, [127](#)
- telebot.asyncio_storage, [125](#)
- telebot.callback_data, [128](#)
- telebot.custom_filters, [73](#)
- telebot.handler_backends, [78](#)
- telebot.storage, [75](#)
- telebot.types, [3](#)
- telebot.util, [128](#)

INDEX

A

- add() (*telebot.types.InlineKeyboardMarkup* method), 10
- add() (*telebot.types.Poll* method), 21
- add() (*telebot.types.ReplyKeyboardMarkup* method), 22
- add_callback_query_handler() (*telebot.async_telebot.AsyncTeleBot* method), 79
- add_callback_query_handler() (*telebot.TeleBot* method), 26
- add_channel_post_handler() (*telebot.async_telebot.AsyncTeleBot* method), 79
- add_channel_post_handler() (*telebot.TeleBot* method), 26
- add_chat_join_request_handler() (*telebot.async_telebot.AsyncTeleBot* method), 79
- add_chat_join_request_handler() (*telebot.TeleBot* method), 26
- add_chat_member_handler() (*telebot.async_telebot.AsyncTeleBot* method), 80
- add_chat_member_handler() (*telebot.TeleBot* method), 27
- add_chosen_inline_handler() (*telebot.async_telebot.AsyncTeleBot* method), 80
- add_chosen_inline_handler() (*telebot.TeleBot* method), 27
- add_custom_filter() (*telebot.async_telebot.AsyncTeleBot* method), 80
- add_custom_filter() (*telebot.TeleBot* method), 27
- add_data() (*telebot.async_telebot.AsyncTeleBot* method), 80
- add_data() (*telebot.TeleBot* method), 27
- add_edited_channel_post_handler() (*telebot.async_telebot.AsyncTeleBot* method), 80
- add_edited_channel_post_handler() (*telebot.TeleBot* method), 27
- add_edited_message_handler() (*telebot.async_telebot.AsyncTeleBot* method), 80
- add_edited_message_handler() (*telebot.TeleBot* method), 27
- add_inline_handler() (*telebot.async_telebot.AsyncTeleBot* method), 80
- add_inline_handler() (*telebot.TeleBot* method), 27
- add_message_handler() (*telebot.async_telebot.AsyncTeleBot* method), 80
- add_message_handler() (*telebot.TeleBot* method), 28
- add_middleware_handler() (*telebot.TeleBot* method), 28
- add_my_chat_member_handler() (*telebot.async_telebot.AsyncTeleBot* method), 81
- add_my_chat_member_handler() (*telebot.TeleBot* method), 28
- add_poll_answer_handler() (*telebot.async_telebot.AsyncTeleBot* method), 81
- add_poll_answer_handler() (*telebot.TeleBot* method), 28
- add_poll_handler() (*telebot.async_telebot.AsyncTeleBot* method), 81
- add_poll_handler() (*telebot.TeleBot* method), 28
- add_pre_checkout_query_handler() (*telebot.async_telebot.AsyncTeleBot* method), 81
- add_pre_checkout_query_handler() (*telebot.TeleBot* method), 28
- add_price() (*telebot.types.ShippingOption* method), 22
- add_shipping_query_handler() (*telebot.async_telebot.AsyncTeleBot* method), 81
- add_shipping_query_handler() (*telebot.TeleBot* method), 28
- add_sticker_to_set() (*telebot.async_telebot.AsyncTeleBot* method), 81

- add_sticker_to_set() (telebot.TeleBot method), 28
- AdvancedCustomFilter (class in telebot.asyncio_filters), 122
- AdvancedCustomFilter (class in telebot.custom_filters), 73
- Animation (class in telebot.types), 3
- answer_callback_query() (telebot.async_telebot.AsyncTeleBot method), 82
- answer_callback_query() (telebot.TeleBot method), 29
- answer_inline_query() (telebot.async_telebot.AsyncTeleBot method), 82
- answer_inline_query() (telebot.TeleBot method), 29
- answer_pre_checkout_query() (telebot.async_telebot.AsyncTeleBot method), 82
- answer_pre_checkout_query() (telebot.TeleBot method), 30
- answer_shipping_query() (telebot.async_telebot.AsyncTeleBot method), 83
- answer_shipping_query() (telebot.TeleBot method), 30
- antiflood() (in module telebot.util), 129
- approve_chat_join_request() (telebot.async_telebot.AsyncTeleBot method), 83
- approve_chat_join_request() (telebot.TeleBot method), 30
- async_dec() (in module telebot.util), 129
- AsyncTask (class in telebot.util), 128
- AsyncTeleBot (class in telebot.async_telebot), 79
- Audio (class in telebot.types), 3
- B**
- ban_chat_member() (telebot.async_telebot.AsyncTeleBot method), 83
- ban_chat_member() (telebot.TeleBot method), 30
- ban_chat_sender_chat() (telebot.async_telebot.AsyncTeleBot method), 83
- ban_chat_sender_chat() (telebot.TeleBot method), 31
- BaseMiddleware (class in telebot.asyncio_handler_backends), 127
- BaseMiddleware (class in telebot.handler_backends), 78
- BotCommand (class in telebot.types), 4
- BotCommandScope (class in telebot.types), 4
- BotCommandScopeAllChatAdministrators (class in telebot.types), 4
- BotCommandScopeAllGroupChats (class in telebot.types), 4
- BotCommandScopeAllPrivateChats (class in telebot.types), 4
- BotCommandScopeChat (class in telebot.types), 4
- BotCommandScopeChatAdministrators (class in telebot.types), 4
- BotCommandScopeChatMember (class in telebot.types), 4
- BotCommandScopeDefault (class in telebot.types), 4
- C**
- callback_query_handler() (telebot.async_telebot.AsyncTeleBot method), 84
- callback_query_handler() (telebot.TeleBot method), 31
- CallbackData (class in telebot.callback_data), 128
- CallbackDataFilter (class in telebot.callback_data), 128
- CallbackQuery (class in telebot.types), 4
- CancelUpdate (class in telebot.asyncio_handler_backends), 127
- CancelUpdate (class in telebot.handler_backends), 78
- channel_post_handler() (telebot.async_telebot.AsyncTeleBot method), 84
- channel_post_handler() (telebot.TeleBot method), 31
- Chat (class in telebot.types), 5
- chat_join_request_handler() (telebot.async_telebot.AsyncTeleBot method), 84
- chat_join_request_handler() (telebot.TeleBot method), 32
- chat_member_handler() (telebot.async_telebot.AsyncTeleBot method), 84
- chat_member_handler() (telebot.TeleBot method), 32
- ChatFilter (class in telebot.asyncio_filters), 122
- ChatFilter (class in telebot.custom_filters), 73
- ChatInviteLink (class in telebot.types), 5
- ChatJoinRequest (class in telebot.types), 5
- ChatLocation (class in telebot.types), 5
- ChatMember (class in telebot.types), 6
- ChatMemberAdministrator (class in telebot.types), 6
- ChatMemberBanned (class in telebot.types), 6
- ChatMemberLeft (class in telebot.types), 6
- ChatMemberMember (class in telebot.types), 7
- ChatMemberOwner (class in telebot.types), 7
- ChatMemberRestricted (class in telebot.types), 7
- ChatMemberUpdated (class in telebot.types), 7
- ChatPermissions (class in telebot.types), 8
- ChatPhoto (class in telebot.types), 8
- check() (telebot.asyncio_filters.AdvancedCustomFilter method), 122
- check() (telebot.asyncio_filters.ChatFilter method), 122

- [check\(\)](#) (*telebot.asyncio_filters.ForwardFilter* method), [123](#)
[check\(\)](#) (*telebot.asyncio_filters.IsAdminFilter* method), [123](#)
[check\(\)](#) (*telebot.asyncio_filters.IsDigitFilter* method), [123](#)
[check\(\)](#) (*telebot.asyncio_filters.IsReplyFilter* method), [123](#)
[check\(\)](#) (*telebot.asyncio_filters.LanguageFilter* method), [123](#)
[check\(\)](#) (*telebot.asyncio_filters.SimpleCustomFilter* method), [124](#)
[check\(\)](#) (*telebot.asyncio_filters.StateFilter* method), [124](#)
[check\(\)](#) (*telebot.asyncio_filters.TextContainsFilter* method), [124](#)
[check\(\)](#) (*telebot.asyncio_filters.TextFilter* method), [124](#)
[check\(\)](#) (*telebot.asyncio_filters.TextMatchFilter* method), [124](#)
[check\(\)](#) (*telebot.asyncio_filters.TextStartsFilter* method), [125](#)
[check\(\)](#) (*telebot.callback_data.CallbackDataFilter* method), [128](#)
[check\(\)](#) (*telebot.custom_filters.AdvancedCustomFilter* method), [73](#)
[check\(\)](#) (*telebot.custom_filters.ChatFilter* method), [73](#)
[check\(\)](#) (*telebot.custom_filters.ForwardFilter* method), [73](#)
[check\(\)](#) (*telebot.custom_filters.IsAdminFilter* method), [73](#)
[check\(\)](#) (*telebot.custom_filters.IsDigitFilter* method), [73](#)
[check\(\)](#) (*telebot.custom_filters.IsReplyFilter* method), [74](#)
[check\(\)](#) (*telebot.custom_filters.LanguageFilter* method), [74](#)
[check\(\)](#) (*telebot.custom_filters.SimpleCustomFilter* method), [74](#)
[check\(\)](#) (*telebot.custom_filters.StateFilter* method), [74](#)
[check\(\)](#) (*telebot.custom_filters.TextContainsFilter* method), [74](#)
[check\(\)](#) (*telebot.custom_filters.TextFilter* method), [75](#)
[check\(\)](#) (*telebot.custom_filters.TextMatchFilter* method), [75](#)
[check\(\)](#) (*telebot.custom_filters.TextStartsFilter* method), [75](#)
[check_commands_input\(\)](#) (*telebot.TeleBot* static method), [32](#)
[check_json\(\)](#) (*telebot.types.JsonDeserializable* static method), [17](#)
[check_regexp_input\(\)](#) (*telebot.TeleBot* static method), [32](#)
[chosen_inline_handler\(\)](#) (*telebot.async_telebot.AsyncTeleBot* method), [84](#)
[chosen_inline_handler\(\)](#) (*telebot.TeleBot* method), [32](#)
[ChosenInlineResult](#) (class in *telebot.types*), [8](#)
[chunks\(\)](#) (in module *telebot.util*), [129](#)
[clear_exceptions\(\)](#) (*telebot.util.ThreadPool* method), [129](#)
[clear_exceptions\(\)](#) (*telebot.util.WorkerThread* method), [129](#)
[clear_handlers\(\)](#) (*telebot.handler_backends.FileHandlerBackend* method), [78](#)
[clear_handlers\(\)](#) (*telebot.handler_backends.HandlerBackend* method), [78](#)
[clear_handlers\(\)](#) (*telebot.handler_backends.MemoryHandlerBackend* method), [78](#)
[clear_handlers\(\)](#) (*telebot.handler_backends.RedisHandlerBackend* method), [79](#)
[clear_reply_handlers\(\)](#) (*telebot.TeleBot* method), [32](#)
[clear_reply_handlers_by_message_id\(\)](#) (*telebot.TeleBot* method), [32](#)
[clear_step_handler\(\)](#) (*telebot.TeleBot* method), [32](#)
[clear_step_handler_by_chat_id\(\)](#) (*telebot.TeleBot* method), [32](#)
[close\(\)](#) (*telebot.async_telebot.AsyncTeleBot* method), [85](#)
[close\(\)](#) (*telebot.TeleBot* method), [32](#)
[close\(\)](#) (*telebot.util.ThreadPool* method), [129](#)
[close_session\(\)](#) (*telebot.async_telebot.AsyncTeleBot* method), [85](#)
[Contact](#) (class in *telebot.types*), [8](#)
[convert_input_media\(\)](#) (*telebot.types.InputMedia* method), [15](#)
[convert_old_to_new\(\)](#) (*telebot.async_storage.StatePickleStorage* method), [125](#)
[convert_old_to_new\(\)](#) (*telebot.storage.StatePickleStorage* method), [76](#)
[copy_message\(\)](#) (*telebot.async_telebot.AsyncTeleBot* method), [85](#)
[copy_message\(\)](#) (*telebot.TeleBot* method), [33](#)
[count](#) (*telebot.util.WorkerThread* attribute), [129](#)
[create_chat_invite_link\(\)](#) (*telebot.async_telebot.AsyncTeleBot* method), [85](#)
[create_chat_invite_link\(\)](#) (*telebot.TeleBot* method), [33](#)
[create_dir\(\)](#) (*telebot.async_storage.StatePickleStorage* method), [125](#)
[create_dir\(\)](#) (*telebot.storage.StatePickleStorage* method), [76](#)
[create_new_sticker_set\(\)](#) (*telebot.TeleBot* method), [32](#)

bot.async_telebot.AsyncTeleBot (method), 86
 create_new_sticker_set() (*telebot.TeleBot* method), 34
 CustomRequestResponse (class in *telebot.util*), 128
D
 de_json() (*telebot.types.Animation* class method), 3
 de_json() (*telebot.types.Audio* class method), 4
 de_json() (*telebot.types.BotCommand* class method), 4
 de_json() (*telebot.types.CallbackQuery* class method), 4
 de_json() (*telebot.types.Chat* class method), 5
 de_json() (*telebot.types.ChatInviteLink* class method), 5
 de_json() (*telebot.types.ChatJoinRequest* class method), 5
 de_json() (*telebot.types.ChatLocation* class method), 5
 de_json() (*telebot.types.ChatMember* class method), 6
 de_json() (*telebot.types.ChatMemberUpdated* class method), 7
 de_json() (*telebot.types.ChatPermissions* class method), 8
 de_json() (*telebot.types.ChatPhoto* class method), 8
 de_json() (*telebot.types.ChosenInlineResult* class method), 8
 de_json() (*telebot.types.Contact* class method), 8
 de_json() (*telebot.types.Dice* class method), 9
 de_json() (*telebot.types.Document* class method), 9
 de_json() (*telebot.types.File* class method), 9
 de_json() (*telebot.types.Game* class method), 10
 de_json() (*telebot.types.GameHighScore* class method), 10
 de_json() (*telebot.types.GroupChat* class method), 10
 de_json() (*telebot.types.InlineKeyboardButton* class method), 10
 de_json() (*telebot.types.InlineKeyboardMarkup* class method), 11
 de_json() (*telebot.types.InlineQuery* class method), 11
 de_json() (*telebot.types.Invoice* class method), 17
 de_json() (*telebot.types.JsonDeserializable* class method), 17
 de_json() (*telebot.types.Location* class method), 18
 de_json() (*telebot.types.LoginUrl* class method), 18
 de_json() (*telebot.types.MaskPosition* class method), 19
 de_json() (*telebot.types.Message* class method), 19
 de_json() (*telebot.types.MessageAutoDeleteTimerChanged* class method), 19
 de_json() (*telebot.types.MessageEntity* class method), 20
 de_json() (*telebot.types.MessageID* class method), 20
 de_json() (*telebot.types.OrderInfo* class method), 20
 de_json() (*telebot.types.PhotoSize* class method), 20
 de_json() (*telebot.types.Poll* class method), 21
 de_json() (*telebot.types.PollAnswer* class method), 21
 de_json() (*telebot.types.PollOption* class method), 21
 de_json() (*telebot.types.PreCheckoutQuery* class method), 21
 de_json() (*telebot.types.ProximityAlertTriggered* class method), 21
 de_json() (*telebot.types.ShippingAddress* class method), 22
 de_json() (*telebot.types.ShippingQuery* class method), 23
 de_json() (*telebot.types.Sticker* class method), 23
 de_json() (*telebot.types.StickerSet* class method), 23
 de_json() (*telebot.types.SuccessfulPayment* class method), 23
 de_json() (*telebot.types.Update* class method), 23
 de_json() (*telebot.types.User* class method), 24
 de_json() (*telebot.types.UserProfilePhotos* class method), 24
 de_json() (*telebot.types.Venue* class method), 24
 de_json() (*telebot.types.Video* class method), 24
 de_json() (*telebot.types.VideoNote* class method), 24
 de_json() (*telebot.types.Voice* class method), 25
 de_json() (*telebot.types.VoiceChatEnded* class method), 25
 de_json() (*telebot.types.VoiceChatParticipantsInvited* class method), 25
 de_json() (*telebot.types.VoiceChatScheduled* class method), 25
 de_json() (*telebot.types.VoiceChatStarted* class method), 25
 de_json() (*telebot.types.WebhookInfo* class method), 25
 decline_chat_join_request() (*telebot.async_telebot.AsyncTeleBot* method), 86
 decline_chat_join_request() (*telebot.TeleBot* method), 34
 delete_chat_photo() (*telebot.async_telebot.AsyncTeleBot* method), 87
 delete_chat_photo() (*telebot.TeleBot* method), 34
 delete_chat_sticker_set() (*telebot.async_telebot.AsyncTeleBot* method), 87
 delete_chat_sticker_set() (*telebot.TeleBot* method), 34
 delete_message() (*telebot.async_telebot.AsyncTeleBot* method), 87
 delete_message() (*telebot.TeleBot* method), 35
 delete_my_commands() (*telebot.async_telebot.AsyncTeleBot* method), 87
 delete_my_commands() (*telebot.TeleBot* method), 35
 delete_record() (*telebot.asyncio_storage.StateRedisStorage*

- method), 126
- delete_record() (telebot.storage.StateRedisStorage method), 76
- delete_state() (telebot.async_telebot.AsyncTeleBot method), 87
- delete_state() (telebot.asyncio_storage.StateMemoryStorage method), 125
- delete_state() (telebot.asyncio_storage.StatePickleStorage method), 125
- delete_state() (telebot.asyncio_storage.StateRedisStorage method), 126
- delete_state() (telebot.asyncio_storage.StateStorageBase method), 127
- delete_state() (telebot.storage.StateMemoryStorage method), 75
- delete_state() (telebot.storage.StatePickleStorage method), 76
- delete_state() (telebot.storage.StateRedisStorage method), 76
- delete_state() (telebot.storage.StateStorageBase method), 77
- delete_state() (telebot.TeleBot method), 35
- delete_sticker_from_set() (telebot.async_telebot.AsyncTeleBot method), 88
- delete_sticker_from_set() (telebot.TeleBot method), 35
- delete_webhook() (telebot.async_telebot.AsyncTeleBot method), 88
- delete_webhook() (telebot.TeleBot method), 35
- deprecated() (in module telebot.util), 129
- Dice (class in telebot.types), 8
- Dictionaryable (class in telebot.types), 9
- difference (telebot.types.ChatMemberUpdated property), 8
- disable_save_next_step_handlers() (telebot.TeleBot method), 36
- disable_save_reply_handlers() (telebot.TeleBot method), 36
- Document (class in telebot.types), 9
- download_file() (telebot.async_telebot.AsyncTeleBot method), 88
- download_file() (telebot.TeleBot method), 36
- dump_handlers() (telebot.handler_backends.FileHandlerBackend static method), 78
- E**
- edit_chat_invite_link() (telebot.async_telebot.AsyncTeleBot method), 88
- edit_chat_invite_link() (telebot.TeleBot method), 36
- edit_message_caption() (telebot.async_telebot.AsyncTeleBot method), 88
- edit_message_caption() (telebot.TeleBot method), 36
- edit_message_live_location() (telebot.async_telebot.AsyncTeleBot method), 89
- edit_message_live_location() (telebot.TeleBot method), 37
- edit_message_media() (telebot.async_telebot.AsyncTeleBot method), 90
- edit_message_media() (telebot.TeleBot method), 37
- edit_message_reply_markup() (telebot.async_telebot.AsyncTeleBot method), 90
- edit_message_reply_markup() (telebot.TeleBot method), 38
- edit_message_text() (telebot.async_telebot.AsyncTeleBot method), 90
- edit_message_text() (telebot.TeleBot method), 38
- edited_channel_post_handler() (telebot.async_telebot.AsyncTeleBot method), 91
- edited_channel_post_handler() (telebot.TeleBot method), 39
- edited_message_handler() (telebot.async_telebot.AsyncTeleBot method), 91
- edited_message_handler() (telebot.TeleBot method), 39
- enable_save_next_step_handlers() (telebot.TeleBot method), 39
- enable_save_reply_handlers() (telebot.TeleBot method), 39
- enable_saving_states() (telebot.async_telebot.AsyncTeleBot method), 91
- enable_saving_states() (telebot.TeleBot method), 40
- escape() (in module telebot.util), 130
- ExceptionHandler (class in telebot), 26
- ExceptionHandler (class in telebot.async_telebot), 122
- export_chat_invite_link() (telebot.async_telebot.AsyncTeleBot method), 91
- export_chat_invite_link() (telebot.TeleBot method), 40
- extract_arguments() (in module telebot.util), 130
- extract_command() (in module telebot.util), 130

F

`File` (class in `telebot.types`), 9

`FileHandlerBackend` (class in `telebot.handler_backends`), 78

`filter()` (`telebot.callback_data.CallbackData` method), 128

`ForceReply` (class in `telebot.types`), 9

`forward_message()` (`telebot.async_telebot.AsyncTeleBot` method), 92

`forward_message()` (`telebot.TeleBot` method), 40

`ForwardFilter` (class in `telebot.asyncio_filters`), 122

`ForwardFilter` (class in `telebot.custom_filters`), 73

`full_name` (`telebot.types.User` property), 24

G

`Game` (class in `telebot.types`), 9

`GameHighScore` (class in `telebot.types`), 10

`generate_random_token()` (in module `telebot.util`), 130

`get_chat()` (`telebot.async_telebot.AsyncTeleBot` method), 92

`get_chat()` (`telebot.TeleBot` method), 40

`get_chat_administrators()` (`telebot.async_telebot.AsyncTeleBot` method), 92

`get_chat_administrators()` (`telebot.TeleBot` method), 40

`get_chat_member()` (`telebot.async_telebot.AsyncTeleBot` method), 92

`get_chat_member()` (`telebot.TeleBot` method), 41

`get_chat_member_count()` (`telebot.async_telebot.AsyncTeleBot` method), 92

`get_chat_member_count()` (`telebot.TeleBot` method), 41

`get_chat_members_count()` (`telebot.async_telebot.AsyncTeleBot` method), 93

`get_chat_members_count()` (`telebot.TeleBot` method), 41

`get_data()` (`telebot.asyncio_storage.StateMemoryStorage` method), 125

`get_data()` (`telebot.asyncio_storage.StatePickleStorage` method), 125

`get_data()` (`telebot.asyncio_storage.StateRedisStorage` method), 126

`get_data()` (`telebot.asyncio_storage.StateStorageBase` method), 127

`get_data()` (`telebot.storage.StateMemoryStorage` method), 75

`get_data()` (`telebot.storage.StatePickleStorage` method), 76

`get_data()` (`telebot.storage.StateRedisStorage` method), 77

`get_data()` (`telebot.storage.StateStorageBase` method), 77

`get_file()` (`telebot.async_telebot.AsyncTeleBot` method), 93

`get_file()` (`telebot.TeleBot` method), 41

`get_file_url()` (`telebot.async_telebot.AsyncTeleBot` method), 93

`get_file_url()` (`telebot.TeleBot` method), 41

`get_game_high_scores()` (`telebot.async_telebot.AsyncTeleBot` method), 93

`get_game_high_scores()` (`telebot.TeleBot` method), 41

`get_handlers()` (`telebot.handler_backends.FileHandlerBackend` method), 78

`get_handlers()` (`telebot.handler_backends.HandlerBackend` method), 78

`get_handlers()` (`telebot.handler_backends.MemoryHandlerBackend` method), 78

`get_handlers()` (`telebot.handler_backends.RedisHandlerBackend` method), 79

`get_interactive_data()` (`telebot.asyncio_storage.StateMemoryStorage` method), 125

`get_interactive_data()` (`telebot.asyncio_storage.StatePickleStorage` method), 125

`get_interactive_data()` (`telebot.asyncio_storage.StateRedisStorage` method), 126

`get_interactive_data()` (`telebot.storage.StateMemoryStorage` method), 75

`get_interactive_data()` (`telebot.storage.StatePickleStorage` method), 76

`get_interactive_data()` (`telebot.storage.StateRedisStorage` method), 77

`get_me()` (`telebot.async_telebot.AsyncTeleBot` method), 93

`get_me()` (`telebot.TeleBot` method), 42

`get_my_commands()` (`telebot.async_telebot.AsyncTeleBot` method), 93

`get_my_commands()` (`telebot.TeleBot` method), 42

`get_record()` (`telebot.asyncio_storage.StateRedisStorage` method), 126

`get_record()` (`telebot.storage.StateRedisStorage` method), 77

get_state() (telebot.async_telebot.AsyncTeleBot method), 93
 get_state() (telebot.asyncio_storage.StateMemoryStorage method), 125
 get_state() (telebot.asyncio_storage.StatePickleStorage method), 126
 get_state() (telebot.asyncio_storage.StateRedisStorage method), 126
 get_state() (telebot.asyncio_storage.StateStorageBase method), 127
 get_state() (telebot.storage.StateMemoryStorage method), 75
 get_state() (telebot.storage.StatePickleStorage method), 76
 get_state() (telebot.storage.StateRedisStorage method), 77
 get_state() (telebot.storage.StateStorageBase method), 77
 get_state() (telebot.TeleBot method), 42
 get_sticker_set() (telebot.async_telebot.AsyncTeleBot method), 94
 get_sticker_set() (telebot.TeleBot method), 42
 get_updates() (telebot.async_telebot.AsyncTeleBot method), 94
 get_updates() (telebot.TeleBot method), 42
 get_user_profile_photos() (telebot.async_telebot.AsyncTeleBot method), 94
 get_user_profile_photos() (telebot.TeleBot method), 42
 get_value() (telebot.asyncio_storage.StateRedisStorage method), 126
 get_value() (telebot.storage.StateRedisStorage method), 77
 get_webhook_info() (telebot.async_telebot.AsyncTeleBot method), 94
 get_webhook_info() (telebot.TeleBot method), 43
 GroupChat (class in telebot.types), 10

H

handle() (telebot.async_telebot.ExceptionHandler method), 122
 handle() (telebot.ExceptionHandler method), 26
 Handler (class in telebot), 26
 Handler (class in telebot.async_telebot), 122
 HandlerBackend (class in telebot.handler_backends), 78
 html_caption (telebot.types.Message property), 19
 html_text (telebot.types.Message property), 19

I

infinity_polling() (telebot.async_telebot.AsyncTeleBot method), 94
 infinity_polling() (telebot.TeleBot method), 43
 inline_handler() (telebot.async_telebot.AsyncTeleBot method), 95
 inline_handler() (telebot.TeleBot method), 43
 InlineKeyboardButton (class in telebot.types), 10
 InlineKeyboardMarkup (class in telebot.types), 10
 InlineQuery (class in telebot.types), 11
 InlineQueryResultArticle (class in telebot.types), 11
 InlineQueryResultAudio (class in telebot.types), 11
 InlineQueryResultBase (class in telebot.types), 12
 InlineQueryResultCachedAudio (class in telebot.types), 12
 InlineQueryResultCachedBase (class in telebot.types), 12
 InlineQueryResultCachedDocument (class in telebot.types), 12
 InlineQueryResultCachedGif (class in telebot.types), 12
 InlineQueryResultCachedMpeg4Gif (class in telebot.types), 12
 InlineQueryResultCachedPhoto (class in telebot.types), 12
 InlineQueryResultCachedSticker (class in telebot.types), 13
 InlineQueryResultCachedVideo (class in telebot.types), 13
 InlineQueryResultCachedVoice (class in telebot.types), 13
 InlineQueryResultContact (class in telebot.types), 13
 InlineQueryResultDocument (class in telebot.types), 13
 InlineQueryResultGame (class in telebot.types), 13
 InlineQueryResultGif (class in telebot.types), 13
 InlineQueryResultLocation (class in telebot.types), 14
 InlineQueryResultMpeg4Gif (class in telebot.types), 14
 InlineQueryResultPhoto (class in telebot.types), 14
 InlineQueryResultVenue (class in telebot.types), 14
 InlineQueryResultVideo (class in telebot.types), 14
 InlineQueryResultVoice (class in telebot.types), 15
 InputContactMessageContent (class in telebot.types), 15
 InputInvoiceMessageContent (class in telebot.types), 15
 InputLocationMessageContent (class in telebot.types), 15
 InputMedia (class in telebot.types), 15
 InputMediaAnimation (class in telebot.types), 16
 InputMediaAudio (class in telebot.types), 16
 InputMediaDocument (class in telebot.types), 16
 InputMediaPhoto (class in telebot.types), 16
 InputMediaVideo (class in telebot.types), 16

InputTextMessageContent (class in telebot.types), 16
 InputVenueMessageContent (class in telebot.types), 17
 Invoice (class in telebot.types), 17
 is_bytes() (in module telebot.util), 130
 is_command() (in module telebot.util), 130
 is_dict() (in module telebot.util), 130
 is_pil_image() (in module telebot.util), 130
 is_string() (in module telebot.util), 130
 IsAdminFilter (class in telebot.asyncio_filters), 123
 IsAdminFilter (class in telebot.custom_filters), 73
 IsDigitFilter (class in telebot.asyncio_filters), 123
 IsDigitFilter (class in telebot.custom_filters), 73
 IsReplyFilter (class in telebot.asyncio_filters), 123
 IsReplyFilter (class in telebot.custom_filters), 73

J

json() (telebot.util.CustomRequestResponse method), 128
 JsonDeserializable (class in telebot.types), 17
 JsonSerializerizable (class in telebot.types), 17

K

key (telebot.asyncio_filters.ChatFilter attribute), 122
 key (telebot.asyncio_filters.ForwardFilter attribute), 123
 key (telebot.asyncio_filters.IsAdminFilter attribute), 123
 key (telebot.asyncio_filters.IsDigitFilter attribute), 123
 key (telebot.asyncio_filters.IsReplyFilter attribute), 123
 key (telebot.asyncio_filters.LanguageFilter attribute), 123
 key (telebot.asyncio_filters.StateFilter attribute), 124
 key (telebot.asyncio_filters.TextContainsFilter attribute), 124
 key (telebot.asyncio_filters.TextMatchFilter attribute), 124
 key (telebot.asyncio_filters.TextStartsFilter attribute), 125
 key (telebot.custom_filters.ChatFilter attribute), 73
 key (telebot.custom_filters.ForwardFilter attribute), 73
 key (telebot.custom_filters.IsAdminFilter attribute), 73
 key (telebot.custom_filters.IsDigitFilter attribute), 73
 key (telebot.custom_filters.IsReplyFilter attribute), 74
 key (telebot.custom_filters.LanguageFilter attribute), 74
 key (telebot.custom_filters.StateFilter attribute), 74
 key (telebot.custom_filters.TextContainsFilter attribute), 74
 key (telebot.custom_filters.TextMatchFilter attribute), 75
 key (telebot.custom_filters.TextStartsFilter attribute), 75
 KeyboardButton (class in telebot.types), 17
 KeyboardButtonPollType (class in telebot.types), 18
 kick_chat_member() (telebot.async_telebot.AsyncTeleBot method), 95
 kick_chat_member() (telebot.TeleBot method), 43

L

LabeledPrice (class in telebot.types), 18
 LanguageFilter (class in telebot.asyncio_filters), 123
 LanguageFilter (class in telebot.custom_filters), 74
 leave_chat() (telebot.async_telebot.AsyncTeleBot method), 95
 leave_chat() (telebot.TeleBot method), 43
 load_handlers() (telebot.handler_backends.FileHandlerBackend method), 78
 load_handlers() (telebot.handler_backends.MemoryHandlerBackend method), 78
 load_next_step_handlers() (telebot.TeleBot method), 44
 load_reply_handlers() (telebot.TeleBot method), 44
 Location (class in telebot.types), 18
 log_out() (telebot.async_telebot.AsyncTeleBot method), 95
 log_out() (telebot.TeleBot method), 44
 LoginUrl (class in telebot.types), 18

M

MaskPosition (class in telebot.types), 19
 max_row_keys (telebot.types.InlineKeyboardMarkup attribute), 11
 max_row_keys (telebot.types.ReplyKeyboardMarkup attribute), 22
 MemoryHandlerBackend (class in telebot.handler_backends), 78
 Message (class in telebot.types), 19
 message_handler() (telebot.async_telebot.AsyncTeleBot method), 95
 message_handler() (telebot.TeleBot method), 44
 MessageAutoDeleteTimerChanged (class in telebot.types), 19
 MessageEntity (class in telebot.types), 20
 MessageID (class in telebot.types), 20
 middleware_handler() (telebot.TeleBot method), 45
 module
 telebot, 26
 telebot.async_telebot, 79
 telebot.asyncio_filters, 122
 telebot.asyncio_handler_backends, 127
 telebot.asyncio_storage, 125
 telebot.callback_data, 128
 telebot.custom_filters, 73
 telebot.handler_backends, 78
 telebot.storage, 75
 telebot.types, 3
 telebot.util, 128
 my_chat_member_handler() (telebot.async_telebot.AsyncTeleBot method),

96
 my_chat_member_handler() (*telebot.TeleBot* method),
 45

N

new() (*telebot.callback_data.CallbackData* method), 128

O

on_exception() (*telebot.util.ThreadPool* method), 129
 or_clear() (*in module telebot.util*), 130
 or_set() (*in module telebot.util*), 130
 OrderInfo (*class in telebot.types*), 20
 OrEvent() (*in module telebot.util*), 128
 orify() (*in module telebot.util*), 130

P

parse() (*telebot.callback_data.CallbackData* method),
 128
 parse_chat() (*telebot.types.Message* class method), 19
 parse_entities() (*telebot.types.Game* class method),
 10
 parse_entities() (*telebot.types.Message* class
 method), 19
 parse_photo() (*telebot.types.Game* class method), 10
 parse_photo() (*telebot.types.Message* class method),
 19
 per_thread() (*in module telebot.util*), 130
 PhotoSize (*class in telebot.types*), 20
 pil_image_to_file() (*in module telebot.util*), 130
 pin_chat_message() (*tele-*
bot.async_telebot.AsyncTeleBot method),
 96
 pin_chat_message() (*telebot.TeleBot* method), 46
 Poll (*class in telebot.types*), 20
 poll_answer_handler() (*tele-*
bot.async_telebot.AsyncTeleBot method),
 96
 poll_answer_handler() (*telebot.TeleBot* method), 46
 poll_handler() (*telebot.async_telebot.AsyncTeleBot*
 method), 96
 poll_handler() (*telebot.TeleBot* method), 46
 PollAnswer (*class in telebot.types*), 21
 polling() (*telebot.async_telebot.AsyncTeleBot*
 method), 97
 polling() (*telebot.TeleBot* method), 46
 PollOption (*class in telebot.types*), 21
 post_process() (*tele-*
bot.asyncio_handler_backends.BaseMiddleware
 method), 127
 post_process() (*tele-*
bot.handler_backends.BaseMiddleware
 method), 78

pre_checkout_query_handler() (*tele-*
bot.async_telebot.AsyncTeleBot method),
 97
 pre_checkout_query_handler() (*telebot.TeleBot*
 method), 47
 pre_process() (*telebot.asyncio_handler_backends.BaseMiddleware*
 method), 127
 pre_process() (*telebot.handler_backends.BaseMiddleware*
 method), 78
 PreCheckoutQuery (*class in telebot.types*), 21
 process_chat_join_request() (*tele-*
bot.async_telebot.AsyncTeleBot method),
 97
 process_middlewarees() (*tele-*
bot.async_telebot.AsyncTeleBot method),
 97
 process_middlewarees() (*telebot.TeleBot* method), 47
 process_new_callback_query() (*tele-*
bot.async_telebot.AsyncTeleBot method),
 97
 process_new_callback_query() (*telebot.TeleBot*
 method), 47
 process_new_channel_posts() (*tele-*
bot.async_telebot.AsyncTeleBot method),
 97
 process_new_channel_posts() (*telebot.TeleBot*
 method), 47
 process_new_chat_join_request() (*telebot.TeleBot*
 method), 47
 process_new_chat_member() (*tele-*
bot.async_telebot.AsyncTeleBot method),
 97
 process_new_chat_member() (*telebot.TeleBot*
 method), 47
 process_new_chosen_inline_query() (*tele-*
bot.async_telebot.AsyncTeleBot method),
 97
 process_new_chosen_inline_query() (*tele-*
bot.TeleBot method), 47
 process_new_edited_channel_posts() (*tele-*
bot.async_telebot.AsyncTeleBot method),
 98
 process_new_edited_channel_posts() (*tele-*
bot.TeleBot method), 47
 process_new_edited_messages() (*tele-*
bot.async_telebot.AsyncTeleBot method),
 98
 process_new_edited_messages() (*telebot.TeleBot*
 method), 47
 process_new_inline_query() (*tele-*
bot.async_telebot.AsyncTeleBot method),
 98
 process_new_inline_query() (*telebot.TeleBot*
 method), 47

<code>process_new_messages()</code> (<i>telebot.AsyncTeleBot method</i>), 98	<code>register_callback_query_handler()</code> (<i>telebot.AsyncTeleBot method</i>), 99
<code>process_new_messages()</code> (<i>telebot.TeleBot method</i>), 47	<code>register_callback_query_handler()</code> (<i>telebot.TeleBot method</i>), 48
<code>process_new_my_chat_member()</code> (<i>telebot.AsyncTeleBot method</i>), 98	<code>register_channel_post_handler()</code> (<i>telebot.AsyncTeleBot method</i>), 99
<code>process_new_my_chat_member()</code> (<i>telebot.TeleBot method</i>), 47	<code>register_channel_post_handler()</code> (<i>telebot.TeleBot method</i>), 49
<code>process_new_poll()</code> (<i>telebot.AsyncTeleBot method</i>), 98	<code>register_chat_join_request_handler()</code> (<i>telebot.AsyncTeleBot method</i>), 99
<code>process_new_poll()</code> (<i>telebot.TeleBot method</i>), 47	<code>register_chat_join_request_handler()</code> (<i>telebot.TeleBot method</i>), 49
<code>process_new_poll_answer()</code> (<i>telebot.AsyncTeleBot method</i>), 98	<code>register_chat_member_handler()</code> (<i>telebot.AsyncTeleBot method</i>), 99
<code>process_new_poll_answer()</code> (<i>telebot.TeleBot method</i>), 47	<code>register_chat_member_handler()</code> (<i>telebot.TeleBot method</i>), 49
<code>process_new_pre_checkout_query()</code> (<i>telebot.AsyncTeleBot method</i>), 98	<code>register_chosen_inline_handler()</code> (<i>telebot.AsyncTeleBot method</i>), 100
<code>process_new_pre_checkout_query()</code> (<i>telebot.TeleBot method</i>), 47	<code>register_chosen_inline_handler()</code> (<i>telebot.TeleBot method</i>), 49
<code>process_new_shipping_query()</code> (<i>telebot.AsyncTeleBot method</i>), 98	<code>register_channel_post_handler()</code> (<i>telebot.AsyncTeleBot method</i>), 100
<code>process_new_shipping_query()</code> (<i>telebot.TeleBot method</i>), 47	<code>register_channel_post_handler()</code> (<i>telebot.TeleBot method</i>), 50
<code>process_new_updates()</code> (<i>telebot.AsyncTeleBot method</i>), 98	<code>register_edited_message_handler()</code> (<i>telebot.AsyncTeleBot method</i>), 100
<code>process_new_updates()</code> (<i>telebot.TeleBot method</i>), 47	<code>register_edited_message_handler()</code> (<i>telebot.TeleBot method</i>), 50
<code>promote_chat_member()</code> (<i>telebot.AsyncTeleBot method</i>), 98	<code>register_for_reply()</code> (<i>telebot.TeleBot method</i>), 50
<code>promote_chat_member()</code> (<i>telebot.TeleBot method</i>), 48	<code>register_for_reply_by_message_id()</code> (<i>telebot.TeleBot method</i>), 50
<code>ProximityAlertTriggered</code> (<i>class in telebot.types</i>), 21	<code>register_handler()</code> (<i>telebot.handler_backends.FileHandlerBackend method</i>), 78
<code>put()</code> (<i>telebot.util.ThreadPool method</i>), 129	<code>register_handler()</code> (<i>telebot.handler_backends.HandlerBackend method</i>), 78
<code>put()</code> (<i>telebot.util.WorkerThread method</i>), 129	<code>register_handler()</code> (<i>telebot.handler_backends.MemoryHandlerBackend method</i>), 78
Q	<code>register_handler()</code> (<i>telebot.handler_backends.RedisHandlerBackend method</i>), 79
<code>quick_markup()</code> (<i>in module telebot.util</i>), 131	<code>register_inline_handler()</code> (<i>telebot.AsyncTeleBot method</i>), 100
R	<code>register_inline_handler()</code> (<i>telebot.TeleBot method</i>), 49
<code>raise_exceptions()</code> (<i>telebot.util.ThreadPool method</i>), 129	
<code>raise_exceptions()</code> (<i>telebot.util.WorkerThread method</i>), 129	
<code>read()</code> (<i>telebot.asyncio_storage.StatePickleStorage method</i>), 126	
<code>read()</code> (<i>telebot.storage.StatePickleStorage method</i>), 76	
<code>RedisHandlerBackend</code> (<i>class in telebot.handler_backends</i>), 78	

`method`), 51
`register_message_handler()` (*telebot.async_telebot.AsyncTeleBot method*), 101
`register_message_handler()` (*telebot.TeleBot method*), 51
`register_middleware_handler()` (*telebot.TeleBot method*), 51
`register_my_chat_member_handler()` (*telebot.async_telebot.AsyncTeleBot method*), 101
`register_my_chat_member_handler()` (*telebot.TeleBot method*), 51
`register_next_step_handler()` (*telebot.TeleBot method*), 52
`register_next_step_handler_by_chat_id()` (*telebot.TeleBot method*), 52
`register_poll_answer_handler()` (*telebot.async_telebot.AsyncTeleBot method*), 101
`register_poll_answer_handler()` (*telebot.TeleBot method*), 52
`register_poll_handler()` (*telebot.async_telebot.AsyncTeleBot method*), 101
`register_poll_handler()` (*telebot.TeleBot method*), 52
`register_pre_checkout_query_handler()` (*telebot.async_telebot.AsyncTeleBot method*), 102
`register_pre_checkout_query_handler()` (*telebot.TeleBot method*), 52
`register_shipping_query_handler()` (*telebot.async_telebot.AsyncTeleBot method*), 102
`register_shipping_query_handler()` (*telebot.TeleBot method*), 53
`remove_webhook()` (*telebot.async_telebot.AsyncTeleBot method*), 102
`remove_webhook()` (*telebot.TeleBot method*), 53
`REPLY_MARKUP_TYPES` (in module *telebot*), 26
`REPLY_MARKUP_TYPES` (in module *telebot.async_telebot*), 122
`reply_to()` (*telebot.async_telebot.AsyncTeleBot method*), 102
`reply_to()` (*telebot.TeleBot method*), 53
`ReplyKeyboardMarkup` (class in *telebot.types*), 21
`ReplyKeyboardRemove` (class in *telebot.types*), 22
`reset_data()` (*telebot.async_telebot.AsyncTeleBot method*), 102
`reset_data()` (*telebot.asyncio_storage.StateMemoryStorage method*), 125
`reset_data()` (*telebot.asyncio_storage.StatePickleStorage method*), 126
`reset_data()` (*telebot.asyncio_storage.StateRedisStorage method*), 126
`reset_data()` (*telebot.asyncio_storage.StateStorageBase method*), 127
`reset_data()` (*telebot.storage.StateMemoryStorage method*), 75
`reset_data()` (*telebot.storage.StatePickleStorage method*), 76
`reset_data()` (*telebot.storage.StateRedisStorage method*), 77
`reset_data()` (*telebot.storage.StateStorageBase method*), 77
`reset_data()` (*telebot.TeleBot method*), 53
`restrict_chat_member()` (*telebot.async_telebot.AsyncTeleBot method*), 102
`restrict_chat_member()` (*telebot.TeleBot method*), 53
`retrieve_data()` (*telebot.async_telebot.AsyncTeleBot method*), 103
`retrieve_data()` (*telebot.TeleBot method*), 54
`return_load_handlers()` (*telebot.handler_backends.FileHandlerBackend static method*), 78
`revoke_chat_invite_link()` (*telebot.async_telebot.AsyncTeleBot method*), 103
`revoke_chat_invite_link()` (*telebot.TeleBot method*), 54
`row()` (*telebot.types.InlineKeyboardMarkup method*), 11
`row()` (*telebot.types.ReplyKeyboardMarkup method*), 22
`run()` (*telebot.util.WorkerThread method*), 129

S

`save()` (*telebot.asyncio_storage.StateMemoryStorage method*), 125
`save()` (*telebot.asyncio_storage.StatePickleStorage method*), 126
`save()` (*telebot.asyncio_storage.StateRedisStorage method*), 126
`save()` (*telebot.asyncio_storage.StateStorageBase method*), 127
`save()` (*telebot.storage.StateMemoryStorage method*), 75
`save()` (*telebot.storage.StatePickleStorage method*), 76
`save()` (*telebot.storage.StateRedisStorage method*), 77
`save()` (*telebot.storage.StateStorageBase method*), 77
`save_handlers()` (*telebot.handler_backends.FileHandlerBackend method*), 78
`send_animation()` (*telebot.async_telebot.AsyncTeleBot method*), 103
`send_animation()` (*telebot.TeleBot method*), 54
`send_audio()` (*telebot.async_telebot.AsyncTeleBot method*), 104

send_audio() (telebot.TeleBot method), 55
 send_chat_action() (telebot.async_telebot.AsyncTeleBot method), 105
 send_chat_action() (telebot.TeleBot method), 56
 send_contact() (telebot.async_telebot.AsyncTeleBot method), 105
 send_contact() (telebot.TeleBot method), 56
 send_dice() (telebot.async_telebot.AsyncTeleBot method), 106
 send_dice() (telebot.TeleBot method), 57
 send_document() (telebot.async_telebot.AsyncTeleBot method), 106
 send_document() (telebot.TeleBot method), 57
 send_game() (telebot.async_telebot.AsyncTeleBot method), 107
 send_game() (telebot.TeleBot method), 58
 send_invoice() (telebot.async_telebot.AsyncTeleBot method), 108
 send_invoice() (telebot.TeleBot method), 58
 send_location() (telebot.async_telebot.AsyncTeleBot method), 109
 send_location() (telebot.TeleBot method), 60
 send_media_group() (telebot.async_telebot.AsyncTeleBot method), 110
 send_media_group() (telebot.TeleBot method), 61
 send_message() (telebot.async_telebot.AsyncTeleBot method), 111
 send_message() (telebot.TeleBot method), 61
 send_photo() (telebot.async_telebot.AsyncTeleBot method), 111
 send_photo() (telebot.TeleBot method), 62
 send_poll() (telebot.async_telebot.AsyncTeleBot method), 112
 send_poll() (telebot.TeleBot method), 62
 send_sticker() (telebot.async_telebot.AsyncTeleBot method), 113
 send_sticker() (telebot.TeleBot method), 63
 send_venue() (telebot.async_telebot.AsyncTeleBot method), 113
 send_venue() (telebot.TeleBot method), 64
 send_video() (telebot.async_telebot.AsyncTeleBot method), 114
 send_video() (telebot.TeleBot method), 65
 send_video_note() (telebot.async_telebot.AsyncTeleBot method), 115
 send_video_note() (telebot.TeleBot method), 66
 send_voice() (telebot.async_telebot.AsyncTeleBot method), 115
 send_voice() (telebot.TeleBot method), 66
 set_chat_administrator_custom_title() (telebot.async_telebot.AsyncTeleBot method), 116
 set_chat_administrator_custom_title() (telebot.TeleBot method), 67
 set_chat_description() (telebot.async_telebot.AsyncTeleBot method), 116
 set_chat_description() (telebot.TeleBot method), 67
 set_chat_permissions() (telebot.async_telebot.AsyncTeleBot method), 117
 set_chat_permissions() (telebot.TeleBot method), 67
 set_chat_photo() (telebot.async_telebot.AsyncTeleBot method), 117
 set_chat_photo() (telebot.TeleBot method), 67
 set_chat_sticker_set() (telebot.async_telebot.AsyncTeleBot method), 117
 set_chat_sticker_set() (telebot.TeleBot method), 68
 set_chat_title() (telebot.async_telebot.AsyncTeleBot method), 117
 set_chat_title() (telebot.TeleBot method), 68
 set_data() (telebot.asyncio_storage.StateMemoryStorage method), 125
 set_data() (telebot.asyncio_storage.StatePickleStorage method), 126
 set_data() (telebot.asyncio_storage.StateRedisStorage method), 126
 set_data() (telebot.asyncio_storage.StateStorageBase method), 127
 set_data() (telebot.storage.StateMemoryStorage method), 76
 set_data() (telebot.storage.StatePickleStorage method), 76
 set_data() (telebot.storage.StateRedisStorage method), 77
 set_data() (telebot.storage.StateStorageBase method), 77
 set_game_score() (telebot.async_telebot.AsyncTeleBot method), 118
 set_game_score() (telebot.TeleBot method), 68
 set_my_commands() (telebot.async_telebot.AsyncTeleBot method), 118
 set_my_commands() (telebot.TeleBot method), 69
 set_record() (telebot.asyncio_storage.StateRedisStorage method), 126
 set_record() (telebot.storage.StateRedisStorage method), 77
 set_state() (telebot.async_telebot.AsyncTeleBot method), 118
 set_state() (telebot.asyncio_storage.StateMemoryStorage method), 125
 set_state() (telebot.asyncio_storage.StatePickleStorage method), 126

- `set_state()` (*telebot.asyncio_storage.StateRedisStorage* method), 127
`set_state()` (*telebot.asyncio_storage.StateStorageBase* method), 127
`set_state()` (*telebot.storage.StateMemoryStorage* method), 76
`set_state()` (*telebot.storage.StatePickleStorage* method), 76
`set_state()` (*telebot.storage.StateRedisStorage* method), 77
`set_state()` (*telebot.storage.StateStorageBase* method), 77
`set_state()` (*telebot.TeleBot* method), 69
`set_sticker_position_in_set()` (*telebot.async_telebot.AsyncTeleBot* method), 118
`set_sticker_position_in_set()` (*telebot.TeleBot* method), 69
`set_sticker_set_thumb()` (*telebot.async_telebot.AsyncTeleBot* method), 119
`set_sticker_set_thumb()` (*telebot.TeleBot* method), 69
`set_update_listener()` (*telebot.async_telebot.AsyncTeleBot* method), 119
`set_update_listener()` (*telebot.TeleBot* method), 70
`set_webhook()` (*telebot.async_telebot.AsyncTeleBot* method), 119
`set_webhook()` (*telebot.TeleBot* method), 70
`setup_middleware()` (*telebot.async_telebot.AsyncTeleBot* method), 120
`setup_middleware()` (*telebot.TeleBot* method), 70
`shipping_query_handler()` (*telebot.async_telebot.AsyncTeleBot* method), 120
`shipping_query_handler()` (*telebot.TeleBot* method), 70
`ShippingAddress` (class in *telebot.types*), 22
`ShippingOption` (class in *telebot.types*), 22
`ShippingQuery` (class in *telebot.types*), 23
`SimpleCustomFilter` (class in *telebot.asyncio_filters*), 124
`SimpleCustomFilter` (class in *telebot.custom_filters*), 74
`skip_updates()` (*telebot.async_telebot.AsyncTeleBot* method), 120
`SkipHandler` (class in *telebot.asyncio_handler_backends*), 127
`SkipHandler` (class in *telebot.handler_backends*), 79
`smart_split()` (in module *telebot.util*), 131
`split_string()` (in module *telebot.util*), 131
`start_save_timer()` (*telebot.handler_backends.FileHandlerBackend* method), 78
`State` (class in *telebot.asyncio_handler_backends*), 127
`State` (class in *telebot.handler_backends*), 79
`StateContext` (class in *telebot.asyncio_storage*), 125
`StateContext` (class in *telebot.storage*), 75
`StateFilter` (class in *telebot.asyncio_filters*), 124
`StateFilter` (class in *telebot.custom_filters*), 74
`StateMemoryStorage` (class in *telebot.asyncio_storage*), 125
`StateMemoryStorage` (class in *telebot.storage*), 75
`StatePickleStorage` (class in *telebot.asyncio_storage*), 125
`StatePickleStorage` (class in *telebot.storage*), 76
`StateRedisStorage` (class in *telebot.asyncio_storage*), 126
`StateRedisStorage` (class in *telebot.storage*), 76
`StatesGroup` (class in *telebot.asyncio_handler_backends*), 127
`StatesGroup` (class in *telebot.handler_backends*), 79
`StateStorageBase` (class in *telebot.asyncio_storage*), 127
`StateStorageBase` (class in *telebot.storage*), 77
`Sticker` (class in *telebot.types*), 23
`StickerSet` (class in *telebot.types*), 23
`stop()` (*telebot.util.WorkerThread* method), 129
`stop_bot()` (*telebot.TeleBot* method), 70
`stop_message_live_location()` (*telebot.async_telebot.AsyncTeleBot* method), 120
`stop_message_live_location()` (*telebot.TeleBot* method), 70
`stop_poll()` (*telebot.async_telebot.AsyncTeleBot* method), 120
`stop_poll()` (*telebot.TeleBot* method), 71
`stop_polling()` (*telebot.TeleBot* method), 71
`SuccessfulPayment` (class in *telebot.types*), 23
- ## T
- `telebot` module, 26
`TeleBot` (class in *telebot*), 26
`telebot.async_telebot` module, 79
`telebot.asyncio_filters` module, 122
`telebot.asyncio_handler_backends` module, 127
`telebot.asyncio_storage` module, 125
`telebot.callback_data` module, 128
`telebot.custom_filters` module, 73

telebot.handler_backends
 module, 78

telebot.storage
 module, 75

telebot.types
 module, 3

telebot.util
 module, 128

TextContainsFilter (class in telebot.asyncio_filters), 124

TextContainsFilter (class in telebot.custom_filters), 74

TextFilter (class in telebot.asyncio_filters), 124

TextFilter (class in telebot.custom_filters), 74

TextMatchFilter (class in telebot.asyncio_filters), 124

TextMatchFilter (class in telebot.custom_filters), 75

TextStartsFilter (class in telebot.asyncio_filters), 124

TextStartsFilter (class in telebot.custom_filters), 75

ThreadPool (class in telebot.util), 129

to_dict() (telebot.types.BotCommand method), 4

to_dict() (telebot.types.ChatInviteLink method), 5

to_dict() (telebot.types.ChatLocation method), 6

to_dict() (telebot.types.ChatPermissions method), 8

to_dict() (telebot.types.Dice method), 9

to_dict() (telebot.types.Dictionaryable method), 9

to_dict() (telebot.types.InlineKeyboardButton method), 10

to_dict() (telebot.types.InlineKeyboardMarkup method), 11

to_dict() (telebot.types.InlineQueryResultArticle method), 11

to_dict() (telebot.types.InlineQueryResultAudio method), 12

to_dict() (telebot.types.InlineQueryResultBase method), 12

to_dict() (telebot.types.InlineQueryResultContact method), 13

to_dict() (telebot.types.InlineQueryResultDocument method), 13

to_dict() (telebot.types.InlineQueryResultGame method), 13

to_dict() (telebot.types.InlineQueryResultGif method), 14

to_dict() (telebot.types.InlineQueryResultLocation method), 14

to_dict() (telebot.types.InlineQueryResultMpeg4Gif method), 14

to_dict() (telebot.types.InlineQueryResultPhoto method), 14

to_dict() (telebot.types.InlineQueryResultVenue method), 14

to_dict() (telebot.types.InlineQueryResultVideo method), 15

to_dict() (telebot.types.InlineQueryResultVoice method), 15

to_dict() (telebot.types.InputContactMessageContent method), 15

to_dict() (telebot.types.InputInvoiceMessageContent method), 15

to_dict() (telebot.types.InputLocationMessageContent method), 15

to_dict() (telebot.types.InputMedia method), 15

to_dict() (telebot.types.InputMediaAnimation method), 16

to_dict() (telebot.types.InputMediaAudio method), 16

to_dict() (telebot.types.InputMediaDocument method), 16

to_dict() (telebot.types.InputMediaPhoto method), 16

to_dict() (telebot.types.InputMediaVideo method), 16

to_dict() (telebot.types.InputTextMessageContent method), 16

to_dict() (telebot.types.InputVenueMessageContent method), 17

to_dict() (telebot.types.KeyboardButton method), 18

to_dict() (telebot.types.KeyboardButtonPollType method), 18

to_dict() (telebot.types.LabeledPrice method), 18

to_dict() (telebot.types.Location method), 18

to_dict() (telebot.types.LoginUrl method), 19

to_dict() (telebot.types.MaskPosition method), 19

to_dict() (telebot.types.MessageEntity method), 20

to_dict() (telebot.types.PollAnswer method), 21

to_dict() (telebot.types.User method), 24

to_json() (telebot.types.BotCommand method), 4

to_json() (telebot.types.BotCommandScope method), 4

to_json() (telebot.types.ChatInviteLink method), 5

to_json() (telebot.types.ChatLocation method), 6

to_json() (telebot.types.ChatPermissions method), 8

to_json() (telebot.types.Dice method), 9

to_json() (telebot.types.ForceReply method), 9

to_json() (telebot.types.InlineKeyboardButton method), 10

to_json() (telebot.types.InlineKeyboardMarkup method), 11

to_json() (telebot.types.InlineQueryResultBase method), 12

to_json() (telebot.types.InlineQueryResultCachedBase method), 12

to_json() (telebot.types.InputMedia method), 16

to_json() (telebot.types.JsonSerializable method), 17

to_json() (telebot.types.KeyboardButton method), 18

to_json() (telebot.types.LabeledPrice method), 18

to_json() (telebot.types.Location method), 18

to_json() (telebot.types.LoginUrl method), 19

to_json() (telebot.types.MaskPosition method), 19

to_json() (telebot.types.MessageEntity method), 20

to_json() (telebot.types.PollAnswer method), 21

to_json() (*telebot.types.ReplyKeyboardMarkup* method), 22
 to_json() (*telebot.types.ReplyKeyboardRemove* method), 22
 to_json() (*telebot.types.ShippingOption* method), 22
 to_json() (*telebot.types.User* method), 24
 to_list_of_dicts() (*telebot.types.MessageEntity* static method), 20

U

unban_chat_member() (*telebot.async_telebot.AsyncTeleBot* method), 121
 unban_chat_member() (*telebot.TeleBot* method), 71
 unban_chat_sender_chat() (*telebot.async_telebot.AsyncTeleBot* method), 121
 unban_chat_sender_chat() (*telebot.TeleBot* method), 71
 unpin_all_chat_messages() (*telebot.async_telebot.AsyncTeleBot* method), 121
 unpin_all_chat_messages() (*telebot.TeleBot* method), 72
 unpin_chat_message() (*telebot.async_telebot.AsyncTeleBot* method), 121
 unpin_chat_message() (*telebot.TeleBot* method), 72
 Update (class in *telebot.types*), 23
 update_data() (*telebot.asyncio_storage.StatePickleStorage* method), 126
 update_data() (*telebot.storage.StatePickleStorage* method), 76
 upload_sticker_file() (*telebot.async_telebot.AsyncTeleBot* method), 122
 upload_sticker_file() (*telebot.TeleBot* method), 72
 User (class in *telebot.types*), 23
 user (*telebot.TeleBot* property), 72
 user_link() (in module *telebot.util*), 132
 UserProfilePhotos (class in *telebot.types*), 24

V

Venue (class in *telebot.types*), 24
 Video (class in *telebot.types*), 24
 VideoNote (class in *telebot.types*), 24
 Voice (class in *telebot.types*), 25
 VoiceChatEnded (class in *telebot.types*), 25
 VoiceChatParticipantsInvited (class in *telebot.types*), 25
 VoiceChatScheduled (class in *telebot.types*), 25
 VoiceChatStarted (class in *telebot.types*), 25

W

wait() (*telebot.util.AsyncTask* method), 128
 webhook_google_functions() (in module *telebot.util*), 132
 WebhookInfo (class in *telebot.types*), 25
 WorkerThread (class in *telebot.util*), 129