
pyTelegramBotAPI

Release 4.17.0

coder2020official

Apr 25, 2024

CONTENTS

1	TeleBot	1
1.1	Chats	1
1.2	Some features:	1
1.3	Content	1
2	Indices and tables	283
	Python Module Index	285
	Index	287

TELEBOT

TeleBot is synchronous and asynchronous implementation of [Telegram Bot API](#).

1.1 Chats

English chat: [Private chat](#)

Russian chat: [@pytelegrambotapi_talks_ru](#)

News: [@pyTelegramBotAPI](#)

Pypi: [Pypi](#)

Source: [Github repository](#)

1.2 Some features:

Easy to learn and use.

Easy to understand.

Both sync and async.

Examples on features.

States

And more...

1.3 Content

1.3.1 Installation Guide

Using PIP

```
$ pip install pyTelegramBotAPI
```

Using pipenv

```
$ pipenv install pyTelegramBotAPI
```

By cloning repository

```
$ git clone https://github.com/eternnoir/pyTelegramBotAPI.git
$ cd pyTelegramBotAPI
$ python setup.py install
```

Directly using pip

```
$ pip install git+https://github.com/eternnoir/pyTelegramBotAPI.git
```

It is generally recommended to use the first option.

While the API is production-ready, it is still under development and it has regular updates, do not forget to update it regularly by calling:

```
$ pip install pytelegrambotapi --upgrade
```

1.3.2 Quick start

Synchronous TeleBot

```
#!/usr/bin/python

# This is a simple echo bot using the decorator mechanism.
# It echoes any incoming text messages.

import telebot

API_TOKEN = '<api_token>'

bot = telebot.TeleBot(API_TOKEN)

# Handle '/start' and '/help'
@bot.message_handler(commands=['help', 'start'])
def send_welcome(message):
    bot.reply_to(message, """\
Hi there, I am EchoBot.
I am here to echo your kind words back to you. Just say anything nice and I'll say the
↳ exact same thing to you!\
""")

# Handle all other messages with content_type 'text' (content_types defaults to ['text'])
@bot.message_handler(func=lambda message: True)
```

(continues on next page)

(continued from previous page)

```
def echo_message(message):
    bot.reply_to(message, message.text)

bot.infinity_polling()
```

Asynchronous TeleBot

```
#!/usr/bin/python

# This is a simple echo bot using the decorator mechanism.
# It echoes any incoming text messages.

from telebot.async_telebot import AsyncTeleBot
bot = AsyncTeleBot('TOKEN')

# Handle '/start' and '/help'
@bot.message_handler(commands=['help', 'start'])
async def send_welcome(message):
    await bot.reply_to(message, """\
Hi there, I am EchoBot.
I am here to echo your kind words back to you. Just say anything nice and I'll say the
↳ exact same thing to you!\
""")

# Handle all other messages with content_type 'text' (content_types defaults to ['text'])
@bot.message_handler(func=lambda message: True)
async def echo_message(message):
    await bot.reply_to(message, message.text)

import asyncio
asyncio.run(bot.polling())
```

1.3.3 Types of API

```
class telebot.types.Animation(file_id, file_unique_id, width=None, height=None, duration=None,
                             thumbnail=None, file_name=None, mime_type=None, file_size=None,
                             **kwargs)
```

Bases: *JsonDeserializable*

This object represents an animation file (GIF or H.264/MPEG-4 AVC video without sound).

Telegram Documentation: <https://core.telegram.org/bots/api#animation>

Parameters

- **file_id** (str) – Identifier for this file, which can be used to download or reuse the file

- **file_unique_id** (str) – Unique identifier for this file, which is supposed to be the same over time and for different bots. Can't be used to download or reuse the file.
- **width** (int) – Video width as defined by sender
- **height** (int) – Video height as defined by sender
- **duration** (int) – Duration of the video in seconds as defined by sender
- **thumbnail** (*telebot.types.PhotoSize*) – Optional. Animation thumbnail as defined by sender
- **file_name** (str) – Optional. Original animation filename as defined by sender
- **mime_type** (str) – Optional. MIME type of the file as defined by sender
- **file_size** (int) – Optional. File size in bytes. It can be bigger than 2^{31} and some programming languages may have difficulty/silent defects in interpreting it. But it has at most 52 significant bits, so a signed 64-bit integer or double-precision float type are safe for storing this value.

Returns

Instance of the class

Return type

telebot.types.Animation

property thumb

```
class telebot.types.Audio(file_id, file_unique_id, duration, performer=None, title=None, file_name=None, mime_type=None, file_size=None, thumbnail=None, **kwargs)
```

Bases: *JsonDeserializable*

This object represents an audio file to be treated as music by the Telegram clients.

Telegram Documentation: <https://core.telegram.org/bots/api#audio>

Parameters

- **file_id** (str) – Identifier for this file, which can be used to download or reuse the file
- **file_unique_id** (str) – Unique identifier for this file, which is supposed to be the same over time and for different bots. Can't be used to download or reuse the file.
- **duration** (int) – Duration of the audio in seconds as defined by sender
- **performer** (str) – Optional. Performer of the audio as defined by sender or by audio tags
- **title** (str) – Optional. Title of the audio as defined by sender or by audio tags
- **file_name** (str) – Optional. Original filename as defined by sender
- **mime_type** (str) – Optional. MIME type of the file as defined by sender
- **file_size** (int) – Optional. File size in bytes. It can be bigger than 2^{31} and some programming languages may have difficulty/silent defects in interpreting it. But it has at most 52 significant bits, so a signed 64-bit integer or double-precision float type are safe for storing this value.
- **thumbnail** (*telebot.types.PhotoSize*) – Optional. Thumbnail of the album cover to which the music file belongs

Returns

Instance of the class

Return type*telebot.types.Audio***property thumb****class** telebot.types.**Birthdate**(*day, month, year=None, **kwargs*)Bases: *JsonDeserializable*

This object represents a user's birthdate.

Telegram documentation: <https://core.telegram.org/bots/api#birthdate>**Parameters**

- **day** (int) – Day of the user's birth; 1-31
- **month** (int) – Month of the user's birth; 1-12
- **year** (int) – Optional. Year of the user's birth

Returns

Instance of the class

Return type*Birthdate***class** telebot.types.**BotCommand**(*command, description, **kwargs*)Bases: *JsonSerializable, JsonDeserializable, Dictionaryable*

This object represents a bot command.

Telegram Documentation: <https://core.telegram.org/bots/api#botcommand>**Parameters**

- **command** (str) – Text of the command; 1-32 characters. Can contain only lowercase English letters, digits and underscores.
- **description** (str) – Description of the command; 1-256 characters.

Returns

Instance of the class

Return type*telebot.types.BotCommand***class** telebot.types.**BotCommandScope**(*type='default', chat_id=None, user_id=None*)Bases: ABC, *JsonSerializable*

This object represents the scope to which bot commands are applied. Currently, the following 7 scopes are supported:

- *BotCommandScopeDefault*
- *BotCommandScopeAllPrivateChats*
- *BotCommandScopeAllGroupChats*
- *BotCommandScopeAllChatAdministrators*
- *BotCommandScopeChat*
- *BotCommandScopeChatAdministrators*
- *BotCommandScopeChatMember*

Determining list of commands The following algorithm is used to determine the list of commands for a particular user viewing the bot menu. The first list of commands which is set is returned:

Commands in the chat with the bot:

- *BotCommandScopeChat* + language_code
- *BotCommandScopeChat*
- *BotCommandScopeAllPrivateChats* + language_code
- *BotCommandScopeAllPrivateChats*
- *BotCommandScopeDefault* + language_code
- *BotCommandScopeDefault*

Commands in group and supergroup chats:

- *BotCommandScopeChatMember* + language_code
- *BotCommandScopeChatMember*
- *BotCommandScopeChatAdministrators* + language_code (administrators only)
- *BotCommandScopeChatAdministrators* (administrators only)
- *BotCommandScopeChat* + language_code
- *BotCommandScopeChat*
- *BotCommandScopeAllChatAdministrators* + language_code (administrators only)
- *BotCommandScopeAllChatAdministrators* (administrators only)
- *BotCommandScopeAllGroupChats* + language_code
- *BotCommandScopeAllGroupChats*
- *BotCommandScopeDefault* + language_code
- *BotCommandScopeDefault*

Returns

Instance of the class

Return type

telebot.types.BotCommandScope

class telebot.types.**BotCommandScopeAllChatAdministrators**

Bases: *BotCommandScope*

Represents the scope of bot commands, covering all group and supergroup chat administrators.

Telegram Documentation: <https://core.telegram.org/bots/api#botcommandscopeallchatadministrators>

Parameters

type (str) – Scope type, must be all_chat_administrators

Returns

Instance of the class

Return type

telebot.types.BotCommandScopeAllChatAdministrators

class telebot.types.**BotCommandScopeAllGroupChats**

Bases: *BotCommandScope*

Represents the scope of bot commands, covering all group and supergroup chats.

Telegram Documentation: <https://core.telegram.org/bots/api#botcommandscopeallgroupchats>

Parameters

type (str) – Scope type, must be all_group_chats

Returns

Instance of the class

Return type

telebot.types.BotCommandScopeAllGroupChats

class telebot.types.**BotCommandScopeAllPrivateChats**

Bases: *BotCommandScope*

Represents the scope of bot commands, covering all private chats.

Telegram Documentation: <https://core.telegram.org/bots/api#botcommandscopeallprivatechats>

Parameters

type (str) – Scope type, must be all_private_chats

Returns

Instance of the class

Return type

telebot.types.BotCommandScopeAllPrivateChats

class telebot.types.**BotCommandScopeChat**(*chat_id=None*)

Bases: *BotCommandScope*

Represents the scope of bot commands, covering a specific chat.

Telegram Documentation: <https://core.telegram.org/bots/api#botcommandscopechat>

Parameters

- **type** (str) – Scope type, must be chat
- **chat_id** (int or str) – Unique identifier for the target chat or username of the target supergroup (in the format @supergroupusername)

Returns

Instance of the class

Return type

telebot.types.BotCommandScopeChat

class telebot.types.**BotCommandScopeChatAdministrators**(*chat_id=None*)

Bases: *BotCommandScope*

Represents the scope of bot commands, covering all administrators of a specific group or supergroup chat.

Telegram Documentation: <https://core.telegram.org/bots/api#botcommandscopechatadministrators>

Parameters

- **type** (str) – Scope type, must be chat_administrators
- **chat_id** (int or str) – Unique identifier for the target chat or username of the target supergroup (in the format @supergroupusername)

Returns

Instance of the class

Return type

telebot.types.BotCommandScopeChatAdministrators

class telebot.types.**BotCommandScopeChatMember**(*chat_id=None, user_id=None*)

Bases: *BotCommandScope*

Represents the scope of bot commands, covering a specific member of a group or supergroup chat.

Telegram Documentation: <https://core.telegram.org/bots/api#botcommandscopeschatmember>

Parameters

- **type** (str) – Scope type, must be chat_member
- **chat_id** (int or str) – Unique identifier for the target chat or username of the target supergroup (in the format @supergroupusername)
- **user_id** (int) – Unique identifier of the target user

Returns

Instance of the class

Return type

telebot.types.BotCommandScopeChatMember

class telebot.types.**BotCommandScopeDefault**

Bases: *BotCommandScope*

Represents the default scope of bot commands. Default commands are used if no commands with a narrower scope are specified for the user.

Telegram Documentation: <https://core.telegram.org/bots/api#botcommandscopedefault>

Parameters

type (str) – Scope type, must be default

Returns

Instance of the class

Return type

telebot.types.BotCommandScopeDefault

class telebot.types.**BotDescription**(*description: str, **kwargs*)

Bases: *JsonDeserializable*

This object represents a bot description.

Telegram documentation: <https://core.telegram.org/bots/api#botdescription>

Parameters

description (str) – Bot description

Returns

Instance of the class

Return type

telebot.types.BotDescription

class telebot.types.**BotName**(*name: str, **kwargs*)

Bases: *JsonDeserializable*

This object represents a bot name.

Telegram Documentation: <https://core.telegram.org/bots/api#botname>

Parameters

name (str) – The bot name

Returns

Instance of the class

Return type

BotName

class telebot.types.**BotShortDescription**(*short_description: str, **kwargs*)

Bases: *JsonDeserializable*

This object represents a bot short description.

Telegram documentation: <https://core.telegram.org/bots/api#botshortdescription>

Parameters

short_description (str) – Bot short description

Returns

Instance of the class

Return type

telebot.types.BotShortDescription

class telebot.types.**BusinessConnection**(*id, user, user_chat_id, date, can_reply, is_enabled, **kwargs*)

Bases: *JsonDeserializable*

This object describes the connection of the bot with a business account.

Telegram documentation: <https://core.telegram.org/bots/api#businessconnection>

Parameters

- **id** (str) – Unique identifier of the business connection
- **user** (*User*) – Business account user that created the business connection
- **user_chat_id** (int) – Identifier of a private chat with the user who created the business connection
- **date** (int) – Date the connection was established in Unix time
- **can_reply** (bool) – True, if the bot can act on behalf of the business account in chats that were active in the last 24 hours
- **is_enabled** (bool) – True, if the connection is active

Returns

Instance of the class

Return type

BusinessConnection

class telebot.types.**BusinessIntro**(*title=None, message=None, sticker=None, **kwargs*)

Bases: *JsonDeserializable*

This object represents a business intro.

Telegram documentation: <https://core.telegram.org/bots/api#businessintro>

Parameters

- **title** (str) – Optional. Title text of the business intro
- **message** (str) – Optional. Message text of the business intro
- **sticker** (*Sticker*) – Optional. Sticker of the business intro

Returns

Instance of the class

Return type

BusinessIntro

class telebot.types.**BusinessLocation**(*address, location=None, **kwargs*)

Bases: *JsonDeserializable*

This object represents a business location.

Telegram documentation: <https://core.telegram.org/bots/api#businesslocation>

Parameters

- **address** (str) – Address of the business
- **location** (*Location*) – Optional. Location of the business

Returns

Instance of the class

Return type

BusinessLocation

class telebot.types.**BusinessMessagesDeleted**(*business_connection_id, chat, message_ids, **kwargs*)

Bases: *JsonDeserializable*

This object is received when messages are deleted from a connected business account.

Telegram documentation: <https://core.telegram.org/bots/api#businessmessagesdeleted>

Parameters

- **business_connection_id** (str) – Unique identifier of the business connection
- **chat** (*Chat*) – Information about a chat in the business account. The bot may not have access to the chat or the corresponding user.
- **message_ids** (list of int) – A JSON-serialized list of identifiers of deleted messages in the chat of the business account

Returns

Instance of the class

Return type

BusinessMessagesDeleted

class telebot.types.**BusinessOpeningHours**(*time_zone_name, opening_hours, **kwargs*)

Bases: *JsonDeserializable*

This object represents business opening hours.

Telegram documentation: <https://core.telegram.org/bots/api#businessopeninghours>

Parameters

- **time_zone_name** (str) – Unique name of the time zone for which the opening hours are defined
- **opening_hours** (list of *BusinessOpeningHoursInterval*) – List of time intervals describing business opening hours

Returns

Instance of the class

Return type

BusinessOpeningHours

class telebot.types.**BusinessOpeningHoursInterval**(*opening_minute, closing_minute, **kwargs*)

Bases: *JsonDeserializable*

This object represents a business opening hours interval.

Telegram documentation: <https://core.telegram.org/bots/api#businessopeninghoursinterval>

Parameters

- **opening_minute** (int) – The minute’s sequence number in a week, starting on Monday, marking the start of the time interval during which the business is open; 0 - 7 24 60
- **closing_minute** (int) – The minute’s sequence number in a week, starting on Monday, marking the end of the time interval during which the business is open; 0 - 8 24 60

Returns

Instance of the class

Return type

BusinessOpeningHoursInterval

class telebot.types.**CallbackQuery**(*id, from_user, data, chat_instance, json_string, message=None, inline_message_id=None, game_short_name=None, **kwargs*)

Bases: *JsonDeserializable*

This object represents an incoming callback query from a callback button in an inline keyboard. If the button that originated the query was attached to a message sent by the bot, the field `message` will be present. If the button was attached to a message sent via the bot (in inline mode), the field `inline_message_id` will be present. Exactly one of the fields `data` or `game_short_name` will be present.

Telegram Documentation: <https://core.telegram.org/bots/api#callbackquery>

Parameters

- **id** (str) – Unique identifier for this query
- **from_user** (*telebot.types.User*) – Sender
- **message** (*telebot.types.Message* or *telebot.types.InaccessibleMessage*) – Optional. Message sent by the bot with the callback button that originated the query
- **inline_message_id** (str) – Optional. Identifier of the message sent via the bot in inline mode, that originated the query.
- **chat_instance** (str) – Global identifier, uniquely corresponding to the chat to which the message with the callback button was sent. Useful for high scores in games.
- **data** (str) – Optional. Data associated with the callback button. Be aware that the message originated the query can contain no callback buttons with this data.
- **game_short_name** (str) – Optional. Short name of a Game to be returned, serves as the unique identifier for the game

Returns

Instance of the class

Return type

telebot.types.CallbackQuery

```
class telebot.types.Chat(id, type, title=None, username=None, first_name=None, last_name=None, photo=None, bio=None, has_private_forwards=None, description=None, invite_link=None, pinned_message=None, permissions=None, slow_mode_delay=None, message_auto_delete_time=None, has_protected_content=None, sticker_set_name=None, can_set_sticker_set=None, linked_chat_id=None, location=None, join_to_send_messages=None, join_by_request=None, has_restricted_voice_and_video_messages=None, is_forum=None, active_usernames=None, emoji_status_custom_emoji_id=None, has_hidden_members=None, has_aggressive_anti_spam_enabled=None, emoji_status_expiration_date=None, available_reactions=None, accent_color_id=None, background_custom_emoji_id=None, profile_accent_color_id=None, profile_background_custom_emoji_id=None, has_visible_history=None, unrestrict_boost_count=None, custom_emoji_sticker_set_name=None, business_intro=None, business_location=None, business_opening_hours=None, personal_chat=None, birthdate=None, **kwargs)
```

Bases: *JsonDeserializable*

This object represents a chat.

Telegram Documentation: <https://core.telegram.org/bots/api#chat>

Parameters

- **id** (int) – Unique identifier for this chat. This number may have more than 32 significant bits and some programming languages may have difficulty/silent defects in interpreting it. But it has at most 52 significant bits, so a signed 64-bit integer or double-precision float type are safe for storing this identifier.
- **type** (str) – Type of chat, can be either “private”, “group”, “supergroup” or “channel”
- **title** (str) – Optional. Title, for supergroups, channels and group chats
- **username** (str) – Optional. Username, for private chats, supergroups and channels if available
- **first_name** (str) – Optional. First name of the other party in a private chat
- **last_name** (str) – Optional. Last name of the other party in a private chat
- **is_forum** (bool) – Optional. True, if the supergroup chat is a forum (has topics enabled)
- **photo** (*telebot.types.ChatPhoto*) – Optional. Chat photo. Returned only in getChat.
- **active_usernames** (list of str) – Optional. If non-empty, the list of all active chat usernames; for private chats, supergroups and channels. Returned only in getChat.
- **birthdate** (str) – Optional. Birthdate of the other party in a private chat. Returned only in getChat.
- **business_intro** (*telebot.types.BusinessIntro*) – Optional. Business intro for the chat. Returned only in getChat.
- **business_location** (*telebot.types.BusinessLocation*) – Optional. Business location for the chat. Returned only in getChat.

:param business_opening_hours : Optional. Business opening hours for the chat. Returned only in getChat.
 :type business_opening_hours: telebot.types.BusinessHours

Parameters

- **personal_chat** (*telebot.types.Chat*) – Optional. For private chats, the personal channel of the user. Returned only in getChat.
- **available_reactions** (list of *telebot.types.ReactionType*) – Optional. List of available chat reactions; for private chats, supergroups and channels. Returned only in getChat.
- **accent_color_id** (int) – Optional. Identifier of the accent color for the chat name and backgrounds of the chat photo, reply header, and link preview. See accent colors for more details. Returned only in getChat. Always returned in getChat.
- **background_custom_emoji_id** (str) – Optional. Custom emoji identifier of emoji chosen by the chat for the reply header and link preview background. Returned only in getChat.
- **profile_accent_color_id** (int) – Optional. Identifier of the accent color for the chat’s profile background. See profile accent colors for more details. Returned only in getChat.
- **profile_background_custom_emoji_id** (str) – Optional. Custom emoji identifier of the emoji chosen by the chat for its profile background. Returned only in getChat.
- **emoji_status_custom_emoji_id** (str) – Optional. Custom emoji identifier of emoji status of the other party in a private chat. Returned only in getChat.
- **emoji_status_expiration_date** (int) – Optional. Expiration date of the emoji status of the other party in a private chat, if any. Returned only in getChat.
- **bio** (str) – Optional. Bio of the other party in a private chat. Returned only in getChat.
- **has_private_forwards** (bool) – Optional. bool, if privacy settings of the other party in the private chat allows to use tg://user?id=<user_id> links only in chats with the user. Returned only in getChat.
- **has_restricted_voice_and_video_messages** – Optional. True, if the privacy settings of the other party restrict sending voice and video note messages in the private chat. Returned only in getChat.

:type bool

Parameters

- **join_to_send_messages** (bool) – Optional. bool, if users need to join the supergroup before they can send messages. Returned only in getChat.
- **join_by_request** (bool) – Optional. bool, if all users directly joining the supergroup need to be approved by supergroup administrators. Returned only in getChat.
- **description** (str) – Optional. Description, for groups, supergroups and channel chats. Returned only in getChat.
- **invite_link** (str) – Optional. Primary invite link, for groups, supergroups and channel chats. Returned only in getChat.
- **pinned_message** (*telebot.types.Message*) – Optional. The most recent pinned message (by sending date). Returned only in getChat.
- **permissions** (*telebot.types.ChatPermissions*) – Optional. Default chat member permissions, for groups and supergroups. Returned only in getChat.

- **slow_mode_delay** (int) – Optional. For supergroups, the minimum allowed delay between consecutive messages sent by each unprivileged user; in seconds. Returned only in `getChat`.
- **unrestrict_boost_count** (int) – Optional. For supergroups, the minimum number of boosts that a non-administrator user needs to add in order to ignore slow mode and chat permissions. Returned only in `getChat`.
- **message_auto_delete_time** (int) – Optional. The time after which all messages sent to the chat will be automatically deleted; in seconds. Returned only in `getChat`.
- **has_aggressive_anti_spam_enabled** (bool) – Optional. bool, if the chat has enabled aggressive anti-spam protection. Returned only in `getChat`.
- **has_hidden_members** (bool) – Optional. bool, if the chat has enabled hidden members. Returned only in `getChat`.
- **has_protected_content** (bool) – Optional. bool, if messages from the chat can't be forwarded to other chats. Returned only in `getChat`.
- **has_visible_history** (bool) – Optional. True, if new chat members will have access to old messages; available only to chat administrators. Returned only in `getChat`.
- **sticker_set_name** (str) – Optional. For supergroups, name of group sticker set. Returned only in `getChat`.
- **can_set_sticker_set** (bool) – Optional. bool, if the bot can change the group sticker set. Returned only in `getChat`.
- **custom_emoji_sticker_set_name** – Optional. For supergroups, the name of the group's custom emoji sticker set. Custom emoji from this set can be used by all users and bots in the group. Returned only in `getChat`.
- **custom_emoji_sticker_set_name** – str
- **linked_chat_id** (int) – Optional. Unique identifier for the linked chat, i.e. the discussion group identifier for a channel and vice versa; for supergroups and channel chats. This identifier may be greater than 32 bits and some programming languages may have difficulty/silent defects in interpreting it. But it is smaller than 52 bits, so a signed 64 bit integer or double-precision float type are safe for storing this identifier. Returned only in `getChat`.
- **location** (*telebot.types.ChatLocation*) – Optional. For supergroups, the location to which the supergroup is connected. Returned only in `getChat`.

Returns

Instance of the class

Return type

telebot.types.Chat

```
class telebot.types.ChatAdministratorRights(is_anonymous: bool, can_manage_chat: bool,
                                           can_delete_messages: bool, can_manage_video_chats:
                                           bool, can_restrict_members: bool, can_promote_members:
                                           bool, can_change_info: bool, can_invite_users: bool,
                                           can_post_messages: bool = None, can_edit_messages:
                                           bool = None, can_pin_messages: bool = None,
                                           can_manage_topics: bool = None, can_post_stories: bool
                                           = None, can_edit_stories: bool = None,
                                           can_delete_stories: bool = None, **kwargs)
```

Bases: *JsonDeserializable, JsonSerializerable, Dictionaryable*

Represents the rights of an administrator in a chat.

Telegram Documentation: <https://core.telegram.org/bots/api#chatadministratorrights>

Parameters

- **is_anonymous** (bool) – True, if the user’s presence in the chat is hidden
- **can_manage_chat** (bool) – True, if the administrator can access the chat event log, chat statistics, message statistics in channels, see channel members, see anonymous administrators in supergroups and ignore slow mode. Implied by any other administrator privilege
- **can_delete_messages** (bool) – True, if the administrator can delete messages of other users
- **can_manage_video_chats** (bool) – True, if the administrator can manage video chats
- **can_restrict_members** (bool) – True, if the administrator can restrict, ban or unban chat members
- **can_promote_members** (bool) – True, if the administrator can add new administrators with a subset of their own privileges or demote administrators that he has promoted, directly or indirectly (promoted by administrators that were appointed by the user)
- **can_change_info** (bool) – True, if the user is allowed to change the chat title, photo and other settings
- **can_invite_users** (bool) – True, if the user is allowed to invite new users to the chat
- **can_post_messages** (bool) – Optional. True, if the administrator can post in the channel; channels only
- **can_edit_messages** (bool) – Optional. True, if the administrator can edit messages of other users and can pin messages; channels only
- **can_pin_messages** (bool) – Optional. True, if the user is allowed to pin messages; groups and supergroups only
- **can_manage_topics** (bool) – Optional. True, if the user is allowed to create, rename, close, and reopen forum topics; supergroups only
- **can_post_stories** (bool) – Optional. True, if the administrator can post channel stories
- **can_edit_stories** (bool) – Optional. True, if the administrator can edit stories
- **can_delete_stories** (bool) – Optional. True, if the administrator can delete stories of other users

Returns

Instance of the class

Return type

telebot.types.ChatAdministratorRights

class telebot.types.**ChatBoost**(*boost_id, add_date, expiration_date, source, **kwargs*)

Bases: *JsonDeserializable*

This object contains information about a chat boost.

Telegram documentation: <https://core.telegram.org/bots/api#chatboost>

Parameters

- **boost_id** (str) – Unique identifier of the boost
- **add_date** (int) – Point in time (Unix timestamp) when the chat was boosted

- **expiration_date** (int) – Point in time (Unix timestamp) when the boost will automatically expire, unless the booster’s Telegram Premium subscription is prolonged
- **source** (*ChatBoostSource*) – Optional. Source of the added boost (made Optional for now due to API error)

Returns

Instance of the class

Return type

ChatBoost

class telebot.types.**ChatBoostAdded**(*boost_count*, ***kwargs*)

Bases: *JsonDeserializable*

This object represents a service message about a user boosting a chat.

Telegram documentation: <https://core.telegram.org/bots/api#chatboostadded>

Parameters

boost_count (int) – Number of boosts added by the user

Returns

Instance of the class

Return type

ChatBoostAdded

class telebot.types.**ChatBoostRemoved**(*chat*, *boost_id*, *remove_date*, *source*, ***kwargs*)

Bases: *JsonDeserializable*

This object represents a boost removed from a chat.

Telegram documentation: <https://core.telegram.org/bots/api#chatboostremoved>

Parameters

- **chat** (*Chat*) – Chat which was boosted
- **boost_id** (str) – Unique identifier of the boost
- **remove_date** (int) – Point in time (Unix timestamp) when the boost was removed
- **source** (*ChatBoostSource*) – Source of the removed boost

Returns

Instance of the class

Return type

ChatBoostRemoved

class telebot.types.**ChatBoostSource**

Bases: ABC, *JsonDeserializable*

This object describes the source of a chat boost. It can be one of

ChatBoostSourcePremium *ChatBoostSourceGiftCode* *ChatBoostSourceGiveaway*

Telegram documentation: <https://core.telegram.org/bots/api#chatboostsource>

Returns

Instance of the class

Return type

ChatBoostSourcePremium or *ChatBoostSourceGiftCode* or *ChatBoostSourceGiveaway*

class telebot.types.ChatBoostSourceGiftCode(*source*, *user*, ***kwargs*)

Bases: [ChatBoostSource](#)

The boost was obtained by the creation of Telegram Premium gift codes to boost a chat.

Telegram documentation: <https://core.telegram.org/bots/api#chatboostsourcegiftcode>

Parameters

- **source** (`str`) – Source of the boost, always “gift_code”
- **user** (`User`) – User for which the gift code was created

Returns

Instance of the class

Return type

[ChatBoostSourceGiftCode](#)

class telebot.types.ChatBoostSourceGiveaway(*source*, *giveaway_message_id*, *user=None*, *is_unclaimed=None*, ***kwargs*)

Bases: [ChatBoostSource](#)

The boost was obtained by the creation of a Telegram Premium giveaway.

Telegram documentation: <https://core.telegram.org/bots/api#chatboostsourcegiveaway>

Parameters

- **source** (`str`) – Source of the boost, always “giveaway”
- **giveaway_message_id** (`int`) – Identifier of a message in the chat with the giveaway; the message could have been deleted already. May be 0 if the message isn’t sent yet.
- **user** (`User`) – User that won the prize in the giveaway if any
- **is_unclaimed** (`bool`) – True, if the giveaway was completed, but there was no user to win the prize

Returns

Instance of the class

Return type

[ChatBoostSourceGiveaway](#)

class telebot.types.ChatBoostSourcePremium(*source*, *user*, ***kwargs*)

Bases: [ChatBoostSource](#)

The boost was obtained by subscribing to Telegram Premium or by gifting a Telegram Premium subscription to another user.

Telegram documentation: <https://core.telegram.org/bots/api#chatboostsourcepremium>

Parameters

- **source** (`str`) – Source of the boost, always “premium”
- **user** (`User`) – User that boosted the chat

Returns

Instance of the class

Return type

[ChatBoostSourcePremium](#)

class telebot.types.ChatBoostUpdated(*chat, boost, **kwargs*)

Bases: *JsonDeserializable*

This object represents a boost added to a chat or changed.

Telegram documentation: <https://core.telegram.org/bots/api#chatboostupdated>

Parameters

- **chat** (*Chat*) – Chat which was boosted
- **boost** (*ChatBoost*) – Information about the chat boost

Returns

Instance of the class

Return type

ChatBoostUpdated

class telebot.types.ChatInviteLink(*invite_link, creator, creates_join_request, is_primary, is_revoked, name=None, expire_date=None, member_limit=None, pending_join_request_count=None, **kwargs*)

Bases: *JsonSerializable, JsonDeserializable, Dictionaryable*

Represents an invite link for a chat.

Telegram Documentation: <https://core.telegram.org/bots/api#chatinvitelink>

Parameters

- **invite_link** (*str*) – The invite link. If the link was created by another chat administrator, then the second part of the link will be replaced with “...”.
- **creator** (*telebot.types.User*) – Creator of the link
- **creates_join_request** (*bool*) – True, if users joining the chat via the link need to be approved by chat administrators
- **is_primary** (*bool*) – True, if the link is primary
- **is_revoked** (*bool*) – True, if the link is revoked
- **name** (*str*) – Optional. Invite link name
- **expire_date** (*int*) – Optional. Point in time (Unix timestamp) when the link will expire or has been expired
- **member_limit** (*int*) – Optional. The maximum number of users that can be members of the chat simultaneously after joining the chat via this invite link; 1-99999
- **pending_join_request_count** (*int*) – Optional. Number of pending join requests created using this link

Returns

Instance of the class

Return type

telebot.types.ChatInviteLink

class telebot.types.ChatJoinRequest(*chat, from_user, user_chat_id, date, bio=None, invite_link=None, **kwargs*)

Bases: *JsonDeserializable*

Represents a join request sent to a chat.

Telegram Documentation: <https://core.telegram.org/bots/api#chatjoinrequest>

Parameters

- **chat** (*telebot.types.Chat*) – Chat to which the request was sent
- **from_user** (*telebot.types.User*) – User that sent the join request
- **user_chat_id** (int) – Optional. Identifier of a private chat with the user who sent the join request. This number may have more than 32 significant bits and some programming languages may have difficulty/silent defects in interpreting it. But it has at most 52 significant bits, so a 64-bit integer or double-precision float type are safe for storing this identifier. The bot can use this identifier for 24 hours to send messages until the join request is processed, assuming no other administrator contacted the user.
- **date** (int) – Date the request was sent in Unix time
- **bio** (str) – Optional. Bio of the user.
- **invite_link** (*telebot.types.ChatInviteLink*) – Optional. Chat invite link that was used by the user to send the join request

Returns

Instance of the class

Return type

telebot.types.ChatJoinRequest

class telebot.types.**ChatLocation**(*location, address, **kwargs*)

Bases: *JsonSerializable, JsonDeserializable, Dictionaryable*

Represents a location to which a chat is connected.

Telegram Documentation: <https://core.telegram.org/bots/api#chatlocation>

Parameters

- **location** (*telebot.types.Location*) – The location to which the supergroup is connected. Can't be a live location.
- **address** (str) – Location address; 1-64 characters, as defined by the chat owner

Returns

Instance of the class

Return type

telebot.types.ChatLocation

class telebot.types.**ChatMember**(*user, status, custom_title=None, is_anonymous=None, can_be_edited=None, can_post_messages=None, can_edit_messages=None, can_delete_messages=None, can_restrict_members=None, can_promote_members=None, can_change_info=None, can_invite_users=None, can_pin_messages=None, is_member=None, can_send_messages=None, can_send_audios=None, can_send_documents=None, can_send_photos=None, can_send_videos=None, can_send_video_notes=None, can_send_voice_notes=None, can_send_polls=None, can_send_other_messages=None, can_add_web_page_previews=None, can_manage_chat=None, can_manage_video_chats=None, until_date=None, can_manage_topics=None, can_post_stories=None, can_edit_stories=None, can_delete_stories=None, **kwargs*)

Bases: *JsonDeserializable*

This object contains information about one member of a chat. Currently, the following 6 types of chat members are supported:

- `telebot.types.ChatMemberOwner`
- `telebot.types.ChatMemberAdministrator`
- `telebot.types.ChatMemberMember`
- `telebot.types.ChatMemberRestricted`
- `telebot.types.ChatMemberLeft`
- `telebot.types.ChatMemberBanned`

Telegram Documentation: <https://core.telegram.org/bots/api#chatmember>

property `can_manage_voice_chats`

```
class telebot.types.ChatMemberAdministrator(user, status, custom_title=None, is_anonymous=None,
                                             can_be_edited=None, can_post_messages=None,
                                             can_edit_messages=None, can_delete_messages=None,
                                             can_restrict_members=None,
                                             can_promote_members=None, can_change_info=None,
                                             can_invite_users=None, can_pin_messages=None,
                                             is_member=None, can_send_messages=None,
                                             can_send_audios=None, can_send_documents=None,
                                             can_send_photos=None, can_send_videos=None,
                                             can_send_video_notes=None,
                                             can_send_voice_notes=None, can_send_polls=None,
                                             can_send_other_messages=None,
                                             can_add_web_page_previews=None,
                                             can_manage_chat=None, can_manage_video_chats=None,
                                             until_date=None, can_manage_topics=None,
                                             can_post_stories=None, can_edit_stories=None,
                                             can_delete_stories=None, **kwargs)
```

Bases: `ChatMember`

Represents a chat member that has some additional privileges.

Telegram Documentation: <https://core.telegram.org/bots/api#chatmemberadministrator>

Parameters

- **status** (str) – The member’s status in the chat, always “administrator”
- **user** (`telebot.types.User`) – Information about the user
- **can_be_edited** (bool) – True, if the bot is allowed to edit administrator privileges of that user
- **is_anonymous** (bool) – True, if the user’s presence in the chat is hidden
- **can_manage_chat** (bool) – True, if the administrator can access the chat event log, chat statistics, message statistics in channels, see channel members, see anonymous administrators in supergroups and ignore slow mode. Implied by any other administrator privilege
- **can_delete_messages** (bool) – True, if the administrator can delete messages of other users
- **can_manage_video_chats** (bool) – True, if the administrator can manage video chats

- **can_restrict_members** (bool) – True, if the administrator can restrict, ban or unban chat members
- **can_promote_members** (bool) – True, if the administrator can add new administrators with a subset of their own privileges or demote administrators that he has promoted, directly or indirectly (promoted by administrators that were appointed by the user)
- **can_change_info** (bool) – True, if the user is allowed to change the chat title, photo and other settings
- **can_invite_users** (bool) – True, if the user is allowed to invite new users to the chat
- **can_post_messages** (bool) – Optional. True, if the administrator can post in the channel; channels only
- **can_edit_messages** (bool) – Optional. True, if the administrator can edit messages of other users and can pin messages; channels only
- **can_pin_messages** (bool) – Optional. True, if the user is allowed to pin messages; groups and supergroups only
- **can_manage_topics** (bool) – Optional. True, if the user is allowed to create, rename, close, and reopen forum topics; supergroups only
- **custom_title** (str) – Optional. Custom title for this user
- **can_post_stories** (bool) – Optional. True, if the administrator can post channel stories
- **can_edit_stories** (bool) – Optional. True, if the administrator can edit stories
- **can_delete_stories** (bool) – Optional. True, if the administrator can delete stories of other users

Returns

Instance of the class

Return type

telebot.types.ChatMemberAdministrator

```
class telebot.types.ChatMemberBanned(user, status, custom_title=None, is_anonymous=None,
can_be_edited=None, can_post_messages=None,
can_edit_messages=None, can_delete_messages=None,
can_restrict_members=None, can_promote_members=None,
can_change_info=None, can_invite_users=None,
can_pin_messages=None, is_member=None,
can_send_messages=None, can_send_audios=None,
can_send_documents=None, can_send_photos=None,
can_send_videos=None, can_send_video_notes=None,
can_send_voice_notes=None, can_send_polls=None,
can_send_other_messages=None,
can_add_web_page_previews=None, can_manage_chat=None,
can_manage_video_chats=None, until_date=None,
can_manage_topics=None, can_post_stories=None,
can_edit_stories=None, can_delete_stories=None, **kwargs)
```

Bases: *ChatMember*

Represents a chat member that was banned in the chat and can't return to the chat or view chat messages.

Telegram Documentation: <https://core.telegram.org/bots/api#chatmemberbanned>

Parameters

- **status** (str) – The member's status in the chat, always "kicked"

- **user** (*telebot.types.User*) – Information about the user
- **until_date** (int) – Date when restrictions will be lifted for this user; unix time. If 0, then the user is banned forever

Returns

Instance of the class

Return type

telebot.types.ChatMemberBanned

```
class telebot.types.ChatMemberLeft(user, status, custom_title=None, is_anonymous=None,
    can_be_edited=None, can_post_messages=None,
    can_edit_messages=None, can_delete_messages=None,
    can_restrict_members=None, can_promote_members=None,
    can_change_info=None, can_invite_users=None,
    can_pin_messages=None, is_member=None,
    can_send_messages=None, can_send_audios=None,
    can_send_documents=None, can_send_photos=None,
    can_send_videos=None, can_send_video_notes=None,
    can_send_voice_notes=None, can_send_polls=None,
    can_send_other_messages=None,
    can_add_web_page_previews=None, can_manage_chat=None,
    can_manage_video_chats=None, until_date=None,
    can_manage_topics=None, can_post_stories=None,
    can_edit_stories=None, can_delete_stories=None, **kwargs)
```

Bases: *ChatMember*

Represents a chat member that isn't currently a member of the chat, but may join it themselves.

Telegram Documentation: <https://core.telegram.org/bots/api#chatmemberleft>

Parameters

- **status** (str) – The member's status in the chat, always "left"
- **user** (*telebot.types.User*) – Information about the user

Returns

Instance of the class

Return type

telebot.types.ChatMemberLeft

```
class telebot.types.ChatMemberMember(user, status, custom_title=None, is_anonymous=None,
    can_be_edited=None, can_post_messages=None,
    can_edit_messages=None, can_delete_messages=None,
    can_restrict_members=None, can_promote_members=None,
    can_change_info=None, can_invite_users=None,
    can_pin_messages=None, is_member=None,
    can_send_messages=None, can_send_audios=None,
    can_send_documents=None, can_send_photos=None,
    can_send_videos=None, can_send_video_notes=None,
    can_send_voice_notes=None, can_send_polls=None,
    can_send_other_messages=None,
    can_add_web_page_previews=None, can_manage_chat=None,
    can_manage_video_chats=None, until_date=None,
    can_manage_topics=None, can_post_stories=None,
    can_edit_stories=None, can_delete_stories=None, **kwargs)
```

Bases: *ChatMember*

Represents a chat member that has no additional privileges or restrictions.

Telegram Documentation: <https://core.telegram.org/bots/api#chatmembermember>

Parameters

- **status** (str) – The member’s status in the chat, always “member”
- **user** (*telebot.types.User*) – Information about the user

Returns

Instance of the class

Return type

telebot.types.ChatMemberMember

```
class telebot.types.ChatMemberOwner(user, status, custom_title=None, is_anonymous=None,
                                     can_be_edited=None, can_post_messages=None,
                                     can_edit_messages=None, can_delete_messages=None,
                                     can_restrict_members=None, can_promote_members=None,
                                     can_change_info=None, can_invite_users=None,
                                     can_pin_messages=None, is_member=None,
                                     can_send_messages=None, can_send_audios=None,
                                     can_send_documents=None, can_send_photos=None,
                                     can_send_videos=None, can_send_video_notes=None,
                                     can_send_voice_notes=None, can_send_polls=None,
                                     can_send_other_messages=None,
                                     can_add_web_page_previews=None, can_manage_chat=None,
                                     can_manage_video_chats=None, until_date=None,
                                     can_manage_topics=None, can_post_stories=None,
                                     can_edit_stories=None, can_delete_stories=None, **kwargs)
```

Bases: *ChatMember*

Represents a chat member that owns the chat and has all administrator privileges.

Telegram Documentation: <https://core.telegram.org/bots/api#chatmemberowner>

Parameters

- **status** (str) – The member’s status in the chat, always “creator”
- **user** (*telebot.types.User*) – Information about the user
- **is_anonymous** (bool) – True, if the user’s presence in the chat is hidden
- **custom_title** (str) – Optional. Custom title for this user

Returns

Instance of the class

Return type

telebot.types.ChatMemberOwner

```
class telebot.types.ChatMemberRestricted(user, status, custom_title=None, is_anonymous=None,
                                         can_be_edited=None, can_post_messages=None,
                                         can_edit_messages=None, can_delete_messages=None,
                                         can_restrict_members=None, can_promote_members=None,
                                         can_change_info=None, can_invite_users=None,
                                         can_pin_messages=None, is_member=None,
                                         can_send_messages=None, can_send_audios=None,
                                         can_send_documents=None, can_send_photos=None,
                                         can_send_videos=None, can_send_video_notes=None,
                                         can_send_voice_notes=None, can_send_polls=None,
                                         can_send_other_messages=None,
                                         can_add_web_page_previews=None, can_manage_chat=None,
                                         can_manage_video_chats=None, until_date=None,
                                         can_manage_topics=None, can_post_stories=None,
                                         can_edit_stories=None, can_delete_stories=None, **kwargs)
```

Bases: *ChatMember*

Represents a chat member that is under certain restrictions in the chat. Supergroups only.

Telegram Documentation: <https://core.telegram.org/bots/api#chatmemberrestricted>

Parameters

- **status** (str) – The member’s status in the chat, always “restricted”
- **user** (*telebot.types.User*) – Information about the user
- **is_member** (bool) – True, if the user is a member of the chat at the moment of the request
- **can_change_info** (bool) – True, if the user is allowed to change the chat title, photo and other settings
- **can_invite_users** (bool) – True, if the user is allowed to invite new users to the chat
- **can_pin_messages** (bool) – True, if the user is allowed to pin messages
- **can_manage_topics** (bool) – True, if the user is allowed to create forum topics
- **can_send_messages** (bool) – True, if the user is allowed to send text messages, contacts, locations and venues
- **can_send_audios** (bool) – True, if the user is allowed to send audios
- **can_send_documents** (bool) – True, if the user is allowed to send documents
- **can_send_photos** (bool) – True, if the user is allowed to send photos
- **can_send_videos** (bool) – True, if the user is allowed to send videos
- **can_send_video_notes** (bool) – True, if the user is allowed to send video notes
- **can_send_voice_notes** (bool) – True, if the user is allowed to send voice notes
- **can_send_polls** (bool) – True, if the user is allowed to send polls
- **can_send_other_messages** (bool) – True, if the user is allowed to send animations, games, stickers and use inline bots
- **can_add_web_page_previews** (bool) – True, if the user is allowed to add web page previews to their messages
- **until_date** (int) – Date when restrictions will be lifted for this user; unix time. If 0, then the user is restricted forever

Returns

Instance of the class

Return type

telebot.types.ChatMemberRestricted

```
class telebot.types.ChatMemberUpdated(chat, from_user, date, old_chat_member, new_chat_member,
                                       invite_link=None, via_chat_folder_invite_link=None, **kwargs)
```

Bases: *JsonDeserializable*

This object represents changes in the status of a chat member.

Telegram Documentation: <https://core.telegram.org/bots/api#chatmemberupdated>

Parameters

- **chat** (*telebot.types.Chat*) – Chat the user belongs to
- **from_user** (*telebot.types.User*) – Performer of the action, which resulted in the change
- **date** (int) – Date the change was done in Unix time
- **old_chat_member** (*telebot.types.ChatMember*) – Previous information about the chat member
- **new_chat_member** (*telebot.types.ChatMember*) – New information about the chat member
- **invite_link** (*telebot.types.ChatInviteLink*) – Optional. Chat invite link, which was used by the user to join the chat; for joining by invite link events only.
- **via_chat_folder_invite_link** (bool) – Optional. True, if the user joined the chat via a chat folder invite link

Returns

Instance of the class

Return type

telebot.types.ChatMemberUpdated

property difference: Dict[str, List]

Get the difference between *old_chat_member* and *new_chat_member* as a dict in the following format { 'parameter': [old_value, new_value]} E.g { 'status': ['member', 'kicked'], 'until_date': [None, 1625055092]}

Returns

Dict of differences

Return type

Dict[str, List]

```
class telebot.types.ChatPermissions(can_send_messages=None, can_send_media_messages=None,
                                       can_send_audios=None, can_send_documents=None,
                                       can_send_photos=None, can_send_videos=None,
                                       can_send_video_notes=None, can_send_voice_notes=None,
                                       can_send_polls=None, can_send_other_messages=None,
                                       can_add_web_page_previews=None, can_change_info=None,
                                       can_invite_users=None, can_pin_messages=None,
                                       can_manage_topics=None, **kwargs)
```

Bases: *JsonDeserializable, JsonSerializerizable, Dictionaryable*

Describes actions that a non-administrator user is allowed to take in a chat.

Telegram Documentation: <https://core.telegram.org/bots/api#chatpermissions>

Parameters

- **can_send_messages** (bool) – Optional. True, if the user is allowed to send text messages, contacts, locations and venues
- **can_send_audios** (bool) – Optional. True, if the user is allowed to send audios
- **can_send_documents** (bool) – Optional. True, if the user is allowed to send documents
- **can_send_photos** (bool) – Optional. True, if the user is allowed to send photos
- **can_send_videos** (bool) – Optional. True, if the user is allowed to send videos
- **can_send_video_notes** (bool) – Optional. True, if the user is allowed to send video notes
- **can_send_voice_notes** (bool) – Optional. True, if the user is allowed to send voice notes
- **can_send_polls** (bool) – Optional. True, if the user is allowed to send polls, implies `can_send_messages`
- **can_send_other_messages** (bool) – Optional. True, if the user is allowed to send animations, games, stickers and use inline bots
- **can_add_web_page_previews** (bool) – Optional. True, if the user is allowed to add web page previews to their messages
- **can_change_info** (bool) – Optional. True, if the user is allowed to change the chat title, photo and other settings. Ignored in public supergroups
- **can_invite_users** (bool) – Optional. True, if the user is allowed to invite new users to the chat
- **can_pin_messages** (bool) – Optional. True, if the user is allowed to pin messages. Ignored in public supergroups
- **can_manage_topics** (bool) – Optional. True, if the user is allowed to create forum topics. If omitted defaults to the value of `can_pin_messages`
- **can_send_media_messages** (bool) – deprecated.

Returns

Instance of the class

Return type

telebot.types.ChatPermissions

```
class telebot.types.ChatPhoto(small_file_id, small_file_unique_id, big_file_id, big_file_unique_id,  
                             **kwargs)
```

Bases: *JsonDeserializable*

This object represents a chat photo.

Telegram Documentation: <https://core.telegram.org/bots/api#chatphoto>

Parameters

- **small_file_id** (str) – File identifier of small (160x160) chat photo. This `file_id` can be used only for photo download and only for as long as the photo is not changed.
- **small_file_unique_id** (str) – Unique file identifier of small (160x160) chat photo, which is supposed to be the same over time and for different bots. Can't be used to download or reuse the file.
- **big_file_id** (str) – File identifier of big (640x640) chat photo. This `file_id` can be used only for photo download and only for as long as the photo is not changed.

- **big_file_unique_id** (str) – Unique file identifier of big (640x640) chat photo, which is supposed to be the same over time and for different bots. Can't be used to download or reuse the file.

Returns

Instance of the class

Return type

telebot.types.ChatPhoto

```
class telebot.types.ChatShared(request_id: int, chat_id: int, title: str | None = None, photo: List[PhotoSize] | None = None, username: str | None = None, **kwargs)
```

Bases: *JsonDeserializable*

This object contains information about the chat whose identifier was shared with the bot using a *telebot.types.KeyboardButtonRequestChat* button.

Telegram documentation: <https://core.telegram.org/bots/api#Chatshared>

Parameters

- **request_id** (int) – identifier of the request
- **chat_id** (int) – Identifier of the shared chat. This number may have more than 32 significant bits and some programming languages may have difficulty/silent defects in interpreting it. But it has at most 52 significant bits, so a 64-bit integer or double-precision float type are safe for storing this identifier. The bot may not have access to the chat and could be unable to use this identifier, unless the chat is already known to the bot by some other means.
- **title** (str) – Optional. Title of the shared chat
- **photo** (list of *telebot.types.PhotoSize*) – Optional. Array of Photosize
- **username** (str) – Optional. Username of the shared chat

Returns

Instance of the class

Return type

telebot.types.ChatShared

```
class telebot.types.ChosenInlineResult(result_id, from_user, query, location=None, inline_message_id=None, **kwargs)
```

Bases: *JsonDeserializable*

Represents a result of an inline query that was chosen by the user and sent to their chat partner.

Telegram Documentation: <https://core.telegram.org/bots/api#choseninlineresult>

Parameters

- **result_id** (str) – The unique identifier for the result that was chosen
- **from** (*telebot.types.User*) – The user that chose the result
- **location** (*telebot.types.Location*) – Optional. Sender location, only for bots that require user location
- **inline_message_id** (str) – Optional. Identifier of the sent inline message. Available only if there is an inline keyboard attached to the message. Will be also received in callback queries and can be used to edit the message.
- **query** (str) – The query that was used to obtain the result

Returns

Instance of the class

Return type

telebot.types.ChosenInlineResult

```
class telebot.types.Contact(phone_number, first_name, last_name=None, user_id=None, vcard=None,
                             **kwargs)
```

Bases: *JsonDeserializable*

This object represents a phone contact.

Telegram Documentation: <https://core.telegram.org/bots/api#contact>

Parameters

- **phone_number** (str) – Contact’s phone number
- **first_name** (str) – Contact’s first name
- **last_name** (str) – Optional. Contact’s last name
- **user_id** (int) – Optional. Contact’s user identifier in Telegram. This number may have more than 32 significant bits and some programming languages may have difficulty/silent defects in interpreting it. But it has at most 52 significant bits, so a 64-bit integer or double-precision float type are safe for storing this identifier.
- **vcard** (str) – Optional. Additional data about the contact in the form of a vCard

Returns

Instance of the class

Return type

telebot.types.Contact

```
class telebot.types.Dice(value, emoji, **kwargs)
```

Bases: *JsonSerializable, Dictionaryable, JsonDeserializable*

This object represents an animated emoji that displays a random value.

Telegram Documentation: <https://core.telegram.org/bots/api#dice>

Parameters

- **emoji** (str) – Emoji on which the dice throw animation is based
- **value** (int) – Value of the dice, 1-6 for “”, “” and “” base emoji, 1-5 for “” and “” base emoji, 1-64 for “” base emoji

Returns

Instance of the class

Return type

telebot.types.Dice

```
class telebot.types.Dictionaryable
```

Bases: object

Subclasses of this class are guaranteed to be able to be converted to dictionary. All subclasses of this class must override to_dict.

```
class telebot.types.Document(file_id, file_unique_id, thumbnail=None, file_name=None, mime_type=None,
                              file_size=None, **kwargs)
```

Bases: *JsonDeserializable*

This object represents a general file (as opposed to photos, voice messages and audio files).

Telegram Documentation: <https://core.telegram.org/bots/api#document>

Parameters

- **file_id** (str) – Identifier for this file, which can be used to download or reuse the file
- **file_unique_id** (str) – Unique identifier for this file, which is supposed to be the same over time and for different bots. Can't be used to download or reuse the file.
- **thumbnail** (*telebot.types.PhotoSize*) – Optional. Document thumbnail as defined by sender
- **file_name** (str) – Optional. Original filename as defined by sender
- **mime_type** (str) – Optional. MIME type of the file as defined by sender
- **file_size** (int) – Optional. File size in bytes. It can be bigger than 2^{31} and some programming languages may have difficulty/silent defects in interpreting it. But it has at most 52 significant bits, so a signed 64-bit integer or double-precision float type are safe for storing this value.

Returns

Instance of the class

Return type

telebot.types.Document

property thumb

```
class telebot.types.ExternalReplyInfo(origin: MessageOrigin, chat: Chat | None = None, message_id: int | None = None, link_preview_options: LinkPreviewOptions | None = None, animation: Animation | None = None, audio: Audio | None = None, document: Document | None = None, photo: List[PhotoSize] | None = None, sticker: Sticker | None = None, story: Story | None = None, video: Video | None = None, video_note: VideoNote | None = None, voice: Voice | None = None, has_media_spoiler: bool | None = None, contact: Contact | None = None, dice: Dice | None = None, game: Game | None = None, giveaway: Giveaway | None = None, giveaway_winners: GiveawayWinners | None = None, invoice: Invoice | None = None, location: Location | None = None, poll: Poll | None = None, venue: Venue | None = None, **kwargs)
```

Bases: *JsonDeserializable*

This object contains information about a message that is being replied to, which may come from another chat or forum topic.

Telegram documentation: <https://core.telegram.org/bots/api#externalreplyinfo>

Parameters

- **origin** (*MessageOrigin*) – Origin of the message replied to by the given message
- **chat** (*Chat*) – Optional. Chat the original message belongs to. Available only if the chat is a supergroup or a channel.
- **message_id** (int) – Optional. Unique message identifier inside the original chat. Available only if the original chat is a supergroup or a channel.

- **link_preview_options** (*LinkPreviewOptions*) – Optional. Options used for link preview generation for the original message, if it is a text message
- **animation** (*Animation*) – Optional. Message is an animation, information about the animation
- **audio** (*Audio*) – Optional. Message is an audio file, information about the file
- **document** (*Document*) – Optional. Message is a general file, information about the file
- **photo** (list of *PhotoSize*) – Optional. Message is a photo, available sizes of the photo
- **sticker** (*Sticker*) – Optional. Message is a sticker, information about the sticker
- **story** (*Story*) – Optional. Message is a forwarded story
- **video** (*Video*) – Optional. Message is a video, information about the video
- **video_note** (*VideoNote*) – Optional. Message is a video note, information about the video message
- **voice** (*Voice*) – Optional. Message is a voice message, information about the file
- **has_media_spoiler** (bool) – Optional. True, if the message media is covered by a spoiler animation
- **contact** (*Contact*) – Optional. Message is a shared contact, information about the contact
- **dice** (*Dice*) – Optional. Message is a dice with random value
- **game** (*Game*) – Optional. Message is a game, information about the game. More about games »
- **giveaway** (*Giveaway*) – Optional. Message is a scheduled giveaway, information about the giveaway
- **giveaway_winners** (*GiveawayWinners*) – Optional. A giveaway with public winners was completed
- **invoice** (*Invoice*) – Optional. Message is an invoice for a payment, information about the invoice. More about payments »
- **location** (*Location*) – Optional. Message is a shared location, information about the location
- **poll** (*Poll*) – Optional. Message is a native poll, information about the poll
- **venue** (*Venue*) – Optional. Message is a venue, information about the venue

Returns

Instance of the class

Return type

ExternalReplyInfo

```
class telebot.types.File(file_id, file_unique_id, file_size=None, file_path=None, **kwargs)
```

Bases: *JsonDeserializable*

This object represents a file ready to be downloaded. The file can be downloaded via the link https://api.telegram.org/file/bot<token>/<file_path>. It is guaranteed that the link will be valid for at least 1 hour. When the link expires, a new one can be requested by calling `getFile`.

Telegram Documentation: <https://core.telegram.org/bots/api#file>

Parameters

- **file_id** (str) – Identifier for this file, which can be used to download or reuse the file

- **file_unique_id** (str) – Unique identifier for this file, which is supposed to be the same over time and for different bots. Can't be used to download or reuse the file.
- **file_size** (int) – Optional. File size in bytes. It can be bigger than 2^{31} and some programming languages may have difficulty/silent defects in interpreting it. But it has at most 52 significant bits, so a signed 64-bit integer or double-precision float type are safe for storing this value.
- **file_path** (str) – Optional. File path. Use https://api.telegram.org/file/bot<token>/<file_path> to get the file.

Returns

Instance of the class

Return type

telebot.types.File

class telebot.types.**ForceReply**(*selective: bool | None = None, input_field_placeholder: str | None = None*)

Bases: *JsonSerializable*

Upon receiving a message with this object, Telegram clients will display a reply interface to the user (act as if the user has selected the bot's message and tapped 'Reply'). This can be extremely useful if you want to create user-friendly step-by-step interfaces without having to sacrifice privacy mode.

Telegram Documentation: <https://core.telegram.org/bots/api#forcereply>

Parameters

- **force_reply** (bool) – Shows reply interface to the user, as if they manually selected the bot's message and tapped 'Reply'
- **input_field_placeholder** (str) – Optional. The placeholder to be shown in the input field when the reply is active; 1-64 characters
- **selective** (bool) – Optional. Use this parameter if you want to force reply from specific users only. Targets: 1) users that are @mentioned in the text of the Message object; 2) if the bot's message is a reply to a message in the same chat and forum topic, sender of the original message.

Returns

Instance of the class

Return type

telebot.types.ForceReply

class telebot.types.**ForumTopic**(*message_thread_id: int, name: str, icon_color: int, icon_custom_emoji_id: str | None = None, **kwargs*)

Bases: *JsonDeserializable*

This object represents a forum topic.

Telegram documentation: <https://core.telegram.org/bots/api#forumtopic>

Parameters

- **message_thread_id** (int) – Unique identifier of the forum topic
- **name** (str) – Name of the topic
- **icon_color** (int) – Color of the topic icon in RGB format
- **icon_custom_emoji_id** (str) – Optional. Unique identifier of the custom emoji shown as the topic icon

Returns

Instance of the class

Return type

telebot.types.ForumTopic

class telebot.types.**ForumTopicClosed**

Bases: *JsonDeserializable*

This object represents a service message about a forum topic closed in the chat. Currently holds no information.

Telegram documentation: <https://core.telegram.org/bots/api#forumtopicclosed>

class telebot.types.**ForumTopicCreated**(*name: str, icon_color: int, icon_custom_emoji_id: str | None = None, **kwargs*)

Bases: *JsonDeserializable*

This object represents a service message about a new forum topic created in the chat.

Telegram documentation: <https://core.telegram.org/bots/api#forumtopiccreated>

Parameters

- **name** (str) – Name of the topic
- **icon_color** (int) – Color of the topic icon in RGB format
- **icon_custom_emoji_id** (str) – Optional. Unique identifier of the custom emoji shown as the topic icon

Returns

Instance of the class

Return type

telebot.types.ForumTopicCreated

class telebot.types.**ForumTopicEdited**(*name: str | None = None, icon_custom_emoji_id: str | None = None, **kwargs*)

Bases: *JsonDeserializable*

This object represents a service message about an edited forum topic.

Telegram documentation: <https://core.telegram.org/bots/api#forumtopicedited>

Parameters

- **name** (str) – Optional. Name of the topic(if updated)
- **icon_custom_emoji_id** (str) – Optional. New identifier of the custom emoji shown as the topic icon, if it was edited; an empty string if the icon was removed

class telebot.types.**ForumTopicReopened**

Bases: *JsonDeserializable*

This object represents a service message about a forum topic reopened in the chat. Currently holds no information.

Telegram documentation: <https://core.telegram.org/bots/api#forumtopicreopened>

class telebot.types.**Game**(*title, description, photo, text=None, text_entities=None, animation=None, **kwargs*)

Bases: *JsonDeserializable*

This object represents a game. Use BotFather to create and edit games, their short names will act as unique identifiers.

Telegram Documentation: <https://core.telegram.org/bots/api#game>

Parameters

- **title** (str) – Title of the game
- **description** (str) – Description of the game
- **photo** (list of *telebot.types.PhotoSize*) – Photo that will be displayed in the game message in chats.
- **text** (str) – Optional. Brief description of the game or high scores included in the game message. Can be automatically edited to include current high scores for the game when the bot calls `setGameScore`, or manually edited using `editMessageText`. 0-4096 characters.
- **text_entities** (list of *telebot.types.MessageEntity*) – Optional. Special entities that appear in text, such as usernames, URLs, bot commands, etc.
- **animation** (*telebot.types.Animation*) – Optional. Animation that will be displayed in the game message in chats. Upload via BotFather

Returns

Instance of the class

Return type

telebot.types.Game

classmethod `parse_entities(message_entity_array)`

Parse the message entity array into a list of `MessageEntity` objects

classmethod `parse_photo(photo_size_array)`

Parse the photo array into a list of `PhotoSize` objects

class `telebot.types.GameHighScore(position, user, score, **kwargs)`

Bases: *JsonDeserializable*

This object represents one row of the high scores table for a game.

Telegram Documentation: <https://core.telegram.org/bots/api#gamehighscore>

Parameters

- **position** (int) – Position in high score table for the game
- **user** (*telebot.types.User*) – User
- **score** (int) – Score

Returns

Instance of the class

Return type

telebot.types.GameHighScore

class `telebot.types.GeneralForumTopicHidden`

Bases: *JsonDeserializable*

This object represents a service message about General forum topic hidden in the chat. Currently holds no information.

Telegram documentation: <https://core.telegram.org/bots/api#generalforumtopichidden>

class telebot.types.GeneralForumTopicUnhidden

Bases: *JsonDeserializable*

This object represents a service message about General forum topic unhidden in the chat. Currently holds no information.

Telegram documentation: <https://core.telegram.org/bots/api#generalforumtopicunhidden>

class telebot.types.Giveaway(*chats: List[Chat], winners_selection_date: int, winner_count: int, only_new_members: bool | None = None, has_public_winners: bool | None = None, prize_description: str | None = None, country_codes: List[str] | None = None, premium_subscription_month_count: int | None = None, **kwargs*)

Bases: *JsonDeserializable*

This object represents a message about a scheduled giveaway.

Telegram documentation: <https://core.telegram.org/bots/api#giveaway>

Parameters

- **chats** (list of *Chat*) – The list of chats which the user must join to participate in the giveaway
- **winners_selection_date** (int) – Point in time (Unix timestamp) when winners of the giveaway will be selected
- **winner_count** (int) – The number of users which are supposed to be selected as winners of the giveaway
- **only_new_members** (bool) – Optional. True, if only users who join the chats after the giveaway started should be eligible to win
- **has_public_winners** (bool) – Optional. True, if the list of giveaway winners will be visible to everyone
- **prize_description** (str) – Optional. Description of additional giveaway prize
- **country_codes** (list of str) – Optional. A list of two-letter ISO 3166-1 alpha-2 country codes indicating the countries from which eligible users for the giveaway must come. If empty, then all users can participate in the giveaway.
- **premium_subscription_month_count** (int) – Optional. The number of months the Telegram Premium subscription won from the giveaway will be active for

Returns

Instance of the class

Return type

Giveaway

class telebot.types.GiveawayCompleted(*winner_count: int, unclaimed_prize_count: int | None = None, giveaway_message: Message | None = None, **kwargs*)

Bases: *JsonDeserializable*

This object represents a service message about the completion of a giveaway without public winners.

Telegram documentation: <https://core.telegram.org/bots/api#giveawaycompleted>

Parameters

- **winner_count** (int) – Number of winners in the giveaway
- **unclaimed_prize_count** (int) – Optional. Number of undistributed prizes

- **giveaway_message** (*Message*) – Optional. Message with the giveaway that was completed, if it wasn't deleted

Returns

Instance of the class

Return type

GiveawayCompleted

class telebot.types.**GiveawayCreated**(**kwargs)

Bases: *JsonDeserializable*

This object represents a service message about the creation of a scheduled giveaway. Currently holds no information.

class telebot.types.**GiveawayWinners**(chat: *Chat*, giveaway_message_id: *int*, winners_selection_date: *int*, winner_count: *int*, winners: *List[User]*, additional_chat_count: *int* | *None* = *None*, premium_subscription_month_count: *int* | *None* = *None*, unclaimed_prize_count: *int* | *None* = *None*, only_new_members: *bool* | *None* = *None*, was_refunded: *bool* | *None* = *None*, prize_description: *str* | *None* = *None*, **kwargs)

Bases: *JsonDeserializable*

This object represents a message about the completion of a giveaway with public winners.

Telegram documentation: <https://core.telegram.org/bots/api#giveawaywinners>

Parameters

- **chat** (*Chat*) – The chat that created the giveaway
- **giveaway_message_id** (*int*) – Identifier of the message with the giveaway in the chat
- **winners_selection_date** (*int*) – Point in time (Unix timestamp) when winners of the giveaway were selected
- **winner_count** (*int*) – Total number of winners in the giveaway
- **winners** (*list of User*) – List of up to 100 winners of the giveaway
- **additional_chat_count** (*int*) – Optional. The number of other chats the user had to join in order to be eligible for the giveaway
- **premium_subscription_month_count** (*int*) – Optional. The number of months the Telegram Premium subscription won from the giveaway will be active for
- **unclaimed_prize_count** (*int*) – Optional. Number of undistributed prizes
- **only_new_members** (*bool*) – Optional. True, if only users who had joined the chats after the giveaway started were eligible to win
- **was_refunded** (*bool*) – Optional. True, if the giveaway was canceled because the payment for it was refunded
- **prize_description** (*str*) – Optional. Description of additional giveaway prize

Returns

Instance of the class

Return type

GiveawayWinners

class telebot.types.InaccessibleMessage(*chat, message_id, date, **kwargs*)

Bases: *JsonDeserializable*

This object describes a message that was deleted or is otherwise inaccessible to the bot.

Telegram documentation: <https://core.telegram.org/bots/api#inaccessiblemessage>

Parameters

- **chat** (*Chat*) – Chat the message belonged to
- **message_id** (int) – Unique message identifier inside the chat
- **date** (int) – Always 0. The field can be used to differentiate regular and inaccessible messages.

Returns

Instance of the class

Return type

InaccessibleMessage

class telebot.types.InlineKeyboardButton(*text, url=None, callback_data=None, web_app=None, switch_inline_query=None, switch_inline_query_current_chat=None, switch_inline_query_chosen_chat=None, callback_game=None, pay=None, login_url=None, **kwargs*)

Bases: *Dictionaryable, JsonSerializerizable, JsonDeserializable*

This object represents one button of an inline keyboard. You must use exactly one of the optional fields.

Telegram Documentation: <https://core.telegram.org/bots/api#inlinekeyboardbutton>

Parameters

- **text** (str) – Label text on the button
- **url** (str) – Optional. HTTP or tg:// URL to be opened when the button is pressed. Links `tg://user?id=<user_id>` can be used to mention a user by their ID without using a username, if this is allowed by their privacy settings.
- **callback_data** (str) – Optional. Data to be sent in a callback query to the bot when button is pressed, 1-64 bytes
- **web_app** (*telebot.types.WebAppInfo*) – Optional. Description of the Web App that will be launched when the user presses the button. The Web App will be able to send an arbitrary message on behalf of the user using the method `answerWebAppQuery`. Available only in private chats between a user and the bot.
- **login_url** (*telebot.types.LoginUrl*) – Optional. An HTTPS URL used to automatically authorize the user. Can be used as a replacement for the Telegram Login Widget.
- **switch_inline_query** (str) – Optional. If set, pressing the button will prompt the user to select one of their chats, open that chat and insert the bot's username and the specified inline query in the input field. May be empty, in which case just the bot's username will be inserted. Note: This offers an easy way for users to start using your bot in inline mode when they are currently in a private chat with it. Especially useful when combined with `switch_pm...` actions - in this case the user will be automatically returned to the chat they switched from, skipping the chat selection screen.
- **switch_inline_query_current_chat** (str) – Optional. If set, pressing the button will insert the bot's username and the specified inline query in the current chat's input field. May be empty, in which case only the bot's username will be inserted. This offers a quick way for

the user to open your bot in inline mode in the same chat - good for selecting something from multiple options.

- **switch_inline_query_chosen_chat** (*telebot.types.SwitchInlineQueryChosenChat*) – Optional. If set, pressing the button will prompt the user to select one of their chats of the specified type, open that chat and insert the bot's username and the specified inline query in the input field
- **callback_game** (*telebot.types.CallbackGame*) – Optional. Description of the game that will be launched when the user presses the button. NOTE: This type of button must always be the first button in the first row.
- **pay** (bool) – Optional. Specify True, to send a Pay button. NOTE: This type of button must always be the first button in the first row and can only be used in invoice messages.

Returns

Instance of the class

Return type

telebot.types.InlineKeyboardButton

class telebot.types.**InlineKeyboardMarkup**(*keyboard=None, row_width=3*)

Bases: *Dictionaryable, JsonSerializable, JsonDeserializable*

This object represents an inline keyboard that appears right next to the message it belongs to.

Note: It is recommended to use *telebot.util.quick_markup()* instead.

Listing 1: Example of a custom keyboard with buttons.

```
from telebot.util import quick_markup

markup = quick_markup({
    'Twitter': {'url': 'https://twitter.com'},
    'Facebook': {'url': 'https://facebook.com'},
    'Back': {'callback_data': 'whatever'}
}, row_width=2)
# returns an InlineKeyboardMarkup with two buttons in a row, one leading to Twitter,
# → the other to facebook
# and a back button below
```

Telegram Documentation: <https://core.telegram.org/bots/api#inlinekeyboardmarkup>

Parameters

- **keyboard** (list of list of *telebot.types.InlineKeyboardButton*) – list of button rows, each represented by an list of *telebot.types.InlineKeyboardButton* objects
- **row_width** (int) – number of *telebot.types.InlineKeyboardButton* objects on each row

Returns

Instance of the class

Return type

telebot.types.InlineKeyboardMarkup

add(*args, row_width=None)

This method adds buttons to the keyboard without exceeding row_width.

E.g. `InlineKeyboardMarkup.add("A", "B", "C")` yields the json result: `{keyboard: [[["A"], ["B"], ["C"]]]}` when row_width is set to 1. When row_width is set to 2, the result: `{keyboard: [[["A", "B"], ["C"]]]}` See <https://core.telegram.org/bots/api#inlinekeyboardmarkup>

Parameters

- **args** (list of `telebot.types.InlineKeyboardButton`) – Array of `InlineKeyboardButton` to append to the keyboard
- **row_width** (int) – width of row

Returns

self, to allow function chaining.

Return type

`telebot.types.InlineKeyboardMarkup`

max_row_keys = 8

row(*args)

Adds a list of `InlineKeyboardButton` to the keyboard. This method does not consider row_width.

`InlineKeyboardMarkup.row("A").row("B", "C").to_json()` outputs: `'{keyboard: [[["A"], ["B"], ["C"]]]}'` See <https://core.telegram.org/bots/api#inlinekeyboardmarkup>

Parameters

args (list of `telebot.types.InlineKeyboardButton`) – Array of `InlineKeyboardButton` to append to the keyboard

Returns

self, to allow function chaining.

Return type

`telebot.types.InlineKeyboardMarkup`

class `telebot.types.InlineQuery`(id, from_user, query, offset, chat_type=None, location=None, **kwargs)

Bases: `JsonDeserializable`

This object represents an incoming inline query. When the user sends an empty query, your bot could return some default or trending results.

Telegram Documentation: <https://core.telegram.org/bots/api#inlinequery>

Parameters

- **id** (str) – Unique identifier for this query
- **from_user** (`telebot.types.User`) – Sender
- **query** (str) – Text of the query (up to 256 characters)
- **offset** (str) – Offset of the results to be returned, can be controlled by the bot
- **chat_type** (str) – Optional. Type of the chat from which the inline query was sent. Can be either "sender" for a private chat with the inline query sender, "private", "group", "super-group", or "channel". The chat type should be always known for requests sent from official clients and most third-party clients, unless the request was sent from a secret chat
- **location** (`telebot.types.Location`) – Optional. Sender location, only for bots that request user location

Returns

Instance of the class

Return type

telebot.types.InlineQuery

```
class telebot.types.InlineQueryResultArticle(id, title, input_message_content, reply_markup=None,
url=None, hide_url=None, description=None,
thumbnail_url=None, thumbnail_width=None,
thumbnail_height=None)
```

Bases: *InlineQueryResultBase*

Represents a link to an article or web page.

Telegram Documentation: <https://core.telegram.org/bots/api#inlinequeryresultarticle>

Parameters

- **type** (str) – Type of the result, must be article
- **id** (str) – Unique identifier for this result, 1-64 Bytes
- **title** (str) – Title of the result
- **input_message_content** (*telebot.types.InputMessageContent*) – Content of the message to be sent
- **reply_markup** (*telebot.types.InlineKeyboardMarkup*) – Optional. Inline keyboard attached to the message
- **url** (str) – Optional. URL of the result
- **hide_url** (bool) – Optional. Pass True, if you don't want the URL to be shown in the message
- **description** (str) – Optional. Short description of the result
- **thumbnail_url** (str) – Optional. Url of the thumbnail for the result
- **thumbnail_width** (int) – Optional. Thumbnail width
- **thumbnail_height** (int) – Optional. Thumbnail height

Returns

Instance of the class

Return type

telebot.types.InlineQueryResultArticle

property thumb_height

property thumb_url

property thumb_width

```
class telebot.types.InlineQueryResultAudio(id, audio_url, title, caption=None, caption_entities=None,
parse_mode=None, performer=None,
audio_duration=None, reply_markup=None,
input_message_content=None)
```

Bases: *InlineQueryResultBase*

Represents a link to an MP3 audio file. By default, this audio file will be sent by the user. Alternatively, you can use `input_message_content` to send a message with the specified content instead of the audio.

Telegram Documentation: <https://core.telegram.org/bots/api#inlinequeryresultaudio>

Parameters

- **type** (str) – Type of the result, must be audio
- **id** (str) – Unique identifier for this result, 1-64 bytes
- **audio_url** (str) – A valid URL for the audio file
- **title** (str) – Title
- **caption** (str) – Optional. Caption, 0-1024 characters after entities parsing
- **parse_mode** (str) – Optional. Mode for parsing entities in the audio caption. See formatting options for more details.
- **caption_entities** (list of *telebot.types.MessageEntity*) – Optional. List of special entities that appear in the caption, which can be specified instead of parse_mode
- **performer** (str) – Optional. Performer
- **audio_duration** (int) – Optional. Audio duration in seconds
- **reply_markup** (*telebot.types.InlineKeyboardMarkup*) – Optional. Inline keyboard attached to the message
- **input_message_content** (*telebot.types.InputMessageContent*) – Optional. Content of the message to be sent instead of the audio

Returns

Instance of the class

Return type

telebot.types.InlineQueryResultAudio

```
class telebot.types.InlineQueryResultBase(type, id, title=None, caption=None,
                                           input_message_content=None, reply_markup=None,
                                           caption_entities=None, parse_mode=None)
```

Bases: ABC, *Dictionaryable*, *JsonSerializable*

This object represents one result of an inline query. Telegram clients currently support results of the following 20 types:

- *InlineQueryResultCachedAudio*
- *InlineQueryResultCachedDocument*
- *InlineQueryResultCachedGif*
- *InlineQueryResultCachedMpeg4Gif*
- *InlineQueryResultCachedPhoto*
- *InlineQueryResultCachedSticker*
- *InlineQueryResultCachedVideo*
- *InlineQueryResultCachedVoice*
- *InlineQueryResultArticle*
- *InlineQueryResultAudio*
- *InlineQueryResultContact*
- *InlineQueryResultGame*
- *InlineQueryResultDocument*

- [*InlineQueryResultGif*](#)
- [*InlineQueryResultLocation*](#)
- [*InlineQueryResultMpeg4Gif*](#)
- [*InlineQueryResultPhoto*](#)
- [*InlineQueryResultVenue*](#)
- [*InlineQueryResultVideo*](#)
- [*InlineQueryResultVoice*](#)

Telegram Documentation: <https://core.telegram.org/bots/api#inlinequeryresult>

```
class telebot.types.InlineQueryResultCachedAudio(id, audio_file_id, caption=None,
caption_entities=None, parse_mode=None,
reply_markup=None,
input_message_content=None)
```

Bases: [*InlineQueryResultCachedBase*](#)

Represents a link to an MP3 audio file stored on the Telegram servers. By default, this audio file will be sent by the user. Alternatively, you can use `input_message_content` to send a message with the specified content instead of the audio.

Telegram Documentation: <https://core.telegram.org/bots/api#inlinequeryresultcachedaudio>

Parameters

- **type** (str) – Type of the result, must be audio
- **id** (str) – Unique identifier for this result, 1-64 bytes
- **audio_file_id** (str) – A valid file identifier for the audio file
- **caption** (str) – Optional. Caption, 0-1024 characters after entities parsing
- **parse_mode** (str) – Optional. Mode for parsing entities in the audio caption. See formatting options for more details.
- **caption_entities** (list of [*telebot.types.MessageEntity*](#)) – Optional. List of special entities that appear in the caption, which can be specified instead of `parse_mode`
- **reply_markup** ([*telebot.types.InlineKeyboardMarkup*](#)) – Optional. Inline keyboard attached to the message
- **input_message_content** ([*telebot.types.InputMessageContent*](#)) – Optional. Content of the message to be sent instead of the audio

Returns

Instance of the class

Return type

[*telebot.types.InlineQueryResultCachedAudio*](#)

```
class telebot.types.InlineQueryResultCachedBase
```

Bases: ABC, [*JsonSerializable*](#)

Base class of all `InlineQueryResultCached*` classes.

```
class telebot.types.InlineQueryResultCachedDocument(id, document_file_id, title, description=None,
caption=None, caption_entities=None,
parse_mode=None, reply_markup=None,
input_message_content=None)
```

Bases: [InlineQueryResultCachedBase](#)

Represents a link to a file stored on the Telegram servers. By default, this file will be sent by the user with an optional caption. Alternatively, you can use `input_message_content` to send a message with the specified content instead of the file.

Telegram Documentation: <https://core.telegram.org/bots/api#inlinequeryresultcacheddocument>

Parameters

- **type** (str) – Type of the result, must be document
- **id** (str) – Unique identifier for this result, 1-64 bytes
- **title** (str) – Title for the result
- **document_file_id** (str) – A valid file identifier for the file
- **description** (str) – Optional. Short description of the result
- **caption** (str) – Optional. Caption of the document to be sent, 0-1024 characters after entities parsing
- **parse_mode** (str) – Optional. Mode for parsing entities in the document caption. See formatting options for more details.
- **caption_entities** (list of [telebot.types.MessageEntity](#)) – Optional. List of special entities that appear in the caption, which can be specified instead of `parse_mode`
- **reply_markup** ([telebot.types.InlineKeyboardMarkup](#)) – Optional. Inline keyboard attached to the message
- **input_message_content** ([telebot.types.InputMessageContent](#)) – Optional. Content of the message to be sent instead of the file

Returns

Instance of the class

Return type

[telebot.types.InlineQueryResultCachedDocument](#)

```
class telebot.types.InlineQueryResultCachedGif(id, gif_file_id, title=None, description=None,
                                              caption=None, caption_entities=None,
                                              parse_mode=None, reply_markup=None,
                                              input_message_content=None)
```

Bases: [InlineQueryResultCachedBase](#)

Represents a link to an animated GIF file stored on the Telegram servers. By default, this animated GIF file will be sent by the user with an optional caption. Alternatively, you can use `input_message_content` to send a message with specified content instead of the animation.

Telegram Documentation: <https://core.telegram.org/bots/api#inlinequeryresultcachedgif>

Parameters

- **type** (str) – Type of the result, must be gif
- **id** (str) – Unique identifier for this result, 1-64 bytes
- **gif_file_id** (str) – A valid file identifier for the GIF file
- **title** (str) – Optional. Title for the result
- **caption** (str) – Optional. Caption of the GIF file to be sent, 0-1024 characters after entities parsing

- **parse_mode** (str) – Optional. Mode for parsing entities in the caption. See formatting options for more details.
- **caption_entities** (list of *telebot.types.MessageEntity*) – Optional. List of special entities that appear in the caption, which can be specified instead of parse_mode
- **reply_markup** (*telebot.types.InlineKeyboardMarkup*) – Optional. Inline keyboard attached to the message
- **input_message_content** (*telebot.types.InputMessageContent*) – Optional. Content of the message to be sent instead of the GIF animation

Returns

Instance of the class

Return type

telebot.types.InlineQueryResultCachedGif

```
class telebot.types.InlineQueryResultCachedMpeg4Gif(id, mpeg4_file_id, title=None,
                                                    description=None, caption=None,
                                                    caption_entities=None, parse_mode=None,
                                                    reply_markup=None,
                                                    input_message_content=None)
```

Bases: *InlineQueryResultCachedBase*

Represents a link to a video animation (H.264/MPEG-4 AVC video without sound) stored on the Telegram servers. By default, this animated MPEG-4 file will be sent by the user with an optional caption. Alternatively, you can use input_message_content to send a message with the specified content instead of the animation.

Telegram Documentation: <https://core.telegram.org/bots/api#inlinequeryresultcachedmpeg4gif>

Parameters

- **type** (str) – Type of the result, must be mpeg4_gif
- **id** (str) – Unique identifier for this result, 1-64 bytes
- **mpeg4_file_id** (str) – A valid file identifier for the MPEG4 file
- **title** (str) – Optional. Title for the result
- **caption** (str) – Optional. Caption of the MPEG-4 file to be sent, 0-1024 characters after entities parsing
- **parse_mode** (str) – Optional. Mode for parsing entities in the caption. See formatting options for more details.
- **caption_entities** (list of *telebot.types.MessageEntity*) – Optional. List of special entities that appear in the caption, which can be specified instead of parse_mode
- **reply_markup** (*telebot.types.InlineKeyboardMarkup*) – Optional. Inline keyboard attached to the message
- **input_message_content** (*telebot.types.InputMessageContent*) – Optional. Content of the message to be sent instead of the video animation

Returns

Instance of the class

Return type

telebot.types.InlineQueryResultCachedMpeg4Gif

```
class telebot.types.InlineQueryResultCachedPhoto(id, photo_file_id, title=None, description=None,
                                                caption=None, caption_entities=None,
                                                parse_mode=None, reply_markup=None,
                                                input_message_content=None)
```

Bases: [InlineQueryResultCachedBase](#)

Represents a link to a photo stored on the Telegram servers. By default, this photo will be sent by the user with an optional caption. Alternatively, you can use `input_message_content` to send a message with the specified content instead of the photo.

Telegram Documentation: <https://core.telegram.org/bots/api#inlinequeryresultcachedphoto>

Parameters

- **type** (str) – Type of the result, must be photo
- **id** (str) – Unique identifier for this result, 1-64 bytes
- **photo_file_id** (str) – A valid file identifier of the photo
- **title** (str) – Optional. Title for the result
- **description** (str) – Optional. Short description of the result
- **caption** (str) – Optional. Caption of the photo to be sent, 0-1024 characters after entities parsing
- **parse_mode** (str) – Optional. Mode for parsing entities in the photo caption. See formatting options for more details.
- **caption_entities** (list of [telebot.types.MessageEntity](#)) – Optional. List of special entities that appear in the caption, which can be specified instead of `parse_mode`
- **reply_markup** ([telebot.types.InlineKeyboardMarkup](#)) – Optional. Inline keyboard attached to the message
- **input_message_content** ([telebot.types.InputMessageContent](#)) – Optional. Content of the message to be sent instead of the photo

Returns

Instance of the class

Return type

[telebot.types.InlineQueryResultCachedPhoto](#)

```
class telebot.types.InlineQueryResultCachedSticker(id, sticker_file_id, reply_markup=None,
                                                  input_message_content=None)
```

Bases: [InlineQueryResultCachedBase](#)

Represents a link to a sticker stored on the Telegram servers. By default, this sticker will be sent by the user. Alternatively, you can use `input_message_content` to send a message with the specified content instead of the sticker.

Telegram Documentation: <https://core.telegram.org/bots/api#inlinequeryresultcachedsticker>

Parameters

- **type** (str) – Type of the result, must be sticker
- **id** (str) – Unique identifier for this result, 1-64 bytes
- **sticker_file_id** (str) – A valid file identifier of the sticker
- **reply_markup** ([telebot.types.InlineKeyboardMarkup](#)) – Optional. Inline keyboard attached to the message

- **input_message_content** (`telebot.types.InputMessageContent`) – Optional. Content of the message to be sent instead of the sticker

Returns

Instance of the class

Return type

`telebot.types.InlineQueryResultCachedSticker`

```
class telebot.types.InlineQueryResultCachedVideo(id, video_file_id, title, description=None,
                                                  caption=None, caption_entities=None,
                                                  parse_mode=None, reply_markup=None,
                                                  input_message_content=None)
```

Bases: `InlineQueryResultCachedBase`

Represents a link to a video file stored on the Telegram servers. By default, this video file will be sent by the user with an optional caption. Alternatively, you can use `input_message_content` to send a message with the specified content instead of the video.

Telegram Documentation: <https://core.telegram.org/bots/api#inlinequeryresultcachedvideo>

Parameters

- **type** (str) – Type of the result, must be video
- **id** (str) – Unique identifier for this result, 1-64 bytes
- **video_file_id** (str) – A valid file identifier for the video file
- **title** (str) – Title for the result
- **description** (str) – Optional. Short description of the result
- **caption** (str) – Optional. Caption of the video to be sent, 0-1024 characters after entities parsing
- **parse_mode** (str) – Optional. Mode for parsing entities in the video caption. See formatting options for more details.
- **caption_entities** (list of `telebot.types.MessageEntity`) – Optional. List of special entities that appear in the caption, which can be specified instead of `parse_mode`
- **reply_markup** (`telebot.types.InlineKeyboardMarkup`) – Optional. Inline keyboard attached to the message
- **input_message_content** (`telebot.types.InputMessageContent`) – Optional. Content of the message to be sent instead of the video

Returns

Instance of the class

Return type

`telebot.types.InlineQueryResultCachedVideo`

```
class telebot.types.InlineQueryResultCachedVoice(id, voice_file_id, title, caption=None,
                                                  caption_entities=None, parse_mode=None,
                                                  reply_markup=None,
                                                  input_message_content=None)
```

Bases: `InlineQueryResultCachedBase`

Represents a link to a voice message stored on the Telegram servers. By default, this voice message will be sent by the user. Alternatively, you can use `input_message_content` to send a message with the specified content instead of the voice message.

Telegram Documentation: <https://core.telegram.org/bots/api#inlinequeryresultcachedvoice>

Parameters

- **type** (str) – Type of the result, must be voice
- **id** (str) – Unique identifier for this result, 1-64 bytes
- **voice_file_id** (str) – A valid file identifier for the voice message
- **title** (str) – Voice message title
- **caption** (str) – Optional. Caption, 0-1024 characters after entities parsing
- **parse_mode** (str) – Optional. Mode for parsing entities in the voice message caption. See formatting options for more details.
- **caption_entities** (list of *telebot.types.MessageEntity*) – Optional. List of special entities that appear in the caption, which can be specified instead of parse_mode
- **reply_markup** (*telebot.types.InlineKeyboardMarkup*) – Optional. Inline keyboard attached to the message
- **input_message_content** (*telebot.types.InputMessageContent*) – Optional. Content of the message to be sent instead of the voice message

Returns

Instance of the class

Return type

telebot.types.InlineQueryResultCachedVoice

```
class telebot.types.InlineQueryResultContact(id, phone_number, first_name, last_name=None,
                                             vcard=None, reply_markup=None,
                                             input_message_content=None, thumbnail_url=None,
                                             thumbnail_width=None, thumbnail_height=None)
```

Bases: *InlineQueryResultBase*

Represents a contact with a phone number. By default, this contact will be sent by the user. Alternatively, you can use `input_message_content` to send a message with the specified content instead of the contact.

Telegram Documentation: <https://core.telegram.org/bots/api#inlinequeryresultcontact>

Parameters

- **type** (str) – Type of the result, must be contact
- **id** (str) – Unique identifier for this result, 1-64 Bytes
- **phone_number** (str) – Contact's phone number
- **first_name** (str) – Contact's first name
- **last_name** (str) – Optional. Contact's last name
- **vcard** (str) – Optional. Additional data about the contact in the form of a vCard, 0-2048 bytes
- **reply_markup** (*telebot.types.InlineKeyboardMarkup*) – Optional. Inline keyboard attached to the message
- **input_message_content** (*telebot.types.InputMessageContent*) – Optional. Content of the message to be sent instead of the contact
- **thumbnail_url** (str) – Optional. Url of the thumbnail for the result
- **thumbnail_width** (int) – Optional. Thumbnail width

- **thumbnail_height** (int) – Optional. Thumbnail height

Returns

Instance of the class

Return type

telebot.types.InlineQueryResultContact

property **thumb_height**

property **thumb_url**

property **thumb_width**

class telebot.types.InlineQueryResultDocument(*id, title, document_url, mime_type, caption=None, caption_entities=None, parse_mode=None, description=None, reply_markup=None, input_message_content=None, thumbnail_url=None, thumbnail_width=None, thumbnail_height=None*)

Bases: *InlineQueryResultBase*

Represents a link to a file. By default, this file will be sent by the user with an optional caption. Alternatively, you can use `input_message_content` to send a message with the specified content instead of the file. Currently, only .PDF and .ZIP files can be sent using this method.

Telegram Documentation: <https://core.telegram.org/bots/api#inlinequeryresultdocument>

Parameters

- **type** (str) – Type of the result, must be document
- **id** (str) – Unique identifier for this result, 1-64 bytes
- **title** (str) – Title for the result
- **caption** (str) – Optional. Caption of the document to be sent, 0-1024 characters after entities parsing
- **parse_mode** (str) – Optional. Mode for parsing entities in the document caption. See formatting options for more details.
- **caption_entities** (list of *telebot.types.MessageEntity*) – Optional. List of special entities that appear in the caption, which can be specified instead of `parse_mode`
- **document_url** (str) – A valid URL for the file
- **mime_type** (str) – MIME type of the content of the file, either “application/pdf” or “application/zip”
- **description** (str) – Optional. Short description of the result
- **reply_markup** (*telebot.types.InlineKeyboardMarkup*) – Optional. Inline keyboard attached to the message
- **input_message_content** (*telebot.types.InputMessageContent*) – Optional. Content of the message to be sent instead of the file
- **thumbnail_url** (str) – Optional. URL of the thumbnail (JPEG only) for the file
- **thumbnail_width** (int) – Optional. Thumbnail width
- **thumbnail_height** (int) – Optional. Thumbnail height

Returns

Instance of the class

Return type*telebot.types.InlineQueryResultDocument*property **thumb_height**property **thumb_url**property **thumb_width****class** telebot.types.**InlineQueryResultGame**(*id, game_short_name, reply_markup=None*)Bases: *InlineQueryResultBase*

Represents a Game.

Telegram Documentation: <https://core.telegram.org/bots/api#inlinequeryresultgame>**Parameters**

- **type** (str) – Type of the result, must be game
- **id** (str) – Unique identifier for this result, 1-64 bytes
- **game_short_name** (str) – Short name of the game
- **reply_markup** (*telebot.types.InlineKeyboardMarkup*) – Optional. Inline keyboard attached to the message

Returns

Instance of the class

Return type*telebot.types.InlineQueryResultGame***class** telebot.types.**InlineQueryResultGif**(*id, gif_url, thumbnail_url, gif_width=None, gif_height=None, title=None, caption=None, caption_entities=None, reply_markup=None, input_message_content=None, gif_duration=None, parse_mode=None, thumbnail_mime_type=None*)Bases: *InlineQueryResultBase*

Represents a link to an animated GIF file. By default, this animated GIF file will be sent by the user with optional caption. Alternatively, you can use `input_message_content` to send a message with the specified content instead of the animation.

Telegram Documentation: <https://core.telegram.org/bots/api#inlinequeryresultgif>**Parameters**

- **type** (str) – Type of the result, must be gif
- **id** (str) – Unique identifier for this result, 1-64 bytes
- **gif_url** (str) – A valid URL for the GIF file. File size must not exceed 1MB
- **gif_width** (int) – Optional. Width of the GIF
- **gif_height** (int) – Optional. Height of the GIF
- **gif_duration** (int) – Optional. Duration of the GIF in seconds
- **thumbnail_url** (str) – URL of the static (JPEG or GIF) or animated (MPEG4) thumbnail for the result
- **thumbnail_mime_type** (str) – Optional. MIME type of the thumbnail, must be one of “image/jpeg”, “image/gif”, or “video/mp4”. Defaults to “image/jpeg”

- **title** (str) – Optional. Title for the result
- **caption** (str) – Optional. Caption of the GIF file to be sent, 0-1024 characters after entities parsing
- **parse_mode** (str) – Optional. Mode for parsing entities in the caption. See formatting options for more details.
- **caption_entities** (list of *telebot.types.MessageEntity*) – Optional. List of special entities that appear in the caption, which can be specified instead of parse_mode
- **reply_markup** (*telebot.types.InlineKeyboardMarkup*) – Optional. Inline keyboard attached to the message
- **input_message_content** (*telebot.types.InputMessageContent*) – Optional. Content of the message to be sent instead of the GIF animation

Returns

Instance of the class

Return type

telebot.types.InlineQueryResultGif

property **thumb_mime_type**

property **thumb_url**

```
class telebot.types.InlineQueryResultLocation(id, title, latitude, longitude, horizontal_accuracy,
                                             live_period=None, reply_markup=None,
                                             input_message_content=None, thumbnail_url=None,
                                             thumbnail_width=None, thumbnail_height=None,
                                             heading=None, proximity_alert_radius=None)
```

Bases: *InlineQueryResultBase*

Represents a location on a map. By default, the location will be sent by the user. Alternatively, you can use `input_message_content` to send a message with the specified content instead of the location.

Telegram Documentation: <https://core.telegram.org/bots/api#inlinequeryresultlocation>

Parameters

- **type** (str) – Type of the result, must be location
- **id** (str) – Unique identifier for this result, 1-64 Bytes
- **latitude** (float number) – Location latitude in degrees
- **longitude** (float number) – Location longitude in degrees
- **title** (str) – Location title
- **horizontal_accuracy** (float number) – Optional. The radius of uncertainty for the location, measured in meters; 0-1500
- **live_period** (int) – Optional. Period in seconds for which the location can be updated, should be between 60 and 86400.
- **heading** (int) – Optional. For live locations, a direction in which the user is moving, in degrees. Must be between 1 and 360 if specified.
- **proximity_alert_radius** (int) – Optional. For live locations, a maximum distance for proximity alerts about approaching another chat member, in meters. Must be between 1 and 100000 if specified.

- **reply_markup** (*telebot.types.InlineKeyboardMarkup*) – Optional. Inline keyboard attached to the message
- **input_message_content** (*telebot.types.InputMessageContent*) – Optional. Content of the message to be sent instead of the location
- **thumbnail_url** (*str*) – Optional. Url of the thumbnail for the result
- **thumbnail_width** (*int*) – Optional. Thumbnail width
- **thumbnail_height** (*int*) – Optional. Thumbnail height

Returns

Instance of the class

Return type

telebot.types.InlineQueryResultLocation

property **thumb_height**

property **thumb_url**

property **thumb_width**

```
class telebot.types.InlineQueryResultMpeg4Gif(id, mpeg4_url, thumbnail_url, mpeg4_width=None,
                                              mpeg4_height=None, title=None, caption=None,
                                              caption_entities=None, parse_mode=None,
                                              reply_markup=None, input_message_content=None,
                                              mpeg4_duration=None, thumbnail_mime_type=None)
```

Bases: *InlineQueryResultBase*

Represents a link to a video animation (H.264/MPEG-4 AVC video without sound). By default, this animated MPEG-4 file will be sent by the user with optional caption. Alternatively, you can use `input_message_content` to send a message with the specified content instead of the animation.

Telegram Documentation: <https://core.telegram.org/bots/api#inlinequeryresultmpeg4gif>

Parameters

- **type** (*str*) – Type of the result, must be `mpeg4_gif`
- **id** (*str*) – Unique identifier for this result, 1-64 bytes
- **mpeg4_url** (*str*) – A valid URL for the MPEG4 file. File size must not exceed 1MB
- **mpeg4_width** (*int*) – Optional. Video width
- **mpeg4_height** (*int*) – Optional. Video height
- **mpeg4_duration** (*int*) – Optional. Video duration in seconds
- **thumbnail_url** (*str*) – URL of the static (JPEG or GIF) or animated (MPEG4) thumbnail for the result
- **thumbnail_mime_type** (*str*) – Optional. MIME type of the thumbnail, must be one of “image/jpeg”, “image/gif”, or “video/mp4”. Defaults to “image/jpeg”
- **title** (*str*) – Optional. Title for the result
- **caption** (*str*) – Optional. Caption of the MPEG-4 file to be sent, 0-1024 characters after entities parsing
- **parse_mode** (*str*) – Optional. Mode for parsing entities in the caption. See formatting options for more details.

- **caption_entities** (list of *telebot.types.MessageEntity*) – Optional. List of special entities that appear in the caption, which can be specified instead of `parse_mode`
- **reply_markup** (*telebot.types.InlineKeyboardMarkup*) – Optional. Inline keyboard attached to the message
- **input_message_content** (*telebot.types.InputMessageContent*) – Optional. Content of the message to be sent instead of the video animation

Returns

Instance of the class

Return type

telebot.types.InlineQueryResultMpeg4Gif

property **thumb_mime_type**

property **thumb_url**

```
class telebot.types.InlineQueryResultPhoto(id, photo_url, thumbnail_url, photo_width=None,
                                           photo_height=None, title=None, description=None,
                                           caption=None, caption_entities=None, parse_mode=None,
                                           reply_markup=None, input_message_content=None)
```

Bases: *InlineQueryResultBase*

Represents a link to a photo. By default, this photo will be sent by the user with optional caption. Alternatively, you can use `input_message_content` to send a message with the specified content instead of the photo.

Telegram Documentation: <https://core.telegram.org/bots/api#inlinequeryresultphoto>

Parameters

- **type** (str) – Type of the result, must be photo
- **id** (str) – Unique identifier for this result, 1-64 bytes
- **photo_url** (str) – A valid URL of the photo. Photo must be in JPEG format. Photo size must not exceed 5MB
- **thumbnail_url** (str) – URL of the thumbnail for the photo
- **photo_width** (int) – Optional. Width of the photo
- **photo_height** (int) – Optional. Height of the photo
- **title** (str) – Optional. Title for the result
- **description** (str) – Optional. Short description of the result
- **caption** (str) – Optional. Caption of the photo to be sent, 0-1024 characters after entities parsing
- **parse_mode** (str) – Optional. Mode for parsing entities in the photo caption. See formatting options for more details.
- **caption_entities** (list of *telebot.types.MessageEntity*) – Optional. List of special entities that appear in the caption, which can be specified instead of `parse_mode`
- **reply_markup** (*telebot.types.InlineKeyboardMarkup*) – Optional. Inline keyboard attached to the message
- **input_message_content** (*telebot.types.InputMessageContent*) – Optional. Content of the message to be sent instead of the photo

Returns

Instance of the class

Return type

telebot.types.InlineQueryResultPhoto

property **thumb_url**

```
class telebot.types.InlineQueryResultVenue(id, title, latitude, longitude, address, foursquare_id=None,
                                           foursquare_type=None, reply_markup=None,
                                           input_message_content=None, thumbnail_url=None,
                                           thumbnail_width=None, thumbnail_height=None,
                                           google_place_id=None, google_place_type=None)
```

Bases: *InlineQueryResultBase*

Represents a venue. By default, the venue will be sent by the user. Alternatively, you can use `input_message_content` to send a message with the specified content instead of the venue.

Telegram Documentation: <https://core.telegram.org/bots/api#inlinequeryresultvenue>

Parameters

- **type** (str) – Type of the result, must be venue
- **id** (str) – Unique identifier for this result, 1-64 Bytes
- **latitude** (float) – Latitude of the venue location in degrees
- **longitude** (float) – Longitude of the venue location in degrees
- **title** (str) – Title of the venue
- **address** (str) – Address of the venue
- **foursquare_id** (str) – Optional. Foursquare identifier of the venue if known
- **foursquare_type** (str) – Optional. Foursquare type of the venue, if known. (For example, “arts_entertainment/default”, “arts_entertainment/aquarium” or “food/icecream”.)
- **google_place_id** (str) – Optional. Google Places identifier of the venue
- **google_place_type** (str) – Optional. Google Places type of the venue. (See supported types.)
- **reply_markup** (*telebot.types.InlineKeyboardMarkup*) – Optional. Inline keyboard attached to the message
- **input_message_content** (*telebot.types.InputMessageContent*) – Optional. Content of the message to be sent instead of the venue
- **thumbnail_url** (str) – Optional. Url of the thumbnail for the result
- **thumbnail_width** (int) – Optional. Thumbnail width
- **thumbnail_height** (int) – Optional. Thumbnail height

Returns

Instance of the class

Return type

telebot.types.InlineQueryResultVenue

property **thumb_height**

property **thumb_url**

property thumb_width

```
class telebot.types.InlineQueryResultVideo(id, video_url, mime_type, thumbnail_url, title,
                                           caption=None, caption_entities=None, parse_mode=None,
                                           video_width=None, video_height=None,
                                           video_duration=None, description=None,
                                           reply_markup=None, input_message_content=None)
```

Bases: [InlineQueryResultBase](#)

Represents a link to a page containing an embedded video player or a video file. By default, this video file will be sent by the user with an optional caption. Alternatively, you can use `input_message_content` to send a message with the specified content instead of the video.

Telegram Documentation: <https://core.telegram.org/bots/api#inlinequeryresultvideo>

Parameters

- **type** (str) – Type of the result, must be video
- **id** (str) – Unique identifier for this result, 1-64 bytes
- **video_url** (str) – A valid URL for the embedded video player or video file
- **mime_type** (str) – MIME type of the content of the video URL, “text/html” or “video/mp4”
- **thumbnail_url** (str) – URL of the thumbnail (JPEG only) for the video
- **title** (str) – Title for the result
- **caption** (str) – Optional. Caption of the video to be sent, 0-1024 characters after entities parsing
- **parse_mode** (str) – Optional. Mode for parsing entities in the video caption. See formatting options for more details.
- **caption_entities** (list of [telebot.types.MessageEntity](#)) – Optional. List of special entities that appear in the caption, which can be specified instead of `parse_mode`
- **video_width** (int) – Optional. Video width
- **video_height** (int) – Optional. Video height
- **video_duration** (int) – Optional. Video duration in seconds
- **description** (str) – Optional. Short description of the result
- **reply_markup** ([telebot.types.InlineKeyboardMarkup](#)) – Optional. Inline keyboard attached to the message
- **input_message_content** ([telebot.types.InputMessageContent](#)) – Optional. Content of the message to be sent instead of the video. This field is required if `InlineQueryResultVideo` is used to send an HTML-page as a result (e.g., a YouTube video).

Returns

Instance of the class

Return type

[telebot.types.InlineQueryResultVideo](#)

property thumb_url

```
class telebot.types.InlineQueryResultVoice(id, voice_url, title, caption=None, caption_entities=None,
                                           parse_mode=None, voice_duration=None,
                                           reply_markup=None, input_message_content=None)
```

Bases: *InlineQueryResultBase*

Represents a link to a voice recording in an .OGG container encoded with OPUS. By default, this voice recording will be sent by the user. Alternatively, you can use `input_message_content` to send a message with the specified content instead of the the voice message.

Telegram Documentation: <https://core.telegram.org/bots/api#inlinequeryresultvoice>

Parameters

- **type** (str) – Type of the result, must be voice
- **id** (str) – Unique identifier for this result, 1-64 bytes
- **voice_url** (str) – A valid URL for the voice recording
- **title** (str) – Recording title
- **caption** (str) – Optional. Caption, 0-1024 characters after entities parsing
- **parse_mode** (str) – Optional. Mode for parsing entities in the voice message caption. See formatting options for more details.
- **caption_entities** (list of *telebot.types.MessageEntity*) – Optional. List of special entities that appear in the caption, which can be specified instead of `parse_mode`
- **voice_duration** (int) – Optional. Recording duration in seconds
- **reply_markup** (*telebot.types.InlineKeyboardMarkup*) – Optional. Inline keyboard attached to the message
- **input_message_content** (*telebot.types.InputMessageContent*) – Optional. Content of the message to be sent instead of the voice recording

Returns

Instance of the class

Return type

telebot.types.InlineQueryResultVoice

```
class telebot.types.InlineQueryResultsButton(text: str, web_app: WebAppInfo | None = None,
                                             start_parameter: str | None = None)
```

Bases: *JsonSerializable, Dictionaryable*

This object represents a button to be shown above inline query results. You must use exactly one of the optional fields.

Telegram documentation: <https://core.telegram.org/bots/api#inlinequeryresultsbutton>

Parameters

- **text** (str) – Label text on the button
- **web_app** (*telebot.types.WebAppInfo*) – Optional. Description of the Web App that will be launched when the user presses the button. The Web App will be able to switch back to the inline mode using the method `web_app_switch_inline_query` inside the Web App.
- **start_parameter** (str) – Optional. Deep-linking parameter for the `/start` message sent to the bot when a user presses the button. 1-64 characters, only A-Z, a-z, 0-9, `_` and `-` are allowed. Example: An inline bot that sends YouTube videos can ask the user to connect the bot to their YouTube account to adapt search results accordingly. To do this, it displays a ‘Connect your YouTube account’ button above the results, or even before showing any. The user presses the button, switches to a private chat with the bot and, in doing so, passes a start parameter that instructs the bot to return an OAuth link. Once done, the bot can offer a

switch_inline button so that the user can easily return to the chat where they wanted to use the bot's inline capabilities.

Returns

Instance of the class

Return type

InlineQueryResultsButton

```
class telebot.types.InputContactMessageContent(phone_number, first_name, last_name=None, vcard=None)
```

Bases: *Dictionaryable*

Represents the content of a contact message to be sent as the result of an inline query.

Telegram Documentation: <https://core.telegram.org/bots/api#inputcontactmessagecontent>

Parameters

- **phone_number** (str) – Contact's phone number
- **first_name** (str) – Contact's first name
- **last_name** (str) – Optional. Contact's last name
- **vcard** (str) – Optional. Additional data about the contact in the form of a vCard, 0-2048 bytes

Returns

Instance of the class

Return type

telebot.types.InputContactMessageContent

```
class telebot.types.InputFile(file)
```

Bases: object

A class to send files through Telegram Bot API.

You need to pass a file, which should be an instance of `io.IOBase` or `pathlib.Path`, or `str`.

If you pass an `str` as a file, it will be opened and closed by the class.

Parameters

file (`io.IOBase` or `pathlib.Path` or `str`) – A file to send.

Listing 2: Example on sending a file using this class

```
from telebot.types import InputFile

# Sending a file from disk
bot.send_document(
    chat_id,
    InputFile('/path/to/file/file.txt')
)

# Sending a file from an io.IOBase object
with open('/path/to/file/file.txt', 'rb') as f:
    bot.send_document(
        chat_id,
```

(continues on next page)

(continued from previous page)

```

        InputFile(f)
    )

    # Sending a file using pathlib.Path:
    bot.send_document(
        chat_id,
        InputFile(pathlib.Path('/path/to/file/file.txt'))
    )

```

property file

File object.

class telebot.types.**InputInvoiceMessageContent**(*title, description, payload, provider_token, currency, prices, max_tip_amount=None, suggested_tip_amounts=None, provider_data=None, photo_url=None, photo_size=None, photo_width=None, photo_height=None, need_name=None, need_phone_number=None, need_email=None, need_shipping_address=None, send_phone_number_to_provider=None, send_email_to_provider=None, is_flexible=None*)

Bases: *Dictionaryable*

Represents the content of an invoice message to be sent as the result of an inline query.

Telegram Documentation: <https://core.telegram.org/bots/api#inputinvoicemessagecontent>**Parameters**

- **title** (str) – Product name, 1-32 characters
- **description** (str) – Product description, 1-255 characters
- **payload** (str) – Bot-defined invoice payload, 1-128 bytes. This will not be displayed to the user, use for your internal processes.
- **provider_token** (str) – Payment provider token, obtained via @BotFather
- **currency** (str) – Three-letter ISO 4217 currency code, see more on currencies
- **prices** (list of *telebot.types.LabeledPrice*) – Price breakdown, a JSON-serialized list of components (e.g. product price, tax, discount, delivery cost, delivery tax, bonus, etc.)
- **max_tip_amount** (int) – Optional. The maximum accepted amount for tips in the smallest units of the currency (integer, not float/double). For example, for a maximum tip of US\$ 1.45 pass `max_tip_amount = 145`. See the `exp` parameter in `currencies.json`, it shows the number of digits past the decimal point for each currency (2 for the majority of currencies). Defaults to 0
- **suggested_tip_amounts** (list of int) – Optional. A JSON-serialized array of suggested amounts of tip in the smallest units of the currency (integer, not float/double). At most 4 suggested tip amounts can be specified. The suggested tip amounts must be positive, passed in a strictly increased order and must not exceed `max_tip_amount`.
- **provider_data** (str) – Optional. A JSON-serialized object for data about the invoice, which will be shared with the payment provider. A detailed description of the required fields should be provided by the payment provider.

- **photo_url** (str) – Optional. URL of the product photo for the invoice. Can be a photo of the goods or a marketing image for a service.
- **photo_size** (int) – Optional. Photo size in bytes
- **photo_width** (int) – Optional. Photo width
- **photo_height** (int) – Optional. Photo height
- **need_name** (bool) – Optional. Pass True, if you require the user’s full name to complete the order
- **need_phone_number** (bool) – Optional. Pass True, if you require the user’s phone number to complete the order
- **need_email** (bool) – Optional. Pass True, if you require the user’s email address to complete the order
- **need_shipping_address** (bool) – Optional. Pass True, if you require the user’s shipping address to complete the order
- **send_phone_number_to_provider** (bool) – Optional. Pass True, if the user’s phone number should be sent to provider
- **send_email_to_provider** (bool) – Optional. Pass True, if the user’s email address should be sent to provider
- **is_flexible** (bool) – Optional. Pass True, if the final price depends on the shipping method

Returns

Instance of the class

Return type

telebot.types.InputInvoiceMessageContent

```
class telebot.types.InputLocationMessageContent(latitude, longitude, horizontal_accuracy=None,
                                                live_period=None, heading=None,
                                                proximity_alert_radius=None)
```

Bases: *Dictionaryable*

Represents the content of a location message to be sent as the result of an inline query.

Telegram Documentation: <https://core.telegram.org/bots/api#inputlocationmessagecontent>

Parameters

- **latitude** (float) – Latitude of the location in degrees
- **longitude** (float) – Longitude of the location in degrees
- **horizontal_accuracy** (float number) – Optional. The radius of uncertainty for the location, measured in meters; 0-1500
- **live_period** (int) – Optional. Period in seconds for which the location can be updated, should be between 60 and 86400.
- **heading** (int) – Optional. For live locations, a direction in which the user is moving, in degrees. Must be between 1 and 360 if specified.
- **proximity_alert_radius** (int) – Optional. For live locations, a maximum distance for proximity alerts about approaching another chat member, in meters. Must be between 1 and 100000 if specified.

Returns

Instance of the class

Return type

telebot.types.InputLocationMessageContent

class telebot.types.**InputMedia**(*type, media, caption=None, parse_mode=None, caption_entities=None*)

Bases: *Dictionaryable, JsonSerializable*

This object represents the content of a media message to be sent. It should be one of

- *InputMediaAnimation*
- *InputMediaDocument*
- *InputMediaAudio*
- *InputMediaPhoto*
- *InputMediaVideo*

class telebot.types.**InputMediaAnimation**(*media, thumbnail=None, caption=None, parse_mode=None, caption_entities=None, width=None, height=None, duration=None, has_spoiler=None*)

Bases: *InputMedia*

Represents an animation file (GIF or H.264/MPEG-4 AVC video without sound) to be sent.

Telegram Documentation: <https://core.telegram.org/bots/api#inputmediaanimation>

Parameters

- **media** (str) – File to send. Pass a file_id to send a file that exists on the Telegram servers (recommended), pass an HTTP URL for Telegram to get a file from the Internet, or pass “attach://<file_attach_name>” to upload a new one using multipart/form-data under <file_attach_name> name. More information on Sending Files »
- **thumbnail** (InputFile or str) – Optional. Thumbnail of the file sent; can be ignored if thumbnail generation for the file is supported server-side. The thumbnail should be in JPEG format and less than 200 kB in size. A thumbnail’s width and height should not exceed 320. Ignored if the file is not uploaded using multipart/form-data. Thumbnails can’t be reused and can be only uploaded as a new file, so you can pass “attach://<file_attach_name>” if the thumbnail was uploaded using multipart/form-data under <file_attach_name>. More information on Sending Files »
- **caption** (str) – Optional. Caption of the animation to be sent, 0-1024 characters after entities parsing
- **parse_mode** (str) – Optional. Mode for parsing entities in the animation caption. See formatting options for more details.
- **caption_entities** (list of *telebot.types.MessageEntity*) – Optional. List of special entities that appear in the caption, which can be specified instead of parse_mode
- **width** (int) – Optional. Animation width
- **height** (int) – Optional. Animation height
- **duration** (int) – Optional. Animation duration in seconds
- **has_spoiler** (bool) – Optional. True, if the uploaded animation is a spoiler

Returns

Instance of the class

Return type*telebot.types.InputMediaAnimation***property thumb**

```
class telebot.types.InputMediaAudio(media, thumbnail=None, caption=None, parse_mode=None,
                                     caption_entities=None, duration=None, performer=None,
                                     title=None)
```

Bases: *InputMedia*

Represents an audio file to be treated as music to be sent.

Telegram Documentation: <https://core.telegram.org/bots/api#inputmediaaudio>**Parameters**

- **media** (str) – File to send. Pass a file_id to send a file that exists on the Telegram servers (recommended), pass an HTTP URL for Telegram to get a file from the Internet, or pass “attach://<file_attach_name>” to upload a new one using multipart/form-data under <file_attach_name> name. More information on Sending Files »
- **thumbnail** (InputFile or str) – Optional. Thumbnail of the file sent; can be ignored if thumbnail generation for the file is supported server-side. The thumbnail should be in JPEG format and less than 200 kB in size. A thumbnail’s width and height should not exceed 320. Ignored if the file is not uploaded using multipart/form-data. Thumbnails can’t be reused and can be only uploaded as a new file, so you can pass “attach://<file_attach_name>” if the thumbnail was uploaded using multipart/form-data under <file_attach_name>. More information on Sending Files »
- **caption** (str) – Optional. Caption of the audio to be sent, 0-1024 characters after entities parsing
- **parse_mode** (str) – Optional. Mode for parsing entities in the audio caption. See formatting options for more details.
- **caption_entities** (list of *telebot.types.MessageEntity*) – Optional. List of special entities that appear in the caption, which can be specified instead of parse_mode
- **duration** (int) – Optional. Duration of the audio in seconds
- **performer** (str) – Optional. Performer of the audio
- **title** (str) – Optional. Title of the audio

Returns

Instance of the class

Return type*telebot.types.InputMediaAudio***property thumb**

```
class telebot.types.InputMediaDocument(media, thumbnail=None, caption=None, parse_mode=None,
                                        caption_entities=None, disable_content_type_detection=None)
```

Bases: *InputMedia*

Represents a general file to be sent.

Telegram Documentation: <https://core.telegram.org/bots/api#inputmediadocument>**Parameters**

- **media** (str) – File to send. Pass a file_id to send a file that exists on the Telegram servers (recommended), pass an HTTP URL for Telegram to get a file from the Internet, or pass “attach://<file_attach_name>” to upload a new one using multipart/form-data under <file_attach_name> name. More information on Sending Files »
- **thumbnail** (InputFile or str) – Optional. Thumbnail of the file sent; can be ignored if thumbnail generation for the file is supported server-side. The thumbnail should be in JPEG format and less than 200 kB in size. A thumbnail’s width and height should not exceed 320. Ignored if the file is not uploaded using multipart/form-data. Thumbnails can’t be reused and can be only uploaded as a new file, so you can pass “attach://<file_attach_name>” if the thumbnail was uploaded using multipart/form-data under <file_attach_name>. More information on Sending Files »
- **caption** (str) – Optional. Caption of the document to be sent, 0-1024 characters after entities parsing
- **parse_mode** (str) – Optional. Mode for parsing entities in the document caption. See formatting options for more details.
- **caption_entities** (list of *telebot.types.MessageEntity*) – Optional. List of special entities that appear in the caption, which can be specified instead of parse_mode
- **disable_content_type_detection** (bool) – Optional. Disables automatic server-side content type detection for files uploaded using multipart/form-data. Always True, if the document is sent as part of an album.

Returns

Instance of the class

Return type

telebot.types.InputMediaDocument

property thumb

```
class telebot.types.InputMediaPhoto(media, caption=None, parse_mode=None, caption_entities=None, has_spoiler=None)
```

Bases: *InputMedia*

Represents a photo to be sent.

Telegram Documentation: <https://core.telegram.org/bots/api#inputmediaphoto>

Parameters

- **media** (str) – File to send. Pass a file_id to send a file that exists on the Telegram servers (recommended), pass an HTTP URL for Telegram to get a file from the Internet, or pass “attach://<file_attach_name>” to upload a new one using multipart/form-data under <file_attach_name> name. More information on Sending Files »
- **caption** (str) – Optional. Caption of the photo to be sent, 0-1024 characters after entities parsing
- **parse_mode** (str) – Optional. Mode for parsing entities in the photo caption. See formatting options for more details.
- **caption_entities** (list of *telebot.types.MessageEntity*) – Optional. List of special entities that appear in the caption, which can be specified instead of parse_mode
- **has_spoiler** (bool) – Optional. True, if the uploaded photo is a spoiler

Returns

Instance of the class

Return type*telebot.types.InputMediaPhoto*

```
class telebot.types.InputMediaVideo(media, thumbnail=None, caption=None, parse_mode=None,
caption_entities=None, width=None, height=None, duration=None,
supports_streaming=None, has_spoiler=None)
```

Bases: *InputMedia*

Represents a video to be sent.

Telegram Documentation: <https://core.telegram.org/bots/api#inputmediavideo>**Parameters**

- **media** (str) – File to send. Pass a file_id to send a file that exists on the Telegram servers (recommended), pass an HTTP URL for Telegram to get a file from the Internet, or pass “attach://<file_attach_name>” to upload a new one using multipart/form-data under <file_attach_name> name. More information on Sending Files »
- **thumbnail** (InputFile or str) – Optional. Thumbnail of the file sent; can be ignored if thumbnail generation for the file is supported server-side. The thumbnail should be in JPEG format and less than 200 kB in size. A thumbnail’s width and height should not exceed 320. Ignored if the file is not uploaded using multipart/form-data. Thumbnails can’t be reused and can be only uploaded as a new file, so you can pass “attach://<file_attach_name>” if the thumbnail was uploaded using multipart/form-data under <file_attach_name>. More information on Sending Files »
- **caption** (str) – Optional. Caption of the video to be sent, 0-1024 characters after entities parsing
- **parse_mode** (str) – Optional. Mode for parsing entities in the video caption. See formatting options for more details.
- **caption_entities** (list of *telebot.types.MessageEntity*) – Optional. List of special entities that appear in the caption, which can be specified instead of parse_mode
- **width** (int) – Optional. Video width
- **height** (int) – Optional. Video height
- **duration** (int) – Optional. Video duration in seconds
- **supports_streaming** (bool) – Optional. Pass True, if the uploaded video is suitable for streaming
- **has_spoiler** (bool) – Optional. True, if the uploaded video is a spoiler

Returns

Instance of the class

Return type*telebot.types.InputMediaVideo***property thumb**

```
class telebot.types.InputSticker(sticker: str | InputFile, emoji_list: List[str], format: str | None = None,
mask_position: MaskPosition | None = None, keywords: List[str] | None
= None)
```

Bases: *Dictionaryable, JsonSerializable*

This object describes a sticker to be added to a sticker set.

Parameters

- **sticker** (str or *telebot.types.InputFile*) – The added sticker. Pass a file_id as a String to send a file that already exists on the Telegram servers, pass an HTTP URL as a String for Telegram to get a file from the Internet, or upload a new one using multipart/form-data. Animated and video stickers can't be uploaded via HTTP URL.
- **emoji_list** (list of str) – One or more (up to 20) emoji(s) corresponding to the sticker
- **mask_position** (*telebot.types.MaskPosition*) – Optional. Position where the mask should be placed on faces. For “mask” stickers only.
- **keywords** (list of str) – Optional. List of 0-20 search keywords for the sticker with total length of up to 64 characters. For “regular” and “custom_emoji” stickers only.
- **format** (str) – Format of the added sticker, must be one of “static” for a .WEBP or .PNG image, “animated” for a .TGS animation, “video” for a WEBM video

Returns

Instance of the class

Return type

telebot.types.InputSticker

convert_input_sticker()

```
class telebot.types.InputTextMessageContent(message_text, parse_mode=None, entities=None,
                                             disable_web_page_preview=None,
                                             link_preview_options=None)
```

Bases: *Dictionaryable*

Represents the content of a text message to be sent as the result of an inline query.

Telegram Documentation: <https://core.telegram.org/bots/api#inputtextmessagecontent>

Parameters

- **message_text** (str) – Text of the message to be sent, 1-4096 characters
- **parse_mode** (str) – Optional. Mode for parsing entities in the message text. See formatting options for more details.
- **entities** (list of *telebot.types.MessageEntity*) – Optional. List of special entities that appear in message text, which can be specified instead of parse_mode
- **disable_web_page_preview** (bool) – deprecated
- **link_preview_options** (*telebot.types.LinkPreviewOptions*) – Optional. Link preview generation options for the message

Returns

Instance of the class

Return type

telebot.types.InputTextMessageContent

```
class telebot.types.InputVenueMessageContent(latitude, longitude, title, address, foursquare_id=None,
                                             foursquare_type=None, google_place_id=None,
                                             google_place_type=None)
```

Bases: *Dictionaryable*

Represents the content of a venue message to be sent as the result of an inline query.

Telegram Documentation: <https://core.telegram.org/bots/api#inputvenuemessagecontent>

Parameters

- **latitude** (float) – Latitude of the venue in degrees
- **longitude** (float) – Longitude of the venue in degrees
- **title** (str) – Name of the venue
- **address** (str) – Address of the venue
- **foursquare_id** (str) – Optional. Foursquare identifier of the venue, if known
- **foursquare_type** (str) – Optional. Foursquare type of the venue, if known. (For example, “arts_entertainment/default”, “arts_entertainment/aquarium” or “food/icecream”.)
- **google_place_id** (str) – Optional. Google Places identifier of the venue
- **google_place_type** (str) – Optional. Google Places type of the venue. (See supported types.)

Returns

Instance of the class

Return type

telebot.types.InputVenueMessageContent

class telebot.types.**Invoice**(title, description, start_parameter, currency, total_amount, **kwargs)

Bases: *JsonDeserializable*

This object contains basic information about an invoice.

Telegram Documentation: <https://core.telegram.org/bots/api#invoice>

Parameters

- **title** (str) – Product name
- **description** (str) – Product description
- **start_parameter** (str) – Unique bot deep-linking parameter that can be used to generate this invoice
- **currency** (str) – Three-letter ISO 4217 currency code
- **total_amount** (int) – Total price in the smallest units of the currency (integer, not float/double). For example, for a price of US\$ 1.45 pass amount = 145. See the exp parameter in currencies.json, it shows the number of digits past the decimal point for each currency (2 for the majority of currencies).

Returns

Instance of the class

Return type

telebot.types.Invoice

class telebot.types.**JsonDeserializable**

Bases: object

Subclasses of this class are guaranteed to be able to be created from a json-style dict or json formatted string. All subclasses of this class must override de_json.

class telebot.types.**JsonSerializable**

Bases: object

Subclasses of this class are guaranteed to be able to be converted to JSON format. All subclasses of this class must override to_json.

```
class telebot.types.KeyboardButton(text: str, request_contact: bool | None = None, request_location: bool | None = None, request_poll: KeyboardButtonPollType | None = None, web_app: WebAppInfo | None = None, request_user: KeyboardButtonRequestUser | None = None, request_chat: KeyboardButtonRequestChat | None = None, request_users: KeyboardButtonRequestUsers | None = None)
```

Bases: *Dictionaryable, JsonSerializerable*

This object represents one button of the reply keyboard. For simple text buttons String can be used instead of this object to specify text of the button. Optional fields `web_app`, `request_contact`, `request_location`, and `request_poll` are mutually exclusive.

Telegram Documentation: <https://core.telegram.org/bots/api#keyboardbutton>

Parameters

- **text** (`str`) – Text of the button. If none of the optional fields are used, it will be sent as a message when the button is pressed
- **request_contact** (`bool`) – Optional. If True, the user’s phone number will be sent as a contact when the button is pressed. Available in private chats only.
- **request_location** (`bool`) – Optional. If True, the user’s current location will be sent when the button is pressed. Available in private chats only.
- **request_poll** (*`telebot.types.KeyboardButtonPollType`*) – Optional. If specified, the user will be asked to create a poll and send it to the bot when the button is pressed. Available in private chats only.
- **web_app** (*`telebot.types.WebAppInfo`*) – Optional. If specified, the described Web App will be launched when the button is pressed. The Web App will be able to send a “web_app_data” service message. Available in private chats only.
- **request_user** (*`telebot.types.KeyboardButtonRequestUser`*) – deprecated
- **request_users** (*`telebot.types.KeyboardButtonRequestUsers`*) – Optional. If specified, pressing the button will open a list of suitable users. Identifiers of selected users will be sent to the bot in a “users_shared” service message. Available in private chats only.
- **request_chat** (*`telebot.types.KeyboardButtonRequestChat`*) – Optional. If specified, pressing the button will open a list of suitable chats. Tapping on a chat will send its identifier to the bot in a “chat_shared” service message. Available in private chats only.

Returns

Instance of the class

Return type

`telebot.types.KeyboardButton`

```
class telebot.types.KeyboardButtonPollType(type="")
```

Bases: *Dictionaryable*

This object represents type of a poll, which is allowed to be created and sent when the corresponding button is pressed.

Telegram Documentation: <https://core.telegram.org/bots/api#keyboardbuttonpolltype>

Parameters

type (`str`) – Optional. If `quiz` is passed, the user will be allowed to create only polls in the quiz mode. If `regular` is passed, only regular polls will be allowed. Otherwise, the user will be allowed to create a poll of any type.

Returns

Instance of the class

Return type

telebot.types.KeyboardButtonPollType

```
class telebot.types.KeyboardButtonRequestChat(request_id: int, chat_is_channel: bool, chat_is_forum: bool | None = None, chat_has_username: bool | None = None, chat_is_created: bool | None = None, user_administrator_rights: ChatAdministratorRights | None = None, bot_administrator_rights: ChatAdministratorRights | None = None, bot_is_member: bool | None = None, request_title: str | None = None, request_photo: bool | None = None, request_username: bool | None = None)
```

Bases: *Dictionaryable*

This object defines the criteria used to request a suitable chat. The identifier of the selected chat will be shared with the bot when the corresponding button is pressed.

Telegram documentation: <https://core.telegram.org/bots/api#keyboardbuttonrequestchat>

Parameters

- **request_id** (int) – Signed 32-bit identifier of the request, which will be received back in the ChatShared object. Must be unique within the message
- **chat_is_channel** (bool) – Pass True to request a channel chat, pass False to request a group or a supergroup chat.
- **chat_is_forum** (bool) – Optional. Pass True to request a forum supergroup, pass False to request a non-forum chat. If not specified, no additional restrictions are applied.
- **chat_has_username** (bool) – Optional. Pass True to request a supergroup or a channel with a username, pass False to request a chat without a username. If not specified, no additional restrictions are applied.
- **chat_is_created** (bool) – Optional. Pass True to request a chat owned by the user. Otherwise, no additional restrictions are applied.
- **user_administrator_rights** (*telebot.types.ChatAdministratorRights*) – Optional. A JSON-serialized object listing the required administrator rights of the user in the chat. The rights must be a superset of bot_administrator_rights. If not specified, no additional restrictions are applied.
- **bot_administrator_rights** (*telebot.types.ChatAdministratorRights*) – Optional. A JSON-serialized object listing the required administrator rights of the bot in the chat. The rights must be a subset of user_administrator_rights. If not specified, no additional restrictions are applied.
- **bot_is_member** (bool) – Optional. Pass True to request a chat where the bot is a member. Otherwise, no additional restrictions are applied.
- **request_title** (bool) – Optional. Request title
- **request_photo** (bool) – Optional. Request photo
- **request_username** (bool) – Optional. Request username

Returns

Instance of the class

Return type*telebot.types.KeyboardButtonRequestChat*

```
class telebot.types.KeyboardButtonRequestUser(request_id: int, user_is_bot: bool | None = None,
                                              user_is_premium: bool | None = None, max_quantity:
                                              int | None = None)
```

Bases: *KeyboardButtonRequestUsers*

Deprecated. Use KeyboardButtonRequestUsers instead.

```
class telebot.types.KeyboardButtonRequestUsers(request_id: int, user_is_bot: bool | None = None,
                                              user_is_premium: bool | None = None, max_quantity:
                                              int | None = None, request_name: str | None = None,
                                              request_username: bool | None = None, request_photo:
                                              bool | None = None)
```

Bases: *Dictionaryable*

This object defines the criteria used to request a suitable user. The identifier of the selected user will be shared with the bot when the corresponding button is pressed.

Telegram documentation: <https://core.telegram.org/bots/api#keyboardbuttonrequestusers>**Parameters**

- **request_id** (int) – Signed 32-bit identifier of the request, which will be received back in the UsersShared object. Must be unique within the message
- **user_is_bot** (bool) – Optional. Pass True to request a bot, pass False to request a regular user. If not specified, no additional restrictions are applied.
- **user_is_premium** (bool) – Optional. Pass True to request a premium user, pass False to request a non-premium user. If not specified, no additional restrictions are applied.
- **max_quantity** (int) – Optional. The maximum number of users to be selected; 1-10. Defaults to 1.
- **request_name** (bool) – Optional. Request name
- **request_username** (bool) – Optional. Request username
- **request_photo** (bool) – Optional. Request photo

Returns

Instance of the class

Return type*telebot.types.KeyboardButtonRequestUsers*

```
class telebot.types.LabeledPrice(label, amount)
```

Bases: *JsonSerializable, Dictionaryable*

This object represents a portion of the price for goods or services.

Telegram Documentation: <https://core.telegram.org/bots/api#labeledprice>**Parameters**

- **label** (str) – Portion label
- **amount** (int) – Price of the product in the smallest units of the currency (integer, not float/double). For example, for a price of US\$ 1.45 pass amount = 145. See the exp parameter in currencies.json, it shows the number of digits past the decimal point for each currency (2 for the majority of currencies).

Returns

Instance of the class

Return type

telebot.types.LabeledPrice

```
class telebot.types.LinkPreviewOptions(is_disabled: bool | None = None, url: str | None = None,
prefer_small_media: bool | None = None, prefer_large_media:
bool | None = None, show_above_text: bool | None = None,
**kwargs)
```

Bases: *JsonDeserializable, Dictionaryable, JsonSerializerable*

Describes the options used for link preview generation.

Telegram documentation: <https://core.telegram.org/bots/api#linkpreviewoptions>

Parameters

- **is_disabled** (bool) – Optional. True, if the link preview is disabled
- **url** (str) – Optional. URL to use for the link preview. If empty, then the first URL found in the message text will be used
- **prefer_small_media** (bool) – Optional. True, if the media in the link preview is supposed to be shrunk; ignored if the URL isn't explicitly specified or media size change isn't supported for the preview
- **prefer_large_media** (bool) – Optional. True, if the media in the link preview is supposed to be enlarged; ignored if the URL isn't explicitly specified or media size change isn't supported for the preview
- **show_above_text** (bool) – Optional. True, if the link preview must be shown above the message text; otherwise, the link preview will be shown below the message text

Returns

Instance of the class

Return type

LinkPreviewOptions

```
class telebot.types.Location(longitude, latitude, horizontal_accuracy=None, live_period=None,
heading=None, proximity_alert_radius=None, **kwargs)
```

Bases: *JsonDeserializable, JsonSerializerable, Dictionaryable*

This object represents a point on the map.

Telegram Documentation: <https://core.telegram.org/bots/api#location>

Parameters

- **longitude** (float) – Longitude as defined by sender
- **latitude** (float) – Latitude as defined by sender
- **horizontal_accuracy** (float number) – Optional. The radius of uncertainty for the location, measured in meters; 0-1500
- **live_period** (int) – Optional. Time relative to the message sending date, during which the location can be updated; in seconds. For active live locations only.
- **heading** (int) – Optional. The direction in which user is moving, in degrees; 1-360. For active live locations only.

- **proximity_alert_radius** (int) – Optional. The maximum distance for proximity alerts about approaching another chat member, in meters. For sent live locations only.

Returns

Instance of the class

Return type

telebot.types.Location

```
class telebot.types.LoginUrl(url, forward_text=None, bot_username=None, request_write_access=None,
                             **kwargs)
```

Bases: *Dictionaryable, JsonSerializerizable, JsonDeserializable*

This object represents a parameter of the inline keyboard button used to automatically authorize a user. Serves as a great replacement for the Telegram Login Widget when the user is coming from Telegram. All the user needs to do is tap/click a button and confirm that they want to log in:

Telegram Documentation: <https://core.telegram.org/bots/api#loginurl>

Parameters

- **url** (str) – An HTTPS URL to be opened with user authorization data added to the query string when the button is pressed. If the user refuses to provide authorization data, the original URL without information about the user will be opened. The data added is the same as described in Receiving authorization data. NOTE: You must always check the hash of the received data to verify the authentication and the integrity of the data as described in Checking authorization.
- **forward_text** (str) – Optional. New text of the button in forwarded messages.
- **bot_username** (str) – Optional. Username of a bot, which will be used for user authorization. See Setting up a bot for more details. If not specified, the current bot’s username will be assumed. The url’s domain must be the same as the domain linked with the bot. See Linking your domain to the bot for more details.
- **request_write_access** (bool) – Optional. Pass True to request the permission for your bot to send messages to the user.

Returns

Instance of the class

Return type

telebot.types.LoginUrl

```
class telebot.types.MaskPosition(point, x_shift, y_shift, scale, **kwargs)
```

Bases: *Dictionaryable, JsonDeserializable, JsonSerializerizable*

This object describes the position on faces where a mask should be placed by default.

Telegram Documentation: <https://core.telegram.org/bots/api#maskposition>

Parameters

- **point** (str) – The part of the face relative to which the mask should be placed. One of “forehead”, “eyes”, “mouth”, or “chin”.
- **x_shift** (float number) – Shift by X-axis measured in widths of the mask scaled to the face size, from left to right. For example, choosing -1.0 will place mask just to the left of the default mask position.
- **y_shift** (float number) – Shift by Y-axis measured in heights of the mask scaled to the face size, from top to bottom. For example, 1.0 will place the mask just below the default mask position.

- **scale** (float number) – Mask scaling coefficient. For example, 2.0 means double size.

Returns

Instance of the class

Return type

telebot.types.MaskPosition

class telebot.types.MenuButton

Bases: *JsonDeserializable, JsonSerializer, Dictionaryable*

This object describes the bot's menu button in a private chat. It should be one of

- *MenuButtonCommands*
- *MenuButtonWebApp*
- *MenuButtonDefault*

If a menu button other than MenuButtonDefault is set for a private chat, then it is applied in the chat. Otherwise the default menu button is applied. By default, the menu button opens the list of bot commands.

class telebot.types.MenuButtonCommands (*type=None, **kwargs*)

Bases: *MenuButton*

Represents a menu button, which opens the bot's list of commands.

Telegram Documentation: <https://core.telegram.org/bots/api#menubuttoncommands>

Parameters

type (str) – Type of the button, must be commands

Returns

Instance of the class

Return type

telebot.types.MenuButtonCommands

class telebot.types.MenuButtonDefault (*type=None, **kwargs*)

Bases: *MenuButton*

Describes that no specific value for the menu button was set.

Telegram Documentation: <https://core.telegram.org/bots/api#menubuttondefault>

Parameters

type (str) – Type of the button, must be default

Returns

Instance of the class

Return type

telebot.types.MenuButtonDefault

class telebot.types.MenuButtonWebApp (*type, text, web_app, **kwargs*)

Bases: *MenuButton*

Represents a menu button, which launches a Web App.

Telegram Documentation: <https://core.telegram.org/bots/api#menubuttonwebapp>

Parameters

- **type** (str) – Type of the button, must be web_app
- **text** (str) – Text on the button

- **web_app** (*telebot.types.WebAppInfo*) – Description of the Web App that will be launched when the user presses the button. The Web App will be able to send an arbitrary message on behalf of the user using the method `answerWebAppQuery`.

Returns

Instance of the class

Return type

telebot.types.MenuButtonWebApp

class telebot.types.**Message**(*message_id, from_user, date, chat, content_type, options, json_string*)

Bases: *JsonDeserializable*

This object represents a message.

Telegram Documentation: <https://core.telegram.org/bots/api#message>

Parameters

- **message_id** (int) – Unique message identifier inside this chat
- **message_thread_id** (int) – Optional. Unique identifier of a message thread to which the message belongs; for supergroups only
- **from_user** (*telebot.types.User*) – Optional. Sender of the message; empty for messages sent to channels. For backward compatibility, the field contains a fake sender user in non-channel chats, if the message was sent on behalf of a chat.
- **sender_chat** (*telebot.types.Chat*) – Optional. Sender of the message, sent on behalf of a chat. For example, the channel itself for channel posts, the supergroup itself for messages from anonymous group administrators, the linked channel for messages automatically forwarded to the discussion group. For backward compatibility, the field from contains a fake sender user in non-channel chats, if the message was sent on behalf of a chat.
- **sender_boost_count** (int) – Optional. If the sender of the message boosted the chat, the number of boosts added by the user
- **info** (*sender_business_bot*) – Optional. Information about the business bot that sent the message
- **date** (int) – Date the message was sent in Unix time
- **business_connection_id** (str) – Optional. Unique identifier of the business connection from which the message was received. If non-empty, the message belongs to a chat of the corresponding business account that is independent from any potential bot chat which might share the same identifier.
- **chat** (*telebot.types.Chat*) – Conversation the message belongs to
- **is_topic_message** (bool) – Optional. True, if the message is sent to a forum topic
- **is_automatic_forward** (bool) – Optional. bool, if the message is a channel post that was automatically forwarded to the connected discussion group
- **reply_to_message** (*telebot.types.Message*) – Optional. For replies, the original message. Note that the Message object in this field will not contain further `reply_to_message` fields even if it itself is a reply.
- **external_reply** (*telebot.types.ExternalReplyInfo*) – Optional. Information about the message that is being replied to, which may come from another chat or forum topic
- **quote** (*telebot.types.TextQuote*) – Optional. For replies that quote part of the original message, the quoted part of the message

- **reply_to_story** (*telebot.types.Story*) – Optional. For replies to a story, the original story
- **via_bot** (*telebot.types.User*) – Optional. Bot through which the message was sent
- **edit_date** (int) – Optional. Date the message was last edited in Unix time
- **has_protected_content** (bool) – Optional. bool, if the message can't be forwarded
- **is_from_offline** (bool) – Optional. True, if the message was sent by an implicit action, for example, as an away or a greeting business message, or as a scheduled message
- **media_group_id** (str) – Optional. The unique identifier of a media message group this message belongs to
- **author_signature** (str) – Optional. Signature of the post author for messages in channels, or the custom title of an anonymous group administrator
- **text** (str) – Optional. For text messages, the actual UTF-8 text of the message
- **entities** (list of *telebot.types.MessageEntity*) – Optional. For text messages, special entities like usernames, URLs, bot commands, etc. that appear in the text
- **link_preview_options** (*telebot.types.LinkPreviewOptions*) – Optional. Options used for link preview generation for the message, if it is a text message and link preview options were changed
- **animation** (*telebot.types.Animation*) – Optional. Message is an animation, information about the animation. For backward compatibility, when this field is set, the document field will also be set
- **audio** (*telebot.types.Audio*) – Optional. Message is an audio file, information about the file
- **document** (*telebot.types.Document*) – Optional. Message is a general file, information about the file
- **photo** (list of *telebot.types.PhotoSize*) – Optional. Message is a photo, available sizes of the photo
- **sticker** (*telebot.types.Sticker*) – Optional. Message is a sticker, information about the sticker
- **story** (*telebot.types.Story*) – Optional. Message is a forwarded story
- **video** (*telebot.types.Video*) – Optional. Message is a video, information about the video
- **video_note** (*telebot.types.VideoNote*) – Optional. Message is a video note, information about the video message
- **voice** (*telebot.types.Voice*) – Optional. Message is a voice message, information about the file
- **caption** (str) – Optional. Caption for the animation, audio, document, photo, video or voice
- **caption_entities** (list of *telebot.types.MessageEntity*) – Optional. For messages with a caption, special entities like usernames, URLs, bot commands, etc. that appear in the caption
- **has_media_spoiler** (bool) – Optional. True, if the message media is covered by a spoiler animation

- **contact** (*telebot.types.Contact*) – Optional. Message is a shared contact, information about the contact
- **dice** (*telebot.types.Dice*) – Optional. Message is a dice with random value
- **game** (*telebot.types.Game*) – Optional. Message is a game, information about the game. More about games »
- **poll** (*telebot.types.Poll*) – Optional. Message is a native poll, information about the poll
- **venue** (*telebot.types.Venue*) – Optional. Message is a venue, information about the venue. For backward compatibility, when this field is set, the location field will also be set
- **location** (*telebot.types.Location*) – Optional. Message is a shared location, information about the location
- **new_chat_members** (list of *telebot.types.User*) – Optional. New members that were added to the group or supergroup and information about them (the bot itself may be one of these members)
- **left_chat_member** (*telebot.types.User*) – Optional. A member was removed from the group, information about them (this member may be the bot itself)
- **new_chat_title** (str) – Optional. A chat title was changed to this value
- **new_chat_photo** (list of *telebot.types.PhotoSize*) – Optional. A chat photo was change to this value
- **delete_chat_photo** (bool) – Optional. Service message: the chat photo was deleted
- **group_chat_created** (bool) – Optional. Service message: the group has been created
- **supergroup_chat_created** (bool) – Optional. Service message: the supergroup has been created. This field can't be received in a message coming through updates, because bot can't be a member of a supergroup when it is created. It can only be found in `reply_to_message` if someone replies to a very first message in a directly created supergroup.
- **channel_chat_created** (bool) – Optional. Service message: the channel has been created. This field can't be received in a message coming through updates, because bot can't be a member of a channel when it is created. It can only be found in `reply_to_message` if someone replies to a very first message in a channel.
- **message_auto_delete_timer_changed** (*telebot.types.MessageAutoDeleteTimerChanged*) – Optional. Service message: auto-delete timer settings changed in the chat
- **migrate_to_chat_id** (int) – Optional. The group has been migrated to a supergroup with the specified identifier. This number may have more than 32 significant bits and some programming languages may have difficulty/silent defects in interpreting it. But it has at most 52 significant bits, so a signed 64-bit integer or double-precision float type are safe for storing this identifier.
- **migrate_from_chat_id** (int) – Optional. The supergroup has been migrated from a group with the specified identifier. This number may have more than 32 significant bits and some programming languages may have difficulty/silent defects in interpreting it. But it has at most 52 significant bits, so a signed 64-bit integer or double-precision float type are safe for storing this identifier.
- **pinned_message** (*telebot.types.Message* or *telebot.types.InaccessibleMessage*) – Optional. Specified message was pinned. Note that the

Message object in this field will not contain further `reply_to_message` fields even if it is itself a reply.

- **invoice** (*telebot.types.Invoice*) – Optional. Message is an invoice for a payment, information about the invoice. More about payments »
- **successful_payment** (*telebot.types.SuccessfulPayment*) – Optional. Message is a service message about a successful payment, information about the payment. More about payments »
- **users_shared** (*telebot.types.UsersShared*) – Optional. Service message: a user was shared with the bot
- **chat_shared** (*telebot.types.ChatShared*) – Optional. Service message: a chat was shared with the bot
- **connected_website** (str) – Optional. The domain name of the website on which the user has logged in. More about Telegram Login »
- **write_access_allowed** (*telebot.types.WriteAccessAllowed*) – Optional. Service message: the user allowed the bot added to the attachment menu to write messages
- **passport_data** (*telebot.types.PassportData*) – Optional. Telegram Passport data
- **proximity_alert_triggered** (*telebot.types.ProximityAlertTriggered*) – Optional. Service message. A user in the chat triggered another user’s proximity alert while sharing Live Location.
- **boost_added** (*telebot.types.ChatBoostAdded*) – Optional. Service message: user boosted the chat
- **forum_topic_created** (*telebot.types.ForumTopicCreated*) – Optional. Service message: forum topic created
- **forum_topic_edited** (*telebot.types.ForumTopicEdited*) – Optional. Service message: forum topic edited
- **forum_topic_closed** (*telebot.types.ForumTopicClosed*) – Optional. Service message: forum topic closed
- **forum_topic_reopened** (*telebot.types.ForumTopicReopened*) – Optional. Service message: forum topic reopened
- **general_forum_topic_hidden** (*telebot.types.GeneralForumTopicHidden*) – Optional. Service message: the ‘General’ forum topic hidden
- **general_forum_topic_unhidden** (*telebot.types.GeneralForumTopicUnhidden*) – Optional. Service message: the ‘General’ forum topic unhidden
- **giveaway_created** (*telebot.types.GiveawayCreated*) – Optional. Service message: a giveaway has been created
- **giveaway** (*telebot.types.Giveaway*) – Optional. The message is a scheduled giveaway message
- **giveaway_winners** (*telebot.types.GiveawayWinners*) – Optional. Service message: giveaway winners(public winners)
- **giveaway_completed** (*telebot.types.GiveawayCompleted*) – Optional. Service message: giveaway completed, without public winners
- **video_chat_scheduled** (*telebot.types.VideoChatScheduled*) – Optional. Service message: video chat scheduled

- **video_chat_started** (*telebot.types.VideoChatStarted*) – Optional. Service message: video chat started
- **video_chat_ended** (*telebot.types.VideoChatEnded*) – Optional. Service message: video chat ended
- **video_chat_participants_invited** (*telebot.types.VideoChatParticipantsInvited*) – Optional. Service message: new participants invited to a video chat
- **web_app_data** (*telebot.types.WebAppData*) – Optional. Service message: data sent by a Web App
- **reply_markup** (*telebot.types.InlineKeyboardMarkup*) – Optional. Inline keyboard attached to the message. login_url buttons are represented as ordinary url buttons.

Forward_origin

Optional. For forwarded messages, information about the original message;

Returns

Instance of the class

Return type

telebot.types.Message

property **forward_date**

property **forward_from**

property **forward_from_chat**

property **forward_from_message_id**

property **forward_sender_name**

property **forward_signature**

property **html_caption**

Returns html-rendered caption.

property **html_text**

Returns html-rendered text.

property **new_chat_member**

classmethod **parse_chat**(*chat*)

Parses chat.

classmethod **parse_entities**(*message_entity_array*)

Parses message entity array.

classmethod **parse_photo**(*photo_size_array*)

Parses photo array.

property **user_shared**

property **voice_chat_ended**

property **voice_chat_participants_invited**

property **voice_chat_scheduled**

property voice_chat_started

class telebot.types.**MessageAutoDeleteTimerChanged**(*message_auto_delete_time*, ***kwargs*)

Bases: *JsonDeserializable*

This object represents a service message about a change in auto-delete timer settings.

Telegram Documentation: <https://core.telegram.org/bots/api#messageautodeletetimerchanged>

Parameters

message_auto_delete_time (int) – New auto-delete time for messages in the chat; in seconds

Returns

Instance of the class

Return type

telebot.types.MessageAutoDeleteTimerChanged

class telebot.types.**MessageEntity**(*type*, *offset*, *length*, *url=None*, *user=None*, *language=None*, *custom_emoji_id=None*, ***kwargs*)

Bases: *Dictionaryable*, *JsonSerializable*, *JsonDeserializable*

This object represents one special entity in a text message. For example, hashtags, usernames, URLs, etc.

Telegram Documentation: <https://core.telegram.org/bots/api#messageentity>

Parameters

- **type** (str) – Type of the entity. Currently, can be “mention” (@username), “hashtag” (#hashtag), “cashtag” (\$USD), “bot_command” (/start@jobs_bot), “url” (<https://telegram.org>), “email” (do-not-reply@telegram.org), “phone_number” (+1-212-555-0123), “bold” (bold text), “italic” (italic text), “underline” (underlined text), “strikethrough” (strikethrough text), “spoiler” (spoiler message), “code” (monowidth string), “pre” (monowidth block), “text_link” (for clickable text URLs), “text_mention” (for users without usernames), “custom_emoji” (for inline custom emoji stickers)
- **offset** (int) – Offset in UTF-16 code units to the start of the entity
- **length** (int) – Length of the entity in UTF-16 code units
- **url** (str) – Optional. For “text_link” only, URL that will be opened after user taps on the text
- **user** (*telebot.types.User*) – Optional. For “text_mention” only, the mentioned user
- **language** (str) – Optional. For “pre” only, the programming language of the entity text
- **custom_emoji_id** (str) – Optional. For “custom_emoji” only, unique identifier of the custom emoji. Use `get_custom_emoji_stickers` to get full information about the sticker.

Returns

Instance of the class

Return type

telebot.types.MessageEntity

static `to_list_of_dicts`(*entity_list*) → List[Dict] | None

Converts a list of MessageEntity objects to a list of dictionaries.

class telebot.types.**MessageID**(*message_id*, ***kwargs*)

Bases: *JsonDeserializable*

This object represents a unique message identifier.

Telegram Documentation: <https://core.telegram.org/bots/api#messageid>

Parameters

message_id (int) – Unique message identifier

Returns

Instance of the class

Return type

`telebot.types.MessageId`

class `telebot.types.MessageOrigin`(*type: str, date: int*)

Bases: *JsonDeserializable*

This object describes the origin of a message.

Telegram documentation: <https://core.telegram.org/bots/api#messageorigin>

Parameters

- **type** (str) – Type of the message origin
- **date** (int) – Date the message was sent originally in Unix time
- **sender_user** (*User*) – User that sent the message originally (for `MessageOriginUser`)
- **sender_user_name** (str) – Name of the user that sent the message originally (for `MessageOriginHiddenUser`)
- **sender_chat** (*Chat*) – Chat that sent the message originally (for `MessageOriginChat`)
- **author_signature** (str) – Optional. Author signature for certain cases

Returns

Instance of the class

Return type

MessageOrigin

class `telebot.types.MessageOriginChannel`(*date: int, chat: Chat, message_id: int, author_signature: str | None = None*)

Bases: *MessageOrigin*

The message was originally sent to a channel chat.

Parameters

- **chat** (*Chat*) – Channel chat to which the message was originally sent
- **message_id** (int) – Unique message identifier inside the chat
- **author_signature** (str) – Optional. Signature of the original post author

class `telebot.types.MessageOriginChat`(*date: int, sender_chat: Chat, author_signature: str | None = None*)

Bases: *MessageOrigin*

The message was originally sent on behalf of a chat to a group chat.

Parameters

- **sender_chat** (*Chat*) – Chat that sent the message originally
- **author_signature** (str) – Optional. For messages originally sent by an anonymous chat administrator, original message author signature

```
class telebot.types.MessageOriginHiddenUser(date: int, sender_user_name: str)
```

Bases: *MessageOrigin*

The message was originally sent by an unknown user.

Parameters

sender_user_name (str) – Name of the user that sent the message originally

```
class telebot.types.MessageOriginUser(date: int, sender_user: User)
```

Bases: *MessageOrigin*

The message was originally sent by a known user.

Parameters

sender_user (*User*) – User that sent the message originally

```
class telebot.types.MessageReactionCountUpdated(chat: Chat, message_id: int, date: int, reactions:
List[ReactionCount], **kwargs)
```

Bases: *JsonDeserializable*

This object represents a service message about a change in the list of the current user’s reactions to a message.

Telegram documentation: <https://core.telegram.org/bots/api#messagereactioncountupdated>

Parameters

- **chat** (*telebot.types.Chat*) – The chat containing the message
- **message_id** (int) – Unique message identifier inside the chat
- **date** (int) – Date of the change in Unix time
- **reactions** (list of *ReactionCount*) – List of reactions that are present on the message

Returns

Instance of the class

Return type

MessageReactionCountUpdated

```
class telebot.types.MessageReactionUpdated(chat: Chat, message_id: int, date: int, old_reaction:
List[ReactionType], new_reaction: List[ReactionType],
user: User | None = None, actor_chat: Chat | None = None,
**kwargs)
```

Bases: *JsonDeserializable*

This object represents a service message about a change in the list of the current user’s reactions to a message.

Telegram documentation: <https://core.telegram.org/bots/api#messagereactionupdated>

Parameters

- **chat** (*telebot.types.Chat*) – The chat containing the message the user reacted to
- **message_id** (int) – Unique identifier of the message inside the chat
- **user** (*telebot.types.User*) – Optional. The user that changed the reaction, if the user isn’t anonymous
- **actor_chat** (*telebot.types.Chat*) – Optional. The chat on behalf of which the reaction was changed, if the user is anonymous
- **date** (int) – Date of the change in Unix time

- **old_reaction** (list of *ReactionType*) – Previous list of reaction types that were set by the user
- **new_reaction** (list of *ReactionType*) – New list of reaction types that have been set by the user

Returns

Instance of the class

Return type

MessageReactionUpdated

class telebot.types.**OrderInfo**(*name=None, phone_number=None, email=None, shipping_address=None, **kwargs*)

Bases: *JsonDeserializable*

This object represents information about an order.

Telegram Documentation: <https://core.telegram.org/bots/api#orderinfo>

Parameters

- **name** (str) – Optional. User name
- **phone_number** (str) – Optional. User’s phone number
- **email** (str) – Optional. User email
- **shipping_address** (*telebot.types.ShippingAddress*) – Optional. User shipping address

Returns

Instance of the class

Return type

telebot.types.OrderInfo

class telebot.types.**PhotoSize**(*file_id, file_unique_id, width, height, file_size=None, **kwargs*)

Bases: *JsonDeserializable*

This object represents one size of a photo or a file / sticker thumbnail.

Telegram Documentation: <https://core.telegram.org/bots/api#photosize>

Parameters

- **file_id** (str) – Identifier for this file, which can be used to download or reuse the file
- **file_unique_id** (str) – Unique identifier for this file, which is supposed to be the same over time and for different bots. Can’t be used to download or reuse the file.
- **width** (int) – Photo width
- **height** (int) – Photo height
- **file_size** (int) – Optional. File size in bytes

Returns

Instance of the class

Return type

telebot.types.PhotoSize

```
class telebot.types.Poll(question, options, poll_id=None, total_voter_count=None, is_closed=None,
    is_anonymous=None, type=None, allows_multiple_answers=None,
    correct_option_id=None, explanation=None, explanation_entities=None,
    open_period=None, close_date=None, poll_type=None, **kwargs)
```

Bases: *JsonDeserializable*

This object contains information about a poll.

Telegram Documentation: <https://core.telegram.org/bots/api#poll>

Parameters

- **id** (str) – Unique poll identifier
- **question** (str) – Poll question, 1-300 characters
- **options** (list of *telebot.types.PollOption*) – List of poll options
- **total_voter_count** (int) – Total number of users that voted in the poll
- **is_closed** (bool) – True, if the poll is closed
- **is_anonymous** (bool) – True, if the poll is anonymous
- **type** (str) – Poll type, currently can be “regular” or “quiz”
- **allows_multiple_answers** (bool) – True, if the poll allows multiple answers
- **correct_option_id** (int) – Optional. 0-based identifier of the correct answer option. Available only for polls in the quiz mode, which are closed, or was sent (not forwarded) by the bot or to the private chat with the bot.
- **explanation** (str) – Optional. Text that is shown when a user chooses an incorrect answer or taps on the lamp icon in a quiz-style poll, 0-200 characters
- **explanation_entities** (list of *telebot.types.MessageEntity*) – Optional. Special entities like usernames, URLs, bot commands, etc. that appear in the explanation
- **open_period** (int) – Optional. Amount of time in seconds the poll will be active after creation
- **close_date** (int) – Optional. Point in time (Unix timestamp) when the poll will be automatically closed

Returns

Instance of the class

Return type

telebot.types.Poll

add(*option*)

Add an option to the poll.

Parameters

- **option** (*telebot.types.PollOption* or str) – Option to add

```
class telebot.types.PollAnswer(poll_id, option_ids, user=None, voter_chat=None, **kwargs)
```

Bases: *JsonSerializable*, *JsonDeserializable*, *Dictionaryable*

This object represents an answer of a user in a non-anonymous poll.

Telegram Documentation: <https://core.telegram.org/bots/api#pollanswer>

Parameters

- **poll_id** (str) – Unique poll identifier

- **voter_chat** (*telebot.types.Chat*) – Optional. The chat that changed the answer to the poll, if the voter is anonymous
- **user** (*telebot.types.User*) – Optional. The user, who changed the answer to the poll
- **option_ids** (list of int) – 0-based identifiers of answer options, chosen by the user. May be empty if the user retracted their vote.

Returns

Instance of the class

Return type

telebot.types.PollAnswer

class telebot.types.PollOption(*text, voter_count=0, **kwargs*)

Bases: *JsonDeserializable*

This object contains information about one answer option in a poll.

Telegram Documentation: <https://core.telegram.org/bots/api#polloption>

Parameters

- **text** (str) – Option text, 1-100 characters
- **voter_count** (int) – Number of users that voted for this option

Returns

Instance of the class

Return type

telebot.types.PollOption

class telebot.types.PreCheckoutQuery(*id, from_user, currency, total_amount, invoice_payload, shipping_option_id=None, order_info=None, **kwargs*)

Bases: *JsonDeserializable*

This object contains information about an incoming pre-checkout query.

Telegram Documentation: <https://core.telegram.org/bots/api#precheckoutquery>

Parameters

- **id** (str) – Unique query identifier
- **from** (*telebot.types.User*) – User who sent the query
- **currency** (str) – Three-letter ISO 4217 currency code
- **total_amount** (int) – Total price in the smallest units of the currency (integer, not float/double). For example, for a price of US\$ 1.45 pass amount = 145. See the exp parameter in currencies.json, it shows the number of digits past the decimal point for each currency (2 for the majority of currencies).
- **invoice_payload** (str) – Bot specified invoice payload
- **shipping_option_id** (str) – Optional. Identifier of the shipping option chosen by the user
- **order_info** (*telebot.types.OrderInfo*) – Optional. Order information provided by the user

Returns

Instance of the class

Return type*telebot.types.PreCheckoutQuery***class** telebot.types.**ProximityAlertTriggered**(*traveler, watcher, distance, **kwargs*)Bases: *JsonDeserializable*

This object represents the content of a service message, sent whenever a user in the chat triggers a proximity alert set by another user.

Telegram Documentation: <https://core.telegram.org/bots/api#proximityalerttriggered>**Parameters**

- **traveler** (*telebot.types.User*) – User that triggered the alert
- **watcher** (*telebot.types.User*) – User that set the alert
- **distance** (int) – The distance between the users

Returns

Instance of the class

Return type*telebot.types.ProximityAlertTriggered***class** telebot.types.**ReactionCount**(*type: ReactionType, total_count: int, **kwargs*)Bases: *JsonDeserializable*

This object represents a reaction added to a message along with the number of times it was added.

Telegram documentation: <https://core.telegram.org/bots/api#reactioncount>**Parameters**

- **type** (*ReactionType*) – Type of the reaction
- **total_count** (int) – Number of times the reaction was added

Returns

Instance of the class

Return type*ReactionCount***class** telebot.types.**ReactionType**(*type: str*)Bases: *JsonDeserializable, Dictionaryable, JsonSerializerizable*

This object represents a reaction type.

Telegram documentation: <https://core.telegram.org/bots/api#reactiontype>**Parameters****type** (str) – Type of the reaction**Returns**

Instance of the class

Return type*ReactionType***class** telebot.types.**ReactionTypeCustomEmoji**(*custom_emoji_id: str, **kwargs*)Bases: *ReactionType*

This object represents a custom emoji reaction type.

Telegram documentation: <https://core.telegram.org/bots/api#reactiontypecustomemoji>

Parameters

- **type** (str) – Type of the reaction, must be custom_emoji
- **custom_emoji_id** (str) – Identifier of the custom emoji

Returns

Instance of the class

Return type

ReactionTypeCustomEmoji

```
class telebot.types.ReactionTypeEmoji(emoji: str, **kwargs)
```

Bases: *ReactionType*

This object represents an emoji reaction type.

Telegram documentation: <https://core.telegram.org/bots/api#reactiontypeemoji>

Parameters

- **type** (str) – Type of the reaction, must be emoji
- **emoji** (str) – Reaction emoji. List is available on the API doc.

Returns

Instance of the class

Return type

ReactionTypeEmoji

```
class telebot.types.ReplyKeyboardMarkup(resize_keyboard: bool | None = None, one_time_keyboard: bool | None = None, selective: bool | None = None, row_width: int = 3, input_field_placeholder: str | None = None, is_persistent: bool | None = None)
```

Bases: *JsonSerializable*

This object represents a custom keyboard with reply options (see Introduction to bots for details and examples).

Listing 3: Example on creating ReplyKeyboardMarkup object

```
from telebot.types import ReplyKeyboardMarkup, KeyboardButton

markup = ReplyKeyboardMarkup(resize_keyboard=True)
markup.add(KeyboardButton('Text'))
# or:
markup.add('Text')

# display this markup:
bot.send_message(chat_id, 'Text', reply_markup=markup)
```

Telegram Documentation: <https://core.telegram.org/bots/api#replykeyboardmarkup>

Parameters

- **keyboard** (list of list of *telebot.types.KeyboardButton*) – list of button rows, each represented by an list of *telebot.types.KeyboardButton* objects
- **resize_keyboard** (bool) – Optional. Requests clients to resize the keyboard vertically for optimal fit (e.g., make the keyboard smaller if there are just two rows of buttons). Defaults to false, in which case the custom keyboard is always of the same height as the app's standard keyboard.

- **one_time_keyboard** (bool) – Optional. Requests clients to hide the keyboard as soon as it's been used. The keyboard will still be available, but clients will automatically display the usual letter-keyboard in the chat - the user can press a special button in the input field to see the custom keyboard again. Defaults to false.
- **input_field_placeholder** (str) – Optional. The placeholder to be shown in the input field when the keyboard is active; 1-64 characters
- **selective** (bool) – Optional. Use this parameter if you want to show the keyboard to specific users only. Targets: 1) users that are @mentioned in the text of the Message object; 2) if the bot's message is a reply to a message in the same chat and forum topic, sender of the original message. Example: A user requests to change the bot's language, bot replies to the request with a keyboard to select the new language. Other users in the group don't see the keyboard.
- **is_persistent** – Optional. Use this parameter if you want to show the keyboard to specific users only. Targets: 1) users that are @mentioned in the text of the Message object; 2) if the bot's message is a reply (has `reply_to_message_id`), sender of the original message.

Example: A user requests to change the bot's language, bot replies to the request with a keyboard to select the new language. Other users in the group don't see the keyboard.

Returns

Instance of the class

Return type

telebot.types.ReplyKeyboardMarkup

add(*args, row_width=None)

This function adds strings to the keyboard, while not exceeding row_width. E.g. `ReplyKeyboardMarkup#add("A", "B", "C")` yields the json result `{keyboard: [[["A"], ["B"], ["C"]]]}` when row_width is set to 1. When row_width is set to 2, the following is the result of this function: `{keyboard: [[["A", "B"], ["C"]]]}` See <https://core.telegram.org/bots/api#replykeyboardmarkup>

Parameters

- **args** (str or *telebot.types.KeyboardButton*) – KeyboardButton to append to the keyboard
- **row_width** (int) – width of row

Returns

self, to allow function chaining.

Return type

telebot.types.ReplyKeyboardMarkup

max_row_keys = 12

row(*args)

Adds a list of KeyboardButton to the keyboard. This function does not consider row_width. `ReplyKeyboardMarkup#row("A")#row("B", "C")#to_json()` outputs `'{keyboard: [[["A"], ["B", "C"]]]}'` See <https://core.telegram.org/bots/api#replykeyboardmarkup>

Parameters

args (str) – strings

Returns

self, to allow function chaining.

Return type

telebot.types.ReplyKeyboardMarkup

```
class telebot.types.ReplyKeyboardRemove(selective=None)
```

Bases: *JsonSerializable*

Upon receiving a message with this object, Telegram clients will remove the current custom keyboard and display the default letter-keyboard. By default, custom keyboards are displayed until a new keyboard is sent by a bot. An exception is made for one-time keyboards that are hidden immediately after the user presses a button (see `ReplyKeyboardMarkup`).

Telegram Documentation: <https://core.telegram.org/bots/api#replykeyboardremove>

Parameters

- **remove_keyboard** (bool) – Requests clients to remove the custom keyboard (user will not be able to summon this keyboard; if you want to hide the keyboard from sight but keep it accessible, use `one_time_keyboard` in `ReplyKeyboardMarkup`) Note that this parameter is set to True by default by the library. You cannot modify it.
- **selective** (bool) – Optional. Use this parameter if you want to remove the keyboard for specific users only. Targets: 1) users that are @mentioned in the text of the Message object; 2) if the bot's message is a reply (has `reply_to_message_id`), sender of the original message. Example: A user votes in a poll, bot returns confirmation message in reply to the vote and removes the keyboard for that user, while still showing the keyboard with poll options to users who haven't voted yet.

Returns

Instance of the class

Return type

telebot.types.ReplyKeyboardRemove

```
class telebot.types.ReplyParameters(message_id: int, chat_id: int | str | None = None,  
allow_sending_without_reply: bool | None = None, quote: str | None  
= None, quote_parse_mode: str | None = None, quote_entities:  
List[MessageEntity] | None = None, quote_position: int | None =  
None, **kwargs)
```

Bases: *JsonDeserializable, Dictionaryable, JsonSerializable*

Describes reply parameters for the message that is being sent.

Telegram documentation: <https://core.telegram.org/bots/api#replyparameters>

Parameters

- **message_id** (int) – Identifier of the message that will be replied to in the current chat, or in the chat `chat_id` if it is specified
- **chat_id** (int or str) – Optional. If the message to be replied to is from a different chat, unique identifier for the chat or username of the channel (in the format `@channelusername`)
- **allow_sending_without_reply** (bool) – Optional. Pass True if the message should be sent even if the specified message to be replied to is not found; can be used only for replies in the same chat and forum topic.
- **quote** (str) – Optional. Quoted part of the message to be replied to; 0-1024 characters after entities parsing. The quote must be an exact substring of the message to be replied to, including bold, italic, underline, strikethrough, spoiler, and `custom_emoji` entities. The message will fail to send if the quote isn't found in the original message.
- **quote_parse_mode** (str) – Optional. Mode for parsing entities in the quote. See formatting options for more details.

- **quote_entities** (list of *MessageEntity*) – Optional. A JSON-serialized list of special entities that appear in the quote. It can be specified instead of `quote_parse_mode`.
- **quote_position** (int) – Optional. Position of the quote in the original message in UTF-16 code units

Returns

Instance of the class

Return type

ReplyParameters

class telebot.types.**SentWebAppMessage**(*inline_message_id=None, **kwargs*)

Bases: *JsonDeserializable, Dictionaryable*

Describes an inline message sent by a Web App on behalf of a user.

Telegram Documentation: <https://core.telegram.org/bots/api#sentwebappmessage>

Parameters

inline_message_id (str) – Optional. Identifier of the sent inline message. Available only if there is an inline keyboard attached to the message.

Returns

Instance of the class

Return type

telebot.types.SentWebAppMessage

class telebot.types.**SharedUser**(*user_id, first_name=None, last_name=None, username=None, photo=None, **kwargs*)

Bases: *JsonDeserializable*

This object contains information about a user that was shared with the bot using a `KeyboardButtonRequestUser` button.

Telegram documentation: <https://core.telegram.org/bots/api#shareduser>

Parameters

- **user_id** (int) – Identifier of the shared user. This number may have more than 32 significant bits and some programming languages may have difficulty/silent defects in interpreting it. But it has at most 52 significant bits, so 64-bit integers or double-precision float types are safe for storing these identifiers. The bot may not have access to the user and could be unable to use this identifier, unless the user is already known to the bot by some other means.
- **first_name** (str) – Optional. First name of the user, if the name was requested by the bot
- **last_name** (str) – Optional. Last name of the user, if the name was requested by the bot
- **username** (str) – Optional. Username of the user, if the username was requested by the bot
- **photo** (list of *PhotoSize*) – Optional. Available sizes of the chat photo, if the photo was requested by the bot

Returns

Instance of the class

Return type

SharedUser

class telebot.types.**ShippingAddress**(*country_code, state, city, street_line1, street_line2, post_code, **kwargs*)

Bases: *JsonDeserializable*

This object represents a shipping address.

Telegram Documentation: <https://core.telegram.org/bots/api#shippingaddress>

Parameters

- **country_code** (str) – Two-letter ISO 3166-1 alpha-2 country code
- **state** (str) – State, if applicable
- **city** (str) – City
- **street_line1** (str) – First line for the address
- **street_line2** (str) – Second line for the address
- **post_code** (str) – Address post code

Returns

Instance of the class

Return type

telebot.types.ShippingAddress

class telebot.types.**ShippingOption**(*id, title*)

Bases: *JsonSerializable*

This object represents one shipping option.

Telegram Documentation: <https://core.telegram.org/bots/api#shippingoption>

Parameters

- **id** (str) – Shipping option identifier
- **title** (str) – Option title
- **prices** (list of *telebot.types.LabeledPrice*) – List of price portions

Returns

Instance of the class

Return type

telebot.types.ShippingOption

add_price(*args)

Add LabeledPrice to ShippingOption

Parameters

args (*LabeledPrice*) – LabeledPrices

Returns

None

class telebot.types.**ShippingQuery**(*id, from_user, invoice_payload, shipping_address, **kwargs*)

Bases: *JsonDeserializable*

This object contains information about an incoming shipping query.

Telegram Documentation: <https://core.telegram.org/bots/api#shippingquery>

Parameters

- **id** (str) – Unique query identifier

- **from** (*telebot.types.User*) – User who sent the query
- **invoice_payload** (str) – Bot specified invoice payload
- **shipping_address** (*telebot.types.ShippingAddress*) – User specified shipping address

Returns

Instance of the class

Return type

telebot.types.ShippingQuery

```
class telebot.types.Sticker(file_id, file_unique_id, type, width, height, is_animated, is_video,
                           thumbnail=None, emoji=None, set_name=None, mask_position=None,
                           file_size=None, premium_animation=None, custom_emoji_id=None,
                           needs_repainting=None, **kwargs)
```

Bases: *JsonDeserializable*

This object represents a sticker.

Telegram Documentation: <https://core.telegram.org/bots/api#sticker>

Parameters

- **file_id** (str) – Identifier for this file, which can be used to download or reuse the file
- **file_unique_id** (str) – Unique identifier for this file, which is supposed to be the same over time and for different bots. Can't be used to download or reuse the file.
- **type** (str) – Type of the sticker, currently one of “regular”, “mask”, “custom_emoji”. The type of the sticker is independent from its format, which is determined by the fields `is_animated` and `is_video`.
- **width** (int) – Sticker width
- **height** (int) – Sticker height
- **is_animated** (bool) – True, if the sticker is animated
- **is_video** (bool) – True, if the sticker is a video sticker
- **thumbnail** (*telebot.types.PhotoSize*) – Optional. Sticker thumbnail in the .WEBP or .JPG format
- **emoji** (str) – Optional. Emoji associated with the sticker
- **set_name** (str) – Optional. Name of the sticker set to which the sticker belongs
- **premium_animation** (*telebot.types.File*) – Optional. Premium animation for the sticker, if the sticker is premium
- **mask_position** (*telebot.types.MaskPosition*) – Optional. For mask stickers, the position where the mask should be placed
- **custom_emoji_id** (str) – Optional. For custom emoji stickers, unique identifier of the custom emoji
- **needs_repainting** (bool) – Optional. True, if the sticker must be repainted to a text color in messages, the color of the Telegram Premium badge in emoji status, white color on chat photos, or another appropriate color in other places
- **file_size** (int) – Optional. File size in bytes

Returns

Instance of the class

Return type

telebot.types.Sticker

property thumb

class telebot.types.**StickerSet**(name, title, sticker_type, stickers, thumbnail=None, **kwargs)

Bases: *JsonDeserializable*

This object represents a sticker set.

Telegram Documentation: <https://core.telegram.org/bots/api#stickerset>

Parameters

- **name** (str) – Sticker set name
- **title** (str) – Sticker set title
- **sticker_type** (str) – Type of stickers in the set, currently one of “regular”, “mask”, “custom_emoji”
- **stickers** (list of *telebot.types.Sticker*) – List of all set stickers
- **thumbnail** (*telebot.types.PhotoSize*) – Optional. Sticker set thumbnail in the .WEBP, .TGS, or .WEBM format

Returns

Instance of the class

Return type

telebot.types.StickerSet

property contains_masks

Deprecated since Bot API 6.2, use sticker_type instead.

property is_animated

Deprecated since Bot API 7.2. Stickers can be mixed now.

property is_video

Deprecated since Bot API 7.2. Stickers can be mixed now.

property thumb

class telebot.types.**Story**(chat: *Chat*, id: int, **kwargs)

Bases: *JsonDeserializable*

This object represents a story.

Telegram documentation: <https://core.telegram.org/bots/api#story>

Parameters

- **chat** (*telebot.types.Chat*) – Chat that posted the story
- **id** (int) – Unique identifier for the story in the chat

Returns

Instance of the class

Return type

Story

```
class telebot.types.SuccessfulPayment(currency, total_amount, invoice_payload,  
shipping_option_id=None, order_info=None,  
telegram_payment_charge_id=None,  
provider_payment_charge_id=None, **kwargs)
```

Bases: *JsonDeserializable*

This object contains basic information about a successful payment.

Telegram Documentation: <https://core.telegram.org/bots/api#successfulpayment>

Parameters

- **currency** (str) – Three-letter ISO 4217 currency code
- **total_amount** (int) – Total price in the smallest units of the currency (integer, not float/double). For example, for a price of US\$ 1.45 pass amount = 145. See the exp parameter in currencies.json, it shows the number of digits past the decimal point for each currency (2 for the majority of currencies).
- **invoice_payload** (str) – Bot specified invoice payload
- **shipping_option_id** (str) – Optional. Identifier of the shipping option chosen by the user
- **order_info** (*telebot.types.OrderInfo*) – Optional. Order information provided by the user
- **telegram_payment_charge_id** (str) – Telegram payment identifier
- **provider_payment_charge_id** (str) – Provider payment identifier

Returns

Instance of the class

Return type

telebot.types.SuccessfulPayment

```
class telebot.types.SwitchInlineQueryChosenChat(query=None, allow_user_chats=None,  
allow_bot_chats=None, allow_group_chats=None,  
allow_channel_chats=None, **kwargs)
```

Bases: *JsonDeserializable, Dictionaryable, JsonSerializerizable*

Represents an inline button that switches the current user to inline mode in a chosen chat, with an optional default inline query.

Telegram Documentation: <https://core.telegram.org/bots/api#inlinekeyboardbutton>

Parameters

- **query** (str) – Optional. The default inline query to be inserted in the input field. If left empty, only the bot's username will be inserted
- **allow_user_chats** (bool) – Optional. True, if private chats with users can be chosen
- **allow_bot_chats** (bool) – Optional. True, if private chats with bots can be chosen
- **allow_group_chats** (bool) – Optional. True, if group and supergroup chats can be chosen
- **allow_channel_chats** (bool) – Optional. True, if channel chats can be chosen

Returns

Instance of the class

Return type

SwitchInlineQueryChosenChat

```
class telebot.types.TextQuote(text: str, position: int, entities: List[MessageEntity] | None = None,
                             is_manual: bool | None = None, **kwargs)
```

Bases: *JsonDeserializable*

This object contains information about the quoted part of a message that is replied to by the given message.

Telegram documentation: <https://core.telegram.org/bots/api#textquote>

Parameters

- **text** (str) – Text of the quoted part of a message that is replied to by the given message
- **entities** (list of *MessageEntity*) – Optional. Special entities that appear in the quote. Currently, only bold, italic, underline, strikethrough, spoiler, and custom_emoji entities are kept in quotes.
- **position** (int) – Approximate quote position in the original message in UTF-16 code units as specified by the sender
- **is_manual** (bool) – Optional. True, if the quote was chosen manually by the message sender. Otherwise, the quote was added automatically by the server.

Returns

Instance of the class

Return type

TextQuote

property `html_text`

Returns html-rendered text.

```
class telebot.types.Update(update_id, message, edited_message, channel_post, edited_channel_post,
                           inline_query, chosen_inline_result, callback_query, shipping_query,
                           pre_checkout_query, poll, poll_answer, my_chat_member, chat_member,
                           chat_join_request, message_reaction, message_reaction_count,
                           removed_chat_boost, chat_boost, business_connection, business_message,
                           edited_business_message, deleted_business_messages, **kwargs)
```

Bases: *JsonDeserializable*

This object represents an incoming update. At most one of the optional parameters can be present in any given update.

Telegram Documentation: <https://core.telegram.org/bots/api#update>

Parameters

- **update_id** (int) – The update's unique identifier. Update identifiers start from a certain positive number and increase sequentially. This ID becomes especially handy if you're using webhooks, since it allows you to ignore repeated updates or to restore the correct update sequence, should they get out of order. If there are no new updates for at least a week, then identifier of the next update will be chosen randomly instead of sequentially.
- **message** (*telebot.types.Message*) – Optional. New incoming message of any kind - text, photo, sticker, etc.
- **edited_message** (*telebot.types.Message*) – Optional. New version of a message that is known to the bot and was edited
- **channel_post** (*telebot.types.Message*) – Optional. New incoming channel post of any kind - text, photo, sticker, etc.
- **edited_channel_post** (*telebot.types.Message*) – Optional. New version of a channel post that is known to the bot and was edited

- **message_reaction** (*telebot.types.MessageReactionUpdated*) – Optional. A reaction to a message was changed by a user. The bot must be an administrator in the chat and must explicitly specify “message_reaction” in the list of allowed_updates to receive these updates. The update isn’t received for reactions set by bots.
- **message_reaction_count** (*telebot.types.MessageReactionCountUpdated*) – Optional. Reactions to a message with anonymous reactions were changed. The bot must be an administrator in the chat and must explicitly specify “message_reaction_count” in the list of allowed_updates to receive these updates.
- **inline_query** (*telebot.types.InlineQuery*) – Optional. New incoming inline query
- **chosen_inline_result** (*telebot.types.ChosenInlineResult*) – Optional. The result of an inline query that was chosen by a user and sent to their chat partner. Please see our documentation on the feedback collecting for details on how to enable these updates for your bot.
- **callback_query** (*telebot.types.CallbackQuery*) – Optional. New incoming callback query
- **shipping_query** (*telebot.types.ShippingQuery*) – Optional. New incoming shipping query. Only for invoices with flexible price
- **pre_checkout_query** (*telebot.types.PreCheckoutQuery*) – Optional. New incoming pre-checkout query. Contains full information about checkout
- **poll** (*telebot.types.Poll*) – Optional. New poll state. Bots receive only updates about stopped polls and polls, which are sent by the bot
- **poll_answer** (*telebot.types.PollAnswer*) – Optional. A user changed their answer in a non-anonymous poll. Bots receive new votes only in polls that were sent by the bot itself.
- **my_chat_member** (*telebot.types.ChatMemberUpdated*) – Optional. The bot’s chat member status was updated in a chat. For private chats, this update is received only when the bot is blocked or unblocked by the user.
- **chat_member** (*telebot.types.ChatMemberUpdated*) – Optional. A chat member’s status was updated in a chat. The bot must be an administrator in the chat and must explicitly specify “chat_member” in the list of allowed_updates to receive these updates.
- **chat_join_request** (*telebot.types.ChatJoinRequest*) – Optional. A request to join the chat has been sent. The bot must have the can_invite_users administrator right in the chat to receive these updates.
- **chat_boost** (*telebot.types.ChatBoostUpdated*) – Optional. A chat boost was added or changed. The bot must be an administrator in the chat to receive these updates.
- **removed_chat_boost** (*telebot.types.RemovedChatBoost*) – Optional. A chat boost was removed. The bot must be an administrator in the chat to receive these updates.
- **business_connection** (*telebot.types.BusinessConnection*) – Optional. The bot was connected to or disconnected from a business account, or a user edited an existing connection with the bot
- **business_message** (*telebot.types.Message*) – Optional. New non-service message from a connected business account
- **edited_business_message** (*telebot.types.Message*) – Optional. New version of a non-service message from a connected business account that is known to the bot and was edited

- **deleted_business_messages** (*telebot.types.Message*) – Optional. Service message: the chat connected to the business account was deleted

Returns

Instance of the class

Return type

telebot.types.Update

```
class telebot.types.User(id, is_bot, first_name, last_name=None, username=None, language_code=None,
                        can_join_groups=None, can_read_all_group_messages=None,
                        supports_inline_queries=None, is_premium=None,
                        added_to_attachment_menu=None, can_connect_to_business=None, **kwargs)
```

Bases: *JsonDeserializable, Dictionaryable, JsonSerializerable*

This object represents a Telegram user or bot.

Telegram Documentation: <https://core.telegram.org/bots/api#user>

Parameters

- **id** (int) – Unique identifier for this user or bot. This number may have more than 32 significant bits and some programming languages may have difficulty/silent defects in interpreting it. But it has at most 52 significant bits, so a 64-bit integer or double-precision float type are safe for storing this identifier.
- **is_bot** (bool) – True, if this user is a bot
- **first_name** (str) – User’s or bot’s first name
- **last_name** (str) – Optional. User’s or bot’s last name
- **username** (str) – Optional. User’s or bot’s username
- **language_code** (str) – Optional. IETF language tag of the user’s language
- **is_premium** (bool) – Optional. bool, if this user is a Telegram Premium user
- **added_to_attachment_menu** (bool) – Optional. bool, if this user added the bot to the attachment menu
- **can_join_groups** (bool) – Optional. True, if the bot can be invited to groups. Returned only in `getMe`.
- **can_read_all_group_messages** (bool) – Optional. True, if privacy mode is disabled for the bot. Returned only in `getMe`.
- **supports_inline_queries** (bool) – Optional. True, if the bot supports inline queries. Returned only in `getMe`.
- **can_connect_to_business** (bool) – Optional. True, if the bot can be connected to a Telegram Business account to receive its messages. Returned only in `getMe`.

Returns

Instance of the class

Return type

telebot.types.User

property full_name

User’s full name

Type

return

class telebot.types.**UserChatBoosts**(*boosts*, ***kwargs*)

Bases: *JsonDeserializable*

This object represents a list of boosts added to a chat by a user.

Telegram documentation: <https://core.telegram.org/bots/api#userchatboosts>

Parameters

boosts (list of *ChatBoost*) – The list of boosts added to the chat by the user

Returns

Instance of the class

Return type

UserChatBoosts

class telebot.types.**UserProfilePhotos**(*total_count*, *photos=None*, ***kwargs*)

Bases: *JsonDeserializable*

This object represent a user's profile pictures.

Telegram Documentation: <https://core.telegram.org/bots/api#userprofilephotos>

Parameters

- **total_count** (int) – Total number of profile pictures the target user has
- **photos** (list of list of *telebot.types.PhotoSize*) – Requested profile pictures (in up to 4 sizes each)

Returns

Instance of the class

Return type

telebot.types.UserProfilePhotos

class telebot.types.**UsersShared**(*request_id*, *user_ids: SharedUser*, ***kwargs*)

Bases: *JsonDeserializable*

This object contains information about the users whose identifiers were shared with the bot using a KeyboardButtonRequestUsers button.

Telegram documentation: <https://core.telegram.org/bots/api#usersshared>

Parameters

- **request_id** (int) – Identifier of the request
- **user_ids** (list of *types.SharedUser*) – Array of *types.SharedUser* of the shared users. These numbers may have more than 32 significant bits and some programming languages may have difficulty/silent defects in interpreting them. But they have at most 52 significant bits, so 64-bit integers or double-precision float types are safe for storing these identifiers. The bot may not have access to the users and could be unable to use these identifiers unless the users are already known to the bot by some other means.

Returns

Instance of the class

Return type

UsersShared

property *user_id*

```
class telebot.types.Venue(location, title, address, foursquare_id=None, foursquare_type=None,
                          google_place_id=None, google_place_type=None, **kwargs)
```

Bases: *JsonDeserializable*

This object represents a venue.

Telegram Documentation: <https://core.telegram.org/bots/api#venue>

Parameters

- **location** (*telebot.types.Location*) – Venue location. Can't be a live location
- **title** (str) – Name of the venue
- **address** (str) – Address of the venue
- **foursquare_id** (str) – Optional. Foursquare identifier of the venue
- **foursquare_type** (str) – Optional. Foursquare type of the venue. (For example, “arts_entertainment/default”, “arts_entertainment/aquarium” or “food/icecream”.)
- **google_place_id** (str) – Optional. Google Places identifier of the venue
- **google_place_type** (str) – Optional. Google Places type of the venue. (See supported types.)

Returns

Instance of the class

Return type

telebot.types.Venue

```
class telebot.types.Video(file_id, file_unique_id, width, height, duration, thumbnail=None, file_name=None,
                          mime_type=None, file_size=None, **kwargs)
```

Bases: *JsonDeserializable*

This object represents a video file.

Telegram Documentation: <https://core.telegram.org/bots/api#video>

Parameters

- **file_id** (str) – Identifier for this file, which can be used to download or reuse the file
- **file_unique_id** (str) – Unique identifier for this file, which is supposed to be the same over time and for different bots. Can't be used to download or reuse the file.
- **width** (int) – Video width as defined by sender
- **height** (int) – Video height as defined by sender
- **duration** (int) – Duration of the video in seconds as defined by sender
- **thumbnail** (*telebot.types.PhotoSize*) – Optional. Video thumbnail
- **file_name** (str) – Optional. Original filename as defined by sender
- **mime_type** (str) – Optional. MIME type of the file as defined by sender
- **file_size** (int) – Optional. File size in bytes. It can be bigger than 2³¹ and some programming languages may have difficulty/silent defects in interpreting it. But it has at most 52 significant bits, so a signed 64-bit integer or double-precision float type are safe for storing this value.

Returns

Instance of the class

Return type*telebot.types.Video***property thumb****class** telebot.types.VideoChatEnded(*duration*, ***kwargs*)Bases: *JsonDeserializable*

This object represents a service message about a video chat ended in the chat.

Telegram Documentation: <https://core.telegram.org/bots/api#videochatended>**Parameters****duration** (int) – Video chat duration in seconds**Returns**

Instance of the class

Return type*telebot.types.VideoChatEnded***class** telebot.types.VideoChatParticipantsInvited(*users=None*, ***kwargs*)Bases: *JsonDeserializable*

This object represents a service message about new members invited to a video chat.

Telegram Documentation: <https://core.telegram.org/bots/api#videochatparticipantsinvited>**Parameters****users** (list of *telebot.types.User*) – New members that were invited to the video chat**Returns**

Instance of the class

Return type*telebot.types.VideoChatParticipantsInvited***class** telebot.types.VideoChatScheduled(*start_date*, ***kwargs*)Bases: *JsonDeserializable*

This object represents a service message about a video chat scheduled in the chat.

Telegram Documentation: <https://core.telegram.org/bots/api#videochatscheduled>**Parameters****start_date** (int) – Point in time (Unix timestamp) when the video chat is supposed to be started by a chat administrator**Returns**

Instance of the class

Return type*telebot.types.VideoChatScheduled***class** telebot.types.VideoChatStartedBases: *JsonDeserializable*

This object represents a service message about a video chat started in the chat. Currently holds no information.

class telebot.types.VideoNote(*file_id*, *file_unique_id*, *length*, *duration*, *thumbnail=None*, *file_size=None*, ***kwargs*)Bases: *JsonDeserializable*

This object represents a video message (available in Telegram apps as of v.4.0).

Telegram Documentation: <https://core.telegram.org/bots/api#videonote>

Parameters

- **file_id** (str) – Identifier for this file, which can be used to download or reuse the file
- **file_unique_id** (str) – Unique identifier for this file, which is supposed to be the same over time and for different bots. Can't be used to download or reuse the file.
- **length** (int) – Video width and height (diameter of the video message) as defined by sender
- **duration** (int) – Duration of the video in seconds as defined by sender
- **thumbnail** (*telebot.types.PhotoSize*) – Optional. Video thumbnail
- **file_size** (int) – Optional. File size in bytes

Returns

Instance of the class

Return type

telebot.types.VideoNote

property thumb

```
class telebot.types.Voice(file_id, file_unique_id, duration, mime_type=None, file_size=None, **kwargs)
```

Bases: *JsonDeserializable*

This object represents a voice note.

Telegram Documentation: <https://core.telegram.org/bots/api#voice>

Parameters

- **file_id** (str) – Identifier for this file, which can be used to download or reuse the file
- **file_unique_id** (str) – Unique identifier for this file, which is supposed to be the same over time and for different bots. Can't be used to download or reuse the file.
- **duration** (int) – Duration of the audio in seconds as defined by sender
- **mime_type** (str) – Optional. MIME type of the file as defined by sender
- **file_size** (int) – Optional. File size in bytes. It can be bigger than 2^{31} and some programming languages may have difficulty/silent defects in interpreting it. But it has at most 52 significant bits, so a signed 64-bit integer or double-precision float type are safe for storing this value.

Returns

Instance of the class

Return type

telebot.types.Voice

```
class telebot.types.VoiceChatEnded(*args, **kwargs)
```

Bases: *VideoChatEnded*

Deprecated, use *VideoChatEnded* instead.

```
class telebot.types.VoiceChatParticipantsInvited(*args, **kwargs)
```

Bases: *VideoChatParticipantsInvited*

Deprecated, use *VideoChatParticipantsInvited* instead.

class telebot.types.VoiceChatScheduled(*args, **kwargs)

Bases: *VideoChatScheduled*

Deprecated, use *VideoChatScheduled* instead.

class telebot.types.VoiceChatStarted

Bases: *VideoChatStarted*

Deprecated, use *VideoChatStarted* instead.

class telebot.types.WebAppData(data, button_text, **kwargs)

Bases: *JsonDeserializable*, *Dictionaryable*

Describes data sent from a Web App to the bot.

Telegram Documentation: <https://core.telegram.org/bots/api#webappdata>

Parameters

- **data** (str) – The data. Be aware that a bad client can send arbitrary data in this field.
- **button_text** (str) – Text of the web_app keyboard button from which the Web App was opened. Be aware that a bad client can send arbitrary data in this field.

Returns

Instance of the class

Return type

telebot.types.WebAppData

class telebot.types.WebAppInfo(url, **kwargs)

Bases: *JsonDeserializable*, *Dictionaryable*

Describes a Web App.

Telegram Documentation: <https://core.telegram.org/bots/api#webappinfo>

Parameters

url (str) – An HTTPS URL of a Web App to be opened with additional data as specified in Initializing Web Apps

Returns

Instance of the class

Return type

telebot.types.WebAppInfo

class telebot.types.WebhookInfo(url, has_custom_certificate, pending_update_count, ip_address=None, last_error_date=None, last_error_message=None, last_synchronization_error_date=None, max_connections=None, allowed_updates=None, **kwargs)

Bases: *JsonDeserializable*

Describes the current status of a webhook.

Telegram Documentation: <https://core.telegram.org/bots/api#webhookinfo>

Parameters

- **url** (str) – Webhook URL, may be empty if webhook is not set up
- **has_custom_certificate** (bool) – True, if a custom certificate was provided for webhook certificate checks
- **pending_update_count** (int) – Number of updates awaiting delivery

- **ip_address** (str) – Optional. Currently used webhook IP address
- **last_error_date** (int) – Optional. Unix time for the most recent error that happened when trying to deliver an update via webhook
- **last_error_message** (str) – Optional. Error message in human-readable format for the most recent error that happened when trying to deliver an update via webhook
- **last_synchronization_error_date** (int) – Optional. Unix time of the most recent error that happened when trying to synchronize available updates with Telegram datacenters
- **max_connections** (int) – Optional. The maximum allowed number of simultaneous HTTPS connections to the webhook for update delivery
- **allowed_updates** (list of str) – Optional. A list of update types the bot is subscribed to. Defaults to all update types except chat_member

Returns

Instance of the class

Return type

telebot.types.WebhookInfo

```
class telebot.types.WriteAccessAllowed(from_request: bool | None = None, web_app_name: str | None = None, from_attachment_menu: bool | None = None, **kwargs)
```

Bases: *JsonDeserializable*

This object represents a service message about a user allowing a bot to write messages after adding it to the attachment menu, launching a Web App from a link, or accepting an explicit request from a Web App sent by the method `requestWriteAccess`.

Telegram documentation: <https://core.telegram.org/bots/api#writeaccessallowed>

Parameters

- **from_request** (bool) – Optional. True, if the access was granted after the user accepted an explicit request from a Web App sent by the method `requestWriteAccess`
- **web_app_name** (str) – Optional. Name of the Web App which was launched from a link
- **from_attachment_menu** (bool) – Optional. True, if the access was granted when the bot was added to the attachment or side menu

1.3.4 TeleBot version

TeleBot methods

```
class telebot.ExceptionHandler
```

Bases: object

Class for handling exceptions while Polling

```
handle(exception)
```

```
class telebot.Handler(callback, *args, **kwargs)
```

Bases: object

Class for (next step|reply) handlers.

`telebot.REPLY_MARKUP_TYPES`

telebot

Type

Module

alias of [InlineKeyboardMarkup](#) | [ReplyKeyboardMarkup](#) | [ReplyKeyboardRemove](#) | [ForceReply](#)

```
class telebot.TeleBot(token: str, parse_mode: str | None = None, threaded: bool | None = True,
    skip_pending: bool | None = False, num_threads: int | None = 2, next_step_backend:
    ~telebot.handler_backends.HandlerBackend | None = None, reply_backend:
    ~telebot.handler_backends.HandlerBackend | None = None, exception_handler:
    ~telebot.ExceptionHandler | None = None, last_update_id: int | None = 0,
    suppress_middleware_exceptions: bool | None = False, state_storage:
    ~telebot.storage.base_storage.StateStorageBase | None =
    <telebot.storage.memory_storage.StateMemoryStorage object>,
    use_class_middlewarees: bool | None = False, disable_web_page_preview: bool | None
    = None, disable_notification: bool | None = None, protect_content: bool | None = None,
    allow_sending_without_reply: bool | None = None, colorful_logs: bool | None = False)
```

Bases: object

This is the main synchronous class for Bot.

It allows you to add handlers for different kind of updates.

Usage:

Listing 4: Creating instance of TeleBot

```
from telebot import TeleBot
bot = TeleBot('token') # get token from @BotFather
# now you can register other handlers/update listeners,
# and use bot methods.
```

See more examples in examples/ directory: <https://github.com/eternnoir/pyTelegramBotAPI/tree/master/examples>**Note:** Install coloredlogs module to specify colorful_logs=True**Parameters**

- **token** (str) – Token of a bot, should be obtained from @BotFather
- **parse_mode** (str, optional) – Default parse mode, defaults to None
- **threaded** (bool, optional) – Threaded or not, defaults to True
- **skip_pending** (bool, optional) – Skips pending updates, defaults to False
- **num_threads** (int, optional) – Number of maximum parallel threads, defaults to 2
- **next_step_backend** (telebot.handler_backends.HandlerBackend, optional) – Next step backend class, defaults to None
- **reply_backend** (telebot.handler_backends.HandlerBackend, optional) – Reply step handler class, defaults to None
- **exception_handler** (telebot.ExceptionHandler, optional) – Exception handler to handle errors, defaults to None

- **last_update_id** (int, optional) – Last update’s id, defaults to 0
- **suppress_middleware_exceptions** (bool, optional) – Suppress middleware exceptions, defaults to False
- **state_storage** (telebot.storage.StateStorageBase, optional) – Storage for states, defaults to StateMemoryStorage()
- **use_class_middlewarees** (bool, optional) – Use class middlewares, defaults to False
- **disable_web_page_preview** (bool, optional) – Default value for disable_web_page_preview, defaults to None
- **disable_notification** (bool, optional) – Default value for disable_notification, defaults to None
- **protect_content** (bool, optional) – Default value for protect_content, defaults to None
- **allow_sending_without_reply** (bool, optional) – Default value for allow_sending_without_reply, defaults to None
- **colorful_logs** (bool, optional) – Outputs colorful logs

add_custom_filter(*custom_filter*: SimpleCustomFilter | AdvancedCustomFilter)

Create custom filter.

Listing 5: Example on checking the text of a message

```
class TextMatchFilter(AdvancedCustomFilter):
    key = 'text'

    def check(self, message, text):
        return text == message.text
```

Parameters

- **custom_filter** – Class with check(message) method.
- **custom_filter** – Custom filter class with key.

add_data(*user_id*: int, *chat_id*: int | None = None, ***kwargs*)

Add data to states.

Parameters

- **user_id** (int) – User’s identifier
- **chat_id** (int) – Chat’s identifier
- **kwargs** – Data to add

Returns

None

add_sticker_to_set(*user_id*: int, *name*: str, *emojis*: List[str] | str, *png_sticker*: str | Any | None = None, *tgs_sticker*: str | Any | None = None, *webm_sticker*: str | Any | None = None, *mask_position*: MaskPosition | None = None, *sticker*: InputSticker | None = None) → bool

Use this method to add a new sticker to a set created by the bot. The format of the added sticker must match the format of the other stickers in the set. Emoji sticker sets can have up to 200 stickers. Animated and

video sticker sets can have up to 50 stickers. Static sticker sets can have up to 120 stickers. Returns True on success.

Telegram documentation: <https://core.telegram.org/bots/api#addstickertoset>

Note: `**_sticker`, `mask_position`, `emojis` parameters are deprecated, use `stickers` instead

Parameters

- **user_id** (int) – User identifier of created sticker set owner
- **name** (str) – Sticker set name
- **emojis** (str) – One or more emoji corresponding to the sticker
- **png_sticker** (str or filelike object) – PNG image with the sticker, must be up to 512 kilobytes in size, dimensions must not exceed 512px, and either width or height must be exactly 512px. Pass a `file_id` as a String to send a file that already exists on the Telegram servers, pass an HTTP URL as a String for Telegram to get a file from the Internet, or upload a new one using multipart/form-data.
- **tgs_sticker** (str or filelike object) – TGS animation with the sticker, uploaded using multipart/form-data.
- **webm_sticker** (str or filelike object) – WebM animation with the sticker, uploaded using multipart/form-data.
- **mask_position** (`telebot.types.MaskPosition`) – A JSON-serialized object for position where the mask should be placed on faces
- **sticker** (`telebot.types.InputSticker`) – A JSON-serialized object for sticker to be added to the sticker set

Returns

On success, True is returned.

Return type

bool

answer_callback_query(*callback_query_id*: int, *text*: str | None = None, *show_alert*: bool | None = None, *url*: str | None = None, *cache_time*: int | None = None) → bool

Use this method to send answers to callback queries sent from inline keyboards. The answer will be displayed to the user as a notification at the top of the chat screen or as an alert.

Telegram documentation: <https://core.telegram.org/bots/api#answercallbackquery>

Parameters

- **callback_query_id** (int) – Unique identifier for the query to be answered
- **text** (str) – Text of the notification. If not specified, nothing will be shown to the user, 0-200 characters
- **show_alert** (bool) – If True, an alert will be shown by the client instead of a notification at the top of the chat screen. Defaults to false.
- **url** (str) – URL that will be opened by the user's client. If you have created a Game and accepted the conditions via `@BotFather`, specify the URL that opens your game - note that this will only work if the query comes from a `callback_game` button.

- **cache_time** – The maximum amount of time in seconds that the result of the callback query may be cached client-side. Telegram apps will support caching starting in version 3.14. Defaults to 0.

Returns

On success, True is returned.

Return type

bool

answer_inline_query(*inline_query_id: str, results: List[Any], cache_time: int | None = None, is_personal: bool | None = None, next_offset: str | None = None, switch_pm_text: str | None = None, switch_pm_parameter: str | None = None, button: InlineQueryResultsButton | None = None*) → bool

Use this method to send answers to an inline query. On success, True is returned. No more than 50 results per query are allowed.

Telegram documentation: <https://core.telegram.org/bots/api#answerinlinequery>

Parameters

- **inline_query_id** (str) – Unique identifier for the answered query
- **results** (list of types. `InlineQueryResult`) – Array of results for the inline query
- **cache_time** (int) – The maximum amount of time in seconds that the result of the inline query may be cached on the server.
- **is_personal** (bool) – Pass True, if results may be cached on the server side only for the user that sent the query.
- **next_offset** (str) – Pass the offset that a client should send in the next query with the same text to receive more results.
- **switch_pm_parameter** (str) – Deep-linking parameter for the /start message sent to the bot when user presses the switch button. 1-64 characters, only A-Z, a-z, 0-9, _ and - are allowed. Example: An inline bot that sends YouTube videos can ask the user to connect the bot to their YouTube account to adapt search results accordingly. To do this, it displays a ‘Connect your YouTube account’ button above the results, or even before showing any. The user presses the button, switches to a private chat with the bot and, in doing so, passes a start parameter that instructs the bot to return an OAuth link. Once done, the bot can offer a switch_inline button so that the user can easily return to the chat where they wanted to use the bot’s inline capabilities.
- **switch_pm_text** (str) – Parameter for the start message sent to the bot when user presses the switch button
- **button** (types. `InlineQueryResultsButton`) – A JSON-serialized object describing a button to be shown above inline query results

Returns

On success, True is returned.

Return type

bool

answer_pre_checkout_query(*pre_checkout_query_id: int, ok: bool, error_message: str | None = None*) → bool

Once the user has confirmed their payment and shipping details, the Bot API sends the final confirmation in the form of an Update with the field `pre_checkout_query`. Use this method to respond to such pre-checkout queries. On success, True is returned.

Note: The Bot API must receive an answer within 10 seconds after the pre-checkout query was sent.

Telegram documentation: <https://core.telegram.org/bots/api#answerprecheckoutquery>

Parameters

- **pre_checkout_query_id** (int) – Unique identifier for the query to be answered
- **ok** (bool) – Specify True if everything is alright (goods are available, etc.) and the bot is ready to proceed with the order. Use False if there are any problems.
- **error_message** (str) – Required if ok is False. Error message in human readable form that explains the reason for failure to proceed with the checkout (e.g. “Sorry, somebody just bought the last of our amazing black T-shirts while you were busy filling out your payment details. Please choose a different color or garment!”). Telegram will display this message to the user.

Returns

On success, True is returned.

Return type

bool

answer_shipping_query(*shipping_query_id: str, ok: bool, shipping_options: List[ShippingOption] | None = None, error_message: str | None = None*) → bool

Asks for an answer to a shipping question.

Telegram documentation: <https://core.telegram.org/bots/api#answershippingquery>

Parameters

- **shipping_query_id** (str) – Unique identifier for the query to be answered
- **ok** (bool) – Specify True if delivery to the specified address is possible and False if there are any problems (for example, if delivery to the specified address is not possible)
- **shipping_options** (list of ShippingOption) – Required if ok is True. A JSON-serialized array of available shipping options.
- **error_message** (str) – Required if ok is False. Error message in human readable form that explains why it is impossible to complete the order (e.g. “Sorry, delivery to your desired address is unavailable”). Telegram will display this message to the user.

Returns

On success, True is returned.

Return type

bool

answer_web_app_query(*web_app_query_id: str, result: InlineQueryResultBase*) → *SentWebAppMessage*

Use this method to set the result of an interaction with a Web App and send a corresponding message on behalf of the user to the chat from which the query originated. On success, a *SentWebAppMessage* object is returned.

Telegram Documentation: <https://core.telegram.org/bots/api#answerwebappquery>

Parameters

- **web_app_query_id** (str) – Unique identifier for the query to be answered
- **result** (*telebot.types.InlineQueryResultBase*) – A JSON-serialized object describing the message to be sent

Returns

On success, a `SentWebAppMessage` object is returned.

Return type

`telebot.types.SentWebAppMessage`

approve_chat_join_request(*chat_id: str | int, user_id: int | str*) → bool

Use this method to approve a chat join request. The bot must be an administrator in the chat for this to work and must have the `can_invite_users` administrator right. Returns True on success.

Telegram documentation: <https://core.telegram.org/bots/api#approvechatjoinrequest>

Parameters

- **chat_id** (int or str) – Unique identifier for the target chat or username of the target supergroup (in the format `@supergroupusername`)
- **user_id** (int or str) – Unique identifier of the target user

Returns

True on success.

Return type

bool

ban_chat_member(*chat_id: int | str, user_id: int, until_date: int | datetime | None = None, revoke_messages: bool | None = None*) → bool

Use this method to ban a user in a group, a supergroup or a channel. In the case of supergroups and channels, the user will not be able to return to the chat on their own using invite links, etc., unless unbanned first. Returns True on success.

Telegram documentation: <https://core.telegram.org/bots/api#banchatmember>

Parameters

- **chat_id** (int or str) – Unique identifier for the target group or username of the target supergroup or channel (in the format `@channelusername`)
- **user_id** (int) – Unique identifier of the target user
- **until_date** (int or datetime) – Date when the user will be unbanned, unix time. If user is banned for more than 366 days or less than 30 seconds from the current time they are considered to be banned forever
- **revoke_messages** (bool) – Pass True to delete all messages from the chat for the user that is being removed. If False, the user will be able to see messages in the group that were sent before the user was removed. Always True for supergroups and channels.

Returns

Returns True on success.

Return type

bool

ban_chat_sender_chat(*chat_id: int | str, sender_chat_id: int | str*) → bool

Use this method to ban a channel chat in a supergroup or a channel. The owner of the chat will not be able to send messages and join live streams on behalf of the chat, unless it is unbanned first. The bot must be an administrator in the supergroup or channel for this to work and must have the appropriate administrator rights. Returns True on success.

Telegram documentation: <https://core.telegram.org/bots/api#banchatsenderchat>

Parameters

- **chat_id** (int or str) – Unique identifier for the target chat or username of the target channel (in the format @channelusername)
- **sender_chat_id** (int or str) – Unique identifier of the target sender chat

Returns

True on success.

Return type

bool

business_connection_handler(*func=None, **kwargs*)

Handles new incoming business connection state.

Parameters

- **func** (function) – Function executed as a filter
- **kwargs** – Optional keyword arguments(custom filters)

Returns

None

business_message_handler(*commands: List[str] | None = None, regexp: str | None = None, func: Callable | None = None, content_types: List[str] | None = None, **kwargs*)

Handles New incoming message of any kind(for business accounts, see bot api 7.2 for more) - text, photo, sticker, etc. As a parameter to the decorator function, it passes `telebot.types.Message` object. All message handlers are tested in the order they were added.

Example:

Listing 6: Usage of business_message_handler

```
bot = TeleBot('TOKEN')

# Handles all messages which text matches regexp.
@bot.business_message_handler(regexp='someregexp')
def command_help(message):
    bot.send_message(message.chat.id, 'Did someone call for help?')

# Handle all sent documents of type 'text/plain'.
@bot.business_message_handler(func=lambda message: message.document.mime_type_
↪ == 'text/plain',
↪ content_types=['document'])
def command_handle_document(message):
    bot.send_message(message.chat.id, 'Document received, sir!')

# Handle all other messages.
@bot.business_message_handler(func=lambda message: True, content_types=['audio',
↪ 'photo', 'voice', 'video', 'document',
↪ 'text', 'location', 'contact', 'sticker'])
def default_command(message):
    bot.send_message(message.chat.id, "This is the default command handler.")
```

Parameters

- **commands** (list of str) – Optional list of strings (commands to handle).
- **regexp** (str) – Optional regular expression.

- **func** (lambda) – Optional lambda function. The lambda receives the message to test as the first parameter. It must return True if the command should handle the message.
- **content_types** (list of str) – Supported message content types. Must be a list. Defaults to ['text'].
- **kwargs** – Optional keyword arguments(custom filters)

Returns

decorated function

callback_query_handler(*func*, ***kwargs*)

Handles new incoming callback query. As a parameter to the decorator function, it passes *telebot.types.CallbackQuery* object.

Parameters

- **func** (function) – Function executed as a filter
- **kwargs** – Optional keyword arguments(custom filters)

Returns

None

channel_post_handler(*commands=None*, *regex=None*, *func=None*, *content_types=None*, ***kwargs*)

Handles new incoming channel post of any kind - text, photo, sticker, etc. As a parameter to the decorator function, it passes *telebot.types.Message* object.

Parameters

- **commands** (list of str) – Optional list of strings (commands to handle).
- **regex** (str) – Optional regular expression.
- **func** (function) – Function executed as a filter
- **content_types** (list of str) – Supported message content types. Must be a list. Defaults to ['text'].
- **kwargs** – Optional keyword arguments(custom filters)

Returns

None

chat_boost_handler(*func=None*, ***kwargs*)

Handles new incoming chat boost state. it passes *telebot.types.ChatBoostUpdated* object.

Parameters

- **func** (function) – Function executed as a filter
- **kwargs** – Optional keyword arguments(custom filters)

Returns

None

chat_join_request_handler(*func=None*, ***kwargs*)

Handles a request to join the chat has been sent. The bot must have the can_invite_users administrator right in the chat to receive these updates. As a parameter to the decorator function, it passes *telebot.types.ChatJoinRequest* object.

Parameters

- **func** (function) – Function executed as a filter

- **kwargs** – Optional keyword arguments(custom filters)

Returns

None

chat_member_handler(*func=None, **kwargs*)

Handles update in a status of a user in a chat. The bot must be an administrator in the chat and must explicitly specify “chat_member” in the list of allowed_updates to receive these updates. As a parameter to the decorator function, it passes `telebot.types.ChatMemberUpdated` object.

Parameters

- **func** (function) – Function executed as a filter
- **kwargs** – Optional keyword arguments(custom filters)

Returns

None

chosen_inline_handler(*func, **kwargs*)

Handles the result of an inline query that was chosen by a user and sent to their chat partner. Please see our documentation on the feedback collecting for details on how to enable these updates for your bot. As a parameter to the decorator function, it passes `telebot.types.ChosenInlineResult` object.

Parameters

- **func** (function) – Function executed as a filter
- **kwargs** – Optional keyword arguments(custom filters)

Returns

None

clear_reply_handlers(*message: Message*) → None

Clears all callback functions registered by `register_for_reply()` and `register_for_reply_by_message_id()`.

Parameters

message (`telebot.types.Message`) – The message for which we want to clear reply handlers

Returns

None

clear_reply_handlers_by_message_id(*message_id: int*) → None

Clears all callback functions registered by `register_for_reply()` and `register_for_reply_by_message_id()`.

Parameters

message_id (int) – The message id for which we want to clear reply handlers

Returns

None

clear_step_handler(*message: Message*) → None

Clears all callback functions registered by `register_next_step_handler()`.

Parameters

message (`telebot.types.Message`) – The message for which we want to handle new message after that in same chat.

Returns

None

clear_step_handler_by_chat_id(*chat_id: int | str*) → None

Clears all callback functions registered by `register_next_step_handler()`.

Parameters

chat_id (int or str) – The chat for which we want to clear next step handlers

Returns

None

close() → bool

Use this method to close the bot instance before moving it from one local server to another. You need to delete the webhook before calling this method to ensure that the bot isn't launched again after server restart. The method will return error 429 in the first 10 minutes after the bot is launched. Returns True on success.

Telegram documentation: <https://core.telegram.org/bots/api#close>

Returns

bool

close_forum_topic(*chat_id: str | int, message_thread_id: int*) → bool

Use this method to close an open topic in a forum supergroup chat. The bot must be an administrator in the chat for this to work and must have the `can_manage_topics` administrator rights, unless it is the creator of the topic. Returns True on success.

Telegram documentation: <https://core.telegram.org/bots/api#closeforumtopic>

Aram chat_id

Unique identifier for the target chat or username of the target channel (in the format `@channelusername`)

Parameters

message_thread_id (int) – Identifier of the topic to close

Returns

On success, True is returned.

Return type

bool

close_general_forum_topic(*chat_id: int | str*) → bool

Use this method to close the 'General' topic in a forum supergroup chat. The bot must be an administrator in the chat for this to work and must have `can_manage_topics` administrator rights. Returns True on success.

Telegram documentation: <https://core.telegram.org/bots/api#closegeneralforumtopic>

Parameters

chat_id (int or str) – Unique identifier for the target chat or username of the target channel (in the format `@channelusername`)

copy_message(*chat_id: int | str, from_chat_id: int | str, message_id: int, caption: str | None = None, parse_mode: str | None = None, caption_entities: List[MessageEntity] | None = None, disable_notification: bool | None = None, protect_content: bool | None = None, reply_to_message_id: int | None = None, allow_sending_without_reply: bool | None = None, reply_markup: InlineKeyboardMarkup | ReplyKeyboardMarkup | ReplyKeyboardRemove | ForceReply | None = None, timeout: int | None = None, message_thread_id: int | None = None, reply_parameters: ReplyParameters | None = None*) → *MessageID*

Use this method to copy messages of any kind.

Telegram documentation: <https://core.telegram.org/bots/api#copymessage>

Parameters

- **chat_id** (int or str) – Unique identifier for the target chat or username of the target channel (in the format @channelusername)
- **from_chat_id** (int or str) – Unique identifier for the chat where the original message was sent (or channel username in the format @channelusername)
- **message_id** (int) – Message identifier in the chat specified in from_chat_id
- **caption** (str) – New caption for media, 0-1024 characters after entities parsing. If not specified, the original caption is kept
- **parse_mode** (str) – Mode for parsing entities in the new caption.
- **caption_entities** (Array of *telebot.types.MessageEntity*) – A JSON-serialized list of special entities that appear in the new caption, which can be specified instead of parse_mode
- **disable_notification** (bool) – Sends the message silently. Users will receive a notification with no sound.
- **protect_content** (bool) – Protects the contents of the sent message from forwarding and saving
- **reply_to_message_id** (int) – deprecated.
- **allow_sending_without_reply** (bool) – deprecated.
- **reply_markup** (*telebot.types.InlineKeyboardMarkup* or *telebot.types.ReplyKeyboardMarkup* or *telebot.types.ReplyKeyboardRemove* or *telebot.types.ForceReply*) – Additional interface options. A JSON-serialized object for an inline keyboard, custom reply keyboard, instructions to remove reply keyboard or to force a reply from the user.
- **timeout** (int) – Timeout in seconds for the request.
- **message_thread_id** (int) – Identifier of a message thread, in which the message will be sent
- **reply_parameters** (*telebot.types.ReplyParameters*) – Additional parameters for replies to messages

Returns

On success, the MessageId of the sent message is returned.

Return type

telebot.types.MessageID

copy_messages(*chat_id: str | int, from_chat_id: str | int, message_ids: List[int], disable_notification: bool | None = None, message_thread_id: int | None = None, protect_content: bool | None = None, remove_caption: bool | None = None*) → List[*MessageID*]

Use this method to copy messages of any kind. If some of the specified messages can't be found or copied, they are skipped. Service messages, giveaway messages, giveaway winners messages, and invoice messages can't be copied. A quiz poll can be copied only if the value of the field correct_option_id is known to the bot. The method is analogous to the method forwardMessages, but the copied messages don't have a link to the original message. Album grouping is kept for copied messages. On success, an array of MessageId of the sent messages is returned.

Telegram documentation: <https://core.telegram.org/bots/api#copymessages>

Parameters

- **chat_id** (int or str) – Unique identifier for the target chat or username of the target channel (in the format @channelusername)

- **from_chat_id** (int or str) – Unique identifier for the chat where the original message was sent (or channel username in the format @channelusername)
- **message_ids** (list of int) – Message identifiers in the chat specified in from_chat_id
- **disable_notification** (bool) – Sends the message silently. Users will receive a notification with no sound
- **message_thread_id** (int) – Identifier of a message thread, in which the messages will be sent
- **protect_content** (bool) – Protects the contents of the forwarded message from forwarding and saving
- **remove_caption** (bool) – Pass True to copy the messages without their captions

Returns

On success, an array of MessageId of the sent messages is returned.

Return type

list of `telebot.types.MessageID`

create_chat_invite_link(*chat_id: int | str, name: str | None = None, expire_date: int | datetime | None = None, member_limit: int | None = None, creates_join_request: bool | None = None*) → *ChatInviteLink*

Use this method to create an additional invite link for a chat. The bot must be an administrator in the chat for this to work and must have the appropriate administrator rights. The link can be revoked using the method `revokeChatInviteLink`. Returns the new invite link as `ChatInviteLink` object.

Telegram documentation: <https://core.telegram.org/bots/api#createchatinvitelink>

Parameters

- **chat_id** (int or str) – Id: Unique identifier for the target chat or username of the target channel (in the format @channelusername)
- **name** (str) – Invite link name; 0-32 characters
- **expire_date** (int or datetime) – Point in time (Unix timestamp) when the link will expire
- **member_limit** (int) – Maximum number of users that can be members of the chat simultaneously
- **creates_join_request** (bool) – True, if users joining the chat via the link need to be approved by chat administrators. If True, member_limit can't be specified

Returns

Returns the new invite link as `ChatInviteLink` object.

Return type

`telebot.types.ChatInviteLink`

create_forum_topic(*chat_id: int, name: str, icon_color: int | None = None, icon_custom_emoji_id: str | None = None*) → *ForumTopic*

Use this method to create a topic in a forum supergroup chat. The bot must be an administrator in the chat for this to work and must have the `can_manage_topics` administrator rights. Returns information about the created topic as a `ForumTopic` object.

Telegram documentation: <https://core.telegram.org/bots/api#createforumtopic>

Parameters

- **chat_id** (int or str) – Unique identifier for the target chat or username of the target channel (in the format @channelusername)
- **name** (str) – Name of the topic, 1-128 characters
- **icon_color** (int) – Color of the topic icon in RGB format. Currently, must be one of 0x6FB9F0, 0xFFD67E, 0xCB86DB, 0x8EEE98, 0xFF93B2, or 0xFB6F5F
- **icon_custom_emoji_id** (str) – Custom emoji for the topic icon. Must be an emoji of type “tgs” and must be exactly 1 character long

Returns

On success, information about the created topic is returned as a ForumTopic object.

Return type

`telebot.types.ForumTopic`

create_invoice_link(*title: str, description: str, payload: str, provider_token: str, currency: str, prices: List[LabeledPrice], max_tip_amount: int | None = None, suggested_tip_amounts: List[int] | None = None, provider_data: str | None = None, photo_url: str | None = None, photo_size: int | None = None, photo_width: int | None = None, photo_height: int | None = None, need_name: bool | None = None, need_phone_number: bool | None = None, need_email: bool | None = None, need_shipping_address: bool | None = None, send_phone_number_to_provider: bool | None = None, send_email_to_provider: bool | None = None, is_flexible: bool | None = None*) → str

Use this method to create a link for an invoice. Returns the created invoice link as String on success.

Telegram documentation: <https://core.telegram.org/bots/api#createinvoicelink>

Parameters

- **title** (str) – Product name, 1-32 characters
- **description** (str) – Product description, 1-255 characters
- **payload** (str) – Bot-defined invoice payload, 1-128 bytes. This will not be displayed to the user, use for your internal processes.
- **provider_token** (str) – Payments provider token, obtained via @Botfather
- **currency** (str) – Three-letter ISO 4217 currency code, see <https://core.telegram.org/bots/payments#supported-currencies>
- **prices** (list of `types.LabeledPrice`) – Price breakdown, a list of components (e.g. product price, tax, discount, delivery cost, delivery tax, bonus, etc.)
- **max_tip_amount** (int) – The maximum accepted amount for tips in the smallest units of the currency
- **suggested_tip_amounts** (list of int) – A JSON-serialized array of suggested amounts of tips in the smallest units of the currency. At most 4 suggested tip amounts can be specified. The suggested tip amounts must be positive, passed in a strictly increased order and must not exceed max_tip_amount.
- **provider_data** (str) – A JSON-serialized data about the invoice, which will be shared with the payment provider. A detailed description of required fields should be provided by the payment provider.
- **photo_url** (str) – URL of the product photo for the invoice. Can be a photo of the goods or a photo of the invoice. People like it better when they see a photo of what they are paying for.

- **photo_size** (int) – Photo size in bytes
- **photo_width** (int) – Photo width
- **photo_height** (int) – Photo height
- **need_name** (bool) – Pass True, if you require the user’s full name to complete the order
- **need_phone_number** (bool) – Pass True, if you require the user’s phone number to complete the order
- **need_email** (bool) – Pass True, if you require the user’s email to complete the order
- **need_shipping_address** (bool) – Pass True, if you require the user’s shipping address to complete the order
- **send_phone_number_to_provider** (bool) – Pass True, if user’s phone number should be sent to provider
- **send_email_to_provider** (bool) – Pass True, if user’s email address should be sent to provider
- **is_flexible** (bool) – Pass True, if the final price depends on the shipping method

Returns

Created invoice link as String on success.

Return type

str

create_new_sticker_set(*user_id: int, name: str, title: str, emojis: List[str] | None = None, png_sticker: Any | str = None, tgs_sticker: Any | str = None, webm_sticker: Any | str = None, contains_masks: bool | None = None, sticker_type: str | None = None, mask_position: MaskPosition | None = None, needs_repainting: bool | None = None, stickers: List[InputSticker] = None, sticker_format: str | None = None*) → bool

Use this method to create new sticker set owned by a user. The bot will be able to edit the created sticker set. Returns True on success.

Telegram documentation: <https://core.telegram.org/bots/api#createnewstickerset>

Note: Fields *_sticker are deprecated, pass a list of stickers to stickers parameter instead.

Parameters

- **user_id** (int) – User identifier of created sticker set owner
- **name** (str) – Short name of sticker set, to be used in t.me/addstickers/ URLs (e.g., animals). Can contain only English letters, digits and underscores. Must begin with a letter, can’t contain consecutive underscores and must end in “_by_<bot_username>”. <bot_username> is case insensitive. 1-64 characters.
- **title** (str) – Sticker set title, 1-64 characters
- **emojis** (str) – One or more emoji corresponding to the sticker
- **png_sticker** (str) – PNG image with the sticker, must be up to 512 kilobytes in size, dimensions must not exceed 512px, and either width or height must be exactly 512px. Pass a file_id as a String to send a file that already exists on the Telegram servers, pass an HTTP URL as a String for Telegram to get a file from the Internet, or upload a new one using multipart/form-data.

- **tgs_sticker** (str) – TGS animation with the sticker, uploaded using multipart/form-data.
- **webm_sticker** (str) – WebM animation with the sticker, uploaded using multipart/form-data.
- **contains_masks** (bool) – Pass True, if a set of mask stickers should be created. Deprecated since Bot API 6.2, use `sticker_type` instead.
- **sticker_type** (str) – Type of stickers in the set, pass “regular”, “mask”, or “custom_emoji”. By default, a regular sticker set is created.
- **mask_position** (*telebot.types.MaskPosition*) – A JSON-serialized object for position where the mask should be placed on faces
- **needs_repainting** (bool) – Pass True if stickers in the sticker set must be repainted to the color of text when used in messages, the accent color if used as emoji status, white on chat photos, or another appropriate color based on context; for custom emoji sticker sets only
- **stickers** (list of *telebot.types.InputSticker*) – List of stickers to be added to the set
- **sticker_format** (str) – deprecated

Returns

On success, True is returned.

Return type

bool

decline_chat_join_request(*chat_id: str | int, user_id: int | str*) → bool

Use this method to decline a chat join request. The bot must be an administrator in the chat for this to work and must have the `can_invite_users` administrator right. Returns True on success.

Telegram documentation: <https://core.telegram.org/bots/api#declinechatjoinrequest>

Parameters

- **chat_id** (int or str) – Unique identifier for the target chat or username of the target supergroup (in the format @supergroupusername)
- **user_id** (int or str) – Unique identifier of the target user

Returns

True on success.

Return type

bool

delete_chat_photo(*chat_id: int | str*) → bool

Use this method to delete a chat photo. Photos can’t be changed for private chats. The bot must be an administrator in the chat for this to work and must have the appropriate admin rights. Returns True on success. Note: In regular groups (non-supergroups), this method will only work if the ‘All Members Are Admins’ setting is off in the target group.

Telegram documentation: <https://core.telegram.org/bots/api#deletechatphoto>

Parameters

chat_id (int or str) – Int or Str: Unique identifier for the target chat or username of the target channel (in the format @channelusername)

Returns

True on success.

Return type

bool

delete_chat_sticker_set(*chat_id: int | str*) → bool

Use this method to delete a group sticker set from a supergroup. The bot must be an administrator in the chat for this to work and must have the appropriate admin rights. Use the field `can_set_sticker_set` optionally returned in `getChat` requests to check if the bot can use this method. Returns True on success.

Telegram documentation: <https://core.telegram.org/bots/api#deletechatstickerset>

Parameters

chat_id (int or str) – Unique identifier for the target chat or username of the target supergroup (in the format @supergroupusername)

Returns

Returns True on success.

Return type

bool

delete_forum_topic(*chat_id: str | int, message_thread_id: int*) → bool

Use this method to delete a topic in a forum supergroup chat. The bot must be an administrator in the chat for this to work and must have the `can_manage_topics` administrator rights, unless it is the creator of the topic. Returns True on success.

Telegram documentation: <https://core.telegram.org/bots/api#deleteforumtopic>

Parameters

- **chat_id** (int or str) – Unique identifier for the target chat or username of the target channel (in the format @channelusername)
- **message_thread_id** (int) – Identifier of the topic to delete

Returns

On success, True is returned.

Return type

bool

delete_message(*chat_id: int | str, message_id: int, timeout: int | None = None*) → bool

Use this method to delete a message, including service messages, with the following limitations: - A message can only be deleted if it was sent less than 48 hours ago. - A dice message in a private chat can only be deleted if it was sent more than 24 hours ago. - Bots can delete outgoing messages in private chats, groups, and supergroups. - Bots can delete incoming messages in private chats. - Bots granted `can_post_messages` permissions can delete outgoing messages in channels. - If the bot is an administrator of a group, it can delete any message there. - If the bot has `can_delete_messages` permission in a supergroup or a channel, it can delete any message there. Returns True on success.

Telegram documentation: <https://core.telegram.org/bots/api#deletemessage>

Parameters

- **chat_id** (int or str) – Unique identifier for the target chat or username of the target channel (in the format @channelusername)
- **message_id** (int) – Identifier of the message to delete
- **timeout** (int) – Timeout in seconds for the request.

Returns

Returns True on success.

Return type

bool

delete_messages(*chat_id*: int | str, *message_ids*: List[int])

Use this method to delete multiple messages simultaneously. If some of the specified messages can't be found, they are skipped. Returns True on success.

Telegram documentation: <https://core.telegram.org/bots/api#deletemessages>

Parameters

- **chat_id** (int or str) – Unique identifier for the target chat or username of the target channel (in the format @channelusername)
- **message_ids** (list of int) – Identifiers of the messages to be deleted

Returns

Returns True on success.

delete_my_commands(*scope*: BotCommandScope | None = None, *language_code*: str | None = None) → bool

Use this method to delete the list of the bot's commands for the given scope and user language. After deletion, higher level commands will be shown to affected users. Returns True on success.

Telegram documentation: <https://core.telegram.org/bots/api#deletemycommands>

Parameters

- **scope** (*telebot.types.BotCommandScope*) – The scope of users for which the commands are relevant. Defaults to BotCommandScopeDefault.
- **language_code** (str) – A two-letter ISO 639-1 language code. If empty, commands will be applied to all users from the given scope, for whose language there are no dedicated commands

Returns

True on success.

Return type

bool

delete_state(*user_id*: int, *chat_id*: int | None = None) → None

Delete the current state of a user.

Parameters

- **user_id** (int) – User's identifier
- **chat_id** (int) – Chat's identifier

Returns

None

delete_sticker_from_set(*sticker*: str) → bool

Use this method to delete a sticker from a set created by the bot. Returns True on success.

Telegram documentation: <https://core.telegram.org/bots/api#deletestickerfromset>

Parameters

sticker – File identifier of the sticker

Returns

On success, True is returned.

Return type

bool

delete_sticker_set(*name: str*) → bool

Use this method to delete a sticker set. Returns True on success.

Parameters

name (str) – Sticker set name

Returns

Returns True on success.

Return type

bool

delete_webhook(*drop_pending_updates: bool | None = None, timeout: int | None = None*) → bool

Use this method to remove webhook integration if you decide to switch back to getUpdates. Returns True on success.

Telegram documentation: <https://core.telegram.org/bots/api#deletewebhook>

Parameters

- **drop_pending_updates** – Pass True to drop all pending updates, defaults to None
- **timeout** (int, optional) – Request connection timeout, defaults to None

Returns

Returns True on success.

Return type

bool

deleted_business_messages_handler(*func=None, **kwargs*)

Handles new incoming deleted messages state.

Parameters

- **func** (function) – Function executed as a filter
- **kwargs** – Optional keyword arguments(custom filters)

Returns

None

disable_save_next_step_handlers()

Disable saving next step handlers (by default saving disable)

This function is left to keep backward compatibility whose purpose was to disable file saving capability for handlers. For the same purpose, MemoryHandlerBackend is reassigned as a new next_step_backend backend instead of FileHandlerBackend.

disable_save_reply_handlers()

Disable saving next step handlers (by default saving disable)

This function is left to keep backward compatibility whose purpose was to disable file saving capability for handlers. For the same purpose, MemoryHandlerBackend is reassigned as a new reply_backend backend instead of FileHandlerBackend.

download_file(*file_path: str*) → bytes

Downloads file.

Parameters

file_path (*str*) – Path where the file should be downloaded.

Returns

bytes

Return type

bytes

edit_chat_invite_link(*chat_id: int | str, invite_link: str | None = None, name: str | None = None, expire_date: int | datetime | None = None, member_limit: int | None = None, creates_join_request: bool | None = None*) → *ChatInviteLink*

Use this method to edit a non-primary invite link created by the bot. The bot must be an administrator in the chat for this to work and must have the appropriate admin rights.

Telegram documentation: <https://core.telegram.org/bots/api#editchatinvitelink>

Parameters

- **chat_id** (*int* or *str*) – Id: Unique identifier for the target chat or username of the target channel (in the format @channelusername)
- **name** (*str*) – Invite link name; 0-32 characters
- **invite_link** (*str*) – The invite link to edit
- **expire_date** (*int* or *datetime*) – Point in time (Unix timestamp) when the link will expire
- **member_limit** (*int*) – Maximum number of users that can be members of the chat simultaneously
- **creates_join_request** (*bool*) – True, if users joining the chat via the link need to be approved by chat administrators. If True, member_limit can't be specified

Returns

Returns the new invite link as ChatInviteLink object.

Return type

telebot.types.ChatInviteLink

edit_forum_topic(*chat_id: int | str, message_thread_id: int, name: str | None = None, icon_custom_emoji_id: str | None = None*) → bool

Use this method to edit name and icon of a topic in a forum supergroup chat. The bot must be an administrator in the chat for this to work and must have can_manage_topics administrator rights, unless it is the creator of the topic. Returns True on success.

Telegram Documentation: <https://core.telegram.org/bots/api#editforumtopic>

Parameters

- **chat_id** (*int* or *str*) – Unique identifier for the target chat or username of the target channel (in the format @channelusername)
- **message_thread_id** (*int*) – Identifier of the topic to edit
- **name** (*str*) – Optional, New name of the topic, 1-128 characters. If not specified or empty, the current name of the topic will be kept

- **icon_custom_emoji_id** (*str*) – Optional, New unique identifier of the custom emoji shown as the topic icon. Use `getForumTopicIconStickers` to get all allowed custom emoji identifiers. Pass an empty string to remove the icon. If not specified, the current icon will be kept

Returns

On success, True is returned.

Return type

bool

edit_general_forum_topic(*chat_id: int | str, name: str*) → bool

Use this method to edit the name of the ‘General’ topic in a forum supergroup chat. The bot must be an administrator in the chat for this to work and must have `can_manage_topics` administrator rights. Returns True on success.

Telegram documentation: <https://core.telegram.org/bots/api#editgeneralforumtopic>

Parameters

- **chat_id** (*int* or *str*) – Unique identifier for the target chat or username of the target channel (in the format `@channelusername`)
- **name** (*str*) – New topic name, 1-128 characters

edit_message_caption(*caption: str, chat_id: int | str | None = None, message_id: int | None = None, inline_message_id: str | None = None, parse_mode: str | None = None, caption_entities: List[MessageEntity] | None = None, reply_markup: InlineKeyboardMarkup | None = None*) → *Message* | bool

Use this method to edit captions of messages.

Telegram documentation: <https://core.telegram.org/bots/api#editmessagecaption>

Parameters

- **caption** (*str*) – New caption of the message
- **chat_id** (*int* | *str*) – Required if `inline_message_id` is not specified. Unique identifier for the target chat or username of the target channel
- **message_id** (*int*) – Required if `inline_message_id` is not specified.
- **inline_message_id** (*str*) – Required if `inline_message_id` is not specified. Identifier of the inline message.
- **parse_mode** (*str*) – New caption of the message, 0-1024 characters after entities parsing
- **caption_entities** (list of *types.MessageEntity*) – A JSON-serialized array of objects that describe how the caption should be parsed.
- **reply_markup** (*InlineKeyboardMarkup*) – A JSON-serialized object for an inline keyboard.

Returns

On success, if edited message is sent by the bot, the edited Message is returned, otherwise True is returned.

Return type

types.Message | bool

edit_message_live_location(*latitude: float, longitude: float, chat_id: int | str | None = None, message_id: int | None = None, inline_message_id: str | None = None, reply_markup: InlineKeyboardMarkup | None = None, timeout: int | None = None, horizontal_accuracy: float | None = None, heading: int | None = None, proximity_alert_radius: int | None = None*) → *Message*

Use this method to edit live location messages. A location can be edited until its live_period expires or editing is explicitly

disabled by a call to stopMessageLiveLocation. On success, if the edited message is not an inline message, the edited Message is returned, otherwise True is returned.

Telegram documentation: <https://core.telegram.org/bots/api#editmessagelivelocation>

Parameters

- **latitude** (float) – Latitude of new location
- **longitude** (float) – Longitude of new location
- **chat_id** (int or str) – Unique identifier for the target chat or username of the target channel (in the format @channelusername)
- **message_id** (int) – Required if inline_message_id is not specified. Identifier of the message to edit
- **reply_markup** (*telebot.types.InlineKeyboardMarkup* or *telebot.types.ReplyKeyboardMarkup* or *telebot.types.ReplyKeyboardRemove* or *telebot.types.ForceReply*) – A JSON-serialized object for a new inline keyboard.
- **timeout** (int) – Timeout in seconds for the request.
- **inline_message_id** (str) – Required if chat_id and message_id are not specified. Identifier of the inline message
- **horizontal_accuracy** (float) – The radius of uncertainty for the location, measured in meters; 0-1500
- **heading** (int) – Direction in which the user is moving, in degrees. Must be between 1 and 360 if specified.
- **proximity_alert_radius** (int) – The maximum distance for proximity alerts about approaching another chat member, in meters. Must be between 1 and 100000 if specified.

Returns

On success, if the edited message is not an inline message, the edited Message is returned, otherwise True is returned.

Return type

telebot.types.Message or bool

edit_message_media(*media: Any, chat_id: int | str | None = None, message_id: int | None = None, inline_message_id: str | None = None, reply_markup: InlineKeyboardMarkup | None = None*) → *Message* | bool

Use this method to edit animation, audio, document, photo, or video messages. If a message is a part of a message album, then it can be edited only to a photo or a video. Otherwise, message type can be changed arbitrarily. When inline message is edited, new file can't be uploaded. Use previously uploaded file via its file_id or specify a URL.

Telegram documentation: <https://core.telegram.org/bots/api#editmessagemedia>

Parameters

- **media** (InputMedia) – A JSON-serialized object for a new media content of the message

- **chat_id** (int or str) – Required if inline_message_id is not specified. Unique identifier for the target chat or username of the target channel (in the format @channelusername)
- **message_id** (int) – Required if inline_message_id is not specified. Identifier of the sent message
- **inline_message_id** (str) – Required if chat_id and message_id are not specified. Identifier of the inline message
- **reply_markup** (`telebot.types.InlineKeyboardMarkup` or `ReplyKeyboardMarkup` or `ReplyKeyboardRemove` or `ForceReply`) – A JSON-serialized object for an inline keyboard.

Returns

On success, if edited message is sent by the bot, the edited Message is returned, otherwise True is returned.

Return type

`types.Message` or bool

edit_message_reply_markup(*chat_id: int | str | None = None, message_id: int | None = None, inline_message_id: str | None = None, reply_markup: InlineKeyboardMarkup | None = None*) → *Message* | bool

Use this method to edit only the reply markup of messages.

Telegram documentation: <https://core.telegram.org/bots/api#editmessagereplymarkup>

Parameters

- **chat_id** (int or str) – Required if inline_message_id is not specified. Unique identifier for the target chat or username of the target channel (in the format @channelusername)
- **message_id** (int) – Required if inline_message_id is not specified. Identifier of the sent message
- **inline_message_id** (str) – Required if chat_id and message_id are not specified. Identifier of the inline message
- **reply_markup** (`InlineKeyboardMarkup` or `ReplyKeyboardMarkup` or `ReplyKeyboardRemove` or `ForceReply`) – A JSON-serialized object for an inline keyboard.

Returns

On success, if edited message is sent by the bot, the edited Message is returned, otherwise True is returned.

Return type

`types.Message` or bool

edit_message_text(*text: str, chat_id: int | str | None = None, message_id: int | None = None, inline_message_id: str | None = None, parse_mode: str | None = None, entities: List[MessageEntity] | None = None, disable_web_page_preview: bool | None = None, reply_markup: InlineKeyboardMarkup | None = None, link_preview_options: LinkPreviewOptions | None = None*) → *Message* | bool

Use this method to edit text and game messages.

Telegram documentation: <https://core.telegram.org/bots/api#editmessagetext>

Parameters

- **text** (str) – New text of the message, 1-4096 characters after entities parsing

- **chat_id** (int or str) – Required if `inline_message_id` is not specified. Unique identifier for the target chat or username of the target channel (in the format @channelusername)
- **message_id** (int) – Required if `inline_message_id` is not specified. Identifier of the sent message
- **inline_message_id** (str) – Required if `chat_id` and `message_id` are not specified. Identifier of the inline message
- **parse_mode** (str) – Mode for parsing entities in the message text.
- **entities** (List of `telebot.types.MessageEntity`) – List of special entities that appear in the message text, which can be specified instead of `parse_mode`
- **disable_web_page_preview** (bool) – deprecated.
- **reply_markup** (InlineKeyboardMarkup) – A JSON-serialized object for an inline keyboard.
- **link_preview_options** (LinkPreviewOptions) – A JSON-serialized object for options used to automatically generate previews for links.

Returns

On success, if edited message is sent by the bot, the edited Message is returned, otherwise True is returned.

Return type

`types.Message` or bool

edited_business_message_handler (*commands=None, regexp=None, func=None, content_types=None, **kwargs*)

Handles new version of a message(business accounts) that is known to the bot and was edited. As a parameter to the decorator function, it passes `telebot.types.Message` object.

Parameters

- **commands** (list of str) – Optional list of strings (commands to handle).
- **regexp** (str) – Optional regular expression.
- **func** (function) – Function executed as a filter
- **content_types** (list of str) – Supported message content types. Must be a list. Defaults to ['text'].
- **kwargs** – Optional keyword arguments(custom filters)

Returns

None

edited_channel_post_handler (*commands=None, regexp=None, func=None, content_types=None, **kwargs*)

Handles new version of a channel post that is known to the bot and was edited. As a parameter to the decorator function, it passes `telebot.types.Message` object.

Parameters

- **commands** (list of str) – Optional list of strings (commands to handle).
- **regexp** (str) – Optional regular expression.
- **func** (function) – Function executed as a filter
- **content_types** (list of str) – Supported message content types. Must be a list. Defaults to ['text'].

- **kwargs** – Optional keyword arguments(custom filters)

Returns

edited_message_handler(*commands=None, regexp=None, func=None, content_types=None, chat_types=None, **kwargs*)

Handles new version of a message that is known to the bot and was edited. As a parameter to the decorator function, it passes `telebot.types.Message` object.

Parameters

- **commands** (list of str) – Optional list of strings (commands to handle).
- **regexp** (str) – Optional regular expression.
- **func** (function) – Function executed as a filter
- **content_types** (list of str) – Supported message content types. Must be a list. Defaults to ['text'].
- **chat_types** (list of str) – list of chat types
- **kwargs** – Optional keyword arguments(custom filters)

Returns

None

enable_save_next_step_handlers(*delay: int | None = 120, filename: str | None = './handler-saves/step.save'*)

Enable saving next step handlers (by default saving disabled)

This function explicitly assigns FileHandlerBackend (instead of Saver) just to keep backward compatibility whose purpose was to enable file saving capability for handlers. And the same implementation is now available with FileHandlerBackend

Parameters

- **delay** (int, optional) – Delay between changes in handlers and saving, defaults to 120
- **filename** (str, optional) – Filename of save file, defaults to “./handler-saves/step.save”

Returns

None

enable_save_reply_handlers(*delay=120, filename='./handler-saves/reply.save'*)

Enable saving reply handlers (by default saving disable)

This function explicitly assigns FileHandlerBackend (instead of Saver) just to keep backward compatibility whose purpose was to enable file saving capability for handlers. And the same implementation is now available with FileHandlerBackend

Parameters

- **delay** (int, optional) – Delay between changes in handlers and saving, defaults to 120
- **filename** (str, optional) – Filename of save file, defaults to “./handler-saves/reply.save”

enable_saving_states(*filename: str | None = './state-save/states.pkl'*)

Enable saving states (by default saving disabled)

Note: It is recommended to pass a `StatePickleStorage` instance as `state_storage` to `TeleBot` class.

Parameters

filename (str, optional) – Filename of saving file, defaults to “./state-save/states.pkl”

export_chat_invite_link(*chat_id: int | str*) → str

Use this method to export an invite link to a supergroup or a channel. The bot must be an administrator in the chat for this to work and must have the appropriate admin rights.

Telegram documentation: <https://core.telegram.org/bots/api#exportchatinvitelink>

Parameters

chat_id (int or str) – Id: Unique identifier for the target chat or username of the target channel (in the format @channelusername)

Returns

exported invite link as String on success.

Return type

str

forward_message(*chat_id: int | str, from_chat_id: int | str, message_id: int, disable_notification: bool | None = None, protect_content: bool | None = None, timeout: int | None = None, message_thread_id: int | None = None*) → *Message*

Use this method to forward messages of any kind.

Telegram documentation: <https://core.telegram.org/bots/api#forwardmessage>

Parameters

- **disable_notification** (bool) – Sends the message silently. Users will receive a notification with no sound
- **chat_id** (int or str) – Unique identifier for the target chat or username of the target channel (in the format @channelusername)
- **from_chat_id** (int or str) – Unique identifier for the chat where the original message was sent (or channel username in the format @channelusername)
- **message_id** (int) – Message identifier in the chat specified in from_chat_id
- **protect_content** (bool) – Protects the contents of the forwarded message from forwarding and saving
- **timeout** (int) – Timeout in seconds for the request.
- **message_thread_id** (int) – Identifier of a message thread, in which the message will be sent

Returns

On success, the sent Message is returned.

Return type

telebot.types.Message

forward_messages(*chat_id: str | int, from_chat_id: str | int, message_ids: List[int], disable_notification: bool | None = None, message_thread_id: int | None = None, protect_content: bool | None = None*) → List[*MessageID*]

Use this method to forward multiple messages of any kind. If some of the specified messages can't be found or forwarded, they are skipped. Service messages and messages with protected content can't be forwarded. Album grouping is kept for forwarded messages. On success, an array of MessageId of the sent messages is returned.

Telegram documentation: <https://core.telegram.org/bots/api#forwardmessages>

Parameters

- **chat_id** (int or str) – Unique identifier for the target chat or username of the target channel (in the format @channelusername)
- **from_chat_id** (int or str) – Unique identifier for the chat where the original message was sent (or channel username in the format @channelusername)
- **message_ids** (list) – Message identifiers in the chat specified in from_chat_id
- **disable_notification** (bool) – Sends the message silently. Users will receive a notification with no sound
- **message_thread_id** (int) – Identifier of a message thread, in which the messages will be sent
- **protect_content** (bool) – Protects the contents of the forwarded message from forwarding and saving

Returns

On success, the sent Message is returned.

Return type

telebot.types.MessageID

get_business_connection(*business_connection_id: str*) → *BusinessConnection*

Use this method to get information about the connection of the bot with a business account. Returns a BusinessConnection object on success.

Telegram documentation: <https://core.telegram.org/bots/api#getbusinessconnection>

Parameters

business_connection_id (str) – Unique identifier of the business connection

Returns

Returns a BusinessConnection object on success.

Return type

telebot.types.BusinessConnection

get_chat(*chat_id: int | str*) → *Chat*

Use this method to get up to date information about the chat (current name of the user for one-on-one conversations, current username of a user, group or channel, etc.). Returns a Chat object on success.

Telegram documentation: <https://core.telegram.org/bots/api#getchat>

Parameters

chat_id (int or str) – Unique identifier for the target chat or username of the target supergroup or channel (in the format @channelusername)

Returns

Chat information

Return type

telebot.types.Chat

get_chat_administrators(*chat_id: int | str*) → List[*ChatMember*]

Use this method to get a list of administrators in a chat. On success, returns an Array of ChatMember objects that contains information about all chat administrators except other bots.

Telegram documentation: <https://core.telegram.org/bots/api#getchatadministrators>

Parameters

chat_id – Unique identifier for the target chat or username of the target supergroup or channel (in the format @channelusername)

Returns

List made of ChatMember objects.

Return type

list of *telebot.types.ChatMember*

get_chat_member(*chat_id: int | str, user_id: int*) → *ChatMember*

Use this method to get information about a member of a chat. Returns a ChatMember object on success.

Telegram documentation: <https://core.telegram.org/bots/api#getchatmember>

Parameters

- **chat_id** (int or str) – Unique identifier for the target chat or username of the target supergroup (in the format @supergroupusername)
- **user_id** (int) – Unique identifier of the target user

Returns

Returns ChatMember object on success.

Return type

telebot.types.ChatMember

get_chat_member_count(*chat_id: int | str*) → int

Use this method to get the number of members in a chat.

Telegram documentation: <https://core.telegram.org/bots/api#getchatmembercount>

Parameters

chat_id (int or str) – Unique identifier for the target chat or username of the target supergroup or channel (in the format @channelusername)

Returns

Number of members in the chat.

Return type

int

get_chat_members_count(***kwargs*)

get_chat_menu_button(*chat_id: int | str = None*) → *MenuButton*

Use this method to get the current value of the bot's menu button in a private chat, or the default menu button. Returns MenuButton on success.

Telegram Documentation: <https://core.telegram.org/bots/api#getchatmenubutton>

Parameters

chat_id (int or str) – Unique identifier for the target private chat. If not specified, default bot's menu button will be returned.

Returns

types.MenuButton

Return type

telebot.types.MenuButton

get_custom_emoji_stickers(*custom_emoji_ids: List[str]*) → List[*Sticker*]

Use this method to get information about custom emoji stickers by their identifiers. Returns an Array of Sticker objects.

Parameters

custom_emoji_ids (list of str) – List of custom emoji identifiers. At most 200 custom emoji identifiers can be specified.

Returns

Returns an Array of Sticker objects.

Return type

list of *telebot.types.Sticker*

get_file(*file_id: str | None*) → *File*

Use this method to get basic info about a file and prepare it for downloading. For the moment, bots can download files of up to 20MB in size. On success, a File object is returned. It is guaranteed that the link will be valid for at least 1 hour. When the link expires, a new one can be requested by calling `get_file` again.

Telegram documentation: <https://core.telegram.org/bots/api#getfile>

Parameters

file_id (str) – File identifier

Returns

telebot.types.File

get_file_url(*file_id: str | None*) → str

Get a valid URL for downloading a file.

Parameters

file_id (str) – File identifier to get download URL for.

Returns

URL for downloading the file.

Return type

str

get_forum_topic_icon_stickers() → List[*Sticker*]

Use this method to get custom emoji stickers, which can be used as a forum topic icon by any user. Requires no parameters. Returns an Array of Sticker objects.

Telegram documentation: <https://core.telegram.org/bots/api#getforumtopiciconstickers>

Returns

On success, a list of StickerSet objects is returned.

Return type

List[*telebot.types.StickerSet*]

get_game_high_scores(*user_id: int, chat_id: int | str | None = None, message_id: int | None = None, inline_message_id: str | None = None*) → List[*GameHighScore*]

Use this method to get data for high score tables. Will return the score of the specified user and several of their neighbors in a game. On success, returns an Array of GameHighScore objects.

This method will currently return scores for the target user, plus two of their closest neighbors on each side. Will also return the top three users if the user and their neighbors are not among them. Please note that this behavior is subject to change.

Telegram documentation: <https://core.telegram.org/bots/api#getgamehighscores>

Parameters

- **user_id** (int) – User identifier
- **chat_id** (int or str) – Required if inline_message_id is not specified. Unique identifier for the target chat or username of the target channel (in the format @channelusername)
- **message_id** (int) – Required if inline_message_id is not specified. Identifier of the sent message
- **inline_message_id** (str) – Required if chat_id and message_id are not specified. Identifier of the inline message

Returns

On success, returns an Array of GameHighScore objects.

Return type

List[*types.GameHighScore*]

get_me() → *User*

A simple method for testing your bot's authentication token. Requires no parameters. Returns basic information about the bot in form of a User object.

Telegram documentation: <https://core.telegram.org/bots/api#getme>

get_my_commands(*scope: BotCommandScope | None = None, language_code: str | None = None*) → List[*BotCommand*]

Use this method to get the current list of the bot's commands. Returns List of BotCommand on success.

Telegram documentation: <https://core.telegram.org/bots/api#getmycommands>

Parameters

- **scope** (*telebot.types.BotCommandScope*) – The scope of users for which the commands are relevant. Defaults to BotCommandScopeDefault.
- **language_code** (str) – A two-letter ISO 639-1 language code. If empty, commands will be applied to all users from the given scope, for whose language there are no dedicated commands

Returns

List of BotCommand on success.

Return type

list of *telebot.types.BotCommand*

get_my_default_administrator_rights(*for_channels: bool | None = None*) → *ChatAdministratorRights*

Use this method to get the current default administrator rights of the bot. Returns ChatAdministratorRights on success.

Telegram documentation: <https://core.telegram.org/bots/api#getmydefaultadministratorrights>

Parameters

for_channels (bool) – Pass True to get the default administrator rights of the bot in channels. Otherwise, the default administrator rights of the bot for groups and supergroups will be returned.

Returns

Returns ChatAdministratorRights on success.

Return type

telebot.types.ChatAdministratorRights

get_my_description(*language_code: str | None = None*)

Use this method to get the current bot description for the given user language. Returns BotDescription on success.

Telegram documentation: <https://core.telegram.org/bots/api#getmydescription>

Parameters

language_code (str) – A two-letter ISO 639-1 language code or an empty string

Returns

telebot.types.BotDescription

get_my_name(*language_code: str | None = None*)

Use this method to get the current bot name for the given user language. Returns BotName on success.

Telegram documentation: <https://core.telegram.org/bots/api#getmyname>

Parameters

language_code (str) – Optional. A two-letter ISO 639-1 language code or an empty string

Returns

telebot.types.BotName

get_my_short_description(*language_code: str | None = None*)

Use this method to get the current bot short description for the given user language. Returns BotShortDescription on success.

Telegram documentation: <https://core.telegram.org/bots/api#getmyshortdescription>

Parameters

language_code (str) – A two-letter ISO 639-1 language code or an empty string

Returns

telebot.types.BotShortDescription

get_state(*user_id: int, chat_id: int | None = None*) → int | str | *State* | None

Gets current state of a user. Not recommended to use this method. But it is ok for debugging.

Parameters

- **user_id** (int) – User’s identifier
- **chat_id** (int) – Chat’s identifier

Returns

state of a user

Return type

int or str or *telebot.types.State*

get_sticker_set(*name: str*) → *StickerSet*

Use this method to get a sticker set. On success, a StickerSet object is returned.

Telegram documentation: <https://core.telegram.org/bots/api#getstickerset>

Parameters

name (str) – Sticker set name

Returns

On success, a StickerSet object is returned.

Return type

telebot.types.StickerSet

get_updates(*offset: int | None = None, limit: int | None = None, timeout: int | None = 20, allowed_updates: List[str] | None = None, long_polling_timeout: int = 20*) → List[*Update*]

Use this method to receive incoming updates using long polling (wiki). An Array of Update objects is returned.

Telegram documentation: <https://core.telegram.org/bots/api#getupdates>

Parameters

- **offset** (int, optional) – Identifier of the first update to be returned. Must be greater by one than the highest among the identifiers of previously received updates. By default, updates starting with the earliest unconfirmed update are returned. An update is considered confirmed as soon as `getUpdates` is called with an offset higher than its `update_id`. The negative offset can be specified to retrieve updates starting from `-offset` update from the end of the updates queue. All previous updates will forgotten.
- **limit** (int, optional) – Limits the number of updates to be retrieved. Values between 1-100 are accepted. Defaults to 100.
- **timeout** (int, optional) – Request connection timeout
- **allowed_updates** (list, optional) – Array of string. List the types of updates you want your bot to receive.
- **long_polling_timeout** (int, optional) – Timeout in seconds for long polling.

Returns

An Array of Update objects is returned.

Return type

list of `telebot.types.Update`

get_user_chat_boosts(*chat_id: int | str, user_id: int*) → *UserChatBoosts*

Use this method to get the list of boosts added to a chat by a user. Requires administrator rights in the chat. Returns a UserChatBoosts object.

Telegram documentation: <https://core.telegram.org/bots/api#getuserchatboosts>

Parameters

- **chat_id** (int | str) – Unique identifier for the target chat or username of the target channel
- **user_id** (int) – Unique identifier of the target user

Returns

On success, a UserChatBoosts object is returned.

Return type

`telebot.types.UserChatBoosts`

get_user_profile_photos(*user_id: int, offset: int | None = None, limit: int | None = None*) → *UserProfilePhotos*

Use this method to get a list of profile pictures for a user. Returns a `telebot.types.UserProfilePhotos` object.

Telegram documentation: <https://core.telegram.org/bots/api#getuserprofilephotos>

Parameters

- **user_id** (int) – Unique identifier of the target user
- **offset** (int) – Sequential number of the first photo to be returned. By default, all photos are returned.

- **limit** (int) – Limits the number of photos to be retrieved. Values between 1-100 are accepted. Defaults to 100.

Returns

UserProfilePhotos

Return type

telebot.types.UserProfilePhotos

get_webhook_info(*timeout: int | None = None*) → *WebhookInfo*

Use this method to get current webhook status. Requires no parameters. On success, returns a WebhookInfo object. If the bot is using getUpdates, will return an object with the url field empty.

Telegram documentation: <https://core.telegram.org/bots/api#getwebhookinfo>

Parameters

timeout (int, optional) – Request connection timeout

Returns

On success, returns a WebhookInfo object.

Return type

telebot.types.WebhookInfo

hide_general_forum_topic(*chat_id: int | str*) → bool

Use this method to hide the ‘General’ topic in a forum supergroup chat. The bot must be an administrator in the chat for this to work and must have can_manage_topics administrator rights. Returns True on success.

Telegram documentation: <https://core.telegram.org/bots/api#hidegeneralforumtopic>

Parameters

chat_id (int or str) – Unique identifier for the target chat or username of the target channel (in the format @channelusername)

infinity_polling(*timeout: int | None = 20, skip_pending: bool | None = False, long_polling_timeout: int | None = 20, logger_level: int | None = 40, allowed_updates: List[str] | None = None, restart_on_change: bool | None = False, path_to_watch: str | None = None, *args, **kwargs*)

Wrap polling with infinite loop and exception handling to avoid bot stops polling.

Note: Install watchdog and psutil before using restart_on_change option.

Parameters

- **timeout** (int) – Request connection timeout.
- **long_polling_timeout** (int) – Timeout in seconds for long polling (see API docs)
- **skip_pending** (bool) – skip old updates
- **logger_level** (int.) – Custom (different from logger itself) logging level for infinity_polling logging. Use logger levels from logging as a value. None/NOTSET = no error logging
- **allowed_updates** (list of str) – A list of the update types you want your bot to receive. For example, specify [“message”, “edited_channel_post”, “callback_query”] to only receive updates of these types. See util.update_types for a complete list of available update types. Specify an empty list to receive all update types except chat_member (default). If not specified, the previous setting will be used. Please note that this parameter doesn’t affect

updates created before the call to the `get_updates`, so unwanted updates may be received for a short period of time.

- **restart_on_change** (bool) – Restart a file on file(s) change. Defaults to False
- **path_to_watch** (str) – Path to watch for changes. Defaults to current directory

Returns

inline_handler(*func*, ***kwargs*)

Handles new incoming inline query. As a parameter to the decorator function, it passes `telebot.types.InlineQuery` object.

Parameters

- **func** (function) – Function executed as a filter
- **kwargs** – Optional keyword arguments(custom filters)

Returns

None

kick_chat_member(***kwargs*)

leave_chat(*chat_id: int | str*) → bool

Use this method for your bot to leave a group, supergroup or channel. Returns True on success.

Telegram documentation: <https://core.telegram.org/bots/api#leavechat>

Parameters

chat_id (int or str) – Unique identifier for the target chat or username of the target supergroup or channel (in the format @channelusername)

Returns

bool

load_next_step_handlers(*filename='./.handler-saves/step.save'*, *del_file_after_loading=True*)

Load next step handlers from save file

This function is left to keep backward compatibility whose purpose was to load handlers from file with the help of FileHandlerBackend and is only recommended to use if `next_step_backend` was assigned as FileHandlerBackend before entering this function

Parameters

- **filename** (str, optional) – Filename of the file where handlers was saved, defaults to “./handler-saves/step.save”
- **del_file_after_loading** (bool, optional) – If True is passed, after the loading file will be deleted, defaults to True

load_reply_handlers(*filename='./.handler-saves/reply.save'*, *del_file_after_loading=True*)

Load reply handlers from save file

This function is left to keep backward compatibility whose purpose was to load handlers from file with the help of FileHandlerBackend and is only recommended to use if `reply_backend` was assigned as FileHandlerBackend before entering this function

Parameters

- **filename** (str, optional) – Filename of the file where handlers was saved, defaults to “./handler-saves/reply.save”

- **del_file_after_loading** (bool, optional) – If True is passed, after the loading file will be deleted, defaults to True, defaults to True

log_out() → bool

Use this method to log out from the cloud Bot API server before launching the bot locally. You MUST log out the bot before running it locally, otherwise there is no guarantee that the bot will receive updates. After a successful call, you can immediately log in on a local server, but will not be able to log in back to the cloud Bot API server for 10 minutes. Returns True on success.

Telegram documentation: <https://core.telegram.org/bots/api#logout>

Returns

True on success.

Return type

bool

message_handler(*commands: List[str] | None = None, regexp: str | None = None, func: Callable | None = None, content_types: List[str] | None = None, chat_types: List[str] | None = None, **kwargs*)

Handles New incoming message of any kind - text, photo, sticker, etc. As a parameter to the decorator function, it passes `telebot.types.Message` object. All message handlers are tested in the order they were added.

Example:

Listing 7: Usage of message_handler

```
bot = TeleBot('TOKEN')

# Handles all messages which text matches regexp.
@bot.message_handler(regexp='someregexp')
def command_help(message):
    bot.send_message(message.chat.id, 'Did someone call for help?')

# Handles messages in private chat
@bot.message_handler(chat_types=['private']) # You can add more chat types
def command_help(message):
    bot.send_message(message.chat.id, 'Private chat detected, sir!')

# Handle all sent documents of type 'text/plain'.
@bot.message_handler(func=lambda message: message.document.mime_type == 'text/
↳ plain',
    content_types=['document'])
def command_handle_document(message):
    bot.send_message(message.chat.id, 'Document received, sir!')

# Handle all other messages.
@bot.message_handler(func=lambda message: True, content_types=['audio', 'photo',
↳ 'voice', 'video', 'document',
    'text', 'location', 'contact', 'sticker'])
def default_command(message):
    bot.send_message(message.chat.id, "This is the default command handler.")
```

Parameters

- **commands** (list of str) – Optional list of strings (commands to handle).

- **regexp** (str) – Optional regular expression.
- **func** (lambda) – Optional lambda function. The lambda receives the message to test as the first parameter. It must return True if the command should handle the message.
- **content_types** (list of str) – Supported message content types. Must be a list. Defaults to ['text'].
- **chat_types** (list of str) – list of chat types
- **kwargs** – Optional keyword arguments(custom filters)

Returns

decorated function

message_reaction_count_handler(*func=None, **kwargs*)

Handles new incoming message reaction count. As a parameter to the decorator function, it passes `telebot.types.MessageReactionCountUpdated` object.

Parameters

- **func** (function) – Function executed as a filter
- **kwargs** – Optional keyword arguments(custom filters)

Returns

message_reaction_handler(*func=None, **kwargs*)

Handles new incoming message reaction. As a parameter to the decorator function, it passes `telebot.types.MessageReactionUpdated` object.

Parameters

- **func** (function) – Function executed as a filter
- **kwargs** – Optional keyword arguments(custom filters)

Returns

middleware_handler(*update_types: List[str] | None = None*)

Function-based middleware handler decorator.

This decorator can be used to decorate functions that must be handled as middlewares before entering any other message handlers. But, be careful and check type of the update inside the handler if more than one `update_type` is given

Example:

Listing 8: Usage of `middleware_handler`

```
bot = TeleBot('TOKEN')

# Print post message text before entering to any post_channel handlers
@bot.middleware_handler(update_types=['channel_post', 'edited_channel_post'])
def print_channel_post_text(bot_instance, channel_post):
    print(channel_post.text)

# Print update id before entering to any handlers
@bot.middleware_handler()
def print_channel_post_text(bot_instance, update):
    print(update.update_id)
```

Parameters

update_types (list of str) – Optional list of update types that can be passed into the middleware handler.

Returns

function

my_chat_member_handler (*func=None, **kwargs*)

Handles update in a status of a bot. For private chats, this update is received only when the bot is blocked or unblocked by the user. As a parameter to the decorator function, it passes `telebot.types.ChatMemberUpdated` object.

Parameters

- **func** (function) – Function executed as a filter
- **kwargs** – Optional keyword arguments(custom filters)

Returns

None

pin_chat_message (*chat_id: int | str, message_id: int, disable_notification: bool | None = False*) → bool

Use this method to pin a message in a supergroup. The bot must be an administrator in the chat for this to work and must have the appropriate admin rights. Returns True on success.

Telegram documentation: <https://core.telegram.org/bots/api#pinchatmessage>

Parameters

- **chat_id** (int or str) – Unique identifier for the target chat or username of the target channel (in the format @channelusername)
- **message_id** (int) – Identifier of a message to pin
- **disable_notification** (bool) – Pass True, if it is not necessary to send a notification to all group members about the new pinned message

Returns

True on success.

Return type

bool

poll_answer_handler (*func=None, **kwargs*)

Handles change of user's answer in a non-anonymous poll(when user changes the vote). Bots receive new votes only in polls that were sent by the bot itself. As a parameter to the decorator function, it passes `telebot.types.PollAnswer` object.

Parameters

- **func** (function) – Function executed as a filter
- **kwargs** – Optional keyword arguments(custom filters)

Returns

None

poll_handler (*func, **kwargs*)

Handles new state of a poll. Bots receive only updates about stopped polls and polls, which are sent by the bot As a parameter to the decorator function, it passes `telebot.types.Poll` object.

Parameters

- **func** (function) – Function executed as a filter
- **kwargs** – Optional keyword arguments(custom filters)

Returns

None

polling(*non_stop*: bool | None = False, *skip_pending*: bool | None = False, *interval*: int | None = 0, *timeout*: int | None = 20, *long_polling_timeout*: int | None = 20, *logger_level*: int | None = 40, *allowed_updates*: List[str] | None = None, *none_stop*: bool | None = None, *restart_on_change*: bool | None = False, *path_to_watch*: str | None = None)

This function creates a new Thread that calls an internal `__retrieve_updates` function. This allows the bot to retrieve Updates automatically and notify listeners and message handlers accordingly.

Warning: Do not call this function more than once!

Always gets updates.

Deprecated since version 4.1.1: Use `infinity_polling()` instead.

Note: Install watchdog and psutil before using `restart_on_change` option.

Parameters

- **interval** (int) – Delay between two update retrivals
- **non_stop** (bool) – Do not stop polling when an ApiException occurs.
- **timeout** (int) – Request connection timeout
- **skip_pending** (bool) – skip old updates
- **long_polling_timeout** (int) – Timeout in seconds for long polling (see API docs)
- **logger_level** (int) – Custom (different from logger itself) logging level for infinity_polling logging. Use logger levels from logging as a value. None/NOTSET = no error logging
- **allowed_updates** (list of str) – A list of the update types you want your bot to receive. For example, specify ["message", "edited_channel_post", "callback_query"] to only receive updates of these types. See `util.update_types` for a complete list of available update types. Specify an empty list to receive all update types except `chat_member` (default). If not specified, the previous setting will be used.

Please note that this parameter doesn't affect updates created before the call to the `get_updates`, so unwanted updates may be received for a short period of time.

- **none_stop** (bool) – deprecated.
- **restart_on_change** (bool) – Restart a file on file(s) change. Defaults to False
- **path_to_watch** (str) – Path to watch for changes. Defaults to None

Returns

pre_checkout_query_handler(*func*, ***kwargs*)

New incoming pre-checkout query. Contains full information about checkout. As a parameter to the decorator function, it passes `telebot.types.PreCheckoutQuery` object.

Parameters

- **func** (function) – Function executed as a filter

- **kwargs** – Optional keyword arguments(custom filters)

Returns

None

process_new_updates(*updates: List[Update]*)

Processes new updates. Just pass list of subclasses of Update to this method.

Parameters

updates (list of *telebot.types.Update*) – List of *telebot.types.Update* objects.

Return None

promote_chat_member(*chat_id: int | str, user_id: int, can_change_info: bool | None = None, can_post_messages: bool | None = None, can_edit_messages: bool | None = None, can_delete_messages: bool | None = None, can_invite_users: bool | None = None, can_restrict_members: bool | None = None, can_pin_messages: bool | None = None, can_promote_members: bool | None = None, is_anonymous: bool | None = None, can_manage_chat: bool | None = None, can_manage_video_chats: bool | None = None, can_manage_voice_chats: bool | None = None, can_manage_topics: bool | None = None, can_post_stories: bool | None = None, can_edit_stories: bool | None = None, can_delete_stories: bool | None = None*) → bool

Use this method to promote or demote a user in a supergroup or a channel. The bot must be an administrator in the chat for this to work and must have the appropriate admin rights. Pass False for all boolean parameters to demote a user.

Telegram documentation: <https://core.telegram.org/bots/api#promotechatmember>

Parameters

- **chat_id** (int or str) – Unique identifier for the target chat or username of the target channel (in the format @channelusername)
- **user_id** (int) – Unique identifier of the target user
- **can_change_info** (bool) – Pass True, if the administrator can change chat title, photo and other settings
- **can_post_messages** (bool) – Pass True, if the administrator can create channel posts, channels only
- **can_edit_messages** (bool) – Pass True, if the administrator can edit messages of other users, channels only
- **can_delete_messages** (bool) – Pass True, if the administrator can delete messages of other users
- **can_invite_users** (bool) – Pass True, if the administrator can invite new users to the chat
- **can_restrict_members** (bool) – Pass True, if the administrator can restrict, ban or unban chat members
- **can_pin_messages** (bool) – Pass True, if the administrator can pin messages, supergroups only
- **can_promote_members** (bool) – Pass True, if the administrator can add new administrators with a subset of his own privileges or demote administrators that he has promoted, directly or indirectly (promoted by administrators that were appointed by him)
- **is_anonymous** (bool) – Pass True, if the administrator’s presence in the chat is hidden

- **can_manage_chat** (bool) – Pass True, if the administrator can access the chat event log, chat statistics, message statistics in channels, see channel members, see anonymous administrators in supergroups and ignore slow mode. Implied by any other administrator privilege
- **can_manage_video_chats** (bool) – Pass True, if the administrator can manage voice chats For now, bots can use this privilege only for passing to other administrators.
- **can_manage_voice_chats** (bool) – Deprecated, use can_manage_video_chats.
- **can_manage_topics** (bool) – Pass True if the user is allowed to create, rename, close, and reopen forum topics, supergroups only
- **can_post_stories** (bool) – Pass True if the administrator can create the channel’s stories
- **can_edit_stories** (bool) – Pass True if the administrator can edit the channel’s stories
- **can_delete_stories** (bool) – Pass True if the administrator can delete the channel’s stories

Returns

True on success.

Return type

bool

register_business_connection_handler(*callback: Callable, func: Callable | None = None, pass_bot: bool | None = False, **kwargs*)

Registers business connection handler.

Parameters

- **callback** (function) – function to be called
- **func** (function) – Function executed as a filter
- **pass_bot** (bool) – True if you need to pass TeleBot instance to handler(useful for separating handlers into different files)
- **kwargs** – Optional keyword arguments(custom filters)

Returns

None

register_business_message_handler(*callback: Callable, commands: List[str] | None = None, regexp: str | None = None, func: Callable | None = None, content_types: List[str] | None = None, **kwargs*)

Registers business connection handler.

Parameters

- **callback** (function) – function to be called
- **commands** (list of str) – list of commands
- **regexp** (str) – Regular expression
- **func** (function) – Function executed as a filter
- **content_types** (list of str) – Supported message content types. Must be a list. Defaults to ['text'].
- **kwargs** – Optional keyword arguments(custom filters)

Returns

None

register_callback_query_handler(*callback: Callable, func: Callable, pass_bot: bool | None = False, **kwargs*)

Registers callback query handler.

Parameters

- **callback** (function) – function to be called
- **func** (function) – Function executed as a filter
- **pass_bot** (bool) – True if you need to pass TeleBot instance to handler(useful for separating handlers into different files)
- **kwargs** – Optional keyword arguments(custom filters)

Returns

None

register_channel_post_handler(*callback: Callable, content_types: List[str] | None = None, commands: List[str] | None = None, regex: str | None = None, func: Callable | None = None, pass_bot: bool | None = False, **kwargs*)

Registers channel post message handler.

Parameters

- **callback** (function) – function to be called
- **content_types** (list of str) – Supported message content types. Must be a list. Defaults to ['text'].
- **commands** (list of str) – list of commands
- **regex** (str) – Regular expression
- **func** (function) – Function executed as a filter
- **pass_bot** (bool) – True if you need to pass TeleBot instance to handler(useful for separating handlers into different files)
- **kwargs** – Optional keyword arguments(custom filters)

Returns

None

register_chat_boost_handler(*callback: Callable, func: Callable | None = None, pass_bot: bool | None = False, **kwargs*)

Registers chat boost handler.

Parameters

- **callback** (function) – function to be called
- **func** (function) – Function executed as a filter
- **pass_bot** – True if you need to pass TeleBot instance to handler(useful for separating handlers into different files)
- **kwargs** – Optional keyword arguments(custom filters)

Returns

None

register_chat_join_request_handler(*callback: Callable, func: Callable | None = None, pass_bot: bool | None = False, **kwargs*)

Registers chat join request handler.

Parameters

- **callback** (function) – function to be called
- **func** (function) – Function executed as a filter
- **pass_bot** (bool) – True if you need to pass TeleBot instance to handler(useful for separating handlers into different files)
- **kwargs** – Optional keyword arguments(custom filters)

Returns

None

register_chat_member_handler(*callback: Callable, func: Callable | None = None, pass_bot: bool | None = False, **kwargs*)

Registers chat member handler.

Parameters

- **callback** (function) – function to be called
- **func** (function) – Function executed as a filter
- **pass_bot** (bool) – True if you need to pass TeleBot instance to handler(useful for separating handlers into different files)
- **kwargs** – Optional keyword arguments(custom filters)

:return:None

register_chosen_inline_handler(*callback: Callable, func: Callable, pass_bot: bool | None = False, **kwargs*)

Registers chosen inline handler.

Parameters

- **callback** (function) – function to be called
- **func** (function) – Function executed as a filter
- **pass_bot** (bool) – True if you need to pass TeleBot instance to handler(useful for separating handlers into different files)
- **kwargs** – Optional keyword arguments(custom filters)

Returns

None

register_deleted_business_messages_handler(*callback: Callable, func: Callable | None = None, pass_bot: bool | None = False, **kwargs*)

Registers deleted business messages handler.

Parameters

- **callback** (function) – function to be called
- **func** (function) – Function executed as a filter
- **pass_bot** (bool) – True if you need to pass TeleBot instance to handler(useful for separating handlers into different files)

- **kwargs** – Optional keyword arguments(custom filters)

Returns

None

register_edited_business_message_handler(*callback: Callable, content_types: List[str] | None = None, commands: List[str] | None = None, regexp: str | None = None, func: Callable | None = None, pass_bot: bool | None = False, **kwargs*)

Registers edited message handler for business accounts.

Parameters

- **callback** (function) – function to be called
- **content_types** (list of str) – Supported message content types. Must be a list. Defaults to ['text'].
- **commands** (list of str) – list of commands
- **regexp** (str) – Regular expression
- **func** (function) – Function executed as a filter
- **pass_bot** (bool) – True if you need to pass TeleBot instance to handler(useful for separating handlers into different files)
- **kwargs** – Optional keyword arguments(custom filters)

Returns

None

register_edited_channel_post_handler(*callback: Callable, content_types: List[str] | None = None, commands: List[str] | None = None, regexp: str | None = None, func: Callable | None = None, pass_bot: bool | None = False, **kwargs*)

Registers edited channel post message handler.

Parameters

- **callback** (function) – function to be called
- **content_types** (list of str) – Supported message content types. Must be a list. Defaults to ['text'].
- **commands** (list of str) – list of commands
- **regexp** (str) – Regular expression
- **func** (function) – Function executed as a filter
- **pass_bot** (bool) – True if you need to pass TeleBot instance to handler(useful for separating handlers into different files)
- **kwargs** – Optional keyword arguments(custom filters)

Returns

decorated function

register_edited_message_handler(*callback: Callable, content_types: List[str] | None = None, commands: List[str] | None = None, regexp: str | None = None, func: Callable | None = None, chat_types: List[str] | None = None, pass_bot: bool | None = False, **kwargs*)

Registers edited message handler.

Parameters

- **callback** (function) – function to be called
- **content_types** (list of str) – Supported message content types. Must be a list. Defaults to ['text'].
- **commands** (list of str) – list of commands
- **regex** (str) – Regular expression
- **func** (function) – Function executed as a filter
- **chat_types** (bool) – True for private chat
- **pass_bot** (bool) – True if you need to pass TeleBot instance to handler(useful for separating handlers into different files)
- **kwargs** – Optional keyword arguments(custom filters)

Returns

None

register_for_reply(*message*: Message, *callback*: Callable, *args, **kwargs) → None

Registers a callback function to be notified when a reply to *message* arrives.

Warning: In case *callback* as lambda function, saving reply handlers will not work.

Parameters

- **message** (telebot.types.Message) – The message for which we are awaiting a reply.
- **callback** (Callable[[telebot.types.Message], None]) – The callback function to be called when a reply arrives. Must accept one *message* parameter, which will contain the replied message.
- **args** – Optional arguments for the callback function.
- **kwargs** – Optional keyword arguments for the callback function.

Returns

None

register_for_reply_by_message_id(*message_id*: int, *callback*: Callable, *args, **kwargs) → None

Registers a callback function to be notified when a reply to *message* arrives.

Warning: In case *callback* as lambda function, saving reply handlers will not work.

Parameters

- **message_id** (int) – The id of the message for which we are awaiting a reply.
- **callback** (Callable[[telebot.types.Message], None]) – The callback function to be called when a reply arrives. Must accept one *message* parameter, which will contain the replied message.
- **args** – Optional arguments for the callback function.
- **kwargs** – Optional keyword arguments for the callback function.

Returns

None

register_inline_handler(*callback*: Callable, *func*: Callable, *pass_bot*: bool | None = False, **kwargs)

Registers inline handler.

Parameters

- **callback** (function) – function to be called
- **func** (function) – Function executed as a filter
- **pass_bot** (bool) – True if you need to pass TeleBot instance to handler(useful for separating handlers into different files)
- **kwargs** – Optional keyword arguments(custom filters)

Returns

decorated function

register_message_handler(*callback: Callable, content_types: List[str] | None = None, commands: List[str] | None = None, regexp: str | None = None, func: Callable | None = None, chat_types: List[str] | None = None, pass_bot: bool | None = False, **kwargs*)

Registers message handler.

Parameters

- **callback** (function) – function to be called
- **content_types** (list of str) – Supported message content types. Must be a list. Defaults to ['text'].
- **commands** (list of str) – list of commands
- **regexp** (str) – Regular expression
- **func** (function) – Function executed as a filter
- **chat_types** (list of str) – List of chat types
- **pass_bot** (bool) – True if you need to pass TeleBot instance to handler(useful for separating handlers into different files)
- **kwargs** – Optional keyword arguments(custom filters)

Returns

None

register_message_reaction_count_handler(*callback: Callable, func: Callable = None, pass_bot: bool | None = False, **kwargs*)

Registers message reaction count handler.

Parameters

- **callback** (function) – function to be called
- **func** (function) – Function executed as a filter
- **pass_bot** (bool) – True if you need to pass TeleBot instance to handler(useful for separating handlers into different files)
- **kwargs** – Optional keyword arguments(custom filters)

Returns

None

register_message_reaction_handler(*callback: Callable, func: Callable = None, pass_bot: bool | None = False, **kwargs*)

Registers message reaction handler.

Parameters

- **callback** (function) – function to be called
- **func** (function) – Function executed as a filter
- **pass_bot** (bool) – True if you need to pass TeleBot instance to handler(useful for separating handlers into different files)
- **kwargs** – Optional keyword arguments(custom filters)

Returns

None

register_middleware_handler(*callback*, *update_types=None*)

Adds function-based middleware handler.

This function will register your decorator function. Function-based middlewares are executed before handlers. But, be careful and check type of the update inside the handler if more than one *update_type* is given

Example:

```
bot = TeleBot('TOKEN')
```

```
bot.register_middleware_handler(print_channel_post_text, update_types=['channel_post',
'edited_channel_post'])
```

Parameters

- **callback** (function) – Function that will be used as a middleware handler.
- **update_types** (list of str) – Optional list of update types that can be passed into the middleware handler.

Returns

None

register_my_chat_member_handler(*callback: Callable*, *func: Callable | None = None*, *pass_bot: bool | None = False*, ***kwargs*)

Registers my chat member handler.

Parameters

- **callback** (function) – function to be called
- **func** (function) – Function executed as a filter
- **pass_bot** (bool) – True if you need to pass TeleBot instance to handler(useful for separating handlers into different files)
- **kwargs** – Optional keyword arguments(custom filters)

Returns

None

register_next_step_handler(*message: Message*, *callback: Callable*, **args*, ***kwargs*) → NoneRegisters a callback function to be notified when new message arrives after *message*.Warning: In case *callback* as lambda function, saving next step handlers will not work.**Parameters**

- **message** (*telebot.types.Message*) – The message for which we want to handle new message in the same chat.
- **callback** (Callable[[*telebot.types.Message*], None]) – The callback function which next new message arrives.

- **args** – Args to pass in callback func
- **kwargs** – Args to pass in callback func

Returns

None

register_next_step_handler_by_chat_id(*chat_id: int, callback: Callable, *args, **kwargs*) → None

Registers a callback function to be notified when new message arrives in the given chat.

Warning: In case *callback* as lambda function, saving next step handlers will not work.

Parameters

- **chat_id** (int) – The chat (chat ID) for which we want to handle new message.
- **callback** (Callable[[`telebot.types.Message`], None]) – The callback function which next new message arrives.
- **args** – Args to pass in callback func
- **kwargs** – Args to pass in callback func

Returns

None

register_poll_answer_handler(*callback: Callable, func: Callable, pass_bot: bool | None = False, **kwargs*)

Registers poll answer handler.

Parameters

- **callback** (function) – function to be called
- **func** (function) – Function executed as a filter
- **pass_bot** (bool) – True if you need to pass TeleBot instance to handler(useful for separating handlers into different files)
- **kwargs** – Optional keyword arguments(custom filters)

Returns

None

register_poll_handler(*callback: Callable, func: Callable, pass_bot: bool | None = False, **kwargs*)

Registers poll handler.

Parameters

- **callback** (function) – function to be called
- **func** (function) – Function executed as a filter
- **pass_bot** (bool) – True if you need to pass TeleBot instance to handler(useful for separating handlers into different files)
- **kwargs** – Optional keyword arguments(custom filters)

Returns

None

register_pre_checkout_query_handler(*callback: Callable, func: Callable, pass_bot: bool | None = False, **kwargs*)

Registers pre-checkout request handler.

Parameters

- **callback** (function) – function to be called
- **func** – Function executed as a filter
- **pass_bot** (bool) – True if you need to pass TeleBot instance to handler(useful for separating handlers into different files)
- **kwargs** – Optional keyword arguments(custom filters)

Returns

decorated function

register_removed_chat_boost_handler(*callback: Callable, func: Callable | None = None, pass_bot: bool | None = False, **kwargs*)

Registers removed chat boost handler.

Parameters

- **callback** (function) – function to be called
- **func** (function) – Function executed as a filter
- **pass_bot** – True if you need to pass TeleBot instance to handler(useful for separating handlers into different files)
- **kwargs** – Optional keyword arguments(custom filters)

Returns

None

register_shipping_query_handler(*callback: Callable, func: Callable, pass_bot: bool | None = False, **kwargs*)

Registers shipping query handler.

Parameters

- **callback** (function) – function to be called
- **func** (function) – Function executed as a filter
- **pass_bot** (bool) – True if you need to pass TeleBot instance to handler(useful for separating handlers into different files)
- **kwargs** – Optional keyword arguments(custom filters)

Returns

None

remove_webhook() → bool

Deletes webhooks using set_webhook() function.

Returns

True on success.

Return type

bool

removed_chat_boost_handler(*func=None, **kwargs*)

Handles new incoming chat boost state. it passes `telebot.types.ChatBoostRemoved` object.**Parameters**

- **func** (function) – Function executed as a filter
- **kwargs** – Optional keyword arguments(custom filters)

Returns

None

reopen_forum_topic(*chat_id: str | int, message_thread_id: int*) → bool

Use this method to reopen a closed topic in a forum supergroup chat. The bot must be an administrator in the chat for this to work and must have the `can_manage_topics` administrator rights, unless it is the creator of the topic. Returns True on success.

Telegram documentation: <https://core.telegram.org/bots/api#reopenforumtopic>

Parameters

- **chat_id** (int or str) – Unique identifier for the target chat or username of the target channel (in the format @channelusername)
- **message_thread_id** (int) – Identifier of the topic to reopen

Returns

On success, True is returned.

Return type

bool

reopen_general_forum_topic(*chat_id: int | str*) → bool

Use this method to reopen the ‘General’ topic in a forum supergroup chat. The bot must be an administrator in the chat for this to work and must have `can_manage_topics` administrator rights. Returns True on success.

Telegram documentation: <https://core.telegram.org/bots/api#reopengeneralforumtopic>

Parameters

chat_id (int or str) – Unique identifier for the target chat or username of the target channel (in the format @channelusername)

replace_sticker_in_set(*user_id: int, name: str, old_sticker: str, sticker: InputSticker*) → bool

Use this method to replace an existing sticker in a sticker set with a new one. The method is equivalent to calling `deleteStickerFromSet`, then `addStickerToSet`, then `setStickerPositionInSet`. Returns True on success.

Telegram documentation: <https://core.telegram.org/bots/api#replaceStickerInSet>

Parameters

- **user_id** (int) – User identifier of the sticker set owner
- **name** (str) – Sticker set name
- **old_sticker** (str) – File identifier of the replaced sticker
- **sticker** (*telebot.types.InputSticker*) – A JSON-serialized object with information about the added sticker. If exactly the same sticker had already been added to the set, then the set remains unchanged.

Returns

Returns True on success.

Return type

bool

reply_to(*message: Message, text: str, **kwargs*) → *Message*

Convenience function for `send_message(message.chat.id, text, reply_parameters=(message.message_id...), **kwargs)`

Parameters

- **message** (*types.Message*) – Instance of *telebot.types.Message*
- **text** (str) – Text of the message.
- **kwargs** – Additional keyword arguments which are passed to *telebot.TeleBot.send_message()*

Returns

On success, the sent Message is returned.

Return type

telebot.types.Message

reset_data(*user_id: int, chat_id: int | None = None*)

Reset data for a user in chat.

Parameters

- **user_id** (int) – User’s identifier
- **chat_id** (int) – Chat’s identifier

Returns

None

restrict_chat_member(*chat_id: int | str, user_id: int, until_date: int | datetime | None = None, can_send_messages: bool | None = None, can_send_media_messages: bool | None = None, can_send_polls: bool | None = None, can_send_other_messages: bool | None = None, can_add_web_page_previews: bool | None = None, can_change_info: bool | None = None, can_invite_users: bool | None = None, can_pin_messages: bool | None = None, permissions: ChatPermissions | None = None, use_independent_chat_permissions: bool | None = None*) → bool

Use this method to restrict a user in a supergroup. The bot must be an administrator in the supergroup for this to work and must have the appropriate admin rights. Pass True for all boolean parameters to lift restrictions from a user.

Telegram documentation: <https://core.telegram.org/bots/api#restrictchatmember>

Warning: Individual parameters are deprecated and will be removed, use ‘permissions’ instead.

Parameters

- **chat_id** (int or str) – Unique identifier for the target group or username of the target supergroup or channel (in the format @channelusername)
- **user_id** (int) – Unique identifier of the target user
- **until_date** (int or datetime, optional) – Date when restrictions will be lifted for the user, unix time. If user is restricted for more than 366 days or less than 30 seconds from the current time, they are considered to be restricted forever
- **can_send_messages** (bool) – deprecated
- **can_send_media_messages** (bool) – deprecated
- **can_send_polls** (bool) – deprecated
- **can_send_other_messages** (bool) – deprecated
- **can_add_web_page_previews** (bool) – deprecated
- **can_change_info** (bool) – deprecated

- **can_invite_users** (bool) – deprecated
- **can_pin_messages** (bool) – deprecated
- **use_independent_chat_permissions** (bool, optional) – Pass True if chat permissions are set independently. Otherwise, the `can_send_other_messages` and `can_add_web_page_previews` permissions will imply the `can_send_messages`, `can_send_audios`, `can_send_documents`, `can_send_photos`, `can_send_videos`, `can_send_video_notes`, and `can_send_voice_notes` permissions; the `can_send_polls` permission will imply the `can_send_messages` permission.
- **permissions** (*telebot.types.ChatPermissions*) – ChatPermissions object defining permissions.

Returns

True on success

Return type

bool

retrieve_data(*user_id: int, chat_id: int | None = None*) → Any | None

Returns context manager with data for a user in chat.

Parameters

- **user_id** (*int*) – User identifier
- **chat_id** (*int, optional*) – Chat’s unique identifier, defaults to `user_id`

Returns

Context manager with data for a user in chat

Return type

Optional[Any]

revoke_chat_invite_link(*chat_id: int | str, invite_link: str*) → *ChatInviteLink*

Use this method to revoke an invite link created by the bot. Note: If the primary link is revoked, a new link is automatically generated. The bot must be an administrator in the chat for this to work and must have the appropriate admin rights.

Telegram documentation: <https://core.telegram.org/bots/api#revokechatinvitelink>

Parameters

- **chat_id** (*int or str*) – Id: Unique identifier for the target chat or username of the target channel (in the format `@channelusername`)
- **invite_link** (*str*) – The invite link to revoke

Returns

Returns the new invite link as *ChatInviteLink* object.

Return type

telebot.types.ChatInviteLink

run_webhooks(*listen: str | None = '127.0.0.1', port: int | None = 443, url_path: str | None = None, certificate: str | None = None, certificate_key: str | None = None, webhook_url: str | None = None, max_connections: int | None = None, allowed_updates: List | None = None, ip_address: str | None = None, drop_pending_updates: bool | None = None, timeout: int | None = None, secret_token: str | None = None, secret_token_length: int | None = 20*)

This class sets webhooks and listens to a given url and port.

Requires fastapi, uvicorn, and latest version of starlette.

Parameters

- **listen** (str, optional) – IP address to listen to, defaults to “127.0.0.1”
- **port** (int, optional) – A port which will be used to listen to webhooks., defaults to 443
- **url_path** (str, optional) – Path to the webhook. Defaults to /token, defaults to None
- **certificate** (str, optional) – Path to the certificate file, defaults to None
- **certificate_key** (str, optional) – Path to the certificate key file, defaults to None
- **webhook_url** (str, optional) – Webhook URL to be set, defaults to None
- **max_connections** (int, optional) – Maximum allowed number of simultaneous HTTPS connections to the webhook for update delivery, 1-100. Defaults to 40. Use lower values to limit the load on your bot’s server, and higher values to increase your bot’s throughput., defaults to None
- **allowed_updates** (list, optional) – A JSON-serialized list of the update types you want your bot to receive. For example, specify [“message”, “edited_channel_post”, “callback_query”] to only receive updates of these types. See Update for a complete list of available update types. Specify an empty list to receive all updates regardless of type (default). If not specified, the previous setting will be used. defaults to None
- **ip_address** (str, optional) – The fixed IP address which will be used to send webhook requests instead of the IP address resolved through DNS, defaults to None
- **drop_pending_updates** (bool, optional) – Pass True to drop all pending updates, defaults to None
- **timeout** (int, optional) – Request connection timeout, defaults to None
- **secret_token** (str, optional) – Secret token to be used to verify the webhook request, defaults to None
- **secret_token_length** (int, optional) – Length of a secret token, defaults to 20

Raises

ImportError – If necessary libraries were not installed.

send_animation(*chat_id: int | str, animation: Any | str, duration: int | None = None, width: int | None = None, height: int | None = None, thumbnail: str | Any | None = None, caption: str | None = None, parse_mode: str | None = None, caption_entities: List[MessageEntity] | None = None, disable_notification: bool | None = None, protect_content: bool | None = None, reply_to_message_id: int | None = None, allow_sending_without_reply: bool | None = None, reply_markup: InlineKeyboardMarkup | ReplyKeyboardMarkup | ReplyKeyboardRemove | ForceReply | None = None, timeout: int | None = None, message_thread_id: int | None = None, has_spoiler: bool | None = None, thumb: str | Any | None = None, reply_parameters: ReplyParameters | None = None, business_connection_id: str | None = None*) → *Message*

Use this method to send animation files (GIF or H.264/MPEG-4 AVC video without sound). On success, the sent Message is returned. Bots can currently send animation files of up to 50 MB in size, this limit may be changed in the future.

Telegram documentation: <https://core.telegram.org/bots/api#sendanimation>

Parameters

- **chat_id** (int or str) – Unique identifier for the target chat or username of the target channel (in the format @channelusername)

- **animation** (str or *telebot.types.InputFile*) – Animation to send. Pass a file_id as String to send an animation that exists on the Telegram servers (recommended), pass an HTTP URL as a String for Telegram to get an animation from the Internet, or upload a new animation using multipart/form-data.
- **duration** (int) – Duration of sent animation in seconds
- **width** (int) – Animation width
- **height** (int) – Animation height
- **thumbnail** (str or *telebot.types.InputFile*) – Thumbnail of the file sent; can be ignored if thumbnail generation for the file is supported server-side. The thumbnail should be in JPEG format and less than 200 kB in size. A thumbnail’s width and height should not exceed 320. Ignored if the file is not uploaded using multipart/form-data. Thumbnails can’t be reused and can be only uploaded as a new file, so you can pass “attach://<file_attach_name>” if the thumbnail was uploaded using multipart/form-data under <file_attach_name>.
- **caption** (str) – Animation caption (may also be used when resending animation by file_id), 0-1024 characters after entities parsing
- **parse_mode** (str) – Mode for parsing entities in the animation caption
- **protect_content** (bool) – Protects the contents of the sent message from forwarding and saving
- **reply_to_message_id** (int) – deprecated.
- **allow_sending_without_reply** (bool) – deprecated.
- **reply_markup** (*telebot.types.InlineKeyboardMarkup* or *telebot.types.ReplyKeyboardMarkup* or *telebot.types.ReplyKeyboardRemove* or *telebot.types.ForceReply*) – Additional interface options. A JSON-serialized object for an inline keyboard, custom reply keyboard, instructions to remove reply keyboard or to force a reply from the user.
- **disable_notification** (bool) – Sends the message silently. Users will receive a notification with no sound.
- **timeout** (int) – Timeout in seconds for the request.
- **caption_entities** (list of *telebot.types.MessageEntity*) – List of special entities that appear in the caption, which can be specified instead of parse_mode
- **message_thread_id** (int) – Identifier of a message thread, in which the video will be sent
- **has_spoiler** (bool) – Pass True, if the animation should be sent as a spoiler
- **thumb** (str or *telebot.types.InputFile*) – deprecated.
- **reply_parameters** (*telebot.types.ReplyParameters*) – Reply parameters.
- **business_connection_id** (str) – Identifier of a business connection

Returns

On success, the sent Message is returned.

Return type

telebot.types.Message

```
send_audio(chat_id: int | str, audio: Any | str, caption: str | None = None, duration: int | None = None,
performer: str | None = None, title: str | None = None, reply_to_message_id: int | None = None,
reply_markup: InlineKeyboardMarkup | ReplyKeyboardMarkup | ReplyKeyboardRemove |
ForceReply | None = None, parse_mode: str | None = None, disable_notification: bool | None =
None, timeout: int | None = None, thumbnail: str | Any | None = None, caption_entities:
List[MessageEntity] | None = None, allow_sending_without_reply: bool | None = None,
protect_content: bool | None = None, message_thread_id: int | None = None, thumb: str | Any |
None = None, reply_parameters: ReplyParameters | None = None, business_connection_id: str |
None = None) → Message
```

Use this method to send audio files, if you want Telegram clients to display them in the music player. Your audio must be in the .MP3 or .M4A format. On success, the sent Message is returned. Bots can currently send audio files of up to 50 MB in size, this limit may be changed in the future.

For sending voice messages, use the `send_voice` method instead.

Telegram documentation: <https://core.telegram.org/bots/api#sendaudio>

Parameters

- **chat_id** (int or str) – Unique identifier for the target chat or username of the target channel (in the format @channelusername)
- **audio** (str or `telebot.types.InputFile`) – Audio file to send. Pass a `file_id` as String to send an audio file that exists on the Telegram servers (recommended), pass an HTTP URL as a String for Telegram to get an audio file from the Internet, or upload a new one using multipart/form-data. Audio must be in the .MP3 or .M4A format.
- **caption** (str) – Audio caption, 0-1024 characters after entities parsing
- **duration** (int) – Duration of the audio in seconds
- **performer** (str) – Performer
- **title** (str) – Track name
- **reply_markup** (`telebot.types.InlineKeyboardMarkup` or `telebot.types.ReplyKeyboardMarkup` or `telebot.types.ReplyKeyboardRemove` or `telebot.types.ForceReply`)
- **parse_mode** (str) – Mode for parsing entities in the audio caption. See formatting options for more details.
- **disable_notification** (bool) – Sends the message silently. Users will receive a notification with no sound.
- **reply_to_message_id** (int) – deprecated.
- **allow_sending_without_reply** (bool) – deprecated.
- **timeout** (int) – Timeout in seconds for the request.
- **thumbnail** (str or `telebot.types.InputFile`) – Thumbnail of the file sent; can be ignored if thumbnail generation for the file is supported server-side. The thumbnail should be in JPEG format and less than 200 kB in size. A thumbnail’s width and height should not exceed 320. Ignored if the file is not uploaded using multipart/form-data. Thumbnails can’t be reused and can be only uploaded as a new file, so you can pass “attach://<file_attach_name>” if the thumbnail was uploaded using multipart/form-data under <file_attach_name>
- **caption_entities** (list of `telebot.types.MessageEntity`) – A JSON-serialized list of special entities that appear in the caption, which can be specified instead of `parse_mode`

- **protect_content** (bool) – Protects the contents of the sent message from forwarding and saving
- **message_thread_id** (int) – Identifier of a message thread, in which the message will be sent
- **thumb** (str or *telebot.types.InputFile*) – deprecated.
- **reply_parameters** (*telebot.types.ReplyParameters*) – Reply parameters.
- **business_connection_id** (str) – Identifier of a business connection, in which the message will be sent

Returns

On success, the sent Message is returned.

Return type

telebot.types.Message

send_chat_action(*chat_id: int | str, action: str, timeout: int | None = None, message_thread_id: int | None = None, business_connection_id: str | None = None*) → bool

Use this method when you need to tell the user that something is happening on the bot's side. The status is set for 5 seconds or less (when a message arrives from your bot, Telegram clients clear its typing status). Returns True on success.

Example: The ImageBot needs some time to process a request and upload the image. Instead of sending a text message along the lines of “Retrieving image, please wait...”, the bot may use sendChatAction with action = upload_photo. The user will see a “sending photo” status for the bot.

Telegram documentation: <https://core.telegram.org/bots/api#sendchataction>

Parameters

- **chat_id** (int or str) – Unique identifier for the target chat or username of the target channel
- **action** (str) – Type of action to broadcast. Choose one, depending on what the user is about to receive: typing for text messages, upload_photo for photos, record_video or upload_video for videos, record_voice or upload_voice for voice notes, upload_document for general files, choose_sticker for stickers, find_location for location data, record_video_note or upload_video_note for video notes.
- **timeout** (int) – Timeout in seconds for the request.
- **message_thread_id** (int) – The thread identifier of a message from which the reply will be sent (supergroups only)
- **business_connection_id** (str) – Identifier of a business connection

Returns

Returns True on success.

Return type

bool

send_contact(*chat_id: int | str, phone_number: str, first_name: str, last_name: str | None = None, vcard: str | None = None, disable_notification: bool | None = None, reply_to_message_id: int | None = None, reply_markup: InlineKeyboardMarkup | ReplyKeyboardMarkup | ReplyKeyboardRemove | ForceReply | None = None, timeout: int | None = None, allow_sending_without_reply: bool | None = None, protect_content: bool | None = None, message_thread_id: int | None = None, reply_parameters: ReplyParameters | None = None, business_connection_id: str | None = None*) → *Message*

Use this method to send phone contacts. On success, the sent Message is returned.

Telegram documentation: <https://core.telegram.org/bots/api#sendcontact>

Parameters

- **chat_id** (int or str) – Unique identifier for the target chat or username of the target channel
- **phone_number** (str) – Contact’s phone number
- **first_name** (str) – Contact’s first name
- **last_name** (str) – Contact’s last name
- **vcard** (str) – Additional data about the contact in the form of a vCard, 0-2048 bytes
- **disable_notification** (bool) – Sends the message silently. Users will receive a notification with no sound.
- **reply_to_message_id** (int) – deprecated.
- **allow_sending_without_reply** (bool) – deprecated.
- **reply_markup** (*telebot.types.InlineKeyboardMarkup* or *telebot.types.ReplyKeyboardMarkup* or *telebot.types.ReplyKeyboardRemove* or *telebot.types.ForceReply*) – Additional interface options. A JSON-serialized object for an inline keyboard, custom reply keyboard, instructions to remove reply keyboard or to force a reply from the user.
- **timeout** (int) – Timeout in seconds for the request.
- **protect_content** (bool) – Protects the contents of the sent message from forwarding and saving
- **message_thread_id** (int) – The thread identifier of a message from which the reply will be sent
- **reply_parameters** (*telebot.types.ReplyParameters*) – Reply parameters.
- **business_connection_id** (str) – Identifier of a business connection

Returns

On success, the sent Message is returned.

Return type

telebot.types.Message

send_dice(*chat_id: int | str, emoji: str | None = None, disable_notification: bool | None = None, reply_to_message_id: int | None = None, reply_markup: InlineKeyboardMarkup | ReplyKeyboardMarkup | ReplyKeyboardRemove | ForceReply | None = None, timeout: int | None = None, allow_sending_without_reply: bool | None = None, protect_content: bool | None = None, message_thread_id: int | None = None, reply_parameters: ReplyParameters | None = None, business_connection_id: str | None = None*) → *Message*

Use this method to send an animated emoji that will display a random value. On success, the sent Message is returned.

Telegram documentation: <https://core.telegram.org/bots/api#senddice>

Parameters

- **chat_id** (int or str) – Unique identifier for the target chat or username of the target channel (in the format @channelusername)

- **emoji** (*str*) – Emoji on which the dice throw animation is based. Currently, must be one of “”, “”, “”, “”, “”, or “”. Dice can have values 1-6 for “”, “” and “”, values 1-5 for “” and “”, and values 1-64 for “”. Defaults to “”
- **disable_notification** (*bool*) – Sends the message silently. Users will receive a notification with no sound.
- **reply_markup** (*telebot.types.InlineKeyboardMarkup* or *telebot.types.ReplyKeyboardMarkup* or *telebot.types.ReplyKeyboardRemove* or *telebot.types.ForceReply*) – Additional interface options. A JSON-serialized object for an inline keyboard, custom reply keyboard, instructions to remove reply keyboard or to force a reply from the user.
- **reply_to_message_id** (*int*) – deprecated.
- **allow_sending_without_reply** (*bool*) – deprecated.
- **timeout** (*int*) – Timeout in seconds for the request.
- **protect_content** (*bool*) – Protects the contents of the sent message from forwarding and saving
- **message_thread_id** (*int*) – Identifier of a message thread, in which the message will be sent
- **reply_parameters** (*telebot.types.ReplyParameters*) – Additional parameters for replies to messages
- **business_connection_id** (*str*) – Identifier of a business connection, in which the message will be sent

Returns

On success, the sent Message is returned.

Return type

telebot.types.Message

send_document(*chat_id: int | str, document: Any | str, reply_to_message_id: int | None = None, caption: str | None = None, reply_markup: InlineKeyboardMarkup | ReplyKeyboardMarkup | ReplyKeyboardRemove | ForceReply | None = None, parse_mode: str | None = None, disable_notification: bool | None = None, timeout: int | None = None, thumbnail: str | Any | None = None, caption_entities: List[MessageEntity] | None = None, allow_sending_without_reply: bool | None = None, visible_file_name: str | None = None, disable_content_type_detection: bool | None = None, data: str | Any | None = None, protect_content: bool | None = None, message_thread_id: int | None = None, thumb: str | Any | None = None, reply_parameters: ReplyParameters | None = None, business_connection_id: str | None = None*) → *Message*

Use this method to send general files.

Telegram documentation: <https://core.telegram.org/bots/api#senddocument>

Parameters

- **chat_id** (*int* or *str*) – Unique identifier for the target chat or username of the target channel (in the format @channelusername)
- **document** (*str* or *telebot.types.InputFile*) – (document) File to send. Pass a file_id as String to send a file that exists on the Telegram servers (recommended), pass an HTTP URL as a String for Telegram to get a file from the Internet, or upload a new one using multipart/form-data

- **caption** (str) – Document caption (may also be used when resending documents by `file_id`), 0-1024 characters after entities parsing
- **reply_markup** (`telebot.types.InlineKeyboardMarkup` or `telebot.types.ReplyKeyboardMarkup` or `telebot.types.ReplyKeyboardRemove` or `telebot.types.ForceReply`) – Additional interface options. A JSON-serialized object for an inline keyboard, custom reply keyboard, instructions to remove reply keyboard or to force a reply from the user.
- **parse_mode** (str) – Mode for parsing entities in the document caption
- **disable_notification** (bool) – Sends the message silently. Users will receive a notification with no sound.
- **reply_to_message_id** (int) – deprecated.
- **allow_sending_without_reply** (bool) – deprecated.
- **timeout** (int) – Timeout in seconds for the request.
- **thumbnail** (str or `telebot.types.InputFile`) – InputFile or String : Thumbnail of the file sent; can be ignored if thumbnail generation for the file is supported server-side. The thumbnail should be in JPEG format and less than 200 kB in size. A thumbnail's width and height should not exceed 320. Ignored if the file is not uploaded using multipart/form-data. Thumbnails can't be reused and can be only uploaded as a new file, so you can pass "attach://<file_attach_name>" if the thumbnail was uploaded using multipart/form-data under <file_attach_name>
- **caption_entities** (list of `telebot.types.MessageEntity`) – A JSON-serialized list of special entities that appear in the caption, which can be specified instead of `parse_mode`
- **visible_file_name** (str) – allows to define file name that will be visible in the Telegram instead of original file name
- **disable_content_type_detection** (bool) – Disables automatic server-side content type detection for files uploaded using multipart/form-data
- **data** (str) – function typo miss compatibility: do not use it
- **protect_content** (bool) – Protects the contents of the sent message from forwarding and saving
- **message_thread_id** (int) – The thread to which the message will be sent
- **thumb** (str or `telebot.types.InputFile`) – deprecated.
- **reply_parameters** (`telebot.types.ReplyParameters`) – Reply parameters.
- **business_connection_id** (str) – Identifier of a business connection, in which the message will be sent

Returns

On success, the sent Message is returned.

Return type

`telebot.types.Message`

send_game(`chat_id: int | str, game_short_name: str, disable_notification: bool | None = None, reply_to_message_id: int | None = None, reply_markup: InlineKeyboardMarkup | ReplyKeyboardMarkup | ReplyKeyboardRemove | ForceReply | None = None, timeout: int | None = None, allow_sending_without_reply: bool | None = None, protect_content: bool | None = None, message_thread_id: int | None = None, reply_parameters: ReplyParameters | None = None, business_connection_id: str | None = None`) → `Message`

Used to send the game.

Telegram documentation: <https://core.telegram.org/bots/api#sendgame>

Parameters

- **chat_id** (int or str) – Unique identifier for the target chat or username of the target channel (in the format @channelusername)
- **game_short_name** (str) – Short name of the game, serves as the unique identifier for the game. Set up your games via @BotFather.
- **disable_notification** (bool) – Sends the message silently. Users will receive a notification with no sound.
- **reply_to_message_id** (int) – deprecated. If the message is a reply, ID of the original message
- **allow_sending_without_reply** (bool) – deprecated. Pass True, if the message should be sent even if the specified replied-to message is not found
- **reply_markup** (InlineKeyboardMarkup or ReplyKeyboardMarkup or ReplyKeyboardRemove or ForceReply) – Additional interface options. A JSON-serialized object for an inline keyboard, custom reply keyboard, instructions to remove reply keyboard or to force a reply from the user.
- **timeout** (int) – Timeout in seconds for waiting for a response from the bot.
- **protect_content** (bool) – Protects the contents of the sent message from forwarding and saving
- **message_thread_id** (int) – The identifier of a message thread, in which the game message will be sent.
- **reply_parameters** (ReplyParameters) – Reply parameters
- **business_connection_id** (str) – Unique identifier of the business connection

Returns

On success, the sent Message is returned.

Return type

`types.Message`

send_invoice(*chat_id: int | str, title: str, description: str, invoice_payload: str, provider_token: str, currency: str, prices: List[LabeledPrice], start_parameter: str | None = None, photo_url: str | None = None, photo_size: int | None = None, photo_width: int | None = None, photo_height: int | None = None, need_name: bool | None = None, need_phone_number: bool | None = None, need_email: bool | None = None, need_shipping_address: bool | None = None, send_phone_number_to_provider: bool | None = None, send_email_to_provider: bool | None = None, is_flexible: bool | None = None, disable_notification: bool | None = None, reply_to_message_id: int | None = None, reply_markup: InlineKeyboardMarkup | ReplyKeyboardMarkup | ReplyKeyboardRemove | ForceReply | None = None, provider_data: str | None = None, timeout: int | None = None, allow_sending_without_reply: bool | None = None, max_tip_amount: int | None = None, suggested_tip_amounts: List[int] | None = None, protect_content: bool | None = None, message_thread_id: int | None = None, reply_parameters: ReplyParameters | None = None*) → *Message*

Sends invoice.

Telegram documentation: <https://core.telegram.org/bots/api#sendinvoice>

Parameters

- **chat_id** (int or str) – Unique identifier for the target private chat
- **title** (str) – Product name, 1-32 characters
- **description** (str) – Product description, 1-255 characters
- **invoice_payload** (str) – Bot-defined invoice payload, 1-128 bytes. This will not be displayed to the user, use for your internal processes.
- **provider_token** (str) – Payments provider token, obtained via @Botfather
- **currency** (str) – Three-letter ISO 4217 currency code, see <https://core.telegram.org/bots/payments#supported-currencies>
- **prices** (List[*types.LabeledPrice*]) – Price breakdown, a list of components (e.g. product price, tax, discount, delivery cost, delivery tax, bonus, etc.)
- **start_parameter** (str) – Unique deep-linking parameter that can be used to generate this invoice when used as a start parameter
- **photo_url** (str) – URL of the product photo for the invoice. Can be a photo of the goods or a marketing image for a service. People like it better when they see what they are paying for.
- **photo_size** (int) – Photo size in bytes
- **photo_width** (int) – Photo width
- **photo_height** (int) – Photo height
- **need_name** (bool) – Pass True, if you require the user’s full name to complete the order
- **need_phone_number** (bool) – Pass True, if you require the user’s phone number to complete the order
- **need_email** (bool) – Pass True, if you require the user’s email to complete the order
- **need_shipping_address** (bool) – Pass True, if you require the user’s shipping address to complete the order
- **is_flexible** (bool) – Pass True, if the final price depends on the shipping method
- **send_phone_number_to_provider** (bool) – Pass True, if user’s phone number should be sent to provider
- **send_email_to_provider** (bool) – Pass True, if user’s email address should be sent to provider
- **disable_notification** (bool) – Sends the message silently. Users will receive a notification with no sound.
- **reply_to_message_id** (int) – deprecated. If the message is a reply, ID of the original message
- **allow_sending_without_reply** (bool) – deprecated. Pass True, if the message should be sent even if the specified replied-to message is not found
- **reply_markup** (str) – A JSON-serialized object for an inline keyboard. If empty, one ‘Pay total price’ button will be shown. If not empty, the first button must be a Pay button
- **provider_data** (str) – A JSON-serialized data about the invoice, which will be shared with the payment provider. A detailed description of required fields should be provided by the payment provider.
- **timeout** (int) – Timeout of a request, defaults to None

- **max_tip_amount** (int) – The maximum accepted amount for tips in the smallest units of the currency
- **suggested_tip_amounts** (list of int) – A JSON-serialized array of suggested amounts of tips in the smallest units of the currency. At most 4 suggested tip amounts can be specified. The suggested tip amounts must be positive, passed in a strictly increased order and must not exceed max_tip_amount.
- **protect_content** (bool) – Protects the contents of the sent message from forwarding and saving
- **message_thread_id** (int) – The identifier of a message thread, in which the invoice message will be sent
- **reply_parameters** (*types.ReplyParameters*) – Required if the message is a reply. Additional interface options.

Returns

On success, the sent Message is returned.

Return type

types.Message

send_location(*chat_id: int | str, latitude: float, longitude: float, live_period: int | None = None, reply_to_message_id: int | None = None, reply_markup: InlineKeyboardMarkup | ReplyKeyboardMarkup | ReplyKeyboardRemove | ForceReply | None = None, disable_notification: bool | None = None, timeout: int | None = None, horizontal_accuracy: float | None = None, heading: int | None = None, proximity_alert_radius: int | None = None, allow_sending_without_reply: bool | None = None, protect_content: bool | None = None, message_thread_id: int | None = None, reply_parameters: ReplyParameters | None = None, business_connection_id: str | None = None*) → *Message*

Use this method to send point on the map. On success, the sent Message is returned.

Telegram documentation: <https://core.telegram.org/bots/api#sendlocation>

Parameters

- **chat_id** (int or str) – Unique identifier for the target chat or username of the target channel (in the format @channelusername)
- **latitude** (float) – Latitude of the location
- **longitude** (float) – Longitude of the location
- **live_period** (int) – Period in seconds for which the location will be updated (see Live Locations, should be between 60 and 86400).
- **reply_markup** (*telebot.types.InlineKeyboardMarkup* or *telebot.types.ReplyKeyboardMarkup* or *telebot.types.ReplyKeyboardRemove* or *telebot.types.ForceReply*) – Additional interface options. A JSON-serialized object for an inline keyboard, custom reply keyboard, instructions to remove reply keyboard or to force a reply from the user.
- **disable_notification** (bool) – Sends the message silently. Users will receive a notification with no sound.
- **reply_to_message_id** (int) – deprecated.
- **allow_sending_without_reply** (bool) – deprecated.
- **timeout** (int) – Timeout in seconds for the request.

- **horizontal_accuracy** (float) – The radius of uncertainty for the location, measured in meters; 0-1500
- **heading** (int) – For live locations, a direction in which the user is moving, in degrees. Must be between 1 and 360 if specified.
- **proximity_alert_radius** (int) – For live locations, a maximum distance for proximity alerts about approaching another chat member, in meters. Must be between 1 and 100000 if specified.
- **protect_content** (bool) – Protects the contents of the sent message from forwarding and saving
- **message_thread_id** (int) – Identifier of a message thread, in which the message will be sent
- **reply_parameters** (*telebot.types.ReplyParameters*) – Reply parameters.
- **business_connection_id** (str) – Identifier of a business connection, in which the message will be sent

Returns

On success, the sent Message is returned.

Return type

telebot.types.Message

send_media_group(*chat_id: int | str, media: List[InputMediaAudio | InputMediaDocument | InputMediaPhoto | InputMediaVideo], disable_notification: bool | None = None, protect_content: bool | None = None, reply_to_message_id: int | None = None, timeout: int | None = None, allow_sending_without_reply: bool | None = None, message_thread_id: int | None = None, reply_parameters: ReplyParameters | None = None, business_connection_id: str | None = None*) → List[*Message*]

Use this method to send a group of photos, videos, documents or audios as an album. Documents and audio files can be only grouped in an album with messages of the same type. On success, an array of Messages that were sent is returned.

Telegram documentation: <https://core.telegram.org/bots/api#sendmediagroup>

Parameters

- **chat_id** (int or str) – Unique identifier for the target chat or username of the target channel (in the format @channelusername)
- **media** (list of *types.InputMedia*) – A JSON-serialized array describing messages to be sent, must include 2-10 items
- **disable_notification** (bool) – Sends the messages silently. Users will receive a notification with no sound.
- **protect_content** (bool) – Protects the contents of the sent message from forwarding and saving
- **reply_to_message_id** (int) – deprecated.
- **allow_sending_without_reply** (bool) – deprecated.
- **timeout** (int) – Timeout in seconds for the request.
- **message_thread_id** (int) – Identifier of a message thread, in which the media group will be sent
- **reply_parameters** (*telebot.types.ReplyParameters*) – Reply parameters.

- **business_connection_id** (str) – Identifier of a business connection, in which the message will be sent

Returns

On success, an array of Messages that were sent is returned.

Return type

List[*types.Message*]

```
send_message(chat_id: int | str, text: str, parse_mode: str | None = None, entities: List[MessageEntity] | None = None, disable_web_page_preview: bool | None = None, disable_notification: bool | None = None, protect_content: bool | None = None, reply_to_message_id: int | None = None, allow_sending_without_reply: bool | None = None, reply_markup: InlineKeyboardMarkup | ReplyKeyboardMarkup | ReplyKeyboardRemove | ForceReply | None = None, timeout: int | None = None, message_thread_id: int | None = None, reply_parameters: ReplyParameters | None = None, link_preview_options: LinkPreviewOptions | None = None, business_connection_id: str | None = None) → Message
```

Use this method to send text messages.

Warning: Do not send more than about 4096 characters each message, otherwise you'll risk an HTTP 414 error. If you must send more than 4096 characters, use the *split_string* or *smart_split* function in *util.py*.

Telegram documentation: <https://core.telegram.org/bots/api#sendmessage>

Parameters

- **chat_id** (int or str) – Unique identifier for the target chat or username of the target channel (in the format @channelusername)
- **text** (str) – Text of the message to be sent
- **parse_mode** (str) – Mode for parsing entities in the message text.
- **entities** (Array of *telebot.types.MessageEntity*) – List of special entities that appear in message text, which can be specified instead of *parse_mode*
- **disable_web_page_preview** (bool) – deprecated.
- **disable_notification** (bool) – Sends the message silently. Users will receive a notification with no sound.
- **protect_content** (bool) – Protects the contents of the sent message from forwarding and saving
- **reply_to_message_id** (int) – deprecated.
- **allow_sending_without_reply** (bool) – deprecated.
- **reply_markup** (*telebot.types.InlineKeyboardMarkup* or *telebot.types.ReplyKeyboardMarkup* or *telebot.types.ReplyKeyboardRemove* or *telebot.types.ForceReply*) – Additional interface options. A JSON-serialized object for an inline keyboard, custom reply keyboard, instructions to remove reply keyboard or to force a reply from the user.
- **timeout** (int) – Timeout in seconds for the request.
- **message_thread_id** (int) – Identifier of a message thread, in which the message will be sent
- **reply_parameters** (*telebot.types.ReplyParameters*) – Reply parameters.
- **link_preview_options** (*telebot.types.LinkPreviewOptions*) – Link preview options.

- **business_connection_id** (str) – Identifier of a business connection, in which the message will be sent

Returns

On success, the sent Message is returned.

Return type

`telebot.types.Message`

send_photo(*chat_id*: int | str, *photo*: Any | str, *caption*: str | None = None, *parse_mode*: str | None = None, *caption_entities*: List[MessageEntity] | None = None, *disable_notification*: bool | None = None, *protect_content*: bool | None = None, *reply_to_message_id*: int | None = None, *allow_sending_without_reply*: bool | None = None, *reply_markup*: InlineKeyboardMarkup | ReplyKeyboardMarkup | ReplyKeyboardRemove | ForceReply | None = None, *timeout*: int | None = None, *message_thread_id*: int | None = None, *has_spoiler*: bool | None = None, *reply_parameters*: ReplyParameters | None = None, *business_connection_id*: str | None = None) → Message

Use this method to send photos. On success, the sent Message is returned.

Telegram documentation: <https://core.telegram.org/bots/api#sendphoto>

Parameters

- **chat_id** (int or str) – Unique identifier for the target chat or username of the target channel (in the format @channelusername)
- **photo** (str or `telebot.types.InputFile`) – Photo to send. Pass a file_id as String to send a photo that exists on the Telegram servers (recommended), pass an HTTP URL as a String for Telegram to get a photo from the Internet, or upload a new photo using multipart/form-data. The photo must be at most 10 MB in size. The photo's width and height must not exceed 10000 in total. Width and height ratio must be at most 20.
- **caption** (str) – Photo caption (may also be used when resending photos by file_id), 0-1024 characters after entities parsing
- **parse_mode** (str) – Mode for parsing entities in the photo caption.
- **caption_entities** (list of `telebot.types.MessageEntity`) – A JSON-serialized list of special entities that appear in the caption, which can be specified instead of parse_mode
- **disable_notification** (bool) – Sends the message silently. Users will receive a notification with no sound.
- **protect_content** (bool) – Protects the contents of the sent message from forwarding and saving
- **reply_to_message_id** (int) – deprecated.
- **allow_sending_without_reply** (bool) – deprecated.
- **reply_markup** (`telebot.types.InlineKeyboardMarkup` or `telebot.types.ReplyKeyboardMarkup` or `telebot.types.ReplyKeyboardRemove` or `telebot.types.ForceReply`) – Additional interface options. A JSON-serialized object for an inline keyboard, custom reply keyboard, instructions to remove reply keyboard or to force a reply from the user.
- **timeout** (int) – Timeout in seconds for the request.
- **message_thread_id** (int) – Identifier of a message thread, in which the message will be sent
- **has_spoiler** (bool) – Pass True, if the photo should be sent as a spoiler

- **reply_parameters** (*telebot.types.ReplyParameters*) – Additional parameters for replies to messages
- **business_connection_id** (str) – Identifier of a business connection, in which the message will be sent

Returns

On success, the sent Message is returned.

Return type

telebot.types.Message

send_poll(*chat_id: int | str, question: str, options: List[str], is_anonymous: bool | None = None, type: str | None = None, allows_multiple_answers: bool | None = None, correct_option_id: int | None = None, explanation: str | None = None, explanation_parse_mode: str | None = None, open_period: int | None = None, close_date: int | datetime | None = None, is_closed: bool | None = None, disable_notification: bool | None = False, reply_to_message_id: int | None = None, reply_markup: InlineKeyboardMarkup | ReplyKeyboardMarkup | ReplyKeyboardRemove | ForceReply | None = None, allow_sending_without_reply: bool | None = None, timeout: int | None = None, explanation_entities: List[MessageEntity] | None = None, protect_content: bool | None = None, message_thread_id: int | None = None, reply_parameters: ReplyParameters | None = None, business_connection_id: str | None = None*) → *Message*

Use this method to send a native poll. On success, the sent Message is returned.

Telegram documentation: <https://core.telegram.org/bots/api#sendpoll>

Parameters

- **chat_id** (int | str) – Unique identifier for the target chat or username of the target channel
- **question** (str) – Poll question, 1-300 characters
- **options** (list of str) – A JSON-serialized list of answer options, 2-10 strings 1-100 characters each
- **is_anonymous** (bool) – True, if the poll needs to be anonymous, defaults to True
- **type** (str) – Poll type, “quiz” or “regular”, defaults to “regular”
- **allows_multiple_answers** (bool) – True, if the poll allows multiple answers, ignored for polls in quiz mode, defaults to False
- **correct_option_id** (int) – 0-based identifier of the correct answer option. Available only for polls in quiz mode, defaults to None
- **explanation** (str) – Text that is shown when a user chooses an incorrect answer or taps on the lamp icon in a quiz-style poll, 0-200 characters with at most 2 line feeds after entities parsing
- **explanation_parse_mode** (str) – Mode for parsing entities in the explanation. See formatting options for more details.
- **open_period** (int) – Amount of time in seconds the poll will be active after creation, 5-600. Can't be used together with close_date.
- **close_date** (int | datetime) – Point in time (Unix timestamp) when the poll will be automatically closed.
- **is_closed** (bool) – Pass True, if the poll needs to be immediately closed. This can be useful for poll preview.
- **disable_notification** (bool) – Sends the message silently. Users will receive a notification with no sound.

- **reply_to_message_id** (int) – deprecated. If the message is a reply, ID of the original message
- **allow_sending_without_reply** (bool) – deprecated. Pass True, if the message should be sent even if the specified replied-to message is not found
- **reply_markup** (InlineKeyboardMarkup | ReplyKeyboardMarkup | ReplyKeyboardRemove | ForceReply) – Additional interface options. A JSON-serialized object for an inline keyboard, custom reply keyboard, instructions to remove reply keyboard or to force a reply from the user.
- **timeout** (int) – Timeout in seconds for waiting for a response from the user.
- **explanation_entities** (list of MessageEntity) – A JSON-serialized list of special entities that appear in the explanation, which can be specified instead of parse_mode
- **protect_content** (bool) – Protects the contents of the sent message from forwarding and saving
- **message_thread_id** (int) – The identifier of a message thread, in which the poll will be sent
- **reply_parameters** (ReplyParameters) – reply parameters.
- **business_connection_id** (str) – Identifier of the business connection to use for the poll

Returns

On success, the sent Message is returned.

Return type

types.Message

send_sticker(*chat_id: int | str, sticker: Any | str, reply_to_message_id: int | None = None, reply_markup: InlineKeyboardMarkup | ReplyKeyboardMarkup | ReplyKeyboardRemove | ForceReply | None = None, disable_notification: bool | None = None, timeout: int | None = None, allow_sending_without_reply: bool | None = None, protect_content: bool | None = None, data: Any | str = None, message_thread_id: int | None = None, emoji: str | None = None, reply_parameters: ReplyParameters | None = None, business_connection_id: str | None = None*) → *Message*

Use this method to send static .WEBP, animated .TGS, or video .WEBM stickers. On success, the sent Message is returned.

Telegram documentation: <https://core.telegram.org/bots/api#sendsticker>

Parameters

- **chat_id** (int or str) – Unique identifier for the target chat or username of the target channel (in the format @channelusername)
- **sticker** (str or *telebot.types.InputFile*) – Sticker to send. Pass a file_id as String to send a file that exists on the Telegram servers (recommended), pass an HTTP URL as a String for Telegram to get a .webp file from the Internet, or upload a new one using multipart/form-data.
- **reply_markup** (*telebot.types.InlineKeyboardMarkup* or *telebot.types.ReplyKeyboardMarkup* or *telebot.types.ReplyKeyboardRemove* or *telebot.types.ForceReply*) – Additional interface options. A JSON-serialized object for an inline keyboard, custom reply keyboard, instructions to remove reply keyboard or to force a reply from the user.
- **disable_notification** (bool) – to disable the notification

- **reply_to_message_id** (int) – deprecated.
- **allow_sending_without_reply** (bool) – deprecated.
- **timeout** (int) – Timeout in seconds for the request.
- **protect_content** (bool) – Protects the contents of the sent message from forwarding and saving
- **data** (str) – function typo miss compatibility: do not use it
- **message_thread_id** (int) – The thread to which the message will be sent
- **emoji** (str) – Emoji associated with the sticker; only for just uploaded stickers
- **reply_parameters** (*telebot.types.ReplyParameters*) – Reply parameters.
- **business_connection_id** (str) – Identifier of a business connection, in which the message will be sent

Returns

On success, the sent Message is returned.

Return type

telebot.types.Message

send_venue(*chat_id: int | str, latitude: float | None, longitude: float | None, title: str, address: str, foursquare_id: str | None = None, foursquare_type: str | None = None, disable_notification: bool | None = None, reply_to_message_id: int | None = None, reply_markup: InlineKeyboardMarkup | ReplyKeyboardMarkup | ReplyKeyboardRemove | ForceReply | None = None, timeout: int | None = None, allow_sending_without_reply: bool | None = None, google_place_id: str | None = None, google_place_type: str | None = None, protect_content: bool | None = None, message_thread_id: int | None = None, reply_parameters: ReplyParameters | None = None, business_connection_id: str | None = None*) → *Message*

Use this method to send information about a venue. On success, the sent Message is returned.

Telegram documentation: <https://core.telegram.org/bots/api#sendvenue>

Parameters

- **chat_id** (int or str) – Unique identifier for the target chat or username of the target channel
- **latitude** (float) – Latitude of the venue
- **longitude** (float) – Longitude of the venue
- **title** (str) – Name of the venue
- **address** (str) – Address of the venue
- **foursquare_id** (str) – Foursquare identifier of the venue
- **foursquare_type** (str) – Foursquare type of the venue, if known. (For example, “arts_entertainment/default”, “arts_entertainment/aquarium” or “food/icecream”.)
- **disable_notification** (bool) – Sends the message silently. Users will receive a notification with no sound.
- **reply_to_message_id** (int) – deprecated.
- **allow_sending_without_reply** (bool) – deprecated.
- **reply_markup** (*telebot.types.InlineKeyboardMarkup* or *telebot.types.ReplyKeyboardMarkup* or *telebot.types.ReplyKeyboardRemove* or *telebot.types.ForceReply*) – Additional interface options. A JSON-serialized object for an

inline keyboard, custom reply keyboard, instructions to remove reply keyboard or to force a reply from the user.

- **timeout** (int) – Timeout in seconds for the request.
- **google_place_id** (str) – Google Places identifier of the venue
- **google_place_type** (str) – Google Places type of the venue.
- **protect_content** (bool) – Protects the contents of the sent message from forwarding and saving
- **message_thread_id** (int) – The thread identifier of a message from which the reply will be sent
- **reply_parameters** (*telebot.types.ReplyParameters*) – Reply parameters.
- **business_connection_id** (str) – Identifier of a business connection

Returns

On success, the sent Message is returned.

Return type

telebot.types.Message

send_video(*chat_id: int | str, video: Any | str, duration: int | None = None, width: int | None = None, height: int | None = None, thumbnail: str | Any | None = None, caption: str | None = None, parse_mode: str | None = None, caption_entities: List[MessageEntity] | None = None, supports_streaming: bool | None = None, disable_notification: bool | None = None, protect_content: bool | None = None, reply_to_message_id: int | None = None, allow_sending_without_reply: bool | None = None, reply_markup: InlineKeyboardMarkup | ReplyKeyboardMarkup | ReplyKeyboardRemove | ForceReply | None = None, timeout: int | None = None, data: str | Any | None = None, message_thread_id: int | None = None, has_spoiler: bool | None = None, thumb: str | Any | None = None, reply_parameters: ReplyParameters | None = None, business_connection_id: str | None = None*) → *Message*

Use this method to send video files, Telegram clients support mp4 videos (other formats may be sent as Document).

Telegram documentation: <https://core.telegram.org/bots/api#sendvideo>

Parameters

- **chat_id** (int or str) – Unique identifier for the target chat or username of the target channel (in the format @channelusername)
- **video** (str or *telebot.types.InputFile*) – Video to send. You can either pass a file_id as String to resend a video that is already on the Telegram servers, or upload a new video file using multipart/form-data.
- **duration** (int) – Duration of sent video in seconds
- **width** (int) – Video width
- **height** (int) – Video height
- **thumbnail** (str or *telebot.types.InputFile*) – Thumbnail of the file sent; can be ignored if thumbnail generation for the file is supported server-side. The thumbnail should be in JPEG format and less than 200 kB in size. A thumbnail’s width and height should not exceed 320. Ignored if the file is not uploaded using multipart/form-data. Thumbnails can’t be reused and can be only uploaded as a new file, so you can pass “attach://<file_attach_name>” if the thumbnail was uploaded using multipart/form-data under <file_attach_name>.

- **caption** (str) – Video caption (may also be used when resending videos by `file_id`), 0-1024 characters after entities parsing
- **parse_mode** (str) – Mode for parsing entities in the video caption
- **caption_entities** (list of `telebot.types.MessageEntity`) – List of special entities that appear in the caption, which can be specified instead of `parse_mode`
- **supports_streaming** (bool) – Pass True, if the uploaded video is suitable for streaming
- **disable_notification** (bool) – Sends the message silently. Users will receive a notification with no sound.
- **protect_content** (bool) – Protects the contents of the sent message from forwarding and saving
- **reply_to_message_id** (int) – deprecated.
- **allow_sending_without_reply** (bool) – deprecated.
- **reply_markup** (`telebot.types.InlineKeyboardMarkup` or `telebot.types.ReplyKeyboardMarkup` or `telebot.types.ReplyKeyboardRemove` or `telebot.types.ForceReply`) – Additional interface options. A JSON-serialized object for an inline keyboard, custom reply keyboard, instructions to remove reply keyboard or to force a reply from the user.
- **timeout** (int) – Timeout in seconds for the request.
- **data** (str) – function typo miss compatibility: do not use it
- **message_thread_id** (int) – Identifier of a message thread, in which the video will be sent
- **has_spoiler** (bool) – Pass True, if the video should be sent as a spoiler
- **thumb** (str or `telebot.types.InputFile`) – deprecated.
- **reply_parameters** (`telebot.types.ReplyParameters`) – Reply parameters
- **business_connection_id** (str) – Identifier of a business connection

Returns

On success, the sent Message is returned.

Return type

`telebot.types.Message`

send_video_note(`chat_id: int | str, data: Any | str, duration: int | None = None, length: int | None = None, reply_to_message_id: int | None = None, reply_markup: InlineKeyboardMarkup | ReplyKeyboardMarkup | ReplyKeyboardRemove | ForceReply | None = None, disable_notification: bool | None = None, timeout: int | None = None, thumbnail: str | Any | None = None, allow_sending_without_reply: bool | None = None, protect_content: bool | None = None, message_thread_id: int | None = None, thumb: str | Any | None = None, reply_parameters: ReplyParameters | None = None, business_connection_id: str | None = None`) → `Message`

As of v.4.0, Telegram clients support rounded square MPEG4 videos of up to 1 minute long. Use this method to send video messages. On success, the sent Message is returned.

Telegram documentation: <https://core.telegram.org/bots/api#sendvideonote>

Parameters

- **chat_id** (int or str) – Unique identifier for the target chat or username of the target channel (in the format @channelusername)

- **data** (str or *telebot.types.InputFile*) – Video note to send. Pass a file_id as String to send a video note that exists on the Telegram servers (recommended) or upload a new video using multipart/form-data. Sending video notes by a URL is currently unsupported
- **duration** (int) – Duration of sent video in seconds
- **length** (int) – Video width and height, i.e. diameter of the video message
- **reply_markup** (*telebot.types.InlineKeyboardMarkup* or *telebot.types.ReplyKeyboardMarkup* or *telebot.types.ReplyKeyboardRemove* or *telebot.types.ForceReply*) – Additional interface options. A JSON-serialized object for an inline keyboard, custom reply keyboard, instructions to remove reply keyboard or to force a reply from the user.
- **disable_notification** (bool) – Sends the message silently. Users will receive a notification with no sound.
- **reply_to_message_id** (int) – deprecated.
- **allow_sending_without_reply** (bool) – deprecated.
- **timeout** (int) – Timeout in seconds for the request.
- **thumbnail** (str or *telebot.types.InputFile*) – Thumbnail of the file sent; can be ignored if thumbnail generation for the file is supported server-side. The thumbnail should be in JPEG format and less than 200 kB in size. A thumbnail’s width and height should not exceed 320. Ignored if the file is not uploaded using multipart/form-data. Thumbnails can’t be reused and can be only uploaded as a new file, so you can pass “attach://<file_attach_name>” if the thumbnail was uploaded using multipart/form-data under <file_attach_name>.
- **protect_content** (bool) – Protects the contents of the sent message from forwarding and saving
- **message_thread_id** (int) – Identifier of a message thread, in which the video note will be sent
- **thumb** (str or *telebot.types.InputFile*) – deprecated.
- **reply_parameters** (*telebot.types.ReplyParameters*) – Reply parameters.
- **business_connection_id** (str) – Identifier of a business connection, in which the message will be sent

Returns

On success, the sent Message is returned.

Return type

telebot.types.Message

send_voice(*chat_id: int | str, voice: Any | str, caption: str | None = None, duration: int | None = None, reply_to_message_id: int | None = None, reply_markup: InlineKeyboardMarkup | ReplyKeyboardMarkup | ReplyKeyboardRemove | ForceReply | None = None, parse_mode: str | None = None, disable_notification: bool | None = None, timeout: int | None = None, caption_entities: List[MessageEntity] | None = None, allow_sending_without_reply: bool | None = None, protect_content: bool | None = None, message_thread_id: int | None = None, reply_parameters: ReplyParameters | None = None, business_connection_id: str | None = None*) → *Message*

Use this method to send audio files, if you want Telegram clients to display the file as a playable voice message. For this to work, your audio must be in an .OGG file encoded with OPUS (other formats may be sent as Audio or Document). On success, the sent Message is returned. Bots can currently send voice messages of up to 50 MB in size, this limit may be changed in the future.

Telegram documentation: <https://core.telegram.org/bots/api#sendvoice>

Parameters

- **chat_id** (int or str) – Unique identifier for the target chat or username of the target channel (in the format @channelusername)
- **voice** (str or *telebot.types.InputFile*) – Audio file to send. Pass a file_id as String to send a file that exists on the Telegram servers (recommended), pass an HTTP URL as a String for Telegram to get a file from the Internet, or upload a new one using multipart/form-data.
- **caption** (str) – Voice message caption, 0-1024 characters after entities parsing
- **duration** (int) – Duration of the voice message in seconds
- **reply_markup** (*telebot.types.InlineKeyboardMarkup* or *telebot.types.ReplyKeyboardMarkup* or *telebot.types.ReplyKeyboardRemove* or *telebot.types.ForceReply*) – Additional interface options. A JSON-serialized object for an inline keyboard, custom reply keyboard, instructions to remove reply keyboard or to force a reply from the user.
- **parse_mode** (str) – Mode for parsing entities in the voice message caption. See formatting options for more details.
- **disable_notification** (bool) – Sends the message silently. Users will receive a notification with no sound.
- **reply_to_message_id** (int) – deprecated.
- **allow_sending_without_reply** (bool) – deprecated.
- **timeout** (int) – Timeout in seconds for the request.
- **caption_entities** (list of *telebot.types.MessageEntity*) – A JSON-serialized list of special entities that appear in the caption, which can be specified instead of parse_mode
- **protect_content** (bool) – Protects the contents of the sent message from forwarding and saving
- **message_thread_id** (int) – Identifier of a message thread, in which the message will be sent
- **reply_parameters** (*telebot.types.ReplyParameters*) – Reply parameters.
- **business_connection_id** (str) – Identifier of a business connection, in which the message will be sent

Returns

On success, the sent Message is returned.

set_chat_administrator_custom_title(*chat_id: int | str, user_id: int, custom_title: str*) → bool

Use this method to set a custom title for an administrator in a supergroup promoted by the bot. Returns True on success.

Telegram documentation: <https://core.telegram.org/bots/api#setchatadministratorcustomtitle>

Parameters

- **chat_id** (int or str) – Unique identifier for the target chat or username of the target supergroup (in the format @supergroupusername)
- **user_id** (int) – Unique identifier of the target user

- **custom_title** (`str`) – New custom title for the administrator; 0-16 characters, emoji are not allowed

Returns

True on success.

Return type

`bool`

set_chat_description(*chat_id: int | str, description: str | None = None*) → `bool`

Use this method to change the description of a supergroup or a channel. The bot must be an administrator in the chat for this to work and must have the appropriate admin rights.

Telegram documentation: <https://core.telegram.org/bots/api#setchatdescription>

Parameters

- **chat_id** (`int` or `str`) – Unique identifier for the target chat or username of the target channel (in the format @channelusername)
- **description** (`str`) – Str: New chat description, 0-255 characters

Returns

True on success.

Return type

`bool`

set_chat_menu_button(*chat_id: int | str = None, menu_button: MenuButton = None*) → `bool`

Use this method to change the bot's menu button in a private chat, or the default menu button. Returns True on success.

Telegram documentation: <https://core.telegram.org/bots/api#setchatmenubutton>

Parameters

- **chat_id** (`int` or `str`) – Unique identifier for the target private chat. If not specified, default bot's menu button will be changed.
- **menu_button** (`telebot.types.MenuButton`) – A JSON-serialized object for the new bot's menu button. Defaults to `MenuButtonDefault`

Returns

True on success.

Return type

`bool`

set_chat_permissions(*chat_id: int | str, permissions: ChatPermissions, use_independent_chat_permissions: bool | None = None*) → `bool`

Use this method to set default chat permissions for all members. The bot must be an administrator in the group or a supergroup for this to work and must have the `can_restrict_members` admin rights.

Telegram documentation: <https://core.telegram.org/bots/api#setchatpermissions>

Parameters

- **chat_id** (`int` or `str`) – Unique identifier for the target chat or username of the target supergroup (in the format @supergroupusername)
- **permissions** (`telebot.types.ChatPermissions`) – New default chat permissions
- **use_independent_chat_permissions** (`bool`) – Pass True if chat permissions are set independently. Otherwise, the `can_send_other_messages` and

`can_add_web_page_previews` permissions will imply the `can_send_messages`, `can_send_audios`, `can_send_documents`, `can_send_photos`, `can_send_videos`, `can_send_video_notes`, and `can_send_voice_notes` permissions; the `can_send_polls` permission will imply the `can_send_messages` permission.

Returns

True on success

Return type

bool

set_chat_photo(*chat_id: int | str, photo: Any*) → bool

Use this method to set a new profile photo for the chat. Photos can't be changed for private chats. The bot must be an administrator in the chat for this to work and must have the appropriate admin rights. Returns True on success. Note: In regular groups (non-supergroups), this method will only work if the 'All Members Are Admins' setting is off in the target group.

Telegram documentation: <https://core.telegram.org/bots/api#setchatphoto>

Parameters

- **chat_id** (int or str) – Int or Str: Unique identifier for the target chat or username of the target channel (in the format @channelusername)
- **photo** (typing.Union[file_like, str]) – InputFile: New chat photo, uploaded using multipart/form-data

Returns

True on success.

Return type

bool

set_chat_sticker_set(*chat_id: int | str, sticker_set_name: str*) → *StickerSet*

Use this method to set a new group sticker set for a supergroup. The bot must be an administrator in the chat for this to work and must have the appropriate administrator rights. Use the field `can_set_sticker_set` optionally returned in `getChat` requests to check if the bot can use this method. Returns True on success.

Telegram documentation: <https://core.telegram.org/bots/api#setchatstickerset>

Parameters

- **chat_id** (int or str) – Unique identifier for the target chat or username of the target supergroup (in the format @supergroupusername)
- **sticker_set_name** (str) – Name of the sticker set to be set as the group sticker set

Returns

StickerSet object

Return type

telebot.types.StickerSet

set_chat_title(*chat_id: int | str, title: str*) → bool

Use this method to change the title of a chat. Titles can't be changed for private chats. The bot must be an administrator in the chat for this to work and must have the appropriate admin rights. Returns True on success. Note: In regular groups (non-supergroups), this method will only work if the 'All Members Are Admins' setting is off in the target group.

Telegram documentation: <https://core.telegram.org/bots/api#setchattitle>

Parameters

- **chat_id** (int or str) – Unique identifier for the target chat or username of the target channel (in the format @channelusername)
- **title** (str) – New chat title, 1-255 characters

Returns

True on success.

Return type

bool

set_custom_emoji_sticker_set_thumbnail(*name: str, custom_emoji_id: str | None = None*) → bool

Use this method to set the thumbnail of a custom emoji sticker set. Returns True on success.

Parameters

- **name** (str) – Sticker set name
- **custom_emoji_id** (str) – Custom emoji identifier of a sticker from the sticker set; pass an empty string to drop the thumbnail and use the first sticker as the thumbnail.

Returns

Returns True on success.

Return type

bool

set_game_score(*user_id: int | str, score: int, force: bool | None = None, chat_id: int | str | None = None, message_id: int | None = None, inline_message_id: str | None = None, disable_edit_message: bool | None = None*) → *Message* | bool

Sets the value of points in the game to a specific user.

Telegram documentation: <https://core.telegram.org/bots/api#setgamescore>

Parameters

- **user_id** (int or str) – User identifier
- **score** (int) – New score, must be non-negative
- **force** (bool) – Pass True, if the high score is allowed to decrease. This can be useful when fixing mistakes or banning cheaters
- **chat_id** (int or str) – Required if inline_message_id is not specified. Unique identifier for the target chat or username of the target channel (in the format @channelusername)
- **message_id** (int) – Required if inline_message_id is not specified. Identifier of the sent message
- **inline_message_id** (str) – Required if chat_id and message_id are not specified. Identifier of the inline message
- **disable_edit_message** (bool) – Pass True, if the game message should not be automatically edited to include the current scoreboard

Returns

On success, if the message was sent by the bot, returns the edited Message, otherwise returns True.

Return type

types.Message or bool

set_message_reaction(*chat_id*: int | str, *message_id*: int, *reaction*: List[ReactionType] | None = None, *is_big*: bool | None = None) → bool

Use this method to change the chosen reactions on a message. Service messages can't be reacted to. Automatically forwarded messages from a channel to its discussion group have the same available reactions as messages in the channel. Returns True on success.

Telegram documentation: <https://core.telegram.org/bots/api#setmessagereaction>

Parameters

- **chat_id** (int or str) – Unique identifier for the target chat or username of the target supergroup or channel (in the format @channelusername)
- **message_id** (int) – Identifier of the message to set reaction to
- **reaction** (list of `telebot.types.ReactionType`) – New list of reaction types to set on the message. Currently, as non-premium users, bots can set up to one reaction per message. A custom emoji reaction can be used if it is either already present on the message or explicitly allowed by chat administrators.
- **is_big** (bool) – Pass True to set the reaction with a big animation

Returns

bool

set_my_commands(*commands*: List[BotCommand], *scope*: BotCommandScope | None = None, *language_code*: str | None = None) → bool

Use this method to change the list of the bot's commands.

Telegram documentation: <https://core.telegram.org/bots/api#setmycommands>

Parameters

- **commands** (list of `telebot.types.BotCommand`) – List of BotCommand. At most 100 commands can be specified.
- **scope** (`telebot.types.BotCommandScope`) – The scope of users for which the commands are relevant. Defaults to BotCommandScopeDefault.
- **language_code** (str) – A two-letter ISO 639-1 language code. If empty, commands will be applied to all users from the given scope, for whose language there are no dedicated commands

Returns

True on success.

Return type

bool

set_my_default_administrator_rights(*rights*: ChatAdministratorRights = None, *for_channels*: bool | None = None) → bool

Use this method to change the default administrator rights requested by the bot when it's added as an administrator to groups or channels. These rights will be suggested to users, but they are free to modify the list before adding the bot. Returns True on success.

Telegram documentation: <https://core.telegram.org/bots/api#setmydefaultadministratorrights>

Parameters

- **rights** (`telebot.types.ChatAdministratorRights`) – A JSON-serialized object describing new default administrator rights. If not specified, the default administrator rights will be cleared.

- **for_channels** (bool) – Pass True to change the default administrator rights of the bot in channels. Otherwise, the default administrator rights of the bot for groups and supergroups will be changed.

Returns

True on success.

Return type

bool

set_my_description(*description: str | None = None, language_code: str | None = None*)

Use this method to change the bot's description, which is shown in the chat with the bot if the chat is empty. Returns True on success.

Telegram documentation: <https://core.telegram.org/bots/api#setmydescription>

Parameters

- **description** (str) – New bot description; 0-512 characters. Pass an empty string to remove the dedicated description for the given language.
- **language_code** (str) – A two-letter ISO 639-1 language code. If empty, the description will be applied to all users for whose language there is no dedicated description.

Returns

True on success.

set_my_name(*name: str | None = None, language_code: str | None = None*)

Use this method to change the bot's name. Returns True on success.

Telegram documentation: <https://core.telegram.org/bots/api#setmyname>

Parameters

- **name** (str) – Optional. New bot name; 0-64 characters. Pass an empty string to remove the dedicated name for the given language.
- **language_code** (str) – Optional. A two-letter ISO 639-1 language code. If empty, the name will be shown to all users for whose language there is no dedicated name.

Returns

True on success.

set_my_short_description(*short_description: str | None = None, language_code: str | None = None*)

Use this method to change the bot's short description, which is shown on the bot's profile page and is sent together with the link when users share the bot. Returns True on success.

Telegram documentation: <https://core.telegram.org/bots/api#setmyshortdescription>

Parameters

- **short_description** (str) – New short description for the bot; 0-120 characters. Pass an empty string to remove the dedicated short description for the given language.
- **language_code** (str) – A two-letter ISO 639-1 language code. If empty, the short description will be applied to all users for whose language there is no dedicated short description.

Returns

True on success.

set_state(*user_id: int, state: int | str | State, chat_id: int | None = None*) → None

Sets a new state of a user.

Note: You should set both user id and chat id in order to set state for a user in a chat. Otherwise, if you only set user_id, chat_id will equal to user_id, this means that state will be set for the user in his private chat with a bot.

Parameters

- **user_id** (int) – User’s identifier
- **state** (int or str or telebot.types.State) – new state. can be string, integer, or telebot.types.State
- **chat_id** (int) – Chat’s identifier

Returns

None

set_sticker_emoji_list(*sticker: str, emoji_list: List[str]*) → bool

Use this method to set the emoji list of a custom emoji sticker set. Returns True on success.

Parameters

- **sticker** (str) – Sticker identifier
- **emoji_list** (list of str) – List of emoji

Returns

Returns True on success.

Return type

bool

set_sticker_keywords(*sticker: str, keywords: List[str] = None*) → bool

Use this method to change search keywords assigned to a regular or custom emoji sticker. The sticker must belong to a sticker set created by the bot. Returns True on success.

Parameters

- **sticker** (str) – File identifier of the sticker.
- **keywords** (list of str) – A JSON-serialized list of 0-20 search keywords for the sticker with total length of up to 64 characters

Returns

On success, True is returned.

Return type

bool

set_sticker_mask_position(*sticker: str, mask_position: MaskPosition = None*) → bool

Use this method to change the mask position of a mask sticker. The sticker must belong to a sticker set that was created by the bot. Returns True on success.

Parameters

- **sticker** (str) – File identifier of the sticker.
- **mask_position** (telebot.types.MaskPosition) – A JSON-serialized object for position where the mask should be placed on faces.

Returns

Returns True on success.

Return type

bool

set_sticker_position_in_set(*sticker: str, position: int*) → bool

Use this method to move a sticker in a set created by the bot to a specific position . Returns True on success.

Telegram documentation: <https://core.telegram.org/bots/api#setstickerpositioninset>

Parameters

- **sticker** (str) – File identifier of the sticker
- **position** (int) – New sticker position in the set, zero-based

Returns

On success, True is returned.

Return type

bool

set_sticker_set_thumb(***kwargs*)

set_sticker_set_thumbnail(*name: str, user_id: int, thumbnail: Any | str = None, format: str | None = None*) → bool

Use this method to set the thumbnail of a sticker set. Animated thumbnails can be set for animated sticker sets only. Returns True on success.

Telegram documentation: <https://core.telegram.org/bots/api#setstickersetthumbnail>

Parameters

- **name** (str) – Sticker set name
- **user_id** (int) – User identifier
- **thumbnail** (filelike object) – A .WEBP or .PNG image with the thumbnail, must be up to 128 kilobytes in size and have a width and height of exactly 100px, or a .TGS animation with a thumbnail up to 32 kilobytes in size (see <https://core.telegram.org/stickers#animated-sticker-requirements> for animated sticker technical requirements), or a WEBM video with the thumbnail up to 32 kilobytes in size; see <https://core.telegram.org/stickers#video-sticker-requirements> for video sticker technical requirements. Pass a file_id as a String to send a file that already exists on the Telegram servers, pass an HTTP URL as a String for Telegram to get a file from the Internet, or upload a new one using multipart/form-data. More information on Sending Files ». Animated and video sticker set thumbnails can't be uploaded via HTTP URL. If omitted, then the thumbnail is dropped and the first sticker is used as the thumbnail.
- **format** (str) – Format of the thumbnail, must be one of “static” for a .WEBP or .PNG image, “animated” for a .TGS animation, or “video” for a WEBM video

Returns

On success, True is returned.

Return type

bool

set_sticker_set_title(*name: str, title: str*) → bool

Use this method to set the title of a created sticker set. Returns True on success.

Parameters

- **name** (*str*) – Sticker set name
- **title** (*str*) – New sticker set title

Returns

Returns True on success.

Return type

bool

set_update_listener(*listener: Callable*)

Sets a listener function to be called when a new update is received.

Parameters

listener (*Callable*) – Listener function.

set_webhook(*url: str | None = None, certificate: str | Any | None = None, max_connections: int | None = None, allowed_updates: List[str] | None = None, ip_address: str | None = None, drop_pending_updates: bool | None = None, timeout: int | None = None, secret_token: str | None = None*) → bool

Use this method to specify a URL and receive incoming updates via an outgoing webhook. Whenever there is an update for the bot, we will send an HTTPS POST request to the specified URL, containing a JSON-serialized Update. In case of an unsuccessful request, we will give up after a reasonable amount of attempts. Returns True on success.

If you'd like to make sure that the webhook was set by you, you can specify secret data in the parameter `secret_token`. If specified, the request will contain a header "X-Telegram-Bot-Api-Secret-Token" with the secret token as content.

Telegram Documentation: <https://core.telegram.org/bots/api#setwebhook>

Parameters

- **url** (*str*, optional) – HTTPS URL to send updates to. Use an empty string to remove webhook integration, defaults to None
- **certificate** (*str*, optional) – Upload your public key certificate so that the root certificate in use can be checked, defaults to None
- **max_connections** (*int*, optional) – The maximum allowed number of simultaneous HTTPS connections to the webhook for update delivery, 1-100. Defaults to 40. Use lower values to limit the load on your bot's server, and higher values to increase your bot's throughput, defaults to None
- **allowed_updates** (*list*, optional) – A JSON-serialized list of the update types you want your bot to receive. For example, specify ["message", "edited_channel_post", "callback_query"] to only receive updates of these types. See Update for a complete list of available update types. Specify an empty list to receive all update types except chat_member (default). If not specified, the previous setting will be used.

Please note that this parameter doesn't affect updates created before the call to the setWebhook, so unwanted updates may be received for a short period of time. Defaults to None

- **ip_address** (*str*, optional) – The fixed IP address which will be used to send webhook requests instead of the IP address resolved through DNS, defaults to None
- **drop_pending_updates** (*bool*, optional) – Pass True to drop all pending updates, defaults to None
- **timeout** (*int*, optional) – Timeout of a request, defaults to None

- **secret_token** (str, optional) – A secret token to be sent in a header “X-Telegram-Bot-Api-Secret-Token” in every webhook request, 1-256 characters. Only characters A-Z, a-z, 0-9, _ and - are allowed. The header is useful to ensure that the request comes from a webhook set by you. Defaults to None

Returns

True on success.

Return type

bool if the request was successful.

setup_middleware(*middleware*: [BaseMiddleware](#))

Registers class-based middleware.

Parameters

middleware ([telebot.handler_backends.BaseMiddleware](#)) – Subclass of [telebot.handler_backends.BaseMiddleware](#)

Returns

None

shipping_query_handler(*func*, ***kwargs*)

Handles new incoming shipping query. Only for invoices with flexible price. As a parameter to the decorator function, it passes [telebot.types.ShippingQuery](#) object.

Parameters

- **func** (function) – Function executed as a filter
- **kwargs** – Optional keyword arguments(custom filters)

Returns

None

stop_bot()

Stops bot by stopping polling and closing the worker pool.

stop_message_live_location(*chat_id*: int | str | None = None, *message_id*: int | None = None, *inline_message_id*: str | None = None, *reply_markup*: [InlineKeyboardMarkup](#) | None = None, *timeout*: int | None = None) → [Message](#)

Use this method to stop updating a live location message before `live_period` expires. On success, if the message is not an inline message, the edited [Message](#) is returned, otherwise True is returned.

Telegram documentation: <https://core.telegram.org/bots/api#stopmessagelivelocation>

Parameters

- **chat_id** (int or str) – Unique identifier for the target chat or username of the target channel (in the format @channelusername)
- **message_id** (int) – Required if `inline_message_id` is not specified. Identifier of the message with live location to stop
- **inline_message_id** (str) – Required if `chat_id` and `message_id` are not specified. Identifier of the inline message with live location to stop
- **reply_markup** ([telebot.types.InlineKeyboardMarkup](#) or [telebot.types.ReplyKeyboardMarkup](#) or [telebot.types.ReplyKeyboardRemove](#) or [telebot.types.ForceReply](#)) – A JSON-serialized object for a new inline keyboard.
- **timeout** (int) – Timeout in seconds for the request.

Returns

On success, if the message is not an inline message, the edited Message is returned, otherwise True is returned.

Return type

telebot.types.Message or bool

stop_poll(*chat_id: int | str, message_id: int, reply_markup: InlineKeyboardMarkup | None = None*) → *Poll*

Use this method to stop a poll which was sent by the bot. On success, the stopped Poll is returned.

Telegram documentation: <https://core.telegram.org/bots/api#stoppoll>

Parameters

- **chat_id** (*int | str*) – Unique identifier for the target chat or username of the target channel
- **message_id** (*int*) – Identifier of the original message with the poll
- **reply_markup** (*InlineKeyboardMarkup*) – A JSON-serialized object for a new message markup.

Returns

On success, the stopped Poll is returned.

Return type

types.Poll

stop_polling()

Stops polling.

Does not accept any arguments.

unban_chat_member(*chat_id: int | str, user_id: int, only_if_banned: bool | None = False*) → bool

Use this method to unban a previously kicked user in a supergroup or channel. The user will not return to the group or channel automatically, but will be able to join via link, etc. The bot must be an administrator for this to work. By default, this method guarantees that after the call the user is not a member of the chat, but will be able to join it. So if the user is a member of the chat they will also be removed from the chat. If you don't want this, use the parameter *only_if_banned*.

Telegram documentation: <https://core.telegram.org/bots/api#unbanchatmember>

Parameters

- **chat_id** (*int or str*) – Unique identifier for the target group or username of the target supergroup or channel (in the format @username)
- **user_id** (*int*) – Unique identifier of the target user
- **only_if_banned** (*bool*) – Do nothing if the user is not banned

Returns

True on success

Return type

bool

unban_chat_sender_chat(*chat_id: int | str, sender_chat_id: int | str*) → bool

Use this method to unban a previously banned channel chat in a supergroup or channel. The bot must be an administrator for this to work and must have the appropriate administrator rights. Returns True on success.

Telegram documentation: <https://core.telegram.org/bots/api#unbanchatsenderchat>

Parameters

- **chat_id** (int or str) – Unique identifier for the target chat or username of the target channel (in the format @channelusername)
- **sender_chat_id** (int or str) – Unique identifier of the target sender chat.

Returns

True on success.

Return type

bool

unhide_general_forum_topic(*chat_id: int | str*) → bool

Use this method to unhide the ‘General’ topic in a forum supergroup chat. The bot must be an administrator in the chat for this to work and must have can_manage_topics administrator rights. Returns True on success.

Telegram documentation: <https://core.telegram.org/bots/api#unhidegeneralforumtopic>

Parameters

chat_id (int or str) – Unique identifier for the target chat or username of the target channel (in the format @channelusername)

unpin_all_chat_messages(*chat_id: int | str*) → bool

Use this method to unpin a all pinned messages in a supergroup chat. The bot must be an administrator in the chat for this to work and must have the appropriate admin rights. Returns True on success.

Telegram documentation: <https://core.telegram.org/bots/api#unpinallchatmessages>

Parameters

chat_id (int or str) – Int or Str: Unique identifier for the target chat or username of the target channel (in the format @channelusername)

Returns

True on success.

Return type

bool

unpin_all_forum_topic_messages(*chat_id: str | int, message_thread_id: int*) → bool

Use this method to clear the list of pinned messages in a forum topic. The bot must be an administrator in the chat for this to work and must have the can_pin_messages administrator right in the supergroup. Returns True on success.

Telegram documentation: <https://core.telegram.org/bots/api#unpinallforumtopicmessages>

Parameters

- **chat_id** (int or str) – Unique identifier for the target chat or username of the target channel (in the format @channelusername)
- **message_thread_id** (int) – Identifier of the topic

Returns

On success, True is returned.

Return type

bool

unpin_all_general_forum_topic_messages(*chat_id: int | str*) → bool

Use this method to clear the list of pinned messages in a General forum topic. The bot must be an administrator in the chat for this to work and must have the can_pin_messages administrator right in the supergroup. Returns True on success.

Telegram documentation: <https://core.telegram.org/bots/api#unpinAllGeneralForumTopicMessages>

Parameters

chat_id (int | str) – Unique identifier for the target chat or username of chat

Returns

On success, True is returned.

Return type

bool

unpin_chat_message(*chat_id: int | str, message_id: int | None = None*) → bool

Use this method to unpin specific pinned message in a supergroup chat. The bot must be an administrator in the chat for this to work and must have the appropriate admin rights. Returns True on success.

Telegram documentation: <https://core.telegram.org/bots/api#unpinchatmessage>

Parameters

- **chat_id** (int or str) – Unique identifier for the target chat or username of the target channel (in the format @channelusername)
- **message_id** (int) – Int: Identifier of a message to unpin

Returns

True on success.

Return type

bool

upload_sticker_file(*user_id: int, png_sticker: Any | str = None, sticker: InputFile | None = None, sticker_format: str | None = None*) → File

Use this method to upload a .png file with a sticker for later use in `createNewStickerSet` and `addStickerToSet` methods (can be used multiple times). Returns the uploaded File on success.

Telegram documentation: <https://core.telegram.org/bots/api#uploadstickerfile>

Parameters

- **user_id** (int) – User identifier of sticker set owner
- **png_sticker** (filelike object) – DEPRECATED: PNG image with the sticker, must be up to 512 kilobytes in size, dimensions must not exceed 512px, and either width or height must be exactly 512px.
- **sticker** (*telebot.types.InputFile*) – A file with the sticker in .WEBP, .PNG, .TGS, or .WEBM format. See <https://core.telegram.org/stickers> for technical requirements. More information on Sending Files »
- **sticker_format** (str) – One of “static”, “animated”, “video”.

Returns

On success, the sent file is returned.

Return type

telebot.types.File

property user: *User*

The User object representing this bot. Equivalent to `bot.get_me()` but the result is cached so only one API call is needed.

Returns

Bot’s info.

Return type

telebot.types.User

custom_filters file**class telebot.custom_filters.AdvancedCustomFilter**

Bases: ABC

Advanced Custom Filter base class. Create child class with check() method. Accepts two parameters, returns bool: True - filter passed, False - filter failed. message: Message class text: Filter value given in handler

Child classes should have .key property.

Listing 9: Example on creating an advanced custom filter.

```
class TextStartsFilter(AdvancedCustomFilter):
    # Filter to check whether message starts with some text.
    key = 'text_startswith'

    def check(self, message, text):
        return message.text.startswith(text)
```

check(message, text)

Perform a check.

key: str = None

class telebot.custom_filters.ChatFilterBases: *AdvancedCustomFilter*

Check whether chat_id corresponds to given chat_id.

Listing 10: Example on using this filter:

```
@bot.message_handler(chat_id=[99999])
# your function
```

key: str = 'chat_id'

class telebot.custom_filters.ForwardFilterBases: *SimpleCustomFilter*

Check whether message was forwarded from channel or group.

Listing 11: Example on using this filter:

```
@bot.message_handler(is_forwarded=True)
# your function
```

key: str = 'is_forwarded'

class telebot.custom_filters.IsAdminFilter(bot)Bases: *SimpleCustomFilter*

Check whether the user is administrator / owner of the chat.

Listing 12: Example on using this filter:

```
@bot.message_handler(chat_types=['supergroup'], is_chat_admin=True)
# your function
```

```
key: str = 'is_chat_admin'
```

```
class telebot.custom_filters.IsDigitFilter
```

Bases: *SimpleCustomFilter*

Filter to check whether the string is made up of only digits.

Listing 13: Example on using this filter:

```
@bot.message_handler(is_digit=True)
# your function
```

```
key: str = 'is_digit'
```

```
class telebot.custom_filters.IsReplyFilter
```

Bases: *SimpleCustomFilter*

Check whether message is a reply.

Listing 14: Example on using this filter:

```
@bot.message_handler(is_reply=True)
# your function
```

```
key: str = 'is_reply'
```

```
class telebot.custom_filters.LanguageFilter
```

Bases: *AdvancedCustomFilter*

Check users language_code.

Listing 15: Example on using this filter:

```
@bot.message_handler(language_code=['ru'])
# your function
```

```
key: str = 'language_code'
```

```
class telebot.custom_filters.SimpleCustomFilter
```

Bases: ABC

Simple Custom Filter base class. Create child class with check() method. Accepts only message, returns bool value, that is compared with given in handler.

Child classes should have .key property.

Listing 16: Example on creating a simple custom filter.

```
class ForwardFilter(SimpleCustomFilter):
    # Check whether message was forwarded from channel or group.
    key = 'is_forwarded'

    def check(self, message):
        return message.forward_date is not None
```

```
check(message)
```

Perform a check.

key: `str = None`

class `telebot.custom_filters.StateFilter`(*bot*)

Bases: *AdvancedCustomFilter*

Filter to check state.

Listing 17: Example on using this filter:

```
@bot.message_handler(state=1)
# your function
```

key: `str = 'state'`

class `telebot.custom_filters.TextContainsFilter`

Bases: *AdvancedCustomFilter*

Filter to check Text message. key: text

Listing 18: Example on using this filter:

```
# Will respond if any message.text contains word 'account'
@bot.message_handler(text_contains=['account'])
# your function
```

key: `str = 'text_contains'`

class `telebot.custom_filters.TextFilter`(*equals: str | None = None, contains: list | tuple | None = None, starts_with: str | list | tuple | None = None, ends_with: str | list | tuple | None = None, ignore_case: bool = False*)

Bases: `object`

Advanced text filter to check (`types.Message`, `types.CallbackQuery`, `types.InlineQuery`, `types.Poll`)

example of usage is in `examples/custom_filters/advanced_text_filter.py`

Parameters

- **equals** (`str`) – string, True if object's text is equal to passed string
- **contains** (`list[str]` or `tuple[str]`) – `list[str]` or `tuple[str]`, True if any string element of iterable is in text
- **starts_with** (`str`) – string, True if object's text starts with passed string
- **ends_with** (`str`) – string, True if object's text starts with passed string
- **ignore_case** (`bool`) – `bool` (default `False`), case insensitive

Raises

ValueError – if incorrect value for a parameter was supplied

Returns

`None`

class `telebot.custom_filters.TextMatchFilter`

Bases: *AdvancedCustomFilter*

Filter to check Text message.

Listing 19: Example on using this filter:

```
@bot.message_handler(text=['account'])
# your function
```

key: str = 'text'

class telebot.custom_filters.TextStartsFilter

Bases: *AdvancedCustomFilter*

Filter to check whether message starts with some text.

Listing 20: Example on using this filter:

```
# Will work if message.text starts with 'sir'.
@bot.message_handler(text_startswith='sir')
# your function
```

key: str = 'text_startswith'

handler_backends file

class telebot.handler_backends.BaseMiddleware

Bases: object

Base class for middleware. Your middlewares should be inherited from this class.

Set `update_sensitive=True` if you want to get different updates on different functions. For example, if you want to handle `pre_process` for message update, then you will have to create `pre_process_message` function, and so on. Same applies to `post_process`.

Note: If you want to use middleware, you have to set `use_class_middlewares=True` in your TeleBot instance.

Listing 21: Example of class-based middlewares.

```
class MyMiddleware(BaseMiddleware):
    def __init__(self):
        self.update_sensitive = True
        self.update_types = ['message', 'edited_message']

    def pre_process_message(self, message, data):
        # only message update here
        pass

    def post_process_message(self, message, data, exception):
        pass # only message update here for post_process

    def pre_process_edited_message(self, message, data):
        # only edited_message update here
        pass

    def post_process_edited_message(self, message, data, exception):
        pass # only edited_message update here for post_process
```

`post_process(message, data, exception)`

`pre_process(message, data)`

`update_sensitive: bool = False`

class telebot.handler_backends.**CancelUpdate**

Bases: object

Class for canceling updates. Just return instance of this class in middleware to skip update. Update will skip handler and execution of `post_process` in middlewares.

class telebot.handler_backends.**ContinueHandling**

Bases: object

Class for continue updates in handlers. Just return instance of this class in handlers to continue process.

Listing 22: Example of using ContinueHandling

```
@bot.message_handler(commands=['start'])
def start(message):
    bot.send_message(message.chat.id, 'Hello World!')
    return ContinueHandling()

@bot.message_handler(commands=['start'])
def start2(message):
    bot.send_message(message.chat.id, 'Hello World2!')
```

class telebot.handler_backends.**SkipHandler**

Bases: object

Class for skipping handlers. Just return instance of this class in middleware to skip handler. Update will go to `post_process`, but will skip execution of handler.

class telebot.handler_backends.**State**

Bases: object

Class representing a state.

```
class MyStates(StatesGroup):
    my_state = State() # returns my_state:State string.
```

class telebot.handler_backends.**StatesGroup**

Bases: object

Class representing common states.

```
class MyStates(StatesGroup):
    my_state = State() # returns my_state:State string.
```

classmethod `state_list()`

Extensions

1.3.5 AsyncTeleBot

AsyncTeleBot methods

```
class telebot.async_telebot.AsyncTeleBot(token: str, parse_mode: str | None = None, offset: int | None = None, exception_handler: ~telebot.async_telebot.ExceptionHandler | None = None, state_storage: ~telebot.asyncio_storage.base_storage.StateStorageBase | None = <telebot.asyncio_storage.memory_storage.StateMemoryStorage object>, disable_web_page_preview: bool | None = None, disable_notification: bool | None = None, protect_content: bool | None = None, allow_sending_without_reply: bool | None = None, colorful_logs: bool | None = False)
```

Bases: object

This is the main asynchronous class for Bot.

It allows you to add handlers for different kind of updates.

Usage:

Listing 23: Using asynchronous implementation of TeleBot.

```
from telebot.async_telebot import AsyncTeleBot
bot = AsyncTeleBot('token') # get token from @BotFather
# now you can register other handlers/update listeners,
# and use bot methods.
# Remember to use async/await keywords when necessary.
```

See more examples in examples/ directory: <https://github.com/eternnoir/pyTelegramBotAPI/tree/master/examples>

Note: Install coloredlogs module to specify colorful_logs=True

Parameters

- **token** (str) – Token of a bot, obtained from @BotFather
- **parse_mode** (str, optional) – Default parse mode, defaults to None
- **offset** (int, optional) – Offset used in get_updates, defaults to None
- **exception_handler** (*Optional [ExceptionHandler], optional*) – Exception handler, which will handle the exception occurred, defaults to None
- **state_storage** (telebot.asyncio_storage.StateMemoryStorage, optional) – Storage for states, defaults to StateMemoryStorage()
- **disable_web_page_preview** (bool, optional) – Default value for disable_web_page_preview, defaults to None
- **disable_notification** (bool, optional) – Default value for disable_notification, defaults to None

- **protect_content** (bool, optional) – Default value for protect_content, defaults to None
- **allow_sending_without_reply** (bool, optional) – Deprecated - Use reply_parameters instead. Default value for allow_sending_without_reply, defaults to None
- **colorful_logs** (bool, optional) – Outputs colorful logs

add_custom_filter(*custom_filter*: SimpleCustomFilter | AdvancedCustomFilter)

Create custom filter.

Listing 24: Example on checking the text of a message

```
class TextMatchFilter(AdvancedCustomFilter):
    key = 'text'

    async def check(self, message, text):
        return text == message.text
```

Parameters

custom_filter (*telebot.asyncio_filters.SimpleCustomFilter* or *telebot.asyncio_filters.AdvancedCustomFilter*) – Class with check(message) method.

Returns

None

async add_data(*user_id*: int, *chat_id*: int | None = None, ***kwargs*)

Add data to states.

Parameters

- **user_id** (int) – User’s identifier
- **chat_id** (int) – Chat’s identifier
- **kwargs** – Data to add

Returns

None

async add_sticker_to_set(*user_id*: int, *name*: str, *emojis*: List[str] | str = None, *png_sticker*: str | Any | None = None, *tgsticker*: str | Any | None = None, *webm_sticker*: str | Any | None = None, *mask_position*: MaskPosition | None = None, *sticker*: InputSticker | None = None) → bool

Use this method to add a new sticker to a set created by the bot. The format of the added sticker must match the format of the other stickers in the set. Emoji sticker sets can have up to 200 stickers. Animated and video sticker sets can have up to 50 stickers. Static sticker sets can have up to 120 stickers. Returns True on success.

Note: ***_sticker*, *mask_position*, *emojis* parameters are deprecated, use stickers instead

Telegram documentation: <https://core.telegram.org/bots/api#addstickertoset>

Parameters

- **user_id** (int) – User identifier of created sticker set owner
- **name** (str) – Sticker set name
- **emojis** (str) – One or more emoji corresponding to the sticker

- **png_sticker** (str or filelike object) – PNG image with the sticker, must be up to 512 kilobytes in size, dimensions must not exceed 512px, and either width or height must be exactly 512px. Pass a file_id as a String to send a file that already exists on the Telegram servers, pass an HTTP URL as a String for Telegram to get a file from the Internet, or upload a new one using multipart/form-data.
- **tgs_sticker** (str or filelike object) – TGS animation with the sticker, uploaded using multipart/form-data.
- **webm_sticker** (str or filelike object) – WebM animation with the sticker, uploaded using multipart/form-data.
- **mask_position** (*telebot.types.MaskPosition*) – A JSON-serialized object for position where the mask should be placed on faces
- **sticker** (*telebot.types.InputSticker*) – A JSON-serialized object for sticker to be added to the sticker set

Returns

On success, True is returned.

Return type

bool

async answer_callback_query(*callback_query_id: int, text: str | None = None, show_alert: bool | None = None, url: str | None = None, cache_time: int | None = None*) → bool

Use this method to send answers to callback queries sent from inline keyboards. The answer will be displayed to the user as a notification at the top of the chat screen or as an alert.

Telegram documentation: <https://core.telegram.org/bots/api#answercallbackquery>

Parameters

- **callback_query_id** (int) – Unique identifier for the query to be answered
- **text** (str) – Text of the notification. If not specified, nothing will be shown to the user, 0-200 characters
- **show_alert** (bool) – If True, an alert will be shown by the client instead of a notification at the top of the chat screen. Defaults to false.
- **url** (str) – URL that will be opened by the user's client. If you have created a Game and accepted the conditions via @BotFather, specify the URL that opens your game - note that this will only work if the query comes from a callback_game button.
- **cache_time** – The maximum amount of time in seconds that the result of the callback query may be cached client-side. Telegram apps will support caching starting in version 3.14. Defaults to 0.

Returns

On success, True is returned.

Return type

bool

async answer_inline_query(*inline_query_id: str, results: List[Any], cache_time: int | None = None, is_personal: bool | None = None, next_offset: str | None = None, switch_pm_text: str | None = None, switch_pm_parameter: str | None = None, button: InlineQueryResultsButton | None = None*) → bool

Use this method to send answers to an inline query. On success, True is returned. No more than 50 results per query are allowed.

Telegram documentation: <https://core.telegram.org/bots/api#answerinlinequery>

Parameters

- **inline_query_id** (str) – Unique identifier for the answered query
- **results** (list of types.InlineQueryResult) – Array of results for the inline query
- **cache_time** (int) – The maximum amount of time in seconds that the result of the inline query may be cached on the server.
- **is_personal** (bool) – Pass True, if results may be cached on the server side only for the user that sent the query.
- **next_offset** (str) – Pass the offset that a client should send in the next query with the same text to receive more results.
- **switch_pm_parameter** (str) – Deep-linking parameter for the /start message sent to the bot when user presses the switch button. 1-64 characters, only A-Z, a-z, 0-9, _ and - are allowed. Example: An inline bot that sends YouTube videos can ask the user to connect the bot to their YouTube account to adapt search results accordingly. To do this, it displays a ‘Connect your YouTube account’ button above the results, or even before showing any. The user presses the button, switches to a private chat with the bot and, in doing so, passes a start parameter that instructs the bot to return an OAuth link. Once done, the bot can offer a switch_inline button so that the user can easily return to the chat where they wanted to use the bot’s inline capabilities.
- **switch_pm_text** (str) – Parameter for the start message sent to the bot when user presses the switch button
- **button** (types.InlineQueryResultsButton) – A JSON-serialized object describing a button to be shown above inline query results

Returns

On success, True is returned.

Return type

bool

async answer_pre_checkout_query(*pre_checkout_query_id: int, ok: bool, error_message: str | None = None*) → bool

Once the user has confirmed their payment and shipping details, the Bot API sends the final confirmation in the form of an Update with the field `pre_checkout_query`. Use this method to respond to such pre-checkout queries. On success, True is returned.

Note: The Bot API must receive an answer within 10 seconds after the pre-checkout query was sent.

Telegram documentation: <https://core.telegram.org/bots/api#answerprecheckoutquery>

Parameters

- **pre_checkout_query_id** (int) – Unique identifier for the query to be answered
- **ok** (bool) – Specify True if everything is alright (goods are available, etc.) and the bot is ready to proceed with the order. Use False if there are any problems.
- **error_message** (str) – Required if ok is False. Error message in human readable form that explains the reason for failure to proceed with the checkout (e.g. “Sorry, somebody just bought the last of our amazing black T-shirts while you were busy filling out your payment details. Please choose a different color or garment!”). Telegram will display this message to the user.

Returns

On success, True is returned.

Return type

bool

async answer_shipping_query(*shipping_query_id: str, ok: bool, shipping_options: List[ShippingOption] | None = None, error_message: str | None = None*) → bool

Asks for an answer to a shipping question.

Telegram documentation: <https://core.telegram.org/bots/api#answershippingquery>

Parameters

- **shipping_query_id** (str) – Unique identifier for the query to be answered
- **ok** (bool) – Specify True if delivery to the specified address is possible and False if there are any problems (for example, if delivery to the specified address is not possible)
- **shipping_options** (list of ShippingOption) – Required if ok is True. A JSON-serialized array of available shipping options.
- **error_message** (str) – Required if ok is False. Error message in human readable form that explains why it is impossible to complete the order (e.g. “Sorry, delivery to your desired address is unavailable”). Telegram will display this message to the user.

Returns

On success, True is returned.

Return type

bool

async answer_web_app_query(*web_app_query_id: str, result: InlineQueryResultBase*) → *SentWebAppMessage*

Use this method to set the result of an interaction with a Web App and send a corresponding message on behalf of the user to the chat from which the query originated. On success, a SentWebAppMessage object is returned.

Telegram Documentation: <https://core.telegram.org/bots/api#answerwebappquery>

Parameters

- **web_app_query_id** (str) – Unique identifier for the query to be answered
- **result** (*telebot.types.InlineQueryResultBase*) – A JSON-serialized object describing the message to be sent

Returns

On success, a SentWebAppMessage object is returned.

Return type

telebot.types.SentWebAppMessage

async approve_chat_join_request(*chat_id: str | int, user_id: int | str*) → bool

Use this method to approve a chat join request. The bot must be an administrator in the chat for this to work and must have the can_invite_users administrator right. Returns True on success.

Telegram documentation: <https://core.telegram.org/bots/api#approvechatjoinrequest>

Parameters

- **chat_id** (int or str) – Unique identifier for the target chat or username of the target supergroup (in the format @supergroupusername)

- **user_id** (int or str) – Unique identifier of the target user

Returns

True on success.

Return type

bool

async ban_chat_member(*chat_id: int | str, user_id: int, until_date: int | datetime | None = None, revoke_messages: bool | None = None*) → bool

Use this method to ban a user in a group, a supergroup or a channel. In the case of supergroups and channels, the user will not be able to return to the chat on their own using invite links, etc., unless unbanned first. Returns True on success.

Telegram documentation: <https://core.telegram.org/bots/api#banchatmember>

Parameters

- **chat_id** (int or str) – Unique identifier for the target group or username of the target supergroup or channel (in the format @channelusername)
- **user_id** (int) – Unique identifier of the target user
- **until_date** (int or datetime) – Date when the user will be unbanned, unix time. If user is banned for more than 366 days or less than 30 seconds from the current time they are considered to be banned forever
- **revoke_messages** (bool) – Bool: Pass True to delete all messages from the chat for the user that is being removed. If False, the user will be able to see messages in the group that were sent before the user was removed. Always True for supergroups and channels.

Returns

Returns True on success.

Return type

bool

async ban_chat_sender_chat(*chat_id: int | str, sender_chat_id: int | str*) → bool

Use this method to ban a channel chat in a supergroup or a channel. The owner of the chat will not be able to send messages and join live streams on behalf of the chat, unless it is unbanned first. The bot must be an administrator in the supergroup or channel for this to work and must have the appropriate administrator rights. Returns True on success.

Telegram documentation: <https://core.telegram.org/bots/api#banchatsenderchat>

Parameters

- **chat_id** (int or str) – Unique identifier for the target chat or username of the target channel (in the format @channelusername)
- **sender_chat_id** (int or str) – Unique identifier of the target sender chat

Returns

True on success.

Return type

bool

business_connection_handler(*func=None, **kwargs*)

Handles new incoming business connection state.

Parameters

- **func** (function) – Function executed as a filter

- **kwargs** – Optional keyword arguments(custom filters)

Returns

None

business_message_handler(*commands: List[str] | None = None, regexp: str | None = None, func: Callable | None = None, content_types: List[str] | None = None, **kwargs*)

Handles New incoming message of any kind(for business accounts, see bot api 7.2 for more) - text, photo, sticker, etc. As a parameter to the decorator function, it passes `telebot.types.Message` object. All message handlers are tested in the order they were added.

Example:

Listing 25: Usage of business_message_handler

```
bot = TeleBot('TOKEN')

# Handles all messages which text matches regexp.
@bot.business_message_handler(regexp='someregexp')
def command_help(message):
    bot.send_message(message.chat.id, 'Did someone call for help?')

# Handle all sent documents of type 'text/plain'.
@bot.business_message_handler(func=lambda message: message.document.mime_type_
↪ == 'text/plain',
    content_types=['document'])
def command_handle_document(message):
    bot.send_message(message.chat.id, 'Document received, sir!')

# Handle all other messages.
@bot.business_message_handler(func=lambda message: True, content_types=['audio',
↪ 'photo', 'voice', 'video', 'document',
    'text', 'location', 'contact', 'sticker'])
def default_command(message):
    bot.send_message(message.chat.id, "This is the default command handler.")
```

Parameters

- **commands** (list of str) – Optional list of strings (commands to handle).
- **regexp** (str) – Optional regular expression.
- **func** (lambda) – Optional lambda function. The lambda receives the message to test as the first parameter. It must return True if the command should handle the message.
- **content_types** (list of str) – Supported message content types. Must be a list. Defaults to ['text'].
- **kwargs** – Optional keyword arguments(custom filters)

Returns

decorated function

callback_query_handler(*func, **kwargs*)

Handles new incoming callback query. As a parameter to the decorator function, it passes `telebot.types.CallbackQuery` object.

Parameters

- **func** (function) – Function executed as a filter
- **kwargs** – Optional keyword arguments(custom filters)

Returns

None

channel_post_handler(*commands=None, regexp=None, func=None, content_types=None, **kwargs*)

Handles new incoming channel post of any kind - text, photo, sticker, etc. As a parameter to the decorator function, it passes *telebot.types.Message* object.

Parameters

- **commands** (list of str) – Optional list of strings (commands to handle).
- **regexp** (str) – Optional regular expression.
- **func** (function) – Function executed as a filter
- **content_types** (list of str) – Supported message content types. Must be a list. Defaults to ['text'].
- **kwargs** – Optional keyword arguments(custom filters)

Returns

None

chat_boost_handler(*func=None, **kwargs*)

Handles new incoming chat boost state. it passes *telebot.types.ChatBoostUpdated* object.

Parameters

- **func** (function) – Function executed as a filter
- **kwargs** – Optional keyword arguments(custom filters)

Returns

None

chat_join_request_handler(*func=None, **kwargs*)

Handles a request to join the chat has been sent. The bot must have the *can_invite_users* administrator right in the chat to receive these updates. As a parameter to the decorator function, it passes *telebot.types.ChatJoinRequest* object.

Parameters

- **func** (function) – Function executed as a filter
- **kwargs** – Optional keyword arguments(custom filters)

Returns

None

chat_member_handler(*func=None, **kwargs*)

Handles update in a status of a user in a chat. The bot must be an administrator in the chat and must explicitly specify "chat_member" in the list of *allowed_updates* to receive these updates. As a parameter to the decorator function, it passes *telebot.types.ChatMemberUpdated* object.

Parameters

- **func** (function) – Function executed as a filter
- **kwargs** – Optional keyword arguments(custom filters)

Returns

None

chosen_inline_handler(*func*, ***kwargs*)

The result of an inline query that was chosen by a user and sent to their chat partner. Please see our documentation on the feedback collecting for details on how to enable these updates for your bot. As a parameter to the decorator function, it passes `telebot.types.ChosenInlineResult` object.

Parameters

- **func** (function) – Function executed as a filter
- **kwargs** – Optional keyword arguments(custom filters)

Returns

None

async close() → bool

Use this method to close the bot instance before moving it from one local server to another. You need to delete the webhook before calling this method to ensure that the bot isn't launched again after server restart. The method will return error 429 in the first 10 minutes after the bot is launched. Returns True on success.

Telegram documentation: <https://core.telegram.org/bots/api#close>

Returns

bool

async close_forum_topic(*chat_id: str | int, message_thread_id: int*) → bool

Use this method to close an open topic in a forum supergroup chat. The bot must be an administrator in the chat for this to work and must have the `can_manage_topics` administrator rights, unless it is the creator of the topic. Returns True on success.

Telegram documentation: <https://core.telegram.org/bots/api#closeforumtopic>

Parameters

- **chat_id** (int or str) – Unique identifier for the target chat or username of the target channel (in the format @channelusername)
- **message_thread_id** (int) – Identifier of the topic to close

Returns

On success, True is returned.

Return type

bool

async close_general_forum_topic(*chat_id: int | str*) → bool

Use this method to close the 'General' topic in a forum supergroup chat. The bot must be an administrator in the chat for this to work and must have `can_manage_topics` administrator rights. Returns True on success.

Telegram documentation: <https://core.telegram.org/bots/api#closegeneralforumtopic>

Parameters

chat_id (int or str) – Unique identifier for the target chat or username of the target channel (in the format @channelusername)

async close_session()

Closes existing session of aiohttp. Use this function if you stop polling/webhooks.

```

async copy_message(chat_id: int | str, from_chat_id: int | str, message_id: int, caption: str | None = None,
                    parse_mode: str | None = None, caption_entities: List[MessageEntity] | None =
                    None, disable_notification: bool | None = None, protect_content: bool | None = None,
                    reply_to_message_id: int | None = None, allow_sending_without_reply: bool | None
                    = None, reply_markup: InlineKeyboardMarkup | ReplyKeyboardMarkup |
                    ReplyKeyboardRemove | ForceReply | None = None, timeout: int | None = None,
                    message_thread_id: int | None = None, reply_parameters: ReplyParameters | None =
                    None) → MessageID

```

Use this method to copy messages of any kind.

Telegram documentation: <https://core.telegram.org/bots/api#copymessage>

Parameters

- **chat_id** (int or str) – Unique identifier for the target chat or username of the target channel (in the format @channelusername)
- **from_chat_id** (int or str) – Unique identifier for the chat where the original message was sent (or channel username in the format @channelusername)
- **message_id** (int) – Message identifier in the chat specified in from_chat_id
- **caption** (str) – New caption for media, 0-1024 characters after entities parsing. If not specified, the original caption is kept
- **parse_mode** (str) – Mode for parsing entities in the new caption.
- **caption_entities** (Array of *telebot.types.MessageEntity*) – A JSON-serialized list of special entities that appear in the new caption, which can be specified instead of parse_mode
- **disable_notification** (bool) – Sends the message silently. Users will receive a notification with no sound.
- **protect_content** (bool) – Protects the contents of the sent message from forwarding and saving
- **reply_to_message_id** (int) – Deprecated - Use reply_parameters instead. If the message is a reply, ID of the original message
- **allow_sending_without_reply** (bool) – Deprecated - Use reply_parameters instead. Pass True, if the message should be sent even if the specified replied-to message is not found
- **reply_markup** (*telebot.types.InlineKeyboardMarkup* or *telebot.types.ReplyKeyboardMarkup* or *telebot.types.ReplyKeyboardRemove* or *telebot.types.ForceReply*) – Additional interface options. A JSON-serialized object for an inline keyboard, custom reply keyboard, instructions to remove reply keyboard or to force a reply from the user.
- **timeout** (int) – Timeout in seconds for the request.
- **message_thread_id** (int) – Identifier of a message thread, in which the message will be sent
- **reply_parameters** (*telebot.types.ReplyParameters*) – Reply parameters.

Returns

On success, the MessageId of the sent message is returned.

Return type

telebot.types.MessageID

```
async copy_messages(chat_id: str | int, from_chat_id: str | int, message_ids: List[int],
                    disable_notification: bool | None = None, message_thread_id: int | None = None,
                    protect_content: bool | None = None, remove_caption: bool | None = None) →
                    List[MessageID]
```

Use this method to copy messages of any kind. If some of the specified messages can't be found or copied, they are skipped. Service messages, giveaway messages, giveaway winners messages, and invoice messages can't be copied. A quiz poll can be copied only if the value of the field `correct_option_id` is known to the bot. The method is analogous to the method `forwardMessages`, but the copied messages don't have a link to the original message. Album grouping is kept for copied messages. On success, an array of `MessageId` of the sent messages is returned.

Telegram documentation: <https://core.telegram.org/bots/api#copymessages>

Parameters

- **chat_id** (int or str) – Unique identifier for the target chat or username of the target channel (in the format `@channelusername`)
- **from_chat_id** (int or str) – Unique identifier for the chat where the original message was sent (or channel username in the format `@channelusername`)
- **message_ids** (list of int) – Message identifiers in the chat specified in `from_chat_id`
- **disable_notification** (bool) – Sends the message silently. Users will receive a notification with no sound
- **message_thread_id** (int) – Identifier of a message thread, in which the messages will be sent
- **protect_content** (bool) – Protects the contents of the forwarded message from forwarding and saving
- **remove_caption** (bool) – Pass True to copy the messages without their captions

Returns

On success, an array of `MessageId` of the sent messages is returned.

Return type

list of `telebot.types.MessageID`

```
async create_chat_invite_link(chat_id: int | str, name: str | None = None, expire_date: int | datetime |
                             None = None, member_limit: int | None = None, creates_join_request:
                             bool | None = None) → ChatInviteLink
```

Use this method to create an additional invite link for a chat. The bot must be an administrator in the chat for this to work and must have the appropriate administrator rights. The link can be revoked using the method `revokeChatInviteLink`. Returns the new invite link as `ChatInviteLink` object.

Telegram documentation: <https://core.telegram.org/bots/api#createchatinviolink>

Parameters

- **chat_id** (int or str) – Id: Unique identifier for the target chat or username of the target channel (in the format `@channelusername`)
- **name** (str) – Invite link name; 0-32 characters
- **expire_date** (int or datetime) – Point in time (Unix timestamp) when the link will expire
- **member_limit** (int) – Maximum number of users that can be members of the chat simultaneously

- **creates_join_request** (bool) – True, if users joining the chat via the link need to be approved by chat administrators. If True, member_limit can't be specified

Returns

Returns the new invite link as ChatInviteLink object.

Return type

telebot.types.ChatInviteLink

async create_forum_topic(*chat_id: int, name: str, icon_color: int | None = None, icon_custom_emoji_id: str | None = None*) → *ForumTopic*

Use this method to create a topic in a forum supergroup chat. The bot must be an administrator in the chat for this to work and must have the can_manage_topics administrator rights. Returns information about the created topic as a ForumTopic object.

Telegram documentation: <https://core.telegram.org/bots/api#createforumtopic>

Parameters

- **chat_id** (int or str) – Unique identifier for the target chat or username of the target channel (in the format @channelusername)
- **name** (str) – Name of the topic, 1-128 characters
- **icon_color** (int) – Color of the topic icon in RGB format. Currently, must be one of 0x6FB9F0, 0xFFD67E, 0xCB86DB, 0x8EEE98, 0xFF93B2, or 0xFB6F5F
- **icon_custom_emoji_id** (str) – Custom emoji for the topic icon. Must be an emoji of type “tgs” and must be exactly 1 character long

Returns

On success, information about the created topic is returned as a ForumTopic object.

Return type

telebot.types.ForumTopic

async create_invoice_link(*title: str, description: str, payload: str, provider_token: str, currency: str, prices: List[LabeledPrice], max_tip_amount: int | None = None, suggested_tip_amounts: List[int] | None = None, provider_data: str | None = None, photo_url: str | None = None, photo_size: int | None = None, photo_width: int | None = None, photo_height: int | None = None, need_name: bool | None = None, need_phone_number: bool | None = None, need_email: bool | None = None, need_shipping_address: bool | None = None, send_phone_number_to_provider: bool | None = None, send_email_to_provider: bool | None = None, is_flexible: bool | None = None*) → str

Use this method to create a link for an invoice. Returns the created invoice link as String on success.

Telegram documentation: <https://core.telegram.org/bots/api#createinvoicelink>

Parameters

- **title** (str) – Product name, 1-32 characters
- **description** (str) – Product description, 1-255 characters
- **payload** (str) – Bot-defined invoice payload, 1-128 bytes. This will not be displayed to the user, use for your internal processes.
- **provider_token** (str) – Payments provider token, obtained via @Botfather
- **currency** (str) – Three-letter ISO 4217 currency code, see <https://core.telegram.org/bots/payments#supported-currencies>

- **prices** (list of `types.LabeledPrice`) – Price breakdown, a list of components (e.g. product price, tax, discount, delivery cost, delivery tax, bonus, etc.)
- **max_tip_amount** (int) – The maximum accepted amount for tips in the smallest units of the currency
- **suggested_tip_amounts** (list of int) – A JSON-serialized array of suggested amounts of tips in the smallest units of the currency. At most 4 suggested tip amounts can be specified. The suggested tip amounts must be positive, passed in a strictly increased order and must not exceed `max_tip_amount`.
- **provider_data** (str) – A JSON-serialized data about the invoice, which will be shared with the payment provider. A detailed description of required fields should be provided by the payment provider.
- **photo_url** (str) – URL of the product photo for the invoice. Can be a photo of the goods or a photo of the invoice. People like it better when they see a photo of what they are paying for.
- **photo_size** (int) – Photo size in bytes
- **photo_width** (int) – Photo width
- **photo_height** (int) – Photo height
- **need_name** (bool) – Pass True, if you require the user’s full name to complete the order
- **need_phone_number** (bool) – Pass True, if you require the user’s phone number to complete the order
- **need_email** (bool) – Pass True, if you require the user’s email to complete the order
- **need_shipping_address** (bool) – Pass True, if you require the user’s shipping address to complete the order
- **send_phone_number_to_provider** (bool) – Pass True, if user’s phone number should be sent to provider
- **send_email_to_provider** (bool) – Pass True, if user’s email address should be sent to provider
- **is_flexible** (bool) – Pass True, if the final price depends on the shipping method

Returns

Created invoice link as String on success.

Return type

str

```
async create_new_sticker_set(user_id: int, name: str, title: str, emojis: List[str] | None = None,
                             png_sticker: Any | str = None, tgs_sticker: Any | str = None,
                             webm_sticker: Any | str = None, contains_masks: bool | None = None,
                             sticker_type: str | None = None, mask_position: MaskPosition | None =
                             None, needs_repainting: bool | None = None, stickers:
                             List[InputSticker] = None, sticker_format: str | None = None) → bool
```

Use this method to create new sticker set owned by a user. The bot will be able to edit the created sticker set. Returns True on success.

Telegram documentation: <https://core.telegram.org/bots/api#createnewstickerset>

Note: Fields *_sticker are deprecated, pass a list of stickers to stickers parameter instead.

Parameters

- **user_id** (int) – User identifier of created sticker set owner
- **name** (str) – Short name of sticker set, to be used in t.me/addstickers/ URLs (e.g., animals). Can contain only English letters, digits and underscores. Must begin with a letter, can't contain consecutive underscores and must end in “_by_<bot_username>”. <bot_username> is case insensitive. 1-64 characters.
- **title** (str) – Sticker set title, 1-64 characters
- **emojis** (str) – One or more emoji corresponding to the sticker
- **png_sticker** (str) – PNG image with the sticker, must be up to 512 kilobytes in size, dimensions must not exceed 512px, and either width or height must be exactly 512px. Pass a file_id as a String to send a file that already exists on the Telegram servers, pass an HTTP URL as a String for Telegram to get a file from the Internet, or upload a new one using multipart/form-data.
- **tgs_sticker** (str) – TGS animation with the sticker, uploaded using multipart/form-data.
- **webm_sticker** (str) – WebM animation with the sticker, uploaded using multipart/form-data.
- **contains_masks** (bool) – Pass True, if a set of mask stickers should be created. Deprecated since Bot API 6.2, use sticker_type instead.
- **sticker_type** (str) – Type of stickers in the set, pass “regular”, “mask”, or “custom_emoji”. By default, a regular sticker set is created.
- **mask_position** (*telebot.types.MaskPosition*) – A JSON-serialized object for position where the mask should be placed on faces
- **needs_repainting** (bool) – Pass True if stickers in the sticker set must be repainted to the color of text when used in messages, the accent color if used as emoji status, white on chat photos, or another appropriate color based on context; for custom emoji sticker sets only
- **stickers** (list of *telebot.types.InputSticker*) – List of stickers to be added to the set
- **sticker_format** (str) – deprecated

Returns

On success, True is returned.

Return type

bool

async decline_chat_join_request(*chat_id: str | int, user_id: int | str*) → bool

Use this method to decline a chat join request. The bot must be an administrator in the chat for this to work and must have the can_invite_users administrator right. Returns True on success.

Telegram documentation: <https://core.telegram.org/bots/api#declinechatjoinrequest>

Parameters

- **chat_id** (int or str) – Unique identifier for the target chat or username of the target supergroup (in the format @supergroupusername)
- **user_id** (int or str) – Unique identifier of the target user

Returns

True on success.

Return type

bool

async delete_chat_photo(*chat_id: int | str*) → bool

Use this method to delete a chat photo. Photos can't be changed for private chats. The bot must be an administrator in the chat for this to work and must have the appropriate admin rights. Returns True on success. Note: In regular groups (non-supergroups), this method will only work if the 'All Members Are Admins' setting is off in the target group.

Telegram documentation: <https://core.telegram.org/bots/api#deletechatphoto>

Parameters

chat_id (int or str) – Int or Str: Unique identifier for the target chat or username of the target channel (in the format @channelusername)

Returns

True on success.

Return type

bool

async delete_chat_sticker_set(*chat_id: int | str*) → bool

Use this method to delete a group sticker set from a supergroup. The bot must be an administrator in the chat for this to work and must have the appropriate admin rights. Use the field `can_set_sticker_set` optionally returned in `getChat` requests to check if the bot can use this method. Returns True on success.

Telegram documentation: <https://core.telegram.org/bots/api#deletechatstickerset>

Parameters

chat_id (int or str) – Unique identifier for the target chat or username of the target supergroup (in the format @supergroupusername)

Returns

Returns True on success.

Return type

bool

async delete_forum_topic(*chat_id: str | int, message_thread_id: int*) → bool

Use this method to delete a topic in a forum supergroup chat. The bot must be an administrator in the chat for this to work and must have the `can_manage_topics` administrator rights, unless it is the creator of the topic. Returns True on success.

Telegram documentation: <https://core.telegram.org/bots/api#deleteforumtopic>

Parameters

- **chat_id** (int or str) – Unique identifier for the target chat or username of the target channel (in the format @channelusername)
- **message_thread_id** (int) – Identifier of the topic to delete

Returns

On success, True is returned.

Return type

bool

async delete_message(*chat_id: int | str, message_id: int, timeout: int | None = None*) → bool

Use this method to delete a message, including service messages, with the following limitations: - A message can only be deleted if it was sent less than 48 hours ago. - A dice message in a private chat can only be deleted if it was sent more than 24 hours ago. - Bots can delete outgoing messages in private chats, groups, and supergroups. - Bots can delete incoming messages in private chats. - Bots granted can_post_messages permissions can delete outgoing messages in channels. - If the bot is an administrator of a group, it can delete any message there. - If the bot has can_delete_messages permission in a supergroup or a channel, it can delete any message there. Returns True on success.

Telegram documentation: <https://core.telegram.org/bots/api#deletemessage>

Parameters

- **chat_id** (int or str) – Unique identifier for the target chat or username of the target channel (in the format @channelusername)
- **message_id** (int) – Identifier of the message to delete
- **timeout** (int) – Timeout in seconds for the request.

Returns

Returns True on success.

Return type

bool

async delete_messages(*chat_id: int | str, message_ids: List[int]*)

Use this method to delete multiple messages simultaneously. If some of the specified messages can't be found, they are skipped. Returns True on success.

Telegram documentation: <https://core.telegram.org/bots/api#deletemessages>

Parameters

- **chat_id** (int or str) – Unique identifier for the target chat or username of the target channel (in the format @channelusername)
- **message_ids** (list of int) – Identifiers of the messages to be deleted

Returns

Returns True on success.

async delete_my_commands(*scope: BotCommandScope | None = None, language_code: int | None = None*) → bool

Use this method to delete the list of the bot's commands for the given scope and user language. After deletion, higher level commands will be shown to affected users. Returns True on success.

Telegram documentation: <https://core.telegram.org/bots/api#deletemycommands>

Parameters

- **scope** (*telebot.types.BotCommandScope*) – The scope of users for which the commands are relevant. Defaults to BotCommandScopeDefault.
- **language_code** (str) – A two-letter ISO 639-1 language code. If empty, commands will be applied to all users from the given scope, for whose language there are no dedicated commands

Returns

True on success.

Return type

bool

async delete_state(*user_id: int, chat_id: int | None = None*)

Delete the current state of a user.

Parameters

- **user_id** (int) – User’s identifier
- **chat_id** (int) – Chat’s identifier

Returns

None

async delete_sticker_from_set(*sticker: str*) → bool

Use this method to delete a sticker from a set created by the bot. Returns True on success.

Telegram documentation: <https://core.telegram.org/bots/api#deletestickerfromset>

Parameters

sticker – File identifier of the sticker

Returns

On success, True is returned.

Return type

bool

async delete_sticker_set(*name: str*) → bool

Use this method to delete a sticker set. Returns True on success.

Parameters

name (str) – Sticker set name

Returns

Returns True on success.

Return type

bool

async delete_webhook(*drop_pending_updates: bool | None = None, timeout: int | None = None*) → bool

Use this method to remove webhook integration if you decide to switch back to getUpdates. Returns True on success.

Telegram documentation: <https://core.telegram.org/bots/api#deletewebhook>

Parameters

- **drop_pending_updates** – Pass True to drop all pending updates, defaults to None
- **timeout** (int, optional) – Request connection timeout, defaults to None

Returns

Returns True on success.

Return type

bool

deleted_business_messages_handler(*func=None, **kwargs*)

Handles new incoming deleted messages state.

Parameters

- **func** (function) – Function executed as a filter
- **kwargs** – Optional keyword arguments(custom filters)

Returns

None

async download_file(*file_path*: str | None) → bytes

Downloads file.

Parameters**file_path** (str) – Path where the file should be downloaded.**Returns**

bytes

Return type

bytes

async edit_chat_invite_link(*chat_id*: int | str, *invite_link*: str | None = None, *name*: str | None = None, *expire_date*: int | datetime | None = None, *member_limit*: int | None = None, *creates_join_request*: bool | None = None) → ChatInviteLink

Use this method to edit a non-primary invite link created by the bot. The bot must be an administrator in the chat for this to work and must have the appropriate admin rights.

Telegram documentation: <https://core.telegram.org/bots/api#editchatinvitelink>**Parameters**

- **chat_id** (int or str) – Id: Unique identifier for the target chat or username of the target channel (in the format @channelusername)
- **name** (str) – Invite link name; 0-32 characters
- **invite_link** (str) – The invite link to edit
- **expire_date** (int or datetime) – Point in time (Unix timestamp) when the link will expire
- **member_limit** (int) – Maximum number of users that can be members of the chat simultaneously
- **creates_join_request** (bool) – True, if users joining the chat via the link need to be approved by chat administrators. If True, member_limit can't be specified

Returns

Returns the new invite link as ChatInviteLink object.

Return type*telebot.types.ChatInviteLink***async edit_forum_topic**(*chat_id*: int | str, *message_thread_id*: int, *name*: str | None = None, *icon_custom_emoji_id*: str | None = None) → bool

Use this method to edit name and icon of a topic in a forum supergroup chat. The bot must be an administrator in the chat for this to work and must have can_manage_topics administrator rights, unless it is the creator of the topic. Returns True on success.

Telegram Documentation: <https://core.telegram.org/bots/api#editforumtopic>**Parameters**

- **chat_id** (int or str) – Unique identifier for the target chat or username of the target channel (in the format @channelusername)
- **message_thread_id** (int) – Identifier of the topic to edit
- **name** (str) – Optional, New name of the topic, 1-128 characters. If not specified or empty, the current name of the topic will be kept

- **icon_custom_emoji_id** (`str`) – Optional, New unique identifier of the custom emoji shown as the topic icon. Use `getForumTopicIconStickers` to get all allowed custom emoji identifiers. Pass an empty string to remove the icon. If not specified, the current icon will be kept

Returns

On success, `True` is returned.

Return type

`bool`

async edit_general_forum_topic(*chat_id: int | str, name: str*) → `bool`

Use this method to edit the name of the ‘General’ topic in a forum supergroup chat. The bot must be an administrator in the chat for this to work and must have `can_manage_topics` administrator rights. Returns `True` on success.

Telegram documentation: <https://core.telegram.org/bots/api#editgeneralforumtopic>

Parameters

- **chat_id** (`int` or `str`) – Unique identifier for the target chat or username of the target channel (in the format `@channelusername`)
- **name** (`str`) – New topic name, 1-128 characters

async edit_message_caption(*caption: str, chat_id: int | str | None = None, message_id: int | None = None, inline_message_id: str | None = None, parse_mode: str | None = None, caption_entities: List[MessageEntity] | None = None, reply_markup: InlineKeyboardMarkup | None = None*) → `Message` | `bool`

Use this method to edit captions of messages.

Telegram documentation: <https://core.telegram.org/bots/api#editmessagecaption>

Parameters

- **caption** (`str`) – New caption of the message
- **chat_id** (`int` | `str`) – Required if `inline_message_id` is not specified. Unique identifier for the target chat or username of the target channel
- **message_id** (`int`) – Required if `inline_message_id` is not specified.
- **inline_message_id** (`str`) – Required if `inline_message_id` is not specified. Identifier of the inline message.
- **parse_mode** (`str`) – New caption of the message, 0-1024 characters after entities parsing
- **caption_entities** (`list of types.MessageEntity`) – A JSON-serialized array of objects that describe how the caption should be parsed.
- **reply_markup** (`InlineKeyboardMarkup`) – A JSON-serialized object for an inline keyboard.

Returns

On success, if edited message is sent by the bot, the edited `Message` is returned, otherwise `True` is returned.

Return type

`types.Message` | `bool`

async edit_message_live_location(*latitude: float, longitude: float, chat_id: int | str | None = None, message_id: int | None = None, inline_message_id: str | None = None, reply_markup: InlineKeyboardMarkup | None = None, timeout: int | None = None, horizontal_accuracy: float | None = None, heading: int | None = None, proximity_alert_radius: int | None = None*) → *Message*

Use this method to edit live location messages. A location can be edited until its live_period expires or editing is explicitly

disabled by a call to stopMessageLiveLocation. On success, if the edited message is not an inline message, the edited Message is returned, otherwise True is returned.

Telegram documentation: <https://core.telegram.org/bots/api#editmessagelivelocation>

Parameters

- **latitude** (float) – Latitude of new location
- **longitude** (float) – Longitude of new location
- **chat_id** (int or str) – Unique identifier for the target chat or username of the target channel (in the format @channelusername)
- **message_id** (int) – Required if inline_message_id is not specified. Identifier of the message to edit
- **reply_markup** (*telebot.types.InlineKeyboardMarkup* or *telebot.types.ReplyKeyboardMarkup* or *telebot.types.ReplyKeyboardRemove* or *telebot.types.ForceReply*) – A JSON-serialized object for a new inline keyboard.
- **timeout** (int) – Timeout in seconds for the request.
- **inline_message_id** (str) – Required if chat_id and message_id are not specified. Identifier of the inline message
- **horizontal_accuracy** (float) – The radius of uncertainty for the location, measured in meters; 0-1500
- **heading** (int) – Direction in which the user is moving, in degrees. Must be between 1 and 360 if specified.
- **proximity_alert_radius** (int) – The maximum distance for proximity alerts about approaching another chat member, in meters. Must be between 1 and 100000 if specified.

Returns

On success, if the edited message is not an inline message, the edited Message is returned, otherwise True is returned.

Return type

telebot.types.Message or bool

async edit_message_media(*media: Any, chat_id: int | str | None = None, message_id: int | None = None, inline_message_id: str | None = None, reply_markup: InlineKeyboardMarkup | None = None*) → *Message* | bool

Use this method to edit animation, audio, document, photo, or video messages. If a message is a part of a message album, then it can be edited only to a photo or a video. Otherwise, message type can be changed arbitrarily. When inline message is edited, new file can't be uploaded. Use previously uploaded file via its file_id or specify a URL.

Telegram documentation: <https://core.telegram.org/bots/api#editmessagemedia>

Parameters

- **media** (`InputMedia`) – A JSON-serialized object for a new media content of the message
- **chat_id** (`int` or `str`) – Required if `inline_message_id` is not specified. Unique identifier for the target chat or username of the target channel (in the format `@channelusername`)
- **message_id** (`int`) – Required if `inline_message_id` is not specified. Identifier of the sent message
- **inline_message_id** (`str`) – Required if `chat_id` and `message_id` are not specified. Identifier of the inline message
- **reply_markup** (`telebot.types.InlineKeyboardMarkup` or `ReplyKeyboardMarkup` or `ReplyKeyboardRemove` or `ForceReply`) – A JSON-serialized object for an inline keyboard.

Returns

On success, if edited message is sent by the bot, the edited `Message` is returned, otherwise `True` is returned.

Return type

`types.Message` or `bool`

```
async edit_message_reply_markup(chat_id: int | str | None = None, message_id: int | None = None,
                                inline_message_id: str | None = None, reply_markup:
                                InlineKeyboardMarkup | None = None) → Message | bool
```

Use this method to edit only the reply markup of messages.

Telegram documentation: <https://core.telegram.org/bots/api#editmessagereplymarkup>

Parameters

- **chat_id** (`int` or `str`) – Required if `inline_message_id` is not specified. Unique identifier for the target chat or username of the target channel (in the format `@channelusername`)
- **message_id** (`int`) – Required if `inline_message_id` is not specified. Identifier of the sent message
- **inline_message_id** (`str`) – Required if `chat_id` and `message_id` are not specified. Identifier of the inline message
- **reply_markup** (`InlineKeyboardMarkup` or `ReplyKeyboardMarkup` or `ReplyKeyboardRemove` or `ForceReply`) – A JSON-serialized object for an inline keyboard.

Returns

On success, if edited message is sent by the bot, the edited `Message` is returned, otherwise `True` is returned.

Return type

`types.Message` or `bool`

```
async edit_message_text(text: str, chat_id: int | str | None = None, message_id: int | None = None,
                        inline_message_id: str | None = None, parse_mode: str | None = None,
                        entities: List[MessageEntity] | None = None, disable_web_page_preview: bool
                        | None = None, reply_markup: InlineKeyboardMarkup | None = None,
                        link_preview_options: LinkPreviewOptions | None = None) → Message | bool
```

Use this method to edit text and game messages.

Telegram documentation: <https://core.telegram.org/bots/api#editmessagetext>

Parameters

- **text** (`str`) – New text of the message, 1-4096 characters after entities parsing

- **chat_id** (int or str) – Required if `inline_message_id` is not specified. Unique identifier for the target chat or username of the target channel (in the format @channelusername)
- **message_id** (int) – Required if `inline_message_id` is not specified. Identifier of the sent message
- **inline_message_id** (str) – Required if `chat_id` and `message_id` are not specified. Identifier of the inline message
- **parse_mode** (str) – Mode for parsing entities in the message text.
- **entities** (List of `telebot.types.MessageEntity`) – List of special entities that appear in the message text, which can be specified instead of `parse_mode`
- **disable_web_page_preview** (bool) – Deprecated - Use `link_preview_options` instead.
- **reply_markup** (InlineKeyboardMarkup) – A JSON-serialized object for an inline keyboard.
- **link_preview_options** (LinkPreviewOptions) – A JSON-serialized object for options used to automatically generate Telegram link previews for messages.

Returns

On success, if edited message is sent by the bot, the edited Message is returned, otherwise True is returned.

Return type

`types.Message` or `bool`

edited_business_message_handler (*commands=None, regexp=None, func=None, content_types=None, **kwargs*)

Handles new version of a message(business accounts) that is known to the bot and was edited. As a parameter to the decorator function, it passes `telebot.types.Message` object.

Parameters

- **commands** (list of str) – Optional list of strings (commands to handle).
- **regexp** (str) – Optional regular expression.
- **func** (function) – Function executed as a filter
- **content_types** (list of str) – Supported message content types. Must be a list. Defaults to ['text'].
- **kwargs** – Optional keyword arguments(custom filters)

Returns

None

edited_channel_post_handler (*commands=None, regexp=None, func=None, content_types=None, **kwargs*)

Handles new version of a channel post that is known to the bot and was edited. As a parameter to the decorator function, it passes `telebot.types.Message` object.

Parameters

- **commands** (list of str) – Optional list of strings (commands to handle).
- **regexp** (str) – Optional regular expression.
- **func** (function) – Function executed as a filter
- **content_types** (list of str) – Supported message content types. Must be a list. Defaults to ['text'].

- **kwargs** – Optional keyword arguments(custom filters)

Returns

edited_message_handler(*commands=None, regexp=None, func=None, content_types=None, chat_types=None, **kwargs*)

Handles new version of a message that is known to the bot and was edited.

As a parameter to the decorator function, it passes *telebot.types.Message* object.

Parameters

- **commands** (list of str) – Optional list of strings (commands to handle).
- **regexp** (str) – Optional regular expression.
- **func** (function) – Function executed as a filter
- **content_types** (list of str) – Supported message content types. Must be a list. Defaults to ['text'].
- **chat_types** (list of str) – list of chat types
- **kwargs** – Optional keyword arguments(custom filters)

Returns

None

enable_saving_states(*filename='./.state-save/states.pkl'*)

Enable saving states (by default saving disabled)

Note: It is recommended to pass a *StatePickleStorage* instance as *state_storage* to *TeleBot* class.

Parameters

filename (str, optional) – Filename of saving file, defaults to “./.state-save/states.pkl”

async export_chat_invite_link(*chat_id: int | str*) → str

Use this method to export an invite link to a supergroup or a channel. The bot must be an administrator in the chat for this to work and must have the appropriate admin rights.

Telegram documentation: <https://core.telegram.org/bots/api#exportchatinviolink>

Parameters

chat_id (int or str) – Id: Unique identifier for the target chat or username of the target channel (in the format @channelusername)

Returns

exported invite link as String on success.

Return type

str

async forward_message(*chat_id: int | str, from_chat_id: int | str, message_id: int, disable_notification: bool | None = None, protect_content: bool | None = None, timeout: int | None = None, message_thread_id: int | None = None*) → *Message*

Use this method to forward messages of any kind.

Telegram documentation: <https://core.telegram.org/bots/api#forwardmessage>

Parameters

- **disable_notification** (bool) – Sends the message silently. Users will receive a notification with no sound
- **chat_id** (int or str) – Unique identifier for the target chat or username of the target channel (in the format @channelusername)
- **from_chat_id** (int or str) – Unique identifier for the chat where the original message was sent (or channel username in the format @channelusername)
- **message_id** (int) – Message identifier in the chat specified in from_chat_id
- **protect_content** (bool) – Protects the contents of the forwarded message from forwarding and saving
- **timeout** (int) – Timeout in seconds for the request.
- **message_thread_id** (int) – Unique identifier for the target message thread (topic) of the forum; for forum supergroups only

Returns

On success, the sent Message is returned.

Return type

telebot.types.Message

async forward_messages(*chat_id: str | int, from_chat_id: str | int, message_ids: List[int], disable_notification: bool | None = None, message_thread_id: int | None = None, protect_content: bool | None = None*) → List[*MessageID*]

Use this method to forward multiple messages of any kind. If some of the specified messages can't be found or forwarded, they are skipped. Service messages and messages with protected content can't be forwarded. Album grouping is kept for forwarded messages. On success, an array of MessageID of the sent messages is returned.

Telegram documentation: <https://core.telegram.org/bots/api#forwardmessages>

Parameters

- **chat_id** (int or str) – Unique identifier for the target chat or username of the target channel (in the format @channelusername)
- **from_chat_id** (int or str) – Unique identifier for the chat where the original message was sent (or channel username in the format @channelusername)
- **message_ids** (list) – Message identifiers in the chat specified in from_chat_id
- **disable_notification** (bool) – Sends the message silently. Users will receive a notification with no sound
- **message_thread_id** (int) – Identifier of a message thread, in which the messages will be sent
- **protect_content** (bool) – Protects the contents of the forwarded message from forwarding and saving

Returns

On success, the sent Message is returned.

Return type

telebot.types.MessageID

async get_business_connection(*business_connection_id: str*) → *BusinessConnection*

Use this method to get information about the connection of the bot with a business account. Returns a BusinessConnection object on success.

Telegram documentation: <https://core.telegram.org/bots/api#getbusinessconnection>

Parameters

business_connection_id (`str`) – Unique identifier of the business connection

Returns

Returns a `BusinessConnection` object on success.

Return type

`telebot.types.BusinessConnection`

async get_chat(`chat_id: int | str`) → `Chat`

Use this method to get up to date information about the chat (current name of the user for one-on-one conversations, current username of a user, group or channel, etc.). Returns a `Chat` object on success.

Telegram documentation: <https://core.telegram.org/bots/api#getchat>

Parameters

chat_id (`int` or `str`) – Unique identifier for the target chat or username of the target supergroup or channel (in the format `@channelusername`)

Returns

Chat information

Return type

`telebot.types.Chat`

async get_chat_administrators(`chat_id: int | str`) → `List[ChatMember]`

Use this method to get a list of administrators in a chat. On success, returns an Array of `ChatMember` objects that contains information about all chat administrators except other bots.

Telegram documentation: <https://core.telegram.org/bots/api#getchatadministrators>

Parameters

chat_id – Unique identifier for the target chat or username of the target supergroup or channel (in the format `@channelusername`)

Returns

List made of `ChatMember` objects.

Return type

list of `telebot.types.ChatMember`

async get_chat_member(`chat_id: int | str, user_id: int`) → `ChatMember`

Use this method to get information about a member of a chat. Returns a `ChatMember` object on success.

Telegram documentation: <https://core.telegram.org/bots/api#getchatmember>

Parameters

- **chat_id** (`int` or `str`) – Unique identifier for the target chat or username of the target supergroup (in the format `@supergroupusername`)
- **user_id** (`int`) – Unique identifier of the target user

Returns

Returns `ChatMember` object on success.

Return type

`telebot.types.ChatMember`

async get_chat_member_count(*chat_id: int | str*) → int

Use this method to get the number of members in a chat.

Telegram documentation: <https://core.telegram.org/bots/api#getchatmembercount>

Parameters

chat_id (int or str) – Unique identifier for the target chat or username of the target supergroup or channel (in the format @channelusername)

Returns

Number of members in the chat.

Return type

int

get_chat_members_count(***kwargs*)

async get_chat_menu_button(*chat_id: int | str = None*) → *MenuButton*

Use this method to get the current value of the bot's menu button in a private chat, or the default menu button. Returns MenuButton on success.

Telegram Documentation: <https://core.telegram.org/bots/api#getchatmenubutton>

Parameters

chat_id (int or str) – Unique identifier for the target private chat. If not specified, default bot's menu button will be returned.

Returns

types.MenuButton

Return type

telebot.types.MenuButton

async get_custom_emoji_stickers(*custom_emoji_ids: List[str]*) → List[*Sticker*]

Use this method to get information about custom emoji stickers by their identifiers. Returns an Array of Sticker objects.

Parameters

custom_emoji_ids (list of str) – List of custom emoji identifiers. At most 200 custom emoji identifiers can be specified.

Returns

Returns an Array of Sticker objects.

Return type

list of *telebot.types.Sticker*

async get_file(*file_id: str | None*) → *File*

Use this method to get basic info about a file and prepare it for downloading. For the moment, bots can download files of up to 20MB in size. On success, a File object is returned. It is guaranteed that the link will be valid for at least 1 hour. When the link expires, a new one can be requested by calling get_file again.

Telegram documentation: <https://core.telegram.org/bots/api#getfile>

Parameters

file_id (str) – File identifier

Returns

telebot.types.File

async get_file_url(*file_id: str | None*) → str

Get a valid URL for downloading a file.

Parameters

file_id (str) – File identifier to get download URL for.

Returns

URL for downloading the file.

Return type

str

async get_forum_topic_icon_stickers() → List[*Sticker*]

Use this method to get custom emoji stickers, which can be used as a forum topic icon by any user. Requires no parameters. Returns an Array of Sticker objects.

Telegram documentation: <https://core.telegram.org/bots/api#getforumtopiciconstickers>

Returns

On success, a list of StickerSet objects is returned.

Return type

List[*telebot.types.StickerSet*]

async get_game_high_scores(*user_id: int, chat_id: int | str | None = None, message_id: int | None = None, inline_message_id: str | None = None*) → List[*GameHighScore*]

Use this method to get data for high score tables. Will return the score of the specified user and several of their neighbors in a game. On success, returns an Array of GameHighScore objects.

This method will currently return scores for the target user, plus two of their closest neighbors on each side. Will also return the top three users if the user and their neighbors are not among them. Please note that this behavior is subject to change.

Telegram documentation: <https://core.telegram.org/bots/api#getgamehighscores>

Parameters

- **user_id** (int) – User identifier
- **chat_id** (int or str) – Required if inline_message_id is not specified. Unique identifier for the target chat or username of the target channel (in the format @channelusername)
- **message_id** (int) – Required if inline_message_id is not specified. Identifier of the sent message
- **inline_message_id** (str) – Required if chat_id and message_id are not specified. Identifier of the inline message

Returns

On success, returns an Array of GameHighScore objects.

Return type

List[*types.GameHighScore*]

async get_me() → *User*

Returns basic information about the bot in form of a User object.

Telegram documentation: <https://core.telegram.org/bots/api#getme>

async get_my_commands(*scope: BotCommandScope | None, language_code: str | None*) → List[*BotCommand*]

Use this method to get the current list of the bot's commands. Returns List of BotCommand on success.

Telegram documentation: <https://core.telegram.org/bots/api#getmycommands>

Parameters

- **scope** (*telebot.types.BotCommandScope*) – The scope of users for which the commands are relevant. Defaults to BotCommandScopeDefault.
- **language_code** (str) – A two-letter ISO 639-1 language code. If empty, commands will be applied to all users from the given scope, for whose language there are no dedicated commands

Returns

List of BotCommand on success.

Return type

list of *telebot.types.BotCommand*

async get_my_default_administrator_rights(*for_channels: bool = None*) → *ChatAdministratorRights*

Use this method to get the current default administrator rights of the bot. Returns ChatAdministratorRights on success.

Telegram documentation: <https://core.telegram.org/bots/api#getmydefaultadministratorrights>

Parameters

for_channels (bool) – Pass True to get the default administrator rights of the bot in channels. Otherwise, the default administrator rights of the bot for groups and supergroups will be returned.

Returns

Returns ChatAdministratorRights on success.

Return type

telebot.types.ChatAdministratorRights

async get_my_description(*language_code: str | None = None*)

Use this method to get the current bot description for the given user language. Returns BotDescription on success.

Parameters

language_code (str) – A two-letter ISO 639-1 language code or an empty string

Returns

telebot.types.BotDescription

async get_my_name(*language_code: str | None = None*)

Use this method to get the current bot name for the given user language. Returns BotName on success.

Telegram documentation: <https://core.telegram.org/bots/api#getmyname>

Parameters

language_code (str) – Optional. A two-letter ISO 639-1 language code or an empty string

Returns

telebot.types.BotName

async get_my_short_description(*language_code: str | None = None*)

Use this method to get the current bot short description for the given user language. Returns BotShortDescription on success.

Parameters

language_code (str) – A two-letter ISO 639-1 language code or an empty string

Returns*telebot.types.BotShortDescription***async get_state**(*user_id, chat_id: int | None = None*)

Gets current state of a user. Not recommended to use this method. But it is ok for debugging.

Parameters

- **user_id** (int) – User’s identifier
- **chat_id** (int) – Chat’s identifier

Returns

state of a user

Return typeint or str or *telebot.types.State***async get_sticker_set**(*name: str*) → *StickerSet*

Use this method to get a sticker set. On success, a StickerSet object is returned.

Telegram documentation: <https://core.telegram.org/bots/api#getstickerset>

Parameters**name** (str) – Sticker set name**Returns**

On success, a StickerSet object is returned.

Return type*telebot.types.StickerSet***async get_updates**(*offset: int | None = None, limit: int | None = None, timeout: int | None = 20, allowed_updates: List | None = None, request_timeout: int | None = None*) → List[*Update*]

Use this method to receive incoming updates using long polling (wiki). An Array of Update objects is returned.

Telegram documentation: <https://core.telegram.org/bots/api#getupdates>

Parameters

- **offset** (int, optional) – Identifier of the first update to be returned. Must be greater by one than the highest among the identifiers of previously received updates. By default, updates starting with the earliest unconfirmed update are returned. An update is considered confirmed as soon as getUpdates is called with an offset higher than its update_id. The negative offset can be specified to retrieve updates starting from -offset update from the end of the updates queue. All previous updates will forgotten.
- **limit** (int, optional) – Limits the number of updates to be retrieved. Values between 1-100 are accepted. Defaults to 100.
- **timeout** (int, optional) – Request connection timeout
- **allowed_updates** (list, optional) – Array of string. List the types of updates you want your bot to receive.
- **request_timeout** (int, optional) – Timeout in seconds for request.

Returns

An Array of Update objects is returned.

Return typelist of *telebot.types.Update*

async get_user_chat_boosts(*chat_id: int | str, user_id: int*) → *UserChatBoosts*

Use this method to get the list of boosts added to a chat by a user. Requires administrator rights in the chat. Returns a UserChatBoosts object.

Telegram documentation: <https://core.telegram.org/bots/api#getuserchatboosts>

Parameters

- **chat_id** (*int | str*) – Unique identifier for the target chat or username of the target channel
- **user_id** (*int*) – Unique identifier of the target user

Returns

On success, a UserChatBoosts object is returned.

Return type

telebot.types.UserChatBoosts

async get_user_profile_photos(*user_id: int, offset: int | None = None, limit: int | None = None*) → *UserProfilePhotos*

Use this method to get a list of profile pictures for a user. Returns a *telebot.types.UserProfilePhotos* object.

Telegram documentation: <https://core.telegram.org/bots/api#getuserprofilephotos>

Parameters

- **user_id** (*int*) – Unique identifier of the target user
- **offset** (*int*) – Sequential number of the first photo to be returned. By default, all photos are returned.
- **limit** (*int*) – Limits the number of photos to be retrieved. Values between 1-100 are accepted. Defaults to 100.

Returns

UserProfilePhotos

Return type

telebot.types.UserProfilePhotos

async get_webhook_info(*timeout: int | None = None*) → *WebhookInfo*

Use this method to get current webhook status. Requires no parameters. On success, returns a WebhookInfo object. If the bot is using getUpdates, will return an object with the url field empty.

Telegram documentation: <https://core.telegram.org/bots/api#getwebhookinfo>

Parameters

timeout (*int, optional*) – Request connection timeout

Returns

On success, returns a WebhookInfo object.

Return type

telebot.types.WebhookInfo

async hide_general_forum_topic(*chat_id: int | str*) → *bool*

Use this method to hide the ‘General’ topic in a forum supergroup chat. The bot must be an administrator in the chat for this to work and must have can_manage_topics administrator rights. Returns True on success.

Telegram documentation: <https://core.telegram.org/bots/api#hidegeneralforumtopic>

Parameters

chat_id (int or str) – Unique identifier for the target chat or username of the target channel (in the format @channelusername)

async infinity_polling (*timeout: int | None = 20, skip_pending: bool | None = False, request_timeout: int | None = None, logger_level: int | None = 40, allowed_updates: List[str] | None = None, restart_on_change: bool | None = False, path_to_watch: str | None = None, *args, **kwargs*)

Wrap polling with infinite loop and exception handling to avoid bot stops polling.

Note: Install watchdog and psutil before using restart_on_change option.

Parameters

- **timeout** (int) – Timeout in seconds for get_updates(Defaults to None)
- **skip_pending** (bool) – skip old updates
- **request_timeout** (int) – Aiohttp's request timeout. Defaults to 5 minutes(aiohttp.ClientTimeout).
- **logger_level** (int) – Custom logging level for infinity_polling logging. Use logger levels from logging as a value. None/NOTSET = no error logging
- **allowed_updates** (list of str) – A list of the update types you want your bot to receive. For example, specify ["message", "edited_channel_post", "callback_query"] to only receive updates of these types. See util.update_types for a complete list of available update types. Specify an empty list to receive all update types except chat_member (default). If not specified, the previous setting will be used.

Please note that this parameter doesn't affect updates created before the call to the get_updates, so unwanted updates may be received for a short period of time.
- **restart_on_change** (bool) – Restart a file on file(s) change. Defaults to False
- **path_to_watch** (str) – Path to watch for changes. Defaults to current directory

Returns

None

inline_handler (*func, **kwargs*)

Handles new incoming inline query. As a parameter to the decorator function, it passes `telebot.types.InlineQuery` object.

Parameters

- **func** (function) – Function executed as a filter
- **kwargs** – Optional keyword arguments(custom filters)

Returns

None

async kick_chat_member (*chat_id: int | str, user_id: int, until_date: int | datetime | None = None, revoke_messages: bool | None = None*) → bool

This function is deprecated. Use `ban_chat_member` instead

async leave_chat(*chat_id: int | str*) → bool

Use this method for your bot to leave a group, supergroup or channel. Returns True on success.

Telegram documentation: <https://core.telegram.org/bots/api#leavechat>

Parameters

chat_id (int or str) – Unique identifier for the target chat or username of the target supergroup or channel (in the format @channelusername)

Returns

bool

async log_out() → bool

Use this method to log out from the cloud Bot API server before launching the bot locally. You MUST log out the bot before running it locally, otherwise there is no guarantee that the bot will receive updates. After a successful call, you can immediately log in on a local server, but will not be able to log in back to the cloud Bot API server for 10 minutes. Returns True on success.

Telegram documentation: <https://core.telegram.org/bots/api#logout>

Returns

True on success.

Return type

bool

message_handler(*commands=None, regexp=None, func=None, content_types=None, chat_types=None, **kwargs*)

Handles new incoming message of any kind - text, photo, sticker, etc. As a parameter to the decorator function, it passes `telebot.types.Message` object. All message handlers are tested in the order they were added.

Example:

Listing 26: Usage of message_handler

```
bot = TeleBot('TOKEN')

# Handles all messages which text matches regexp.
@bot.message_handler(regexp='someregexp')
async def command_help(message):
    await bot.send_message(message.chat.id, 'Did someone call for help?')

# Handles messages in private chat
@bot.message_handler(chat_types=['private']) # You can add more chat types
async def command_help(message):
    await bot.send_message(message.chat.id, 'Private chat detected, sir!')

# Handle all sent documents of type 'text/plain'.
@bot.message_handler(func=lambda message: message.document.mime_type == 'text/
↳plain',
    content_types=['document'])
async def command_handle_document(message):
    await bot.send_message(message.chat.id, 'Document received, sir!')

# Handle all other messages.
@bot.message_handler(func=lambda message: True, content_types=['audio', 'photo',
```

(continues on next page)

(continued from previous page)

```

↪ 'voice', 'video', 'document',
  'text', 'location', 'contact', 'sticker'])
async def default_command(message):
    await bot.send_message(message.chat.id, "This is the default command.
↪handler.")

```

Parameters

- **commands** (list of str) – Optional list of strings (commands to handle).
- **regexp** (str) – Optional regular expression.
- **func** – Optional lambda function. The lambda receives the message to test as the first parameter. It must return True if the command should handle the message.
- **content_types** (list of str) – Supported message content types. Must be a list. Defaults to ['text'].
- **chat_types** (list of str) – list of chat types
- **kwargs** – Optional keyword arguments(custom filters)

Returns

decorated function

message_reaction_count_handler(*func=None, **kwargs*)

Handles new incoming message reaction count. As a parameter to the decorator function, it passes `telebot.types.MessageReactionCountUpdated` object.

Parameters

- **func** (function) – Function executed as a filter
- **kwargs** – Optional keyword arguments(custom filters)

Returns**message_reaction_handler**(*func=None, **kwargs*)

Handles new incoming message reaction. As a parameter to the decorator function, it passes `telebot.types.MessageReactionUpdated` object.

Parameters

- **func** (function) – Function executed as a filter
- **kwargs** – Optional keyword arguments(custom filters)

Returns**my_chat_member_handler**(*func=None, **kwargs*)

Handles update in a status of a bot. For private chats, this update is received only when the bot is blocked or unblocked by the user. As a parameter to the decorator function, it passes `telebot.types.ChatMemberUpdated` object.

Parameters

- **func** (function) – Function executed as a filter
- **kwargs** – Optional keyword arguments(custom filters)

Returns

None

async pin_chat_message(*chat_id: int | str, message_id: int, disable_notification: bool | None = False*) → bool

Use this method to pin a message in a supergroup. The bot must be an administrator in the chat for this to work and must have the appropriate admin rights. Returns True on success.

Telegram documentation: <https://core.telegram.org/bots/api#pinchatmessage>

Parameters

- **chat_id** (int or str) – Unique identifier for the target chat or username of the target channel (in the format @channelusername)
- **message_id** (int) – Identifier of a message to pin
- **disable_notification** (bool) – Pass True, if it is not necessary to send a notification to all group members about the new pinned message

Returns

True on success.

Return type

bool

poll_answer_handler(*func=None, **kwargs*)

Handles change of user's answer in a non-anonymous poll(when user changes the vote). Bots receive new votes only in polls that were sent by the bot itself. As a parameter to the decorator function, it passes `telebot.types.PollAnswer` object.

Parameters

- **func** (function) – Function executed as a filter
- **kwargs** – Optional keyword arguments(custom filters)

Returns

None

poll_handler(*func, **kwargs*)

Handles new state of a poll. Bots receive only updates about stopped polls and polls, which are sent by the bot As a parameter to the decorator function, it passes `telebot.types.Poll` object.

Parameters

- **func** (function) – Function executed as a filter
- **kwargs** – Optional keyword arguments(custom filters)

Returns

None

async polling(*non_stop: bool = False, skip_pending=False, interval: int = 0, timeout: int = 20, request_timeout: int | None = None, allowed_updates: List[str] | None = None, none_stop: bool | None = None, restart_on_change: bool | None = False, path_to_watch: str | None = None*)

Runs bot in long-polling mode in a main loop. This allows the bot to retrieve Updates automatically and notify listeners and message handlers accordingly.

Warning: Do not call this function more than once!

Always gets updates.

Note: Set `non_stop=True` if you want your bot to continue receiving updates if there is an error.

Note: Install `watchdog` and `psutil` before using `restart_on_change` option.

Parameters

- **non_stop** (bool) – Do not stop polling when an `ApiException` occurs.
- **skip_pending** (bool) – skip old updates
- **interval** (int) – Delay between two update retrivals
- **timeout** (int) – Request connection timeout
- **request_timeout** (int) – Timeout in seconds for `get_updates`(Defaults to None)
- **allowed_updates** (list of str) – A list of the update types you want your bot to receive. For example, specify `["message", "edited_channel_post", "callback_query"]` to only receive updates of these types. See `util.update_types` for a complete list of available update types. Specify an empty list to receive all update types except `chat_member` (default). If not specified, the previous setting will be used.

Please note that this parameter doesn't affect updates created before the call to the `get_updates`, so unwanted updates may be received for a short period of time.

- **none_stop** (bool) – Deprecated, use `non_stop`. Old typo, kept for backward compatibility.
- **restart_on_change** (bool) – Restart a file on file(s) change. Defaults to `False`.
- **path_to_watch** (str) – Path to watch for changes. Defaults to current directory

Returns

pre_checkout_query_handler(*func*, ***kwargs*)

New incoming pre-checkout query. Contains full information about checkout. As a parameter to the decorator function, it passes `telebot.types.PreCheckoutQuery` object.

Parameters

- **func** (function) – Function executed as a filter
- **kwargs** – Optional keyword arguments(custom filters)

Returns

None

async process_new_updates(*updates: List[Update]*)

Process new updates. Just pass list of updates - each update should be instance of `Update` object.

Parameters

updates (list of `telebot.types.Update`) – list of updates

Returns

None

```

async promote_chat_member(chat_id: int | str, user_id: int, can_change_info: bool | None = None,
can_post_messages: bool | None = None, can_edit_messages: bool | None =
None, can_delete_messages: bool | None = None, can_invite_users: bool |
None = None, can_restrict_members: bool | None = None,
can_pin_messages: bool | None = None, can_promote_members: bool |
None = None, is_anonymous: bool | None = None, can_manage_chat: bool |
None = None, can_manage_video_chats: bool | None = None,
can_manage_voice_chats: bool | None = None, can_manage_topics: bool |
None = None, can_post_stories: bool | None = None, can_edit_stories: bool
| None = None, can_delete_stories: bool | None = None) → bool

```

Use this method to promote or demote a user in a supergroup or a channel. The bot must be an administrator in the chat for this to work and must have the appropriate admin rights. Pass False for all boolean parameters to demote a user.

Telegram documentation: <https://core.telegram.org/bots/api#promotechatmember>

Parameters

- **chat_id** (int or str) – Unique identifier for the target chat or username of the target channel (in the format @channelusername)
- **user_id** (int) – Unique identifier of the target user
- **can_change_info** (bool) – Pass True, if the administrator can change chat title, photo and other settings
- **can_post_messages** (bool) – Pass True, if the administrator can create channel posts, channels only
- **can_edit_messages** (bool) – Pass True, if the administrator can edit messages of other users, channels only
- **can_delete_messages** (bool) – Pass True, if the administrator can delete messages of other users
- **can_invite_users** (bool) – Pass True, if the administrator can invite new users to the chat
- **can_restrict_members** (bool) – Pass True, if the administrator can restrict, ban or unban chat members
- **can_pin_messages** (bool) – Pass True, if the administrator can pin messages, supergroups only
- **can_promote_members** (bool) – Pass True, if the administrator can add new administrators with a subset of his own privileges or demote administrators that he has promoted, directly or indirectly (promoted by administrators that were appointed by him)
- **is_anonymous** (bool) – Pass True, if the administrator’s presence in the chat is hidden
- **can_manage_chat** (bool) – Pass True, if the administrator can access the chat event log, chat statistics, message statistics in channels, see channel members, see anonymous administrators in supergroups and ignore slow mode. Implied by any other administrator privilege
- **can_manage_video_chats** (bool) – Pass True, if the administrator can manage voice chats For now, bots can use this privilege only for passing to other administrators.
- **can_manage_voice_chats** (bool) – Deprecated, use can_manage_video_chats.
- **can_manage_topics** (bool) – Pass True if the user is allowed to create, rename, close, and reopen forum topics, supergroups only

- **can_post_stories** (bool) – Pass True if the administrator can create the channel’s stories
- **can_edit_stories** (bool) – Pass True if the administrator can edit the channel’s stories
- **can_delete_stories** (bool) – Pass True if the administrator can delete the channel’s stories

Returns

True on success.

Return type

bool

register_business_connection_handler(*callback: Callable, func: Callable | None = None, pass_bot: bool | None = False, **kwargs*)

Registers business connection handler.

Parameters

- **callback** (function) – function to be called
- **func** (function) – Function executed as a filter
- **pass_bot** (bool) – True if you need to pass TeleBot instance to handler(useful for separating handlers into different files)
- **kwargs** – Optional keyword arguments(custom filters)

Returns

None

register_business_message_handler(*callback: Callable, commands: List[str] | None = None, regexp: str | None = None, func: Callable | None = None, content_types: List[str] | None = None, **kwargs*)

Registers business connection handler.

Parameters

- **callback** (function) – function to be called
- **func** (function) – Function executed as a filter
- **pass_bot** (bool) – True if you need to pass TeleBot instance to handler(useful for separating handlers into different files)
- **kwargs** – Optional keyword arguments(custom filters)

Returns

None

register_callback_query_handler(*callback: Callable[[Any], Awaitable], func: Callable, pass_bot: bool | None = False, **kwargs*)

Registers callback query handler.

Parameters

- **callback** (Awaitable) – function to be called
- **func** (function) – Function executed as a filter
- **pass_bot** (bool) – True if you need to pass TeleBot instance to handler(useful for separating handlers into different files)
- **kwargs** – Optional keyword arguments(custom filters)

Returns

None

register_channel_post_handler(*callback: Callable[[Any], Awaitable], content_types: List[str] | None = None, commands: List[str] | None = None, regexp: str | None = None, func: Callable | None = None, pass_bot: bool | None = False, **kwargs*)

Registers channel post message handler.

Parameters

- **callback** (Awaitable) – function to be called
- **content_types** (list of str) – Supported message content types. Must be a list. Defaults to ['text'].
- **commands** (list of str) – list of commands
- **regexp** (str) – Regular expression
- **func** (function) – Function executed as a filter
- **pass_bot** (bool) – True if you need to pass TeleBot instance to handler(useful for separating handlers into different files)
- **kwargs** – Optional keyword arguments(custom filters)

Returns

None

register_chat_boost_handler(*callback: Callable, func: Callable | None = None, pass_bot: bool | None = False, **kwargs*)

Registers chat boost handler.

Parameters

- **callback** (function) – function to be called
- **func** (function) – Function executed as a filter
- **pass_bot** – True if you need to pass TeleBot instance to handler(useful for separating handlers into different files)
- **kwargs** – Optional keyword arguments(custom filters)

Returns

None

register_chat_join_request_handler(*callback: Callable[[Any], Awaitable], func: Callable | None = None, pass_bot: bool | None = False, **kwargs*)

Registers chat join request handler.

Parameters

- **callback** (Awaitable) – function to be called
- **func** (function) – Function executed as a filter
- **pass_bot** (bool) – True if you need to pass TeleBot instance to handler(useful for separating handlers into different files)
- **kwargs** – Optional keyword arguments(custom filters)

Returns

None

register_chat_member_handler(*callback: Callable[[Any], Awaitable], func: Callable | None = None, pass_bot: bool | None = False, **kwargs*)

Registers chat member handler.

Parameters

- **callback** (*Awaitable`*) – function to be called
- **func** (*function*) – Function executed as a filter
- **pass_bot** (*bool*) – True if you need to pass TeleBot instance to handler(useful for separating handlers into different files)
- **kwargs** – Optional keyword arguments(custom filters)

:return:None

register_chosen_inline_handler(*callback: Callable[[Any], Awaitable], func: Callable, pass_bot: bool | None = False, **kwargs*)

Registers chosen inline handler.

Parameters

- **callback** (*Awaitable*) – function to be called
- **func** (*function*) – Function executed as a filter
- **pass_bot** (*bool*) – True if you need to pass TeleBot instance to handler(useful for separating handlers into different files)
- **kwargs** – Optional keyword arguments(custom filters)

Returns

None

register_deleted_business_messages_handler(*callback: Callable, func: Callable | None = None, pass_bot: bool | None = False, **kwargs*)

Registers deleted business messages handler.

Parameters

- **callback** (*function*) – function to be called
- **func** (*function*) – Function executed as a filter
- **pass_bot** (*bool*) – True if you need to pass TeleBot instance to handler(useful for separating handlers into different files)
- **kwargs** – Optional keyword arguments(custom filters)

Returns

None

register_edited_business_message_handler(*callback: Callable, content_types: List[str] | None = None, commands: List[str] | None = None, regexp: str | None = None, func: Callable | None = None, pass_bot: bool | None = False, **kwargs*)

Registers edited message handler for business accounts.

Parameters

- **callback** (*function*) – function to be called
- **content_types** (*list of str*) – Supported message content types. Must be a list. Defaults to ['text'].

- **commands** (list of str) – list of commands
- **regexp** (str) – Regular expression
- **func** (function) – Function executed as a filter
- **pass_bot** (bool) – True if you need to pass TeleBot instance to handler(useful for separating handlers into different files)
- **kwargs** – Optional keyword arguments(custom filters)

Returns

None

register_edited_channel_post_handler(*callback: Callable[[Any], Awaitable], content_types: List[str] | None = None, commands: List[str] | None = None, regexp: str | None = None, func: Callable | None = None, pass_bot: bool | None = False, **kwargs*)

Registers edited channel post message handler.

Parameters

- **callback** (Awaitable) – function to be called
- **content_types** (list of str) – Supported message content types. Must be a list. Defaults to ['text'].
- **commands** (list of str) – list of commands
- **regexp** (str) – Regular expression
- **func** (function) – Function executed as a filter
- **pass_bot** (bool) – True if you need to pass TeleBot instance to handler(useful for separating handlers into different files)
- **kwargs** – Optional keyword arguments(custom filters)

Returns

decorated function

register_edited_message_handler(*callback: Callable[[Any], Awaitable], content_types: List[str] | None = None, commands: List[str] | None = None, regexp: str | None = None, func: Callable | None = None, chat_types: List[str] | None = None, pass_bot: bool | None = False, **kwargs*)

Registers edited message handler.

Parameters

- **callback** (Awaitable) – function to be called
- **content_types** (list of str) – Supported message content types. Must be a list. Defaults to ['text'].
- **commands** (list of str) – list of commands
- **regexp** (str) – Regular expression
- **func** (function) – Function executed as a filter
- **chat_types** (bool) – True for private chat
- **pass_bot** (bool) – True if you need to pass TeleBot instance to handler(useful for separating handlers into different files)
- **kwargs** – Optional keyword arguments(custom filters)

Returns

None

register_inline_handler(*callback: Callable[[Any], Awaitable], func: Callable, pass_bot: bool | None = False, **kwargs*)

Registers inline handler.

Parameters

- **callback** (Awaitable) – function to be called
- **func** (function) – Function executed as a filter
- **pass_bot** (bool) – True if you need to pass TeleBot instance to handler(useful for separating handlers into different files)
- **kwargs** – Optional keyword arguments(custom filters)

Returns

decorated function

register_message_handler(*callback: Callable[[Any], Awaitable], content_types: List[str] | None = None, commands: List[str] | None = None, regexp: str | None = None, func: Callable | None = None, chat_types: List[str] | None = None, pass_bot: bool | None = False, **kwargs*)

Registers message handler.

Parameters

- **callback** (Awaitable) – function to be called
- **content_types** (list of str) – Supported message content types. Must be a list. Defaults to ['text'].
- **commands** (list of str) – list of commands
- **regexp** (str)
- **func** (function) – Function executed as a filter
- **chat_types** (list of str) – List of chat types
- **pass_bot** (bool) – True if you need to pass TeleBot instance to handler(useful for separating handlers into different files)
- **kwargs** – Optional keyword arguments(custom filters)

Returns

None

register_message_reaction_count_handler(*callback: Callable[[Any], Awaitable], func: Callable = None, pass_bot: bool | None = False, **kwargs*)

Registers message reaction count handler.

Parameters

- **callback** (Awaitable) – function to be called
- **func** (function) – Function executed as a filter
- **pass_bot** (bool) – True if you need to pass TeleBot instance to handler(useful for separating handlers into different files)
- **kwargs** – Optional keyword arguments(custom filters)

Returns

None

register_message_reaction_handler(*callback: Callable[[Any], Awaitable], func: Callable = None, pass_bot: bool | None = False, **kwargs*)

Registers message reaction handler.

Parameters

- **callback** (Awaitable) – function to be called
- **func** (function) – Function executed as a filter
- **pass_bot** (bool) – True if you need to pass TeleBot instance to handler(useful for separating handlers into different files)
- **kwargs** – Optional keyword arguments(custom filters)

Returns

None

register_my_chat_member_handler(*callback: Callable[[Any], Awaitable], func: Callable | None = None, pass_bot: bool | None = False, **kwargs*)

Registers my chat member handler.

Parameters

- **callback** (Awaitable) – function to be called
- **func** (function) – Function executed as a filter
- **pass_bot** (bool) – True if you need to pass TeleBot instance to handler(useful for separating handlers into different files)
- **kwargs** – Optional keyword arguments(custom filters)

Returns

None

register_poll_answer_handler(*callback: Callable[[Any], Awaitable], func: Callable, pass_bot: bool | None = False, **kwargs*)

Registers poll answer handler.

Parameters

- **callback** (Awaitable) – function to be called
- **func** (function) – Function executed as a filter
- **pass_bot** (bool) – True if you need to pass TeleBot instance to handler(useful for separating handlers into different files)
- **kwargs** – Optional keyword arguments(custom filters)

Returns

None

register_poll_handler(*callback: Callable[[Any], Awaitable], func: Callable, pass_bot: bool | None = False, **kwargs*)

Registers poll handler.

Parameters

- **callback** (Awaitable) – function to be called

- **func** (function) – Function executed as a filter
- **pass_bot** (bool) – True if you need to pass TeleBot instance to handler(useful for separating handlers into different files)
- **kwargs** – Optional keyword arguments(custom filters)

Returns

None

register_pre_checkout_query_handler(*callback: Callable[[Any], Awaitable], func: Callable, pass_bot: bool | None = False, **kwargs*)

Registers pre-checkout request handler.

Parameters

- **callback** (Awaitable) – function to be called
- **func** – Function executed as a filter
- **pass_bot** (bool) – True if you need to pass TeleBot instance to handler(useful for separating handlers into different files)
- **kwargs** – Optional keyword arguments(custom filters)

Returns

decorated function

register_removed_chat_boost_handler(*callback: Callable, func: Callable | None = None, pass_bot: bool | None = False, **kwargs*)

Registers removed chat boost handler.

Parameters

- **callback** (function) – function to be called
- **func** (function) – Function executed as a filter
- **pass_bot** – True if you need to pass TeleBot instance to handler(useful for separating handlers into different files)
- **kwargs** – Optional keyword arguments(custom filters)

Returns

None

register_shipping_query_handler(*callback: Callable[[Any], Awaitable], func: Callable, pass_bot: bool | None = False, **kwargs*)

Registers shipping query handler.

Parameters

- **callback** (Awaitable) – function to be called
- **func** (function) – Function executed as a filter
- **pass_bot** (bool) – True if you need to pass TeleBot instance to handler(useful for separating handlers into different files)
- **kwargs** – Optional keyword arguments(custom filters)

Returns

None

async remove_webhook() → bool

Alternative for delete_webhook but uses set_webhook

removed_chat_boost_handler(*func=None, **kwargs*)

Handles new incoming chat boost state. it passes `telebot.types.ChatBoostRemoved` object.

Parameters

- **func** (function) – Function executed as a filter
- **kwargs** – Optional keyword arguments(custom filters)

Returns

None

async reopen_forum_topic(*chat_id: str | int, message_thread_id: int*) → bool

Use this method to reopen a closed topic in a forum supergroup chat. The bot must be an administrator in the chat for this to work and must have the can_manage_topics administrator rights, unless it is the creator of the topic. Returns True on success.

Telegram documentation: <https://core.telegram.org/bots/api#reopenforumtopic>

Parameters

- **chat_id** (int or str) – Unique identifier for the target chat or username of the target channel (in the format @channelusername)
- **message_thread_id** (int) – Identifier of the topic to reopen

Returns

On success, True is returned.

Return type

bool

async reopen_general_forum_topic(*chat_id: int | str*) → bool

Use this method to reopen the ‘General’ topic in a forum supergroup chat. The bot must be an administrator in the chat for this to work and must have can_manage_topics administrator rights. Returns True on success.

Telegram documentation: <https://core.telegram.org/bots/api#reopengeneralforumtopic>

Parameters

chat_id (int or str) – Unique identifier for the target chat or username of the target channel (in the format @channelusername)

async replace_sticker_in_set(*user_id: int, name: str, old_sticker: str, sticker: InputSticker*) → bool

Use this method to replace an existing sticker in a sticker set with a new one. The method is equivalent to calling deleteStickerFromSet, then addStickerToSet, then setStickerPositionInSet. Returns True on success.

Telegram documentation: <https://core.telegram.org/bots/api#replaceStickerInSet>

Parameters

- **user_id** (int) – User identifier of the sticker set owner
- **name** (str) – Sticker set name
- **old_sticker** (str) – File identifier of the replaced sticker
- **sticker** (`telebot.types.InputSticker`) – A JSON-serialized object with information about the added sticker. If exactly the same sticker had already been added to the set, then the set remains unchanged.

Returns

Returns True on success.

Return type

bool

async reply_to(*message*: Message, *text*: str, ***kwargs*) → Message

Convenience function for `send_message(message.chat.id, text, reply_parameters=(message.message_id...), **kwargs)`

Parameters

- **message** (types.Message) – Instance of `telebot.types.Message`
- **text** (str) – Text of the message.
- **kwargs** – Additional keyword arguments which are passed to `telebot.TeleBot.send_message()`

Returns

On success, the sent Message is returned.

Return type

`telebot.types.Message`

async reset_data(*user_id*: int, *chat_id*: int | None = None)

Reset data for a user in chat.

Parameters

- **user_id** (int) – User’s identifier
- **chat_id** (int) – Chat’s identifier

Returns

None

async restrict_chat_member(*chat_id*: int | str, *user_id*: int, *until_date*: int | datetime | None = None, *can_send_messages*: bool | None = None, *can_send_media_messages*: bool | None = None, *can_send_polls*: bool | None = None, *can_send_other_messages*: bool | None = None, *can_add_web_page_previews*: bool | None = None, *can_change_info*: bool | None = None, *can_invite_users*: bool | None = None, *can_pin_messages*: bool | None = None, *permissions*: ChatPermissions | None = None, *use_independent_chat_permissions*: bool | None = None) → bool

Use this method to restrict a user in a supergroup. The bot must be an administrator in the supergroup for this to work and must have the appropriate admin rights. Pass True for all boolean parameters to lift restrictions from a user.

Telegram documentation: <https://core.telegram.org/bots/api#restrictchatmember>

Warning: Individual parameters are deprecated and will be removed, use ‘permissions’ instead

Parameters

- **chat_id** (int or str) – Unique identifier for the target group or username of the target supergroup or channel (in the format @channelusername)
- **user_id** (int) – Unique identifier of the target user

- **until_date** (int or datetime, optional) – Date when restrictions will be lifted for the user, unix time. If user is restricted for more than 366 days or less than 30 seconds from the current time, they are considered to be restricted forever
- **can_send_messages** (bool) – deprecated
- **can_send_media_messages** (bool) – deprecated
- **can_send_polls** (bool) – deprecated
- **can_send_other_messages** (bool) – deprecated
- **can_add_web_page_previews** (bool) – deprecated
- **can_change_info** (bool) – deprecated
- **can_invite_users** (bool) – deprecated
- **can_pin_messages** (bool) – deprecated
- **use_independent_chat_permissions** (bool, optional) – Pass True if chat permissions are set independently. Otherwise, the `can_send_other_messages` and `can_add_web_page_previews` permissions will imply the `can_send_messages`, `can_send_audios`, `can_send_documents`, `can_send_photos`, `can_send_videos`, `can_send_video_notes`, and `can_send_voice_notes` permissions; the `can_send_polls` permission will imply the `can_send_messages` permission.
- **permissions** (types.ChatPermissions) – Pass ChatPermissions object to set all permissions at once. Use this parameter instead of passing all boolean parameters to avoid backward compatibility problems in future.

Returns

True on success

Return type

bool

retrieve_data(*user_id: int, chat_id: int | None = None*)

Returns context manager with data for a user in chat.

Parameters

- **user_id** (*int*) – User identifier
- **chat_id** (*int, optional*) – Chat's unique identifier, defaults to `user_id`

Returns

Context manager with data for a user in chat

Return type

Optional[Any]

async revoke_chat_invite_link(*chat_id: int | str, invite_link: str*) → *ChatInviteLink*

Use this method to revoke an invite link created by the bot. Note: If the primary link is revoked, a new link is automatically generated. The bot must be an administrator in the chat for this to work and must have the appropriate admin rights.

Telegram documentation: <https://core.telegram.org/bots/api#revokechatinvitelink>

Parameters

- **chat_id** (int or str) – Id: Unique identifier for the target chat or username of the target channel (in the format `@channelusername`)

- **invite_link** (str) – The invite link to revoke

Returns

Returns the new invite link as ChatInviteLink object.

Return type

telebot.types.ChatInviteLink

```
async run_webhooks(listen: str | None = '127.0.0.1', port: int | None = 443, url_path: str | None = None,
                    certificate: str | None = None, certificate_key: str | None = None, webhook_url: str |
                    None = None, max_connections: int | None = None, allowed_updates: List | None =
                    None, ip_address: str | None = None, drop_pending_updates: bool | None = None,
                    timeout: int | None = None, secret_token: str | None = None, secret_token_length: int
                    | None = 20, debug: bool | None = False)
```

This class sets webhooks and listens to a given url and port.

Parameters

- **listen** – IP address to listen to. Defaults to 0.0.0.0
- **port** – A port which will be used to listen to webhooks.
- **url_path** – Path to the webhook. Defaults to /token
- **certificate** – Path to the certificate file.
- **certificate_key** – Path to the certificate key file.
- **webhook_url** – Webhook URL.
- **max_connections** – Maximum allowed number of simultaneous HTTPS connections to the webhook for update delivery, 1-100. Defaults to 40. Use lower values to limit the load on your bot's server, and higher values to increase your bot's throughput.
- **allowed_updates** – A JSON-serialized list of the update types you want your bot to receive. For example, specify ["message", "edited_channel_post", "callback_query"] to only receive updates of these types. See Update for a complete list of available update types. Specify an empty list to receive all updates regardless of type (default). If not specified, the previous setting will be used.
- **ip_address** – The fixed IP address which will be used to send webhook requests instead of the IP address resolved through DNS
- **drop_pending_updates** – Pass True to drop all pending updates
- **timeout** – Integer. Request connection timeout
- **secret_token** – Secret token to be used to verify the webhook request.
- **secret_token_length** – Length of a secret token, defaults to 20
- **debug** – Debug mode, defaults to False

Returns

```

async send_animation(chat_id: int | str, animation: Any | str, duration: int | None = None, width: int |
    None = None, height: int | None = None, thumbnail: str | Any | None = None,
    caption: str | None = None, parse_mode: str | None = None, caption_entities:
    List[MessageEntity] | None = None, disable_notification: bool | None = None,
    protect_content: bool | None = None, reply_to_message_id: int | None = None,
    allow_sending_without_reply: bool | None = None, reply_markup:
    InlineKeyboardMarkup | ReplyKeyboardMarkup | ReplyKeyboardRemove |
    ForceReply | None = None, timeout: int | None = None, message_thread_id: int |
    None = None, has_spoiler: bool | None = None, thumb: str | Any | None = None,
    reply_parameters: ReplyParameters | None = None, business_connection_id: str |
    None = None) → Message

```

Use this method to send animation files (GIF or H.264/MPEG-4 AVC video without sound). On success, the sent Message is returned. Bots can currently send animation files of up to 50 MB in size, this limit may be changed in the future.

Telegram documentation: <https://core.telegram.org/bots/api#sendanimation>

Parameters

- **chat_id** (int or str) – Unique identifier for the target chat or username of the target channel (in the format @channelusername)
- **animation** (str or `telebot.types.InputFile`) – Animation to send. Pass a file_id as String to send an animation that exists on the Telegram servers (recommended), pass an HTTP URL as a String for Telegram to get an animation from the Internet, or upload a new animation using multipart/form-data.
- **duration** (int) – Duration of sent animation in seconds
- **width** (int) – Animation width
- **height** (int) – Animation height
- **thumbnail** (str or `telebot.types.InputFile`) – Thumbnail of the file sent; can be ignored if thumbnail generation for the file is supported server-side. The thumbnail should be in JPEG format and less than 200 kB in size. A thumbnail's width and height should not exceed 320. Ignored if the file is not uploaded using multipart/form-data. Thumbnails can't be reused and can be only uploaded as a new file, so you can pass “attach://<file_attach_name>” if the thumbnail was uploaded using multipart/form-data under <file_attach_name>.
- **caption** (str) – Animation caption (may also be used when resending animation by file_id), 0-1024 characters after entities parsing
- **parse_mode** (str) – Mode for parsing entities in the animation caption
- **protect_content** (bool) – Protects the contents of the sent message from forwarding and saving
- **reply_to_message_id** (int) – Deprecated - Use reply_parameters instead. If the message is a reply, ID of the original message
- **reply_markup** (`telebot.types.InlineKeyboardMarkup` or `telebot.types.ReplyKeyboardMarkup` or `telebot.types.ReplyKeyboardRemove` or `telebot.types.ForceReply`) – Additional interface options. A JSON-serialized object for an inline keyboard, custom reply keyboard, instructions to remove reply keyboard or to force a reply from the user.
- **disable_notification** (bool) – Sends the message silently. Users will receive a notification with no sound.

- **timeout** (int) – Timeout in seconds for the request.
- **caption_entities** (list of `telebot.types.MessageEntity`) – List of special entities that appear in the caption, which can be specified instead of `parse_mode`
- **allow_sending_without_reply** (bool) – Deprecated - Use `reply_parameters` instead. Pass True, if the message should be sent even if the specified replied-to message is not found
- **message_thread_id** (int) – Identifier of a message thread, in which the video will be sent
- **has_spoiler** (bool) – Pass True, if the animation should be sent as a spoiler
- **thumb** (str or `telebot.types.InputFile`) – Deprecated. Use `thumbnail` instead
- **reply_parameters** (`telebot.types.ReplyParameters`) – Reply parameters.
- **business_connection_id** (str) – Identifier of a business connection, in which the message will be sent

Returns

On success, the sent Message is returned.

Return type

`telebot.types.Message`

async send_audio(*chat_id: int | str, audio: Any | str, caption: str | None = None, duration: int | None = None, performer: str | None = None, title: str | None = None, reply_to_message_id: int | None = None, reply_markup: InlineKeyboardMarkup | ReplyKeyboardMarkup | ReplyKeyboardRemove | ForceReply | None = None, parse_mode: str | None = None, disable_notification: bool | None = None, timeout: int | None = None, thumbnail: str | Any | None = None, caption_entities: List[MessageEntity] | None = None, allow_sending_without_reply: bool | None = None, protect_content: bool | None = None, message_thread_id: int | None = None, thumb: str | Any | None = None, reply_parameters: ReplyParameters | None = None, business_connection_id: str | None = None*) → `Message`

Use this method to send audio files, if you want Telegram clients to display them in the music player. Your audio must be in the .MP3 or .M4A format. On success, the sent Message is returned. Bots can currently send audio files of up to 50 MB in size, this limit may be changed in the future.

For sending voice messages, use the `send_voice` method instead.

Telegram documentation: <https://core.telegram.org/bots/api#sendaudio>

Parameters

- **chat_id** (int or str) – Unique identifier for the target chat or username of the target channel (in the format @channelusername)
- **audio** (str or `telebot.types.InputFile`) – Audio file to send. Pass a `file_id` as String to send an audio file that exists on the Telegram servers (recommended), pass an HTTP URL as a String for Telegram to get an audio file from the Internet, or upload a new one using `multipart/form-data`. Audio must be in the .MP3 or .M4A format.
- **caption** (str) – Audio caption, 0-1024 characters after entities parsing
- **duration** (int) – Duration of the audio in seconds
- **performer** (str) – Performer
- **title** (str) – Track name

- **reply_to_message_id** (int) – Deprecated - Use `reply_parameters` instead. If the message is a reply, ID of the original message
- **reply_markup** (`telebot.types.InlineKeyboardMarkup` or `telebot.types.ReplyKeyboardMarkup` or `telebot.types.ReplyKeyboardRemove` or `telebot.types.ForceReply`)
- **parse_mode** (str) – Mode for parsing entities in the audio caption. See formatting options for more details.
- **disable_notification** (bool) – Sends the message silently. Users will receive a notification with no sound.
- **timeout** (int) – Timeout in seconds for the request.
- **thumbnail** (str or `telebot.types.InputFile`) – Thumbnail of the file sent; can be ignored if thumbnail generation for the file is supported server-side. The thumbnail should be in JPEG format and less than 200 kB in size. A thumbnail’s width and height should not exceed 320. Ignored if the file is not uploaded using multipart/form-data. Thumbnails can’t be reused and can be only uploaded as a new file, so you can pass “attach://<file_attach_name>” if the thumbnail was uploaded using multipart/form-data under <file_attach_name>
- **caption_entities** (list of `telebot.types.MessageEntity`) – A JSON-serialized list of special entities that appear in the caption, which can be specified instead of `parse_mode`
- **allow_sending_without_reply** (bool) – Deprecated - Use `reply_parameters` instead. Pass True, if the message should be sent even if the specified replied-to message is not found
- **protect_content** (bool) – Protects the contents of the sent message from forwarding and saving
- **message_thread_id** (int) – Identifier of a message thread, in which the message will be sent
- **thumb** (str or `telebot.types.InputFile`) – Deprecated. Use `thumbnail` instead
- **reply_parameters** (`telebot.types.ReplyParameters`) – Reply parameters.
- **business_connection_id** (str) – Unique identifier for the target business connection

Returns

On success, the sent Message is returned.

Return type

`telebot.types.Message`

async send_chat_action(`chat_id: int | str, action: str, timeout: int | None = None, message_thread_id: int | None = None, business_connection_id: str | None = None`) → bool

Use this method when you need to tell the user that something is happening on the bot’s side. The status is set for 5 seconds or less (when a message arrives from your bot, Telegram clients clear its typing status). Returns True on success.

Example: The ImageBot needs some time to process a request and upload the image. Instead of sending a text message along the lines of “Retrieving image, please wait...”, the bot may use `sendChatAction` with `action = upload_photo`. The user will see a “sending photo” status for the bot.

Telegram documentation: <https://core.telegram.org/bots/api#sendchataction>

Parameters

- **chat_id** (int or str) – Unique identifier for the target chat or username of the target channel
- **action** (str) – Type of action to broadcast. Choose one, depending on what the user is about to receive: typing for text messages, upload_photo for photos, record_video or upload_video for videos, record_voice or upload_voice for voice notes, upload_document for general files, choose_sticker for stickers, find_location for location data, record_video_note or upload_video_note for video notes.
- **timeout** (int) – Timeout in seconds for the request.
- **message_thread_id** (int) – The thread to which the message will be sent (supergroups only)
- **business_connection_id** (str) – Identifier of a business connection, in which the message will be sent

Returns

Returns True on success.

Return type

bool

async send_contact(*chat_id: int | str, phone_number: str, first_name: str, last_name: str | None = None, vcard: str | None = None, disable_notification: bool | None = None, reply_to_message_id: int | None = None, reply_markup: InlineKeyboardMarkup | ReplyKeyboardMarkup | ReplyKeyboardRemove | ForceReply | None = None, timeout: int | None = None, allow_sending_without_reply: bool | None = None, protect_content: bool | None = None, message_thread_id: int | None = None, reply_parameters: ReplyParameters | None = None, business_connection_id: str | None = None*) → *Message*

Use this method to send phone contacts. On success, the sent Message is returned.

Telegram documentation: <https://core.telegram.org/bots/api#sendcontact>

Parameters

- **chat_id** (int or str) – Unique identifier for the target chat or username of the target channel
- **phone_number** (str) – Contact's phone number
- **first_name** (str) – Contact's first name
- **last_name** (str) – Contact's last name
- **vcard** (str) – Additional data about the contact in the form of a vCard, 0-2048 bytes
- **disable_notification** (bool) – Sends the message silently. Users will receive a notification with no sound.
- **reply_to_message_id** (int) – Deprecated - Use reply_parameters instead. If the message is a reply, ID of the original message
- **reply_markup** (*telebot.types.InlineKeyboardMarkup* or *telebot.types.ReplyKeyboardMarkup* or *telebot.types.ReplyKeyboardRemove* or *telebot.types.ForceReply*) – Additional interface options. A JSON-serialized object for an inline keyboard, custom reply keyboard, instructions to remove reply keyboard or to force a reply from the user.
- **timeout** (int) – Timeout in seconds for the request.

- **allow_sending_without_reply** (bool) – Deprecated - Use `reply_parameters` instead. Pass True, if the message should be sent even if one of the specified replied-to messages is not found.
- **protect_content** (bool) – Protects the contents of the sent message from forwarding and saving
- **message_thread_id** (int) – The thread to which the message will be sent
- **reply_parameters** (`telebot.types.ReplyParameters`) – Reply parameters.
- **business_connection_id** (str) – Identifier of a business connection, in which the message will be sent

Returns

On success, the sent Message is returned.

Return type

`telebot.types.Message`

```
async send_dice(chat_id: int | str, emoji: str | None = None, disable_notification: bool | None = None,
               reply_to_message_id: int | None = None, reply_markup: InlineKeyboardMarkup |
               ReplyKeyboardMarkup | ReplyKeyboardRemove | ForceReply | None = None, timeout:
               int | None = None, allow_sending_without_reply: bool | None = None, protect_content:
               bool | None = None, message_thread_id: int | None = None, reply_parameters:
               ReplyParameters | None = None, business_connection_id: str | None = None) → Message
```

Use this method to send an animated emoji that will display a random value. On success, the sent Message is returned.

Telegram documentation: <https://core.telegram.org/bots/api#senddice>

Parameters

- **chat_id** (int or str) – Unique identifier for the target chat or username of the target channel (in the format @channelusername)
- **emoji** (str) – Emoji on which the dice throw animation is based. Currently, must be one of “”, “”, “”, “”, “”, or “”. Dice can have values 1-6 for “”, “” and “”, values 1-5 for “” and “”, and values 1-64 for “”. Defaults to “”
- **disable_notification** (bool) – Sends the message silently. Users will receive a notification with no sound.
- **reply_to_message_id** (int) – Deprecated - Use `reply_parameters` instead. If the message is a reply, ID of the original message
- **reply_markup** (`telebot.types.InlineKeyboardMarkup` or `telebot.types.ReplyKeyboardMarkup` or `telebot.types.ReplyKeyboardRemove` or `telebot.types.ForceReply`) – Additional interface options. A JSON-serialized object for an inline keyboard, custom reply keyboard, instructions to remove reply keyboard or to force a reply from the user.
- **timeout** (int) – Timeout in seconds for the request.
- **allow_sending_without_reply** (bool) – Deprecated - Use `reply_parameters` instead. Pass True, if the message should be sent even if the specified replied-to message is not found
- **protect_content** (bool) – Protects the contents of the sent message from forwarding
- **message_thread_id** (int) – The identifier of a message thread, unique within the chat to which the message with the thread identifier belongs

- **reply_parameters** (*telebot.types.ReplyParameters*) – Reply parameters.
- **business_connection_id** (str) – Unique identifier for the target business connection

Returns

On success, the sent Message is returned.

Return type

telebot.types.Message

```
async send_document(chat_id: int | str, document: Any | str, reply_to_message_id: int | None = None,
    caption: str | None = None, reply_markup: InlineKeyboardMarkup |
    ReplyKeyboardMarkup | ReplyKeyboardRemove | ForceReply | None = None,
    parse_mode: str | None = None, disable_notification: bool | None = None, timeout:
    int | None = None, thumbnail: str | Any | None = None, caption_entities:
    List[MessageEntity] | None = None, allow_sending_without_reply: bool | None =
    None, visible_file_name: str | None = None, disable_content_type_detection: bool |
    None = None, data: str | Any | None = None, protect_content: bool | None = None,
    message_thread_id: int | None = None, thumb: str | Any | None = None,
    reply_parameters: ReplyParameters | None = None, business_connection_id: str |
    None = None) → Message
```

Use this method to send general files.

Telegram documentation: <https://core.telegram.org/bots/api#senddocument>

Parameters

- **chat_id** (int or str) – Unique identifier for the target chat or username of the target channel (in the format @channelusername)
- **document** (str or *telebot.types.InputFile*) – (document) File to send. Pass a file_id as String to send a file that exists on the Telegram servers (recommended), pass an HTTP URL as a String for Telegram to get a file from the Internet, or upload a new one using multipart/form-data
- **reply_to_message_id** (int) – Deprecated - Use reply_parameters instead. If the message is a reply, ID of the original message
- **caption** (str) – Document caption (may also be used when resending documents by file_id), 0-1024 characters after entities parsing
- **reply_markup** (*telebot.types.InlineKeyboardMarkup* or *telebot.types.ReplyKeyboardMarkup* or *telebot.types.ReplyKeyboardRemove* or *telebot.types.ForceReply*) – Additional interface options. A JSON-serialized object for an inline keyboard, custom reply keyboard, instructions to remove reply keyboard or to force a reply from the user.
- **parse_mode** (str) – Mode for parsing entities in the document caption
- **disable_notification** (bool) – Sends the message silently. Users will receive a notification with no sound.
- **timeout** (int) – Timeout in seconds for the request.
- **thumbnail** (str or *telebot.types.InputFile*) – InputFile or String : Thumbnail of the file sent; can be ignored if thumbnail generation for the file is supported server-side. The thumbnail should be in JPEG format and less than 200 kB in size. A thumbnail's width and height should not exceed 320. Ignored if the file is not uploaded using multipart/form-data. Thumbnails can't be reused and can be only uploaded as a new file, so you can pass "attach://<file_attach_name>" if the thumbnail was uploaded using multipart/form-data under <file_attach_name>

- **caption_entities** (list of *telebot.types.MessageEntity*) – A JSON-serialized list of special entities that appear in the caption, which can be specified instead of `parse_mode`
- **allow_sending_without_reply** (bool) – Deprecated - Use `reply_parameters` instead. Pass True, if the message should be sent even if the specified replied-to message is not found
- **visible_file_name** (str) – allows to define file name that will be visible in the Telegram instead of original file name
- **disable_content_type_detection** (bool) – Disables automatic server-side content type detection for files uploaded using multipart/form-data
- **data** (str) – function typo miss compatibility: do not use it
- **protect_content** (bool) – Protects the contents of the sent message from forwarding and saving
- **message_thread_id** (int) – Identifier of a message thread, in which the message will be sent
- **thumb** (str or *telebot.types.InputFile*) – Deprecated. Use thumbnail instead
- **reply_parameters** (*telebot.types.ReplyParameters*) – Reply parameters.
- **business_connection_id** (str) – Unique identifier for the target business connection

Returns

On success, the sent Message is returned.

Return type

telebot.types.Message

async send_game(*chat_id: int | str, game_short_name: str, disable_notification: bool | None = None, reply_to_message_id: int | None = None, reply_markup: InlineKeyboardMarkup | ReplyKeyboardMarkup | ReplyKeyboardRemove | ForceReply | None = None, timeout: int | None = None, allow_sending_without_reply: bool | None = None, protect_content: bool | None = None, message_thread_id: int | None = None, reply_parameters: ReplyParameters | None = None, business_connection_id: str | None = None*) → *Message*

Used to send the game.

Telegram documentation: <https://core.telegram.org/bots/api#sendgame>

Parameters

- **chat_id** (int or str) – Unique identifier for the target chat or username of the target channel (in the format @channelusername)
- **game_short_name** (str) – Short name of the game, serves as the unique identifier for the game. Set up your games via @BotFather.
- **disable_notification** (bool) – Sends the message silently. Users will receive a notification with no sound.
- **reply_to_message_id** (int) – Deprecated - Use `reply_parameters` instead. If the message is a reply, ID of the original message
- **reply_markup** (InlineKeyboardMarkup or ReplyKeyboardMarkup or ReplyKeyboardRemove or ForceReply) – Additional interface options. A JSON-serialized object for an inline keyboard, custom reply keyboard, instructions to remove reply keyboard or to force a reply from the user.
- **timeout** (int) – Timeout in seconds for waiting for a response from the bot.

- **allow_sending_without_reply** (bool) – Deprecated - Use `reply_parameters` instead. Pass True, if the message should be sent even if one of the specified replied-to messages is not found.
- **protect_content** (bool) – Pass True, if content of the message needs to be protected from being viewed by the bot.
- **message_thread_id** (int) – Identifier of the thread to which the message will be sent.
- **reply_parameters** (`telebot.types.ReplyParameters`) – Reply parameters.
- **business_connection_id** (str) – Identifier of the business connection.

Returns

On success, the sent Message is returned.

Return type

`types.Message`

async send_invoice(*chat_id: int | str, title: str, description: str, invoice_payload: str, provider_token: str, currency: str, prices: List[LabeledPrice], start_parameter: str | None = None, photo_url: str | None = None, photo_size: int | None = None, photo_width: int | None = None, photo_height: int | None = None, need_name: bool | None = None, need_phone_number: bool | None = None, need_email: bool | None = None, need_shipping_address: bool | None = None, send_phone_number_to_provider: bool | None = None, send_email_to_provider: bool | None = None, is_flexible: bool | None = None, disable_notification: bool | None = None, reply_to_message_id: int | None = None, reply_markup: InlineKeyboardMarkup | ReplyKeyboardMarkup | ReplyKeyboardRemove | ForceReply | None = None, provider_data: str | None = None, timeout: int | None = None, allow_sending_without_reply: bool | None = None, max_tip_amount: int | None = None, suggested_tip_amounts: List[int] | None = None, protect_content: bool | None = None, message_thread_id: int | None = None, reply_parameters: ReplyParameters | None = None*) → *Message*

Sends invoice.

Telegram documentation: <https://core.telegram.org/bots/api#sendinvoice>

Parameters

- **chat_id** (int or str) – Unique identifier for the target private chat
- **title** (str) – Product name, 1-32 characters
- **description** (str) – Product description, 1-255 characters
- **invoice_payload** (str) – Bot-defined invoice payload, 1-128 bytes. This will not be displayed to the user, use for your internal processes.
- **provider_token** (str) – Payments provider token, obtained via @Botfather
- **currency** (str) – Three-letter ISO 4217 currency code, see <https://core.telegram.org/bots/payments#supported-currencies>
- **prices** (List[types.LabeledPrice]) – Price breakdown, a list of components (e.g. product price, tax, discount, delivery cost, delivery tax, bonus, etc.)
- **start_parameter** (str) – Unique deep-linking parameter that can be used to generate this invoice when used as a start parameter
- **photo_url** (str) – URL of the product photo for the invoice. Can be a photo of the goods or a marketing image for a service. People like it better when they see what they are paying for.

- **photo_size** (int) – Photo size in bytes
- **photo_width** (int) – Photo width
- **photo_height** (int) – Photo height
- **need_name** (bool) – Pass True, if you require the user’s full name to complete the order
- **need_phone_number** (bool) – Pass True, if you require the user’s phone number to complete the order
- **need_email** (bool) – Pass True, if you require the user’s email to complete the order
- **need_shipping_address** (bool) – Pass True, if you require the user’s shipping address to complete the order
- **is_flexible** (bool) – Pass True, if the final price depends on the shipping method
- **send_phone_number_to_provider** (bool) – Pass True, if user’s phone number should be sent to provider
- **send_email_to_provider** (bool) – Pass True, if user’s email address should be sent to provider
- **disable_notification** (bool) – Sends the message silently. Users will receive a notification with no sound.
- **reply_to_message_id** (int) – Deprecated - Use `reply_parameters` instead. If the message is a reply, ID of the original message
- **reply_markup** (str) – A JSON-serialized object for an inline keyboard. If empty, one ‘Pay total price’ button will be shown. If not empty, the first button must be a Pay button
- **provider_data** (str) – A JSON-serialized data about the invoice, which will be shared with the payment provider. A detailed description of required fields should be provided by the payment provider.
- **timeout** (int) – Timeout of a request, defaults to None
- **allow_sending_without_reply** (bool) – Deprecated - Use `reply_parameters` instead. Pass True, if the message should be sent even if the specified replied-to message is not found
- **max_tip_amount** (int) – The maximum accepted amount for tips in the smallest units of the currency
- **suggested_tip_amounts** (list of int) – A JSON-serialized array of suggested amounts of tips in the smallest units of the currency. At most 4 suggested tip amounts can be specified. The suggested tip amounts must be positive, passed in a strictly increased order and must not exceed `max_tip_amount`.
- **protect_content** (bool) – Protects the contents of the sent message from forwarding and saving
- **message_thread_id** (int) – The identifier of a message thread, in which the invoice message will be sent
- **reply_parameters** (*telebot.types.ReplyParameters*) – Reply parameters.

Returns

On success, the sent Message is returned.

Return type

`types.Message`

```

async send_location(chat_id: int | str, latitude: float, longitude: float, live_period: int | None = None,
                    reply_to_message_id: int | None = None, reply_markup: InlineKeyboardMarkup |
                    ReplyKeyboardMarkup | ReplyKeyboardRemove | ForceReply | None = None,
                    disable_notification: bool | None = None, timeout: int | None = None,
                    horizontal_accuracy: float | None = None, heading: int | None = None,
                    proximity_alert_radius: int | None = None, allow_sending_without_reply: bool |
                    None = None, protect_content: bool | None = None, message_thread_id: int | None
                    = None, reply_parameters: ReplyParameters | None = None,
                    business_connection_id: str | None = None) → Message

```

Use this method to send point on the map. On success, the sent Message is returned.

Telegram documentation: <https://core.telegram.org/bots/api#sendlocation>

Parameters

- **chat_id** (int or str) – Unique identifier for the target chat or username of the target channel (in the format @channelusername)
- **latitude** (float) – Latitude of the location
- **longitude** (float) – Longitude of the location
- **live_period** (int) – Period in seconds for which the location will be updated (see Live Locations, should be between 60 and 86400).
- **reply_to_message_id** (int) – Deprecated - Use reply_parameters instead. If the message is a reply, ID of the original message
- **reply_markup** (*telebot.types.InlineKeyboardMarkup* or *telebot.types.ReplyKeyboardMarkup* or *telebot.types.ReplyKeyboardRemove* or *telebot.types.ForceReply*) – Additional interface options. A JSON-serialized object for an inline keyboard, custom reply keyboard, instructions to remove reply keyboard or to force a reply from the user.
- **disable_notification** (bool) – Sends the message silently. Users will receive a notification with no sound.
- **timeout** (int) – Timeout in seconds for the request.
- **horizontal_accuracy** (float) – The radius of uncertainty for the location, measured in meters; 0-1500
- **heading** (int) – For live locations, a direction in which the user is moving, in degrees. Must be between 1 and 360 if specified.
- **proximity_alert_radius** (int) – For live locations, a maximum distance for proximity alerts about approaching another chat member, in meters. Must be between 1 and 100000 if specified.
- **allow_sending_without_reply** (bool) – Deprecated - Use reply_parameters instead. Pass True, if the message should be sent even if the specified replied-to message is not found
- **protect_content** (bool) – Protects the contents of the sent message from forwarding and saving
- **message_thread_id** (int) – Identifier of a message thread, in which the message will be sent
- **reply_parameters** (*telebot.types.ReplyParameters*) – Reply parameters.
- **business_connection_id** (str) – Identifier of a business connection, in which the message will be sent

Returns

On success, the sent Message is returned.

Return type

telebot.types.Message

```
async send_media_group(chat_id: int | str, media: List[InputMediaAudio | InputMediaDocument |
InputMediaPhoto | InputMediaVideo], disable_notification: bool | None = None,
protect_content: bool | None = None, reply_to_message_id: int | None = None,
timeout: int | None = None, allow_sending_without_reply: bool | None = None,
message_thread_id: int | None = None, reply_parameters: ReplyParameters |
None = None, business_connection_id: str | None = None) → List[Message]
```

Use this method to send a group of photos, videos, documents or audios as an album. Documents and audio files can be only grouped in an album with messages of the same type. On success, an array of Messages that were sent is returned.

Telegram documentation: <https://core.telegram.org/bots/api#sendmediagroup>

Parameters

- **chat_id** (int or str) – Unique identifier for the target chat or username of the target channel (in the format @channelusername)
- **media** (list of types.InputMedia) – A JSON-serialized array describing messages to be sent, must include 2-10 items
- **disable_notification** (bool) – Sends the messages silently. Users will receive a notification with no sound.
- **protect_content** (bool) – Protects the contents of the sent message from forwarding and saving
- **reply_to_message_id** (int) – Deprecated - Use reply_parameters instead. If the message is a reply, ID of the original message
- **timeout** (int) – Timeout in seconds for the request.
- **allow_sending_without_reply** (bool) – Deprecated - Use reply_parameters instead. Pass True, if the message should be sent even if the specified replied-to message is not found
- **message_thread_id** (int) – Identifier of a message thread, in which the messages will be sent
- **reply_parameters** (*telebot.types.ReplyParameters*) – Reply parameters.
- **business_connection_id** (str) – Identifier of a business connection, in which the message will be sent

Returns

On success, an array of Messages that were sent is returned.

Return type

List[*types.Message*]

```

async send_message(chat_id: int | str, text: str, parse_mode: str | None = None, entities:
    List[MessageEntity] | None = None, disable_web_page_preview: bool | None = None,
    disable_notification: bool | None = None, protect_content: bool | None = None,
    reply_to_message_id: int | None = None, allow_sending_without_reply: bool | None
    = None, reply_markup: InlineKeyboardMarkup | ReplyKeyboardMarkup |
    ReplyKeyboardRemove | ForceReply | None = None, timeout: int | None = None,
    message_thread_id: int | None = None, reply_parameters: ReplyParameters | None =
    None, link_preview_options: LinkPreviewOptions | None = None,
    business_connection_id: str | None = None) → Message

```

Use this method to send text messages.

Warning: Do not send more than about 4096 characters each message, otherwise you'll risk an HTTP 414 error. If you must send more than 4096 characters, use the `split_string` or `smart_split` function in `util.py`.

Telegram documentation: <https://core.telegram.org/bots/api#sendmessage>

Parameters

- **chat_id** (int or str) – Unique identifier for the target chat or username of the target channel (in the format @channelusername)
- **text** (str) – Text of the message to be sent
- **parse_mode** (str) – Mode for parsing entities in the message text.
- **entities** (Array of `telebot.types.MessageEntity`) – List of special entities that appear in message text, which can be specified instead of `parse_mode`
- **disable_web_page_preview** (bool) – Deprecated - Use `link_preview_options` instead.
- **disable_notification** (bool) – Sends the message silently. Users will receive a notification with no sound.
- **protect_content** (bool) – If True, the message content will be hidden for all users except for the target user
- **reply_to_message_id** (int) – Deprecated - Use `reply_parameters` instead. If the message is a reply, ID of the original message
- **allow_sending_without_reply** (bool) – Deprecated - Use `reply_parameters` instead. Pass True, if the message should be sent even if the specified replied-to message is not found
- **reply_markup** (`telebot.types.InlineKeyboardMarkup` or `telebot.types.ReplyKeyboardMarkup` or `telebot.types.ReplyKeyboardRemove` or `telebot.types.ForceReply`) – Additional interface options. A JSON-serialized object for an inline keyboard, custom reply keyboard, instructions to remove reply keyboard or to force a reply from the user.
- **timeout** (int) – Timeout in seconds for the request.
- **message_thread_id** (int) – Unique identifier for the target message thread (topic) of the forum; for forum supergroups only
- **reply_parameters** (`telebot.types.ReplyParameters`) – Reply parameters.
- **link_preview_options** (`telebot.types.LinkPreviewOptions`) – Options for previewing links.
- **business_connection_id** (str) – Unique identifier for the target business connection

Returns

On success, the sent Message is returned.

Return type`telebot.types.Message`

async send_photo(*chat_id*: int | str, *photo*: Any | str, *caption*: str | None = None, *parse_mode*: str | None = None, *caption_entities*: List[MessageEntity] | None = None, *disable_notification*: bool | None = None, *protect_content*: bool | None = None, *reply_to_message_id*: int | None = None, *allow_sending_without_reply*: bool | None = None, *reply_markup*: InlineKeyboardMarkup | ReplyKeyboardMarkup | ReplyKeyboardRemove | ForceReply | None = None, *timeout*: int | None = None, *message_thread_id*: int | None = None, *has_spoiler*: bool | None = None, *reply_parameters*: ReplyParameters | None = None, *business_connection_id*: str | None = None) → Message

Use this method to send photos. On success, the sent Message is returned.

Telegram documentation: <https://core.telegram.org/bots/api#sendphoto>

Parameters

- **chat_id** (int or str) – Unique identifier for the target chat or username of the target channel (in the format @channelusername)
- **photo** (str or `telebot.types.InputFile`) – Photo to send. Pass a file_id as String to send a photo that exists on the Telegram servers (recommended), pass an HTTP URL as a String for Telegram to get a photo from the Internet, or upload a new photo using multipart/form-data. The photo must be at most 10 MB in size. The photo's width and height must not exceed 10000 in total. Width and height ratio must be at most 20.
- **caption** (str) – Photo caption (may also be used when resending photos by file_id), 0-1024 characters after entities parsing
- **parse_mode** (str) – Mode for parsing entities in the photo caption.
- **caption_entities** (list of `telebot.types.MessageEntity`) – A JSON-serialized list of special entities that appear in the caption, which can be specified instead of parse_mode
- **disable_notification** (bool) – Sends the message silently. Users will receive a notification with no sound.
- **protect_content** (bool) – Protects the contents of the sent message from forwarding and saving
- **reply_to_message_id** (int) – Deprecated - Use reply_parameters instead. If the message is a reply, ID of the original message
- **allow_sending_without_reply** (bool) – Deprecated - Use reply_parameters instead. Pass True, if the message should be sent even if the specified replied-to message is not found
- **reply_markup** (`telebot.types.InlineKeyboardMarkup` or `telebot.types.ReplyKeyboardMarkup` or `telebot.types.ReplyKeyboardRemove` or `telebot.types.ForceReply`) – Additional interface options. A JSON-serialized object for an inline keyboard, custom reply keyboard, instructions to remove reply keyboard or to force a reply from the user.
- **timeout** (int) – Timeout in seconds for the request.
- **message_thread_id** (int) – Identifier of a message thread, in which the message will be sent
- **has_spoiler** (bool) – Pass True, if the photo should be sent as a spoiler
- **reply_parameters** (`telebot.types.ReplyParameters`) – Reply parameters.

- **business_connection_id** (str) – Unique identifier for the target business connection

Returns

On success, the sent Message is returned.

Return type

`telebot.types.Message`

```
async send_poll(chat_id: int | str, question: str, options: List[str], is_anonymous: bool | None = None,
               type: str | None = None, allows_multiple_answers: bool | None = None,
               correct_option_id: int | None = None, explanation: str | None = None,
               explanation_parse_mode: str | None = None, open_period: int | None = None,
               close_date: int | datetime | None = None, is_closed: bool | None = None,
               disable_notification: bool | None = False, reply_to_message_id: int | None = None,
               reply_markup: InlineKeyboardMarkup | ReplyKeyboardMarkup | ReplyKeyboardRemove
               | ForceReply | None = None, allow_sending_without_reply: bool | None = None, timeout:
               int | None = None, explanation_entities: List[MessageEntity] | None = None,
               protect_content: bool | None = None, message_thread_id: int | None = None,
               reply_parameters: ReplyParameters | None = None, business_connection_id: str | None =
               None) → Message
```

Use this method to send a native poll. On success, the sent Message is returned.

Telegram documentation: <https://core.telegram.org/bots/api#sendpoll>

Parameters

- **chat_id** (int | str) – Unique identifier for the target chat or username of the target channel
- **question** (str) – Poll question, 1-300 characters
- **options** (list of str) – A JSON-serialized list of answer options, 2-10 strings 1-100 characters each
- **is_anonymous** (bool) – True, if the poll needs to be anonymous, defaults to True
- **type** (str) – Poll type, “quiz” or “regular”, defaults to “regular”
- **allows_multiple_answers** (bool) – True, if the poll allows multiple answers, ignored for polls in quiz mode, defaults to False
- **correct_option_id** (int) – 0-based identifier of the correct answer option. Available only for polls in quiz mode, defaults to None
- **explanation** (str) – Text that is shown when a user chooses an incorrect answer or taps on the lamp icon in a quiz-style poll, 0-200 characters with at most 2 line feeds after entities parsing
- **explanation_parse_mode** (str) – Mode for parsing entities in the explanation. See formatting options for more details.
- **open_period** (int) – Amount of time in seconds the poll will be active after creation, 5-600. Can’t be used together with close_date.
- **close_date** (int | datetime) – Point in time (Unix timestamp) when the poll will be automatically closed.
- **is_closed** (bool) – Pass True, if the poll needs to be immediately closed. This can be useful for poll preview.
- **disable_notification** (bool) – Sends the message silently. Users will receive a notification with no sound.

- **reply_to_message_id** (int) – Deprecated - Use `reply_parameters` instead. If the message is a reply, ID of the original message
- **allow_sending_without_reply** (bool) – Deprecated - Use `reply_parameters` instead. Pass True, if the poll allows multiple options to be voted simultaneously.
- **reply_markup** (InlineKeyboardMarkup | ReplyKeyboardMarkup | ReplyKeyboardRemove | ForceReply) – Additional interface options. A JSON-serialized object for an inline keyboard, custom reply keyboard, instructions to remove reply keyboard or to force a reply from the user.
- **timeout** (int) – Timeout in seconds for waiting for a response from the user.
- **explanation_entities** (list of MessageEntity) – A JSON-serialized list of special entities that appear in the explanation, which can be specified instead of `parse_mode`
- **protect_content** (bool) – Protects the contents of the sent message from forwarding and saving
- **message_thread_id** (int) – The identifier of a message thread, in which the poll will be sent
- **reply_parameters** (*telebot.types.ReplyParameters*) – Reply parameters.
- **business_connection_id** (str) – Identifier of the business connection to send the message through

Returns

On success, the sent Message is returned.

Return type

`types.Message`

async send_sticker(*chat_id: int | str, sticker: Any | str, reply_to_message_id: int | None = None, reply_markup: InlineKeyboardMarkup | ReplyKeyboardMarkup | ReplyKeyboardRemove | ForceReply | None = None, disable_notification: bool | None = None, timeout: int | None = None, allow_sending_without_reply: bool | None = None, protect_content: bool | None = None, data: Any | str = None, message_thread_id: int | None = None, emoji: str | None = None, reply_parameters: ReplyParameters | None = None, business_connection_id: str | None = None*) → *Message*

Use this method to send static .WEBP, animated .TGS, or video .WEBM stickers. On success, the sent Message is returned.

Telegram documentation: <https://core.telegram.org/bots/api#sendsticker>

Parameters

- **chat_id** (int or str) – Unique identifier for the target chat or username of the target channel (in the format @channelusername)
- **sticker** (str or *telebot.types.InputFile*) – Sticker to send. Pass a file_id as String to send a file that exists on the Telegram servers (recommended), pass an HTTP URL as a String for Telegram to get a .webp file from the Internet, or upload a new one using multipart/form-data.
- **reply_to_message_id** (int) – Deprecated - Use `reply_parameters` instead. If the message is a reply, ID of the original message
- **reply_markup** (*telebot.types.InlineKeyboardMarkup* or *telebot.types.ReplyKeyboardMarkup* or *telebot.types.ReplyKeyboardRemove* or *telebot.types.ForceReply*) – Additional interface options. A JSON-serialized object for an

inline keyboard, custom reply keyboard, instructions to remove reply keyboard or to force a reply from the user.

- **disable_notification** (bool) – to disable the notification
- **timeout** (int) – Timeout in seconds for the request.
- **allow_sending_without_reply** (bool) – Deprecated - Use `reply_parameters` instead. Pass True, if the message should be sent even if the specified replied-to message is not found
- **protect_content** (bool) – Protects the contents of the sent message from forwarding and saving
- **data** (str) – function typo miss compatibility: do not use it
- **message_thread_id** (int) – Identifier of a message thread, in which the message will be sent
- **emoji** (str) – Emoji associated with the sticker; only for just uploaded stickers
- **reply_parameters** (*telebot.types.ReplyParameters*) – Reply parameters.
- **business_connection_id** (str) – Unique identifier for the target business connection

Returns

On success, the sent Message is returned.

Return type

telebot.types.Message

async send_venue(*chat_id: int | str, latitude: float, longitude: float, title: str, address: str, foursquare_id: str | None = None, foursquare_type: str | None = None, disable_notification: bool | None = None, reply_to_message_id: int | None = None, reply_markup: InlineKeyboardMarkup | ReplyKeyboardMarkup | ReplyKeyboardRemove | ForceReply | None = None, timeout: int | None = None, allow_sending_without_reply: bool | None = None, google_place_id: str | None = None, google_place_type: str | None = None, protect_content: bool | None = None, message_thread_id: int | None = None, reply_parameters: ReplyParameters | None = None, business_connection_id: str | None = None*) → *Message*

Use this method to send information about a venue. On success, the sent Message is returned.

Telegram documentation: <https://core.telegram.org/bots/api#sendvenue>

Parameters

- **chat_id** (int or str) – Unique identifier for the target chat or username of the target channel
- **latitude** (float) – Latitude of the venue
- **longitude** (float) – Longitude of the venue
- **title** (str) – Name of the venue
- **address** (str) – Address of the venue
- **foursquare_id** (str) – Foursquare identifier of the venue
- **foursquare_type** (str) – Foursquare type of the venue, if known. (For example, “arts_entertainment/default”, “arts_entertainment/aquarium” or “food/icecream”.)
- **disable_notification** (bool) – Sends the message silently. Users will receive a notification with no sound.

- **reply_to_message_id** (int) – Deprecated - Use `reply_parameters` instead. If the message is a reply, ID of the original message
- **reply_markup** (`telebot.types.InlineKeyboardMarkup` or `telebot.types.ReplyKeyboardMarkup` or `telebot.types.ReplyKeyboardRemove` or `telebot.types.ForceReply`) – Additional interface options. A JSON-serialized object for an inline keyboard, custom reply keyboard, instructions to remove reply keyboard or to force a reply from the user.
- **timeout** (int) – Timeout in seconds for the request.
- **allow_sending_without_reply** (bool) – Deprecated - Use `reply_parameters` instead. Pass True, if the message should be sent even if one of the specified replied-to messages is not found.
- **google_place_id** (str) – Google Places identifier of the venue
- **google_place_type** (str) – Google Places type of the venue.
- **protect_content** (bool) – Protects the contents of the sent message from forwarding and saving
- **message_thread_id** (int) – The thread to which the message will be sent
- **reply_parameters** (`telebot.types.ReplyParameters`) – Reply parameters.
- **business_connection_id** (str) – Identifier of a business connection, in which the message will be sent

Returns

On success, the sent Message is returned.

Return type

`telebot.types.Message`

async send_video(*chat_id: int | str, video: Any | str, duration: int | None = None, width: int | None = None, height: int | None = None, thumbnail: str | Any | None = None, caption: str | None = None, parse_mode: str | None = None, caption_entities: List[MessageEntity] | None = None, supports_streaming: bool | None = None, disable_notification: bool | None = None, protect_content: bool | None = None, reply_to_message_id: int | None = None, allow_sending_without_reply: bool | None = None, reply_markup: InlineKeyboardMarkup | ReplyKeyboardMarkup | ReplyKeyboardRemove | ForceReply | None = None, timeout: int | None = None, data: str | Any | None = None, message_thread_id: int | None = None, has_spoiler: bool | None = None, thumb: str | Any | None = None, reply_parameters: ReplyParameters | None = None, business_connection_id: str | None = None*) → *Message*

Use this method to send video files, Telegram clients support mp4 videos (other formats may be sent as Document).

Telegram documentation: <https://core.telegram.org/bots/api#sendvideo>

Parameters

- **chat_id** (int or str) – Unique identifier for the target chat or username of the target channel (in the format @channelusername)
- **video** (str or `telebot.types.InputFile`) – Video to send. You can either pass a `file_id` as String to resend a video that is already on the Telegram servers, or upload a new video file using multipart/form-data.
- **duration** (int) – Duration of sent video in seconds
- **width** (int) – Video width

- **height** (int) – Video height
- **thumbnail** (str or *telebot.types.InputFile*) – Thumbnail of the file sent; can be ignored if thumbnail generation for the file is supported server-side. The thumbnail should be in JPEG format and less than 200 kB in size. A thumbnail’s width and height should not exceed 320. Ignored if the file is not uploaded using multipart/form-data. Thumbnails can’t be reused and can be only uploaded as a new file, so you can pass “attach://<file_attach_name>” if the thumbnail was uploaded using multipart/form-data under <file_attach_name>.
- **caption** (str) – Video caption (may also be used when resending videos by file_id), 0-1024 characters after entities parsing
- **parse_mode** (str) – Mode for parsing entities in the video caption
- **caption_entities** (list of *telebot.types.MessageEntity*) – List of special entities that appear in the caption, which can be specified instead of parse_mode
- **supports_streaming** (bool) – Pass True, if the uploaded video is suitable for streaming
- **disable_notification** (bool) – Sends the message silently. Users will receive a notification with no sound.
- **protect_content** (bool) – Protects the contents of the sent message from forwarding and saving
- **reply_to_message_id** (int) – Deprecated - Use reply_parameters instead. If the message is a reply, ID of the original message
- **allow_sending_without_reply** (bool) – Deprecated - Use reply_parameters instead. Pass True, if the message should be sent even if the specified replied-to message is not found
- **reply_markup** (*telebot.types.InlineKeyboardMarkup* or *telebot.types.ReplyKeyboardMarkup* or *telebot.types.ReplyKeyboardRemove* or *telebot.types.ForceReply*) – Additional interface options. A JSON-serialized object for an inline keyboard, custom reply keyboard, instructions to remove reply keyboard or to force a reply from the user.
- **timeout** (int) – Timeout in seconds for the request.
- **data** (str) – function typo miss compatibility: do not use it
- **message_thread_id** (int) – Identifier of a message thread, in which the video will be sent
- **has_spoiler** (bool) – Pass True, if the video should be sent as a spoiler
- **thumb** (str or *telebot.types.InputFile*) – Deprecated. Use thumbnail instead
- **reply_parameters** (*telebot.types.ReplyParameters*) – Reply parameters.
- **business_connection_id** (str) – Identifier of a business connection, in which the message will be sent

Returns

On success, the sent Message is returned.

Return type

telebot.types.Message

```

async send_video_note(chat_id: int | str, data: Any | str, duration: int | None = None, length: int | None
= None, reply_to_message_id: int | None = None, reply_markup:
InlineKeyboardMarkup | ReplyKeyboardMarkup | ReplyKeyboardRemove |
ForceReply | None = None, disable_notification: bool | None = None, timeout: int
| None = None, thumbnail: str | Any | None = None,
allow_sending_without_reply: bool | None = None, protect_content: bool | None
= None, message_thread_id: int | None = None, thumb: str | Any | None = None,
reply_parameters: ReplyParameters | None = None, business_connection_id: str |
None = None) → Message

```

As of v.4.0, Telegram clients support rounded square MPEG4 videos of up to 1 minute long. Use this method to send video messages. On success, the sent Message is returned.

Telegram documentation: <https://core.telegram.org/bots/api#sendvideonote>

Parameters

- **chat_id** (int or str) – Unique identifier for the target chat or username of the target channel (in the format @channelusername)
- **data** (str or `telebot.types.InputFile`) – Video note to send. Pass a file_id as String to send a video note that exists on the Telegram servers (recommended) or upload a new video using multipart/form-data. Sending video notes by a URL is currently unsupported
- **duration** (int) – Duration of sent video in seconds
- **length** (int) – Video width and height, i.e. diameter of the video message
- **reply_to_message_id** (int) – Deprecated - Use reply_parameters instead. If the message is a reply, ID of the original message
- **reply_markup** (`telebot.types.InlineKeyboardMarkup` or `telebot.types.ReplyKeyboardMarkup` or `telebot.types.ReplyKeyboardRemove` or `telebot.types.ForceReply`) – Additional interface options. A JSON-serialized object for an inline keyboard, custom reply keyboard, instructions to remove reply keyboard or to force a reply from the user.
- **disable_notification** (bool) – Sends the message silently. Users will receive a notification with no sound.
- **timeout** (int) – Timeout in seconds for the request.
- **thumbnail** (str or `telebot.types.InputFile`) – Thumbnail of the file sent; can be ignored if thumbnail generation for the file is supported server-side. The thumbnail should be in JPEG format and less than 200 kB in size. A thumbnail’s width and height should not exceed 320. Ignored if the file is not uploaded using multipart/form-data. Thumbnails can’t be reused and can be only uploaded as a new file, so you can pass “attach://<file_attach_name>” if the thumbnail was uploaded using multipart/form-data under <file_attach_name>.
- **allow_sending_without_reply** (bool) – Deprecated - Use reply_parameters instead. Pass True, if the message should be sent even if the specified replied-to message is not found
- **protect_content** (bool) – Protects the contents of the sent message from forwarding and saving
- **message_thread_id** (int) – Identifier of a message thread, in which the video note will be sent
- **thumb** (str or `telebot.types.InputFile`) – Deprecated. Use thumbnail instead
- **reply_parameters** (`telebot.types.ReplyParameters`) – Reply parameters.

- **business_connection_id** (str) – Identifier of a business connection, in which the message will be sent

Returns

On success, the sent Message is returned.

Return type

`telebot.types.Message`

```
async send_voice(chat_id: int | str, voice: Any | str, caption: str | None = None, duration: int | None = None, reply_to_message_id: int | None = None, reply_markup: InlineKeyboardMarkup | ReplyKeyboardMarkup | ReplyKeyboardRemove | ForceReply | None = None, parse_mode: str | None = None, disable_notification: bool | None = None, timeout: int | None = None, caption_entities: List[MessageEntity] | None = None, allow_sending_without_reply: bool | None = None, protect_content: bool | None = None, message_thread_id: int | None = None, reply_parameters: ReplyParameters | None = None, business_connection_id: str | None = None) → Message
```

Use this method to send audio files, if you want Telegram clients to display the file as a playable voice message. For this to work, your audio must be in an .OGG file encoded with OPUS (other formats may be sent as Audio or Document). On success, the sent Message is returned. Bots can currently send voice messages of up to 50 MB in size, this limit may be changed in the future.

Telegram documentation: <https://core.telegram.org/bots/api#sendvoice>

Parameters

- **chat_id** (int or str) – Unique identifier for the target chat or username of the target channel (in the format @channelusername)
- **voice** (str or `telebot.types.InputFile`) – Audio file to send. Pass a file_id as String to send a file that exists on the Telegram servers (recommended), pass an HTTP URL as a String for Telegram to get a file from the Internet, or upload a new one using multipart/form-data.
- **caption** (str) – Voice message caption, 0-1024 characters after entities parsing
- **duration** (int) – Duration of the voice message in seconds
- **reply_to_message_id** (int) – Deprecated - Use reply_parameters instead. If the message is a reply, ID of the original message
- **reply_markup** (`telebot.types.InlineKeyboardMarkup` or `telebot.types.ReplyKeyboardMarkup` or `telebot.types.ReplyKeyboardRemove` or `telebot.types.ForceReply`) – Additional interface options. A JSON-serialized object for an inline keyboard, custom reply keyboard, instructions to remove reply keyboard or to force a reply from the user.
- **parse_mode** (str) – Mode for parsing entities in the voice message caption. See formatting options for more details.
- **disable_notification** (bool) – Sends the message silently. Users will receive a notification with no sound.
- **timeout** (int) – Timeout in seconds for the request.
- **caption_entities** (list of `telebot.types.MessageEntity`) – A JSON-serialized list of special entities that appear in the caption, which can be specified instead of parse_mode
- **allow_sending_without_reply** (bool) – Deprecated - Use reply_parameters instead. Pass True, if the message should be sent even if the specified replied-to message is not found

- **protect_content** (bool) – Protects the contents of the sent message from forwarding and saving
- **message_thread_id** (int) – Identifier of a message thread, in which the message will be sent
- **reply_parameters** (*telebot.types.ReplyParameters*) – Reply parameters.
- **business_connection_id** (str) – Unique identifier for the target business connection

Returns

On success, the sent Message is returned.

async set_chat_administrator_custom_title(*chat_id: int | str, user_id: int, custom_title: str*) → bool

Use this method to set a custom title for an administrator in a supergroup promoted by the bot. Returns True on success.

Telegram documentation: <https://core.telegram.org/bots/api#setchatadministratorcustomtitle>

Parameters

- **chat_id** (int or str) – Unique identifier for the target chat or username of the target supergroup (in the format @supergroupusername)
- **user_id** (int) – Unique identifier of the target user
- **custom_title** (str) – New custom title for the administrator; 0-16 characters, emoji are not allowed

Returns

True on success.

Return type

bool

async set_chat_description(*chat_id: int | str, description: str | None = None*) → bool

Use this method to change the description of a supergroup or a channel. The bot must be an administrator in the chat for this to work and must have the appropriate admin rights.

Telegram documentation: <https://core.telegram.org/bots/api#setchatdescription>

Parameters

- **chat_id** (int or str) – Unique identifier for the target chat or username of the target channel (in the format @channelusername)
- **description** (str) – Str: New chat description, 0-255 characters

Returns

True on success.

Return type

bool

async set_chat_menu_button(*chat_id: int | str = None, menu_button: MenuButton = None*) → bool

Use this method to change the bot's menu button in a private chat, or the default menu button. Returns True on success.

Telegram documentation: <https://core.telegram.org/bots/api#setchatmenubutton>

Parameters

- **chat_id** (int or str) – Unique identifier for the target private chat. If not specified, default bot's menu button will be changed.

- **menu_button** (*telebot.types.MenuButton*) – A JSON-serialized object for the new bot’s menu button. Defaults to `MenuButtonDefault`

Returns

True on success.

Return type

bool

async set_chat_permissions(*chat_id: int | str, permissions: ChatPermissions, use_independent_chat_permissions: bool | None = None*) → bool

Use this method to set default chat permissions for all members. The bot must be an administrator in the group or a supergroup for this to work and must have the `can_restrict_members` admin rights.

Telegram documentation: <https://core.telegram.org/bots/api#setchatpermissions>

Parameters

- **chat_id** (int or str) – Unique identifier for the target chat or username of the target supergroup (in the format `@supergroupusername`)
- **permissions** (*telebot.types.ChatPermissions*) – New default chat permissions
- **use_independent_chat_permissions** (bool) – Pass True if chat permissions are set independently. Otherwise, the `can_send_other_messages` and `can_add_web_page_previews` permissions will imply the `can_send_messages`, `can_send_audios`, `can_send_documents`, `can_send_photos`, `can_send_videos`, `can_send_video_notes`, and `can_send_voice_notes` permissions; the `can_send_polls` permission will imply the `can_send_messages` permission.

Returns

True on success

Return type

bool

async set_chat_photo(*chat_id: int | str, photo: Any*) → bool

Use this method to set a new profile photo for the chat. Photos can’t be changed for private chats. The bot must be an administrator in the chat for this to work and must have the appropriate admin rights. Returns True on success. Note: In regular groups (non-supergroups), this method will only work if the ‘All Members Are Admins’ setting is off in the target group.

Telegram documentation: <https://core.telegram.org/bots/api#setchatphoto>

Parameters

- **chat_id** (int or str) – Int or Str: Unique identifier for the target chat or username of the target channel (in the format `@channelusername`)
- **photo** (*typing.Union[file_like, str]*) – `InputFile`: New chat photo, uploaded using multipart/form-data

Returns

True on success.

Return type

bool

async set_chat_sticker_set(*chat_id: int | str, sticker_set_name: str*) → *StickerSet*

Use this method to set a new group sticker set for a supergroup. The bot must be an administrator in the chat for this to work and must have the appropriate administrator rights. Use the field `can_set_sticker_set` optionally returned in `getChat` requests to check if the bot can use this method. Returns True on success.

Telegram documentation: <https://core.telegram.org/bots/api#setchatstickerset>

Parameters

- **chat_id** (int or str) – Unique identifier for the target chat or username of the target supergroup (in the format @supergroupusername)
- **sticker_set_name** (str) – Name of the sticker set to be set as the group sticker set

Returns

StickerSet object

Return type

telebot.types.StickerSet

async set_chat_title(*chat_id: int | str, title: str*) → bool

Use this method to change the title of a chat. Titles can't be changed for private chats. The bot must be an administrator in the chat for this to work and must have the appropriate admin rights. Returns True on success. Note: In regular groups (non-supergroups), this method will only work if the 'All Members Are Admins' setting is off in the target group.

Telegram documentation: <https://core.telegram.org/bots/api#setchattitle>

Parameters

- **chat_id** (int or str) – Unique identifier for the target chat or username of the target channel (in the format @channelusername)
- **title** (str) – New chat title, 1-255 characters

Returns

True on success.

Return type

bool

async set_custom_emoji_sticker_set_thumbnail(*name: str, custom_emoji_id: str | None = None*) → bool

Use this method to set the thumbnail of a custom emoji sticker set. Returns True on success.

Parameters

- **name** (str) – Sticker set name
- **custom_emoji_id** (str) – Custom emoji identifier of a sticker from the sticker set; pass an empty string to drop the thumbnail and use the first sticker as the thumbnail.

Returns

Returns True on success.

Return type

bool

async set_game_score(*user_id: int | str, score: int, force: bool | None = None, chat_id: int | str | None = None, message_id: int | None = None, inline_message_id: str | None = None, disable_edit_message: bool | None = None*) → *Message* | bool

Sets the value of points in the game to a specific user.

Telegram documentation: <https://core.telegram.org/bots/api#setgamescore>

Parameters

- **user_id** (int or str) – User identifier
- **score** (int) – New score, must be non-negative

- **force** (bool) – Pass True, if the high score is allowed to decrease. This can be useful when fixing mistakes or banning cheaters
- **chat_id** (int or str) – Required if `inline_message_id` is not specified. Unique identifier for the target chat or username of the target channel (in the format @channelusername)
- **message_id** (int) – Required if `inline_message_id` is not specified. Identifier of the sent message
- **inline_message_id** (str) – Required if `chat_id` and `message_id` are not specified. Identifier of the inline message
- **disable_edit_message** (bool) – Pass True, if the game message should not be automatically edited to include the current scoreboard

Returns

On success, if the message was sent by the bot, returns the edited Message, otherwise returns True.

Return type

`types.Message` or `bool`

```
async set_message_reaction(chat_id: int | str, message_id: int, reaction: List[ReactionType] | None = None, is_big: bool | None = None) → bool
```

Use this method to change the chosen reactions on a message. Service messages can't be reacted to. Automatically forwarded messages from a channel to its discussion group have the same available reactions as messages in the channel. Returns True on success.

Telegram documentation: <https://core.telegram.org/bots/api#setmessagereaction>

Parameters

- **chat_id** (int or str) – Unique identifier for the target chat or username of the target supergroup or channel (in the format @channelusername)
- **message_id** (int) – Identifier of the message to set reaction to
- **reaction** (list of `telebot.types.ReactionType`) – New list of reaction types to set on the message. Currently, as non-premium users, bots can set up to one reaction per message. A custom emoji reaction can be used if it is either already present on the message or explicitly allowed by chat administrators.
- **is_big** (bool) – Pass True to set the reaction with a big animation

Returns

`bool`

```
async set_my_commands(commands: List[BotCommand], scope: BotCommandScope | None = None, language_code: str | None = None) → bool
```

Use this method to change the list of the bot's commands.

Telegram documentation: <https://core.telegram.org/bots/api#setmycommands>

Parameters

- **commands** (list of `telebot.types.BotCommand`) – List of BotCommand. At most 100 commands can be specified.
- **scope** (`telebot.types.BotCommandScope`) – The scope of users for which the commands are relevant. Defaults to `BotCommandScopeDefault`.

- **language_code** (str) – A two-letter ISO 639-1 language code. If empty, commands will be applied to all users from the given scope, for whose language there are no dedicated commands

Returns

True on success.

Return type

bool

async set_my_default_administrator_rights(rights: ChatAdministratorRights = None, for_channels: bool = None) → bool

Use this method to change the default administrator rights requested by the bot when it's added as an administrator to groups or channels. These rights will be suggested to users, but they are free to modify the list before adding the bot. Returns True on success.

Telegram documentation: <https://core.telegram.org/bots/api#setmydefaultadministratorrights>

Parameters

- **rights** (*telebot.types.ChatAdministratorRights*) – A JSON-serialized object describing new default administrator rights. If not specified, the default administrator rights will be cleared.
- **for_channels** (bool) – Pass True to change the default administrator rights of the bot in channels. Otherwise, the default administrator rights of the bot for groups and supergroups will be changed.

Returns

True on success.

Return type

bool

async set_my_description(description: str | None = None, language_code: str | None = None)

Use this method to change the bot's description, which is shown in the chat with the bot if the chat is empty. Returns True on success.

Parameters

- **description** (str) – New bot description; 0-512 characters. Pass an empty string to remove the dedicated description for the given language.
- **language_code** (str) – A two-letter ISO 639-1 language code. If empty, the description will be applied to all users for whose language there is no dedicated description.

Returns

True on success.

async set_my_name(name: str | None = None, language_code: str | None = None)

Use this method to change the bot's name. Returns True on success.

Telegram documentation: <https://core.telegram.org/bots/api#setmyname>

Parameters

- **name** (str) – Optional. New bot name; 0-64 characters. Pass an empty string to remove the dedicated name for the given language.
- **language_code** (str) – Optional. A two-letter ISO 639-1 language code. If empty, the name will be shown to all users for whose language there is no dedicated name.

Returns

True on success.

async set_my_short_description(*short_description: str | None = None, language_code: str | None = None*)

Use this method to change the bot's short description, which is shown on the bot's profile page and is sent together with the link when users share the bot. Returns True on success.

Parameters

- **short_description** (str) – New short description for the bot; 0-120 characters. Pass an empty string to remove the dedicated short description for the given language.
- **language_code** (str) – A two-letter ISO 639-1 language code. If empty, the short description will be applied to all users for whose language there is no dedicated short description.

Returns

True on success.

async set_state(*user_id: int, state: State | int | str, chat_id: int | None = None*)

Sets a new state of a user.

Note: You should set both user id and chat id in order to set state for a user in a chat. Otherwise, if you only set user_id, chat_id will equal to user_id, this means that state will be set for the user in his private chat with a bot.

Parameters

- **user_id** (int) – User's identifier
- **state** (int or str or telebot.types.State) – new state. can be string, integer, or telebot.types.State
- **chat_id** (int) – Chat's identifier

Returns

None

async set_sticker_emoji_list(*name: str, emoji_list: List[str]*) → bool

Use this method to set the emoji list of a sticker set. Returns True on success.

Parameters

- **name** (str) – Sticker set name
- **emoji_list** (list of str) – List of emojis

Returns

Returns True on success.

Return type

bool

async set_sticker_keywords(*sticker: str, keywords: List[str] = None*) → bool

Use this method to change search keywords assigned to a regular or custom emoji sticker. The sticker must belong to a sticker set created by the bot. Returns True on success.

Parameters

- **sticker** (str) – File identifier of the sticker.
- **keywords** (list of str) – A JSON-serialized list of 0-20 search keywords for the sticker with total length of up to 64 characters

Returns

On success, True is returned.

Return type

bool

async set_sticker_mask_position(*sticker: str, mask_position: MaskPosition = None*) → bool

Use this method to change the mask position of a mask sticker. The sticker must belong to a sticker set that was created by the bot. Returns True on success.

Parameters

- **sticker** (str) – File identifier of the sticker.
- **mask_position** (*telebot.types.MaskPosition*) – A JSON-serialized object for position where the mask should be placed on faces.

Returns

Returns True on success.

Return type

bool

async set_sticker_position_in_set(*sticker: str, position: int*) → bool

Use this method to move a sticker in a set created by the bot to a specific position . Returns True on success.

Telegram documentation: <https://core.telegram.org/bots/api#setstickerpositioninset>

Parameters

- **sticker** (str) – File identifier of the sticker
- **position** (int) – New sticker position in the set, zero-based

Returns

On success, True is returned.

Return type

bool

set_sticker_set_thumb(***kwargs*)

async set_sticker_set_thumbnail(*name: str, user_id: int, thumbnail: Any | str = None, format: str | None = None*) → bool

Use this method to set the thumbnail of a sticker set. Animated thumbnails can be set for animated sticker sets only. Returns True on success.

Telegram documentation: <https://core.telegram.org/bots/api#setstickersetthumbnail>

Parameters

- **name** (str) – Sticker set name
- **user_id** (int) – User identifier
- **thumbnail** (filelike object) – A .WEBP or .PNG image with the thumbnail, must be up to 128 kilobytes in size and have a width and height of exactly 100px, or a .TGS animation with a thumbnail up to 32 kilobytes in size (see <https://core.telegram.org/stickers#animated-sticker-requirements> for animated sticker technical requirements), or a WEBM

video with the thumbnail up to 32 kilobytes in size; see <https://core.telegram.org/stickers#video-sticker-requirements> for video sticker technical requirements. Pass a `file_id` as a String to send a file that already exists on the Telegram servers, pass an HTTP URL as a String for Telegram to get a file from the Internet, or upload a new one using multipart/form-data. More information on Sending Files ». Animated and video sticker set thumbnails can't be uploaded via HTTP URL. If omitted, then the thumbnail is dropped and the first sticker is used as the thumbnail.

Returns

On success, True is returned.

Return type

bool

async set_sticker_set_title(*name: str, title: str*) → bool

Use this method to set the title of a created sticker set. Returns True on success.

Parameters

- **name** (str) – Sticker set name
- **title** (str) – New sticker set title

Returns

Returns True on success.

Return type

bool

set_update_listener(*func: Awaitable*)

Update listener is a function that gets any update.

Parameters

func (Awaitable) – function that should get update.

Listing 27: Example on asynchronous update listeners.

```

async def update_listener(new_messages):
    for message in new_messages:
        print(message.text) # Prints message text

bot.set_update_listener(update_listener)

```

Returns

None

async set_webhook(*url: str | None = None, certificate: str | Any | None = None, max_connections: int | None = None, allowed_updates: List[str] | None = None, ip_address: str | None = None, drop_pending_updates: bool | None = None, timeout: int | None = None, secret_token: str | None = None*) → bool

Use this method to specify a URL and receive incoming updates via an outgoing webhook. Whenever there is an update for the bot, we will send an HTTPS POST request to the specified URL, containing a JSON-serialized Update. In case of an unsuccessful request, we will give up after a reasonable amount of attempts. Returns True on success.

If you'd like to make sure that the webhook was set by you, you can specify secret data in the parameter `secret_token`. If specified, the request will contain a header “X-Telegram-Bot-Api-Secret-Token” with the secret token as content.

Telegram Documentation: <https://core.telegram.org/bots/api#setwebhook>

Parameters

- **url** (str, optional) – HTTPS URL to send updates to. Use an empty string to remove webhook integration, defaults to None
- **certificate** (str, optional) – Upload your public key certificate so that the root certificate in use can be checked, defaults to None
- **max_connections** (int, optional) – The maximum allowed number of simultaneous HTTPS connections to the webhook for update delivery, 1-100. Defaults to 40. Use lower values to limit the load on your bot’s server, and higher values to increase your bot’s throughput, defaults to None
- **allowed_updates** (list, optional) – A JSON-serialized list of the update types you want your bot to receive. For example, specify [“message”, “edited_channel_post”, “callback_query”] to only receive updates of these types. See Update for a complete list of available update types. Specify an empty list to receive all update types except chat_member (default). If not specified, the previous setting will be used.

Please note that this parameter doesn’t affect updates created before the call to the setWebhook, so unwanted updates may be received for a short period of time. Defaults to None

- **ip_address** (str, optional) – The fixed IP address which will be used to send webhook requests instead of the IP address resolved through DNS, defaults to None
- **drop_pending_updates** (bool, optional) – Pass True to drop all pending updates, defaults to None
- **timeout** (int, optional) – Timeout of a request, defaults to None
- **secret_token** (str, optional) – A secret token to be sent in a header “X-Telegram-Bot-Api-Secret-Token” in every webhook request, 1-256 characters. Only characters A-Z, a-z, 0-9, _ and - are allowed. The header is useful to ensure that the request comes from a webhook set by you. Defaults to None

Returns

True on success.

Return type

bool if the request was successful.

setup_middleware(*middleware*: [BaseMiddleware](#))

Setup middleware.

Note: Take a look at the [telebot.asyncio_handler_backends.BaseMiddleware](#) section for more.

Parameters

middleware ([telebot.asyncio_handler_backends.BaseMiddleware](#)) – Middleware-class.

Returns

None

shipping_query_handler(*func*, ***kwargs*)

Handles new incoming shipping query. Only for invoices with flexible price. As a parameter to the decorator function, it passes [telebot.types.ShippingQuery](#) object.

Parameters

- **func** (function) – Function executed as a filter
- **kwargs** – Optional keyword arguments(custom filters)

Returns

None

async skip_updates()

Skip existing updates. Only last update will remain on server.

async stop_message_live_location(*chat_id: int | str | None = None, message_id: int | None = None, inline_message_id: str | None = None, reply_markup: InlineKeyboardMarkup | None = None, timeout: int | None = None*) → *Message*

Use this method to stop updating a live location message before `live_period` expires. On success, if the message is not an inline message, the edited `Message` is returned, otherwise `True` is returned.

Telegram documentation: <https://core.telegram.org/bots/api#stopmessagelivelocation>

Parameters

- **chat_id** (int or str) – Unique identifier for the target chat or username of the target channel (in the format @channelusername)
- **message_id** (int) – Required if `inline_message_id` is not specified. Identifier of the message with live location to stop
- **inline_message_id** (str) – Required if `chat_id` and `message_id` are not specified. Identifier of the inline message with live location to stop
- **reply_markup** (*telebot.types.InlineKeyboardMarkup* or *telebot.types.ReplyKeyboardMarkup* or *telebot.types.ReplyKeyboardRemove* or *telebot.types.ForceReply*) – A JSON-serialized object for a new inline keyboard.
- **timeout** (int) – Timeout in seconds for the request.

Returns

On success, if the message is not an inline message, the edited `Message` is returned, otherwise `True` is returned.

Return type*telebot.types.Message* or bool

async stop_poll(*chat_id: int | str, message_id: int, reply_markup: InlineKeyboardMarkup | None = None*) → *Poll*

Use this method to stop a poll which was sent by the bot. On success, the stopped `Poll` is returned.

Telegram documentation: <https://core.telegram.org/bots/api#stoppoll>

Parameters

- **chat_id** (int | str) – Unique identifier for the target chat or username of the target channel
- **message_id** (int) – Identifier of the original message with the poll
- **reply_markup** (`InlineKeyboardMarkup`) – A JSON-serialized object for a new message markup.

Returns

On success, the stopped `Poll` is returned.

Return type

types.Poll

async unban_chat_member(*chat_id: int | str, user_id: int, only_if_banned: bool | None = False*) → bool

Use this method to unban a previously kicked user in a supergroup or channel. The user will not return to the group or channel automatically, but will be able to join via link, etc. The bot must be an administrator for this to work. By default, this method guarantees that after the call the user is not a member of the chat, but will be able to join it. So if the user is a member of the chat they will also be removed from the chat. If you don't want this, use the parameter `only_if_banned`.

Telegram documentation: <https://core.telegram.org/bots/api#unbanchatmember>

Parameters

- **chat_id** (int or str) – Unique identifier for the target group or username of the target supergroup or channel (in the format @username)
- **user_id** (int) – Unique identifier of the target user
- **only_if_banned** (bool) – Do nothing if the user is not banned

Returns

True on success

Return type

bool

async unban_chat_sender_chat(*chat_id: int | str, sender_chat_id: int | str*) → bool

Use this method to unban a previously banned channel chat in a supergroup or channel. The bot must be an administrator for this to work and must have the appropriate administrator rights. Returns True on success.

Telegram documentation: <https://core.telegram.org/bots/api#unbanchatsenderchat>

Parameters

- **chat_id** (int or str) – Unique identifier for the target chat or username of the target channel (in the format @channelusername)
- **sender_chat_id** (int or str) – Unique identifier of the target sender chat.

Returns

True on success.

Return type

bool

async unhide_general_forum_topic(*chat_id: int | str*) → bool

Use this method to unhide the 'General' topic in a forum supergroup chat. The bot must be an administrator in the chat for this to work and must have `can_manage_topics` administrator rights. Returns True on success.

Telegram documentation: <https://core.telegram.org/bots/api#unhidegeneralforumtopic>

Parameters

chat_id (int or str) – Unique identifier for the target chat or username of the target channel (in the format @channelusername)

async unpin_all_chat_messages(*chat_id: int | str*) → bool

Use this method to unpin all pinned messages in a supergroup chat. The bot must be an administrator in the chat for this to work and must have the appropriate admin rights. Returns True on success.

Telegram documentation: <https://core.telegram.org/bots/api#unpinallchatmessages>

Parameters

chat_id (int or str) – Int or Str: Unique identifier for the target chat or username of the target channel (in the format @channelusername)

Returns

True on success.

Return type

bool

async unpin_all_forum_topic_messages(*chat_id: str | int, message_thread_id: int*) → bool

Use this method to clear the list of pinned messages in a forum topic. The bot must be an administrator in the chat for this to work and must have the can_pin_messages administrator right in the supergroup. Returns True on success.

Telegram documentation: <https://core.telegram.org/bots/api#unpinallforumtopicmessages>

Parameters

- **chat_id** (int or str) – Unique identifier for the target chat or username of the target channel (in the format @channelusername)
- **message_thread_id** (int) – Identifier of the topic

Returns

On success, True is returned.

Return type

bool

async unpin_all_general_forum_topic_messages(*chat_id: int | str*) → bool

Use this method to clear the list of pinned messages in a General forum topic. The bot must be an administrator in the chat for this to work and must have the can_pin_messages administrator right in the supergroup. Returns True on success.

Telegram documentation: <https://core.telegram.org/bots/api#unpinAllGeneralForumTopicMessages>

Parameters

chat_id (int | str) – Unique identifier for the target chat or username of chat

Returns

On success, True is returned.

Return type

bool

async unpin_chat_message(*chat_id: int | str, message_id: int | None = None*) → bool

Use this method to unpin specific pinned message in a supergroup chat. The bot must be an administrator in the chat for this to work and must have the appropriate admin rights. Returns True on success.

Telegram documentation: <https://core.telegram.org/bots/api#unpinchatmessage>

Parameters

- **chat_id** (int or str) – Unique identifier for the target chat or username of the target channel (in the format @channelusername)
- **message_id** (int) – Int: Identifier of a message to unpin

Returns

True on success.

Return type

bool

async upload_sticker_file(*user_id: int, png_sticker: Any | str = None, sticker: InputFile | None = None, sticker_format: str | None = None*) → *File*

Use this method to upload a .png file with a sticker for later use in `createNewStickerSet` and `addStickerToSet` methods (can be used multiple times). Returns the uploaded File on success.

Telegram documentation: <https://core.telegram.org/bots/api#uploadstickerfile>

Parameters

- **user_id** (int) – User identifier of sticker set owner
- **png_sticker** (filelike object) – DEPRECATED: PNG image with the sticker, must be up to 512 kilobytes in size, dimensions must not exceed 512px, and either width or height must be exactly 512px.
- **sticker** (*telebot.types.InputFile*) – A file with the sticker in .WEBP, .PNG, .TGS, or .WEBM format. See <https://core.telegram.org/stickers> for technical requirements. More information on Sending Files »
- **sticker_format** (str) – One of “static”, “animated”, “video”.

Returns

On success, the sent file is returned.

Return type

telebot.types.File

property user

class telebot.async_telebot.ExceptionHandler

Bases: object

Class for handling exceptions while Polling

async handle(*exception*)

class telebot.async_telebot.Handler(*callback, *args, **kwargs*)

Bases: object

Class for (next step|reply) handlers

Asyncio filters

class telebot.asyncio_filters.AdvancedCustomFilter

Bases: ABC

Advanced Custom Filter base class. Create child class with `check()` method. Accepts two parameters, returns bool: True - filter passed, False - filter failed. message: Message class text: Filter value given in handler

Child classes should have `.key` property.

Listing 28: Example on creating an advanced custom filter.

```
class TextStartsFilter(AdvancedCustomFilter):
    # Filter to check whether message starts with some text.
    key = 'text_startswith'

    def check(self, message, text):
        return message.text.startswith(text)
```

async check(*message, text*)

Perform a check.

key: `str = None`

class telebot.asyncio_filters.**ChatFilter**

Bases: *AdvancedCustomFilter*

Check whether chat_id corresponds to given chat_id.

Listing 29: Example on using this filter:

```
@bot.message_handler(chat_id=[99999])  
# your function
```

key: `str = 'chat_id'`

class telebot.asyncio_filters.**ForwardFilter**

Bases: *SimpleCustomFilter*

Check whether message was forwarded from channel or group.

Listing 30: Example on using this filter:

```
@bot.message_handler(is_forwarded=True)  
# your function
```

key: `str = 'is_forwarded'`

class telebot.asyncio_filters.**IsAdminFilter**(*bot*)

Bases: *SimpleCustomFilter*

Check whether the user is administrator / owner of the chat.

Listing 31: Example on using this filter:

```
@bot.message_handler(chat_types=['supergroup'], is_chat_admin=True)  
# your function
```

key: `str = 'is_chat_admin'`

class telebot.asyncio_filters.**IsDigitFilter**

Bases: *SimpleCustomFilter*

Filter to check whether the string is made up of only digits.

Listing 32: Example on using this filter:

```
@bot.message_handler(is_digit=True)  
# your function
```

key: `str = 'is_digit'`

class telebot.asyncio_filters.**IsReplyFilter**

Bases: *SimpleCustomFilter*

Check whether message is a reply.

Listing 33: Example on using this filter:

```
@bot.message_handler(is_reply=True)
# your function
```

key: str = 'is_reply'

class telebot.asyncio_filters.LanguageFilter

Bases: *AdvancedCustomFilter*

Check users language_code.

Listing 34: Example on using this filter:

```
@bot.message_handler(language_code=['ru'])
# your function
```

key: str = 'language_code'

class telebot.asyncio_filters.SimpleCustomFilter

Bases: ABC

Simple Custom Filter base class. Create child class with check() method. Accepts only message, returns bool value, that is compared with given in handler.

Child classes should have .key property.

Listing 35: Example on creating a simple custom filter.

```
class ForwardFilter(SimpleCustomFilter):
    # Check whether message was forwarded from channel or group.
    key = 'is_forwarded'

    def check(self, message):
        return message.forward_date is not None
```

async check(message)

Perform a check.

key: str = None

class telebot.asyncio_filters.StateFilter(bot)

Bases: *AdvancedCustomFilter*

Filter to check state.

Listing 36: Example on using this filter:

```
@bot.message_handler(state=1)
# your function
```

key: str = 'state'

class telebot.asyncio_filters.TextContainsFilter

Bases: *AdvancedCustomFilter*

Filter to check Text message. key: text

Listing 37: Example on using this filter:

```
# Will respond if any message.text contains word 'account'
@bot.message_handler(text_contains=['account'])
# your function
```

key: `str = 'text_contains'`

```
class telebot.asyncio_filters.TextFilter(equals: str | None = None, contains: list | tuple | None = None,
    starts_with: str | list | tuple | None = None, ends_with: str | list
    | tuple | None = None, ignore_case: bool = False)
```

Bases: `object`

Advanced text filter to check (types.Message, types.CallbackQuery, types.InlineQuery, types.Poll)

example of usage is in examples/asynchronous_telebot/custom_filters/advanced_text_filter.py

Parameters

- **equals** (`str`) – string, True if object’s text is equal to passed string
- **contains** (`list[str]` or `tuple[str]`) – list[str] or tuple[str], True if any string element of iterable is in text
- **starts_with** (`str`) – string, True if object’s text starts with passed string
- **ends_with** (`str`) – string, True if object’s text starts with passed string
- **ignore_case** (`bool`) – bool (default False), case insensitive

Raises

ValueError – if incorrect value for a parameter was supplied

Returns

None

```
class telebot.asyncio_filters.TextMatchFilter
```

Bases: `AdvancedCustomFilter`

Filter to check Text message.

Listing 38: Example on using this filter:

```
@bot.message_handler(text=['account'])
# your function
```

key: `str = 'text'`

```
class telebot.asyncio_filters.TextStartsFilter
```

Bases: `AdvancedCustomFilter`

Filter to check whether message starts with some text.

Listing 39: Example on using this filter:

```
# Will work if message.text starts with 'sir'.
@bot.message_handler(text_startswith='sir')
# your function
```

key: `str = 'text_startswith'`

Asyncio handler backends

File with all middleware classes, states.

`class telebot.asyncio_handler_backends.BaseMiddleware`

Bases: object

Base class for middleware. Your middlewares should be inherited from this class.

Set `update_sensitive=True` if you want to get different updates on different functions. For example, if you want to handle `pre_process` for message update, then you will have to create `pre_process_message` function, and so on. Same applies to `post_process`.

Listing 40: Example of class-based middlewares

```
class MyMiddleware(BaseMiddleware):
    def __init__(self):
        self.update_sensitive = True
        self.update_types = ['message', 'edited_message']

    async def pre_process_message(self, message, data):
        # only message update here
        pass

    async def post_process_message(self, message, data, exception):
        pass # only message update here for post_process

    async def pre_process_edited_message(self, message, data):
        # only edited_message update here
        pass

    async def post_process_edited_message(self, message, data, exception):
        pass # only edited_message update here for post_process
```

```
async post_process(message, data, exception)
```

```
async pre_process(message, data)
```

```
update_sensitive: bool = False
```

`class telebot.asyncio_handler_backends.CancelUpdate`

Bases: object

Class for canceling updates. Just return instance of this class in middleware to skip update. Update will skip handler and execution of `post_process` in middlewares.

`class telebot.asyncio_handler_backends.ContinueHandling`

Bases: object

Class for continue updates in handlers. Just return instance of this class in handlers to continue process.

Listing 41: Example of using ContinueHandling

```
@bot.message_handler(commands=['start'])
async def start(message):
    await bot.send_message(message.chat.id, 'Hello World!')
    return ContinueHandling()
```

(continues on next page)

(continued from previous page)

```
@bot.message_handler(commands=['start'])
async def start2(message):
    await bot.send_message(message.chat.id, 'Hello World2!')
```

class telebot.asyncio_handler_backends.SkipHandler

Bases: object

Class for skipping handlers. Just return instance of this class in middleware to skip handler. Update will go to post_process, but will skip execution of handler.

class telebot.asyncio_handler_backends.State

Bases: object

Class representing a state.

```
class MyStates(StatesGroup):
    my_state = State() # returns my_state:State string.
```

class telebot.asyncio_handler_backends.StatesGroup

Bases: object

Class representing common states.

```
class MyStates(StatesGroup):
    my_state = State() # returns my_state:State string.
```

classmethod state_list()

Extensions

1.3.6 Callback data factory

callback_data file

Callback data factory's file.

class telebot.callback_data.CallbackData(*parts, prefix: str, sep=':')

Bases: object

Callback data factory This class will help you to work with CallbackQuery

filter(**config) → CallbackDataFilter

Generate filter

Parameters

config – specified named parameters will be checked with CallbackQuery.data

Returns

CallbackDataFilter class

new(*args, **kwargs) → str

Generate callback data

Parameters

- **args** – positional parameters of CallbackData instance parts
- **kwargs** – named parameters

Returns

str

parse(*callback_data: str*) → Dict[str, str]

Parse data from the callback data

Parameters**callback_data** – string, use to telebot.types.CallbackQuery to parse it from string to a dict**Returns**

dict parsed from callback data

class telebot.callback_data.CallbackDataFilter(*factory, config: Dict[str, str]*)

Bases: object

Filter for CallbackData.

check(*query*) → bool

Checks if query.data appropriates to specified config

Parameters**query** (telebot.types.CallbackQuery) – telebot.types.CallbackQuery**Returns**

True if query.data appropriates to specified config

Return type

bool

1.3.7 Utils

util file

telebot.util.antiflood(*function: Callable, *args, number_retries=5, **kwargs*)

Use this function inside loops in order to avoid getting TooManyRequests error. Example:

```
from telebot.util import antiflood
for chat_id in chat_id_list:
    msg = antiflood(bot.send_message, chat_id, text)
```

Parameters

- **function** (:obj:int) – The function to call
- **number_retries** – Number of retries to send
- **args** (tuple) – The arguments to pass to the function
- **kwargs** (dict) – The keyword arguments to pass to the function

Returns

None

telebot.util.chunks(*lst, n*)

Yield successive n-sized chunks from lst.

```
telebot.util.content_type_media = ['text', 'animation', 'audio', 'document', 'photo',
' sticker', 'story', 'video', 'video_note', 'voice', 'contact', 'dice', 'game', 'poll',
'venue', 'location', 'invoice', 'successful_payment', 'connected_website',
'passport_data', 'web_app_data']
```

Contains all media content types.

```
telebot.util.content_type_service = ['new_chat_members', 'left_chat_member',
'new_chat_title', 'new_chat_photo', 'delete_chat_photo', 'group_chat_created',
' supergroup_chat_created', 'channel_chat_created', 'message_auto_delete_timer_changed',
' migrate_to_chat_id', 'migrate_from_chat_id', 'pinned_message', 'users_shared',
' chat_shared', 'write_access_allowed', 'proximity_alert_triggered',
' forum_topic_created', 'forum_topic_edited', 'forum_topic_closed',
' forum_topic_reopened', 'general_forum_topic_hidden', 'general_forum_topic_unhidden',
' giveaway_created', 'giveaway', 'giveaway_winners', 'giveaway_completed',
' video_chat_scheduled', 'video_chat_started', 'video_chat_ended',
' video_chat_participants_invited']
```

Contains all service content types such as *User joined the group*.

```
telebot.util.escape(text: str) → str | None
```

Replaces the following chars in *text* ('&' with '&', '<' with '<' and '>' with '>').

Parameters

text – the text to escape

Returns

the escaped text

```
telebot.util.extract_arguments(text: str) → str
```

Returns the argument after the command.

Listing 42: Examples:

```
extract_arguments("/get name"): 'name'
extract_arguments("/get"): ''
extract_arguments("/get@botName name"): 'name'
```

Parameters

text (str) – String to extract the arguments from a command

Returns

the arguments if *text* is a command (according to `is_command`), else `None`.

Return type

str or `None`

```
telebot.util.extract_command(text: str) → str | None
```

Extracts the command from *text* (minus the '/') if *text* is a command (see `is_command`). If *text* is not a command, this function returns `None`.

Listing 43: Examples:

```
extract_command('/help'): 'help'
extract_command('/help@BotName'): 'help'
extract_command('/search black eyed peas'): 'search'
extract_command('Good day to you'): None
```

Parameters**text** (str) – String to extract the command from**Returns**the command if *text* is a command (according to `is_command`), else `None`.**Return type**str or `None``telebot.util.generate_random_token()` → str

Generates a random token consisting of letters and digits, 16 characters long.

Returns

a random token

Return type

str

`telebot.util.is_bytes(var)` → bool

Returns True if the given object is a bytes object.

Parameters**var** (object) – object to be checked**Returns**

True if the given object is a bytes object.

Return type

bool

`telebot.util.is_command(text: str)` → boolChecks if *text* is a command. Telegram chat commands start with the ‘/’ character.**Parameters****text** (str) – Text to check.**Returns**True if *text* is a command, else `False`.**Return type**

bool

`telebot.util.is_dict(var)` → bool

Returns True if the given object is a dictionary.

Parameters**var** (object) – object to be checked**Returns**

True if the given object is a dictionary.

Return type

bool

`telebot.util.is_pil_image(var)` → boolReturns True if the given object is a `PIL.Image.Image` object.**Parameters****var** (object) – object to be checked**Returns**True if the given object is a `PIL.Image.Image` object.

Return type

bool

telebot.util.is_string(*var*) → bool

Returns True if the given object is a string.

telebot.util.parse_web_app_data(*token: str, raw_init_data: str*)

Parses web app data.

Parameters

- **token** (str) – The bot token
- **raw_init_data** (str) – The raw init data

Returns

The parsed init data

telebot.util.pil_image_to_file(*image, extension='JPEG', quality='web_low'*)telebot.util.quick_markup(*values: Dict[str, Dict[str, Any]], row_width: int = 2*) → *InlineKeyboardMarkup*

Returns a reply markup from a dict in this format: {'text': kwargs} This is useful to avoid always typing 'btn1 = InlineKeyboardButton(...)' 'btn2 = InlineKeyboardButton(...)'

Example:

Listing 44: Using quick_markup:

```

from telebot.util import quick_markup

markup = quick_markup({
    'Twitter': {'url': 'https://twitter.com'},
    'Facebook': {'url': 'https://facebook.com'},
    'Back': {'callback_data': 'whatever'}
}, row_width=2)
# returns an InlineKeyboardMarkup with two buttons in a row, one leading to Twitter,
# ↔ the other to facebook
# and a back button below

# kwargs can be:
{
    'url': None,
    'callback_data': None,
    'switch_inline_query': None,
    'switch_inline_query_current_chat': None,
    'callback_game': None,
    'pay': None,
    'login_url': None,
    'web_app': None
}

```

Parameters

- **values** (dict) – a dict containing all buttons to create in this format: {text: kwargs} {str:}
- **row_width** (int) – number of *telebot.types.InlineKeyboardButton* objects on each row

Returns

InlineKeyboardMarkup

Return type

types.InlineKeyboardMarkup

telebot.util.**smart_split**(*text: str, chars_per_string: int = 4096*) → List[str]

Splits one string into multiple strings, with a maximum amount of *chars_per_string* characters per string. This is very useful for splitting one giant message into multiples. If *chars_per_string* > 4096: *chars_per_string* = 4096. Splits by 'n', '.', ' ' or ' ' in exactly this priority.

Parameters

- **text** (str) – The text to split
- **chars_per_string** (int) – The number of maximum characters per part the text is split to.

Returns

The splitted text as a list of strings.

Return type

list of str

telebot.util.**split_string**(*text: str, chars_per_string: int*) → List[str]

Splits one string into multiple strings, with a maximum amount of *chars_per_string* characters per string. This is very useful for splitting one giant message into multiples.

Parameters

- **text** (str) – The text to split
- **chars_per_string** (int) – The number of characters per line the text is split into.

Returns

The splitted text as a list of strings.

Return type

list of str

```
telebot.util.update_types = ['message', 'edited_message', 'channel_post',
'edited_channel_post', 'inline_query', 'chosen_inline_result', 'callback_query',
'shipping_query', 'pre_checkout_query', 'poll', 'poll_answer', 'my_chat_member',
'chat_member', 'chat_join_request', 'message_reaction', 'message_reaction_count',
'chat_boost', 'removed_chat_boost', 'business_connection', 'business_message',
'edited_business_message', 'deleted_business_messages']
```

All update types, should be used for allowed_updates parameter in polling.

telebot.util.**user_link**(*user: User, include_id: bool = False*) → str

Returns an HTML user link. This is useful for reports. Attention: Don't forget to set parse_mode to 'HTML'!

Listing 45: Example:

```
bot.send_message(your_user_id, user_link(message.from_user) + ' started the bot!',
↳parse_mode='HTML')
```

Note: You can use formatting.* for all other formatting options(bold, italic, links, and etc.) This method is kept for backward compatibility, and it is recommended to use formatting.* for more options.

Parameters

- **user** (*telebot.types.User*) – the user (not the user_id)
- **include_id** (bool) – include the user_id

Returns

HTML user link

Return type

str

`telebot.util.validate_web_app_data(token: str, raw_init_data: str)`

Validates web app data.

Parameters

- **token** (str) – The bot token
- **raw_init_data** (str) – The raw init data

Returns

The parsed init data

`telebot.util.webhook_google_functions(bot, request)`

A webhook endpoint for Google Cloud Functions FaaS.

Parameters

- **bot** (*telebot.TeleBot* or *telebot.async_telebot.AsyncTeleBot*) – The bot instance
- **request** (*flask.Request*) – The request object

Returns

The response object

1.3.8 Formatting options

Markdown & HTML formatting functions.

Added in version 4.5.1.

`telebot.formatting.apply_html_entities(text: str, entities: List | None, custom_subs: Dict[str, str] | None)`
→ str

Author: @sviat9440 Updaters: @badiboy, @EgorKhabarov Message: “*Test parse _formatting_*, [url](https://example.com), [text_mention](tg://user?id=123456) and mention @username”

Listing 46: Example:

```
apply_html_entities(text, entities)
>> "<b>Test</b> parse <i>formatting</i>, <a href='https://example.com'>url</a>, <a
↳ href='tg://user?id=123456'>text_mention</a> and mention @username"
```

Custom subs:

You can customize the substitutes. By default, there is no substitute for the entities: hashtag, bot_command, email. You can add or modify substitute an existing entity.

Listing 47: Example:

```

apply_html_entities(
    text,
    entities,
    {"bold": "<strong class='example'>{text}</strong>", "italic": "<i class='example
↳>{text}</i>", "mention": "<a href={url}>{text}</a>"},
)
>> "<strong class='example'>Test</strong> parse <i class='example'>formatting</i>,
↳<a href='https://example.com'>url</a> and <a href='tg://user?id=123456'>text_
↳mention</a> and mention <a href='https://t.me/username'>@username</a>"

```

telebot.formatting.**escape_html**(*content: str*) → str

Escapes HTML characters in a string of HTML.

Parameters

content (str) – The string of HTML to escape.

Returns

The escaped string.

Return type

str

telebot.formatting.**escape_markdown**(*content: str*) → str

Escapes Markdown characters in a string of Markdown.

Credits to: simonsmh

Parameters

content (str) – The string of Markdown to escape.

Returns

The escaped string.

Return type

str

telebot.formatting.**format_text**(**args*, *separator='\n'*)

Formats a list of strings into a single string.

```

format_text( # just an example
    mbold('Hello'),
    mitalic('World')
)

```

Parameters

- **args** (str) – Strings to format.
- **separator** (str) – The separator to use between each string.

Returns

The formatted string.

Return type

str

`telebot.formatting.hbold`(*content: str, escape: bool | None = True*) → str

Returns an HTML-formatted bold string.

Parameters

- **content** (str) – The string to bold.
- **escape** (bool) – True if you need to escape special characters. Defaults to True.

Returns

The formatted string.

Return type

str

`telebot.formatting.hcite`(*content: str, escape: bool | None = True*) → str

Returns a html-formatted block-quotation string.

Parameters

- **content** (str) – The string to bold.
- **escape** (bool) – True if you need to escape special characters. Defaults to True.

Returns

The formatted string.

Return type

str

`telebot.formatting.hcode`(*content: str, escape: bool | None = True*) → str

Returns an HTML-formatted code string.

Parameters

- **content** (str) – The string to code.
- **escape** (bool) – True if you need to escape special characters. Defaults to True.

Returns

The formatted string.

Return type

str

`telebot.formatting.hide_link`(*url: str*) → str

Hide url of an image.

Parameters

url (str) – The url of the image.

Returns

The hidden url.

Return type

str

`telebot.formatting.hitalic`(*content: str, escape: bool | None = True*) → str

Returns an HTML-formatted italic string.

Parameters

- **content** (str) – The string to italicize.
- **escape** (bool) – True if you need to escape special characters. Defaults to True.

Returns

The formatted string.

Return type

str

`telebot.formatting.hlink`(*content: str, url: str, escape: bool | None = True*) → str

Returns an HTML-formatted link string.

Parameters

- **content** (str) – The string to link.
- **url** (str) – The URL to link to.
- **escape** (bool) – True if you need to escape special characters. Defaults to True.

Returns

The formatted string.

Return type

str

`telebot.formatting.hpre`(*content: str, escape: bool | None = True, language: str = ""*) → str

Returns an HTML-formatted preformatted string.

Parameters

- **content** (str) – The string to preformatted.
- **escape** (bool) – True if you need to escape special characters. Defaults to True.

Returns

The formatted string.

Return type

str

`telebot.formatting.hspoiler`(*content: str, escape: bool | None = True*) → str

Returns an HTML-formatted spoiler string.

Parameters

- **content** (str) – The string to spoiler.
- **escape** (bool) – True if you need to escape special characters. Defaults to True.

Returns

The formatted string.

Return type

str

`telebot.formatting.hstrikethrough`(*content: str, escape: bool | None = True*) → str

Returns an HTML-formatted strikethrough string.

Parameters

- **content** (str) – The string to strikethrough.
- **escape** (bool) – True if you need to escape special characters. Defaults to True.

Returns

The formatted string.

Return type

str

telebot.formatting.**hunderline**(*content: str, escape: bool | None = True*) → str

Returns an HTML-formatted underline string.

Parameters

- **content** (str) – The string to underline.
- **escape** (bool) – True if you need to escape special characters. Defaults to True.

Returns

The formatted string.

Return type

str

telebot.formatting.**mbold**(*content: str, escape: bool | None = True*) → str

Returns a Markdown-formatted bold string.

Parameters

- **content** (str) – The string to bold.
- **escape** (bool) – True if you need to escape special characters. Defaults to True.

Returns

The formatted string.

Return type

str

telebot.formatting.**mcite**(*content: str, escape: bool | None = True*) → str

Returns a Markdown-formatted block-quotation string.

Parameters

- **content** (str) – The string to bold.
- **escape** (bool) – True if you need to escape special characters. Defaults to True.

Returns

The formatted string.

Return type

str

telebot.formatting.**mcode**(*content: str, language: str = "", escape: bool | None = True*) → str

Returns a Markdown-formatted code string.

Parameters

- **content** (str) – The string to code.
- **escape** (bool) – True if you need to escape special characters. Defaults to True.

Returns

The formatted string.

Return type

str

`telebot.formatting.mitalic`(*content: str, escape: bool | None = True*) → str

Returns a Markdown-formatted italic string.

Parameters

- **content** (str) – The string to italicize.
- **escape** (bool) – True if you need to escape special characters. Defaults to True.

Returns

The formatted string.

Return type

str

`telebot.formatting.mlink`(*content: str, url: str, escape: bool | None = True*) → str

Returns a Markdown-formatted link string.

Parameters

- **content** (str) – The string to link.
- **url** (str) – The URL to link to.
- **escape** (bool) – True if you need to escape special characters. Defaults to True.

Returns

The formatted string.

Return type

str

`telebot.formatting.mspoiler`(*content: str, escape: bool | None = True*) → str

Returns a Markdown-formatted spoiler string.

Parameters

- **content** (str) – The string to spoiler.
- **escape** (bool) – True if you need to escape special characters. Defaults to True.

Returns

The formatted string.

Return type

str

`telebot.formatting.mstrikethrough`(*content: str, escape: bool | None = True*) → str

Returns a Markdown-formatted strikethrough string.

Parameters

- **content** (str) – The string to strikethrough.
- **escape** (bool) – True if you need to escape special characters. Defaults to True.

Returns

The formatted string.

Return type

str

`telebot.formatting.munderline`(*content: str, escape: bool | None = True*) → str

Returns a Markdown-formatted underline string.

Parameters

- **content** (`str`) – The string to underline.
- **escape** (`bool`) – True if you need to escape special characters. Defaults to True.

Returns

The formatted string.

Return type

`str`

INDICES AND TABLES

- genindex
- modindex
- search

PYTHON MODULE INDEX

t

- telebot, 98
- telebot.async_telebot, 186
- telebot.asyncio_filters, 265
- telebot.asyncio_handler_backends, 269
- telebot.callback_data, 270
- telebot.custom_filters, 181
- telebot.formatting, 276
- telebot.handler_backends, 184
- telebot.types, 3
- telebot.util, 271

A

add() (*telebot.types.InlineKeyboardMarkup* method), 37
 add() (*telebot.types.Poll* method), 79
 add() (*telebot.types.ReplyKeyboardMarkup* method), 83
 add_custom_filter() (*telebot.async_telebot.AsyncTeleBot* method), 187
 add_custom_filter() (*telebot.TeleBot* method), 100
 add_data() (*telebot.async_telebot.AsyncTeleBot* method), 187
 add_data() (*telebot.TeleBot* method), 100
 add_price() (*telebot.types.ShippingOption* method), 86
 add_sticker_to_set() (*telebot.async_telebot.AsyncTeleBot* method), 187
 add_sticker_to_set() (*telebot.TeleBot* method), 100
 AdvancedCustomFilter (class in *telebot.asyncio_filters*), 265
 AdvancedCustomFilter (class in *telebot.custom_filters*), 181
 Animation (class in *telebot.types*), 3
 answer_callback_query() (*telebot.async_telebot.AsyncTeleBot* method), 188
 answer_callback_query() (*telebot.TeleBot* method), 101
 answer_inline_query() (*telebot.async_telebot.AsyncTeleBot* method), 188
 answer_inline_query() (*telebot.TeleBot* method), 102
 answer_pre_checkout_query() (*telebot.async_telebot.AsyncTeleBot* method), 189
 answer_pre_checkout_query() (*telebot.TeleBot* method), 102
 answer_shipping_query() (*telebot.async_telebot.AsyncTeleBot* method), 190
 answer_shipping_query() (*telebot.TeleBot* method), 103
 answer_web_app_query() (*telebot.async_telebot.AsyncTeleBot* method),

190
 answer_web_app_query() (*telebot.TeleBot* method), 103
 antiflood() (in module *telebot.util*), 271
 apply_html_entities() (in module *telebot.formatting*), 276
 approve_chat_join_request() (*telebot.async_telebot.AsyncTeleBot* method), 190
 approve_chat_join_request() (*telebot.TeleBot* method), 104
 AsyncTeleBot (class in *telebot.async_telebot*), 186
 Audio (class in *telebot.types*), 4

B

ban_chat_member() (*telebot.async_telebot.AsyncTeleBot* method), 191
 ban_chat_member() (*telebot.TeleBot* method), 104
 ban_chat_sender_chat() (*telebot.async_telebot.AsyncTeleBot* method), 191
 ban_chat_sender_chat() (*telebot.TeleBot* method), 104
 BaseMiddleware (class in *telebot.asyncio_handler_backends*), 269
 BaseMiddleware (class in *telebot.handler_backends*), 184
 Birthdate (class in *telebot.types*), 5
 BotCommand (class in *telebot.types*), 5
 BotCommandScope (class in *telebot.types*), 5
 BotCommandScopeAllChatAdministrators (class in *telebot.types*), 6
 BotCommandScopeAllGroupChats (class in *telebot.types*), 6
 BotCommandScopeAllPrivateChats (class in *telebot.types*), 7
 BotCommandScopeChat (class in *telebot.types*), 7
 BotCommandScopeChatAdministrators (class in *telebot.types*), 7
 BotCommandScopeChatMember (class in *telebot.types*), 8

- BotCommandScopeDefault (class in telebot.types), 8
- BotDescription (class in telebot.types), 8
- BotName (class in telebot.types), 8
- BotShortDescription (class in telebot.types), 9
- business_connection_handler() (telebot.async_telebot.AsyncTeleBot method), 191
- business_connection_handler() (telebot.TeleBot method), 105
- business_message_handler() (telebot.async_telebot.AsyncTeleBot method), 192
- business_message_handler() (telebot.TeleBot method), 105
- BusinessConnection (class in telebot.types), 9
- BusinessIntro (class in telebot.types), 9
- BusinessLocation (class in telebot.types), 10
- BusinessMessagesDeleted (class in telebot.types), 10
- BusinessOpeningHours (class in telebot.types), 10
- BusinessOpeningHoursInterval (class in telebot.types), 11
- C**
- callback_query_handler() (telebot.async_telebot.AsyncTeleBot method), 192
- callback_query_handler() (telebot.TeleBot method), 106
- CallbackData (class in telebot.callback_data), 270
- CallbackDataFilter (class in telebot.callback_data), 271
- CallbackQuery (class in telebot.types), 11
- can_manage_voice_chats (telebot.types.ChatMember property), 20
- CancelUpdate (class in telebot.asyncio_handler_backends), 269
- CancelUpdate (class in telebot.handler_backends), 185
- channel_post_handler() (telebot.async_telebot.AsyncTeleBot method), 193
- channel_post_handler() (telebot.TeleBot method), 106
- Chat (class in telebot.types), 12
- chat_boost_handler() (telebot.async_telebot.AsyncTeleBot method), 193
- chat_boost_handler() (telebot.TeleBot method), 106
- chat_join_request_handler() (telebot.async_telebot.AsyncTeleBot method), 193
- chat_join_request_handler() (telebot.TeleBot method), 106
- chat_member_handler() (telebot.async_telebot.AsyncTeleBot method), 193
- chat_member_handler() (telebot.TeleBot method), 107
- ChatAdministratorRights (class in telebot.types), 14
- ChatBoost (class in telebot.types), 15
- ChatBoostAdded (class in telebot.types), 16
- ChatBoostRemoved (class in telebot.types), 16
- ChatBoostSource (class in telebot.types), 16
- ChatBoostSourceGiftCode (class in telebot.types), 16
- ChatBoostSourceGiveaway (class in telebot.types), 17
- ChatBoostSourcePremium (class in telebot.types), 17
- ChatBoostUpdated (class in telebot.types), 17
- ChatFilter (class in telebot.asyncio_filters), 266
- ChatFilter (class in telebot.custom_filters), 181
- ChatInviteLink (class in telebot.types), 18
- ChatJoinRequest (class in telebot.types), 18
- ChatLocation (class in telebot.types), 19
- ChatMember (class in telebot.types), 19
- ChatMemberAdministrator (class in telebot.types), 20
- ChatMemberBanned (class in telebot.types), 21
- ChatMemberLeft (class in telebot.types), 22
- ChatMemberMember (class in telebot.types), 22
- ChatMemberOwner (class in telebot.types), 23
- ChatMemberRestricted (class in telebot.types), 23
- ChatMemberUpdated (class in telebot.types), 25
- ChatPermissions (class in telebot.types), 25
- ChatPhoto (class in telebot.types), 26
- ChatShared (class in telebot.types), 27
- check() (telebot.asyncio_filters.AdvancedCustomFilter method), 265
- check() (telebot.asyncio_filters.SimpleCustomFilter method), 267
- check() (telebot.callback_data.CallbackDataFilter method), 271
- check() (telebot.custom_filters.AdvancedCustomFilter method), 181
- check() (telebot.custom_filters.SimpleCustomFilter method), 182
- chosen_inline_handler() (telebot.async_telebot.AsyncTeleBot method), 193
- chosen_inline_handler() (telebot.TeleBot method), 107
- ChosenInlineResult (class in telebot.types), 27
- chunks() (in module telebot.util), 271
- clear_reply_handlers() (telebot.TeleBot method), 107
- clear_reply_handlers_by_message_id() (telebot.TeleBot method), 107
- clear_step_handler() (telebot.TeleBot method), 107
- clear_step_handler_by_chat_id() (telebot.TeleBot method), 107
- close() (telebot.async_telebot.AsyncTeleBot method), 194
- close() (telebot.TeleBot method), 108

- close_forum_topic() (*telebot.async_telebot.AsyncTeleBot* method), 194
 close_forum_topic() (*telebot.TeleBot* method), 108
 close_general_forum_topic() (*telebot.async_telebot.AsyncTeleBot* method), 194
 close_general_forum_topic() (*telebot.TeleBot* method), 108
 close_session() (*telebot.async_telebot.AsyncTeleBot* method), 194
 Contact (class in *telebot.types*), 28
 contains_masks (*telebot.types.StickerSet* property), 88
 content_type_media (in module *telebot.util*), 271
 content_type_service (in module *telebot.util*), 272
 ContinueHandling (class in *telebot.asyncio_handler_backends*), 269
 ContinueHandling (class in *telebot.handler_backends*), 185
 convert_input_sticker() (*telebot.types.InputSticker* method), 62
 copy_message() (*telebot.async_telebot.AsyncTeleBot* method), 194
 copy_message() (*telebot.TeleBot* method), 108
 copy_messages() (*telebot.async_telebot.AsyncTeleBot* method), 195
 copy_messages() (*telebot.TeleBot* method), 109
 create_chat_invite_link() (*telebot.async_telebot.AsyncTeleBot* method), 196
 create_chat_invite_link() (*telebot.TeleBot* method), 110
 create_forum_topic() (*telebot.async_telebot.AsyncTeleBot* method), 197
 create_forum_topic() (*telebot.TeleBot* method), 110
 create_invoice_link() (*telebot.async_telebot.AsyncTeleBot* method), 197
 create_invoice_link() (*telebot.TeleBot* method), 111
 create_new_sticker_set() (*telebot.async_telebot.AsyncTeleBot* method), 198
 create_new_sticker_set() (*telebot.TeleBot* method), 112
- D**
- decline_chat_join_request() (*telebot.async_telebot.AsyncTeleBot* method), 199
 decline_chat_join_request() (*telebot.TeleBot* method), 113
 delete_chat_photo() (*telebot.async_telebot.AsyncTeleBot* method), 200
 delete_chat_photo() (*telebot.TeleBot* method), 113
 delete_chat_sticker_set() (*telebot.async_telebot.AsyncTeleBot* method), 200
 delete_chat_sticker_set() (*telebot.TeleBot* method), 114
 delete_forum_topic() (*telebot.async_telebot.AsyncTeleBot* method), 200
 delete_forum_topic() (*telebot.TeleBot* method), 114
 delete_message() (*telebot.async_telebot.AsyncTeleBot* method), 200
 delete_message() (*telebot.TeleBot* method), 114
 delete_messages() (*telebot.async_telebot.AsyncTeleBot* method), 201
 delete_messages() (*telebot.TeleBot* method), 115
 delete_my_commands() (*telebot.async_telebot.AsyncTeleBot* method), 201
 delete_my_commands() (*telebot.TeleBot* method), 115
 delete_state() (*telebot.async_telebot.AsyncTeleBot* method), 201
 delete_state() (*telebot.TeleBot* method), 115
 delete_sticker_from_set() (*telebot.async_telebot.AsyncTeleBot* method), 202
 delete_sticker_from_set() (*telebot.TeleBot* method), 115
 delete_sticker_set() (*telebot.async_telebot.AsyncTeleBot* method), 202
 delete_sticker_set() (*telebot.TeleBot* method), 116
 delete_webhook() (*telebot.async_telebot.AsyncTeleBot* method), 202
 delete_webhook() (*telebot.TeleBot* method), 116
 deleted_business_messages_handler() (*telebot.async_telebot.AsyncTeleBot* method), 202
 deleted_business_messages_handler() (*telebot.TeleBot* method), 116
 Dice (class in *telebot.types*), 28
 Dictionaryable (class in *telebot.types*), 28
 difference (*telebot.types.ChatMemberUpdated* property), 25
 disable_save_next_step_handlers() (*telebot.TeleBot* method), 116
 disable_save_reply_handlers() (*telebot.TeleBot* method), 116
 Document (class in *telebot.types*), 28
 download_file() (*telebot.async_telebot.AsyncTeleBot* method), 203
 download_file() (*telebot.TeleBot* method), 116

E

- edit_chat_invite_link() (telebot.TeleBot method), 117
- edit_chat_invite_link() (telebot.TeleBot method), 203
- edit_forum_topic() (telebot.TeleBot method), 117
- edit_forum_topic() (telebot.TeleBot method), 203
- edit_general_forum_topic() (telebot.TeleBot method), 118
- edit_message_caption() (telebot.TeleBot method), 118
- edit_message_caption() (telebot.TeleBot method), 204
- edit_message_live_location() (telebot.TeleBot method), 118
- edit_message_live_location() (telebot.TeleBot method), 204
- edit_message_live_location() (telebot.TeleBot method), 205
- edit_message_media() (telebot.TeleBot method), 119
- edit_message_reply_markup() (telebot.TeleBot method), 120
- edit_message_reply_markup() (telebot.TeleBot method), 206
- edit_message_text() (telebot.TeleBot method), 120
- edit_message_text() (telebot.TeleBot method), 206
- edited_business_message_handler() (telebot.TeleBot method), 121
- edited_business_message_handler() (telebot.TeleBot method), 207
- edited_channel_post_handler() (telebot.TeleBot method), 121
- edited_channel_post_handler() (telebot.TeleBot method), 207
- edited_message_handler() (telebot.TeleBot method), 122
- edited_message_handler() (telebot.TeleBot method), 208
- enable_save_next_step_handlers() (telebot.TeleBot method), 122
- enable_save_reply_handlers() (telebot.TeleBot method), 122
- enable_saving_states() (telebot.TeleBot method), 122
- enable_saving_states() (telebot.TeleBot method), 208
- escape() (in module telebot.util), 272
- escape_html() (in module telebot.formatting), 277
- escape_markdown() (in module telebot.formatting), 277
- ExceptionHandler (class in telebot), 98
- ExceptionHandler (class in telebot.async_telebot), 265
- export_chat_invite_link() (telebot.TeleBot method), 123
- export_chat_invite_link() (telebot.TeleBot method), 208
- ExternalReplyInfo (class in telebot.types), 29
- extract_arguments() (in module telebot.util), 272
- extract_command() (in module telebot.util), 272

F

- File (class in telebot.types), 30
- file (telebot.types.InputFile property), 56
- filter() (telebot.callback_data.CallbackData method), 270
- ForceReply (class in telebot.types), 31
- format_text() (in module telebot.formatting), 277
- ForumTopic (class in telebot.types), 31
- ForumTopicClosed (class in telebot.types), 32
- ForumTopicCreated (class in telebot.types), 32
- ForumTopicEdited (class in telebot.types), 32
- ForumTopicReopened (class in telebot.types), 32
- forward_date (telebot.types.Message property), 74
- forward_from (telebot.types.Message property), 74
- forward_from_chat (telebot.types.Message property), 74
- forward_from_message_id (telebot.types.Message property), 74
- forward_message() (telebot.TeleBot method), 123
- forward_message() (telebot.TeleBot method), 208
- forward_messages() (telebot.TeleBot method), 123
- forward_messages() (telebot.TeleBot method), 209
- forward_messages() (telebot.TeleBot method), 213
- forward_sender_name (telebot.types.Message property), 74
- forward_signature (telebot.types.Message property), 74
- ForwardFilter (class in telebot.asyncio_filters), 266
- ForwardFilter (class in telebot.custom_filters), 181

full_name (*telebot.types.User* property), 92

G

Game (*class in telebot.types*), 32

GameHighScore (*class in telebot.types*), 33

GeneralForumTopicHidden (*class in telebot.types*), 33

GeneralForumTopicUnhidden (*class in telebot.types*), 33

generate_random_token() (*in module telebot.util*), 273

get_business_connection() (*telebot.async_telebot.AsyncTeleBot* method), 209

get_business_connection() (*telebot.TeleBot* method), 124

get_chat() (*telebot.async_telebot.AsyncTeleBot* method), 210

get_chat() (*telebot.TeleBot* method), 124

get_chat_administrators() (*telebot.async_telebot.AsyncTeleBot* method), 210

get_chat_administrators() (*telebot.TeleBot* method), 124

get_chat_member() (*telebot.async_telebot.AsyncTeleBot* method), 210

get_chat_member() (*telebot.TeleBot* method), 125

get_chat_member_count() (*telebot.async_telebot.AsyncTeleBot* method), 210

get_chat_member_count() (*telebot.TeleBot* method), 125

get_chat_members_count() (*telebot.async_telebot.AsyncTeleBot* method), 211

get_chat_members_count() (*telebot.TeleBot* method), 125

get_chat_menu_button() (*telebot.async_telebot.AsyncTeleBot* method), 211

get_chat_menu_button() (*telebot.TeleBot* method), 125

get_custom_emoji_stickers() (*telebot.async_telebot.AsyncTeleBot* method), 211

get_custom_emoji_stickers() (*telebot.TeleBot* method), 125

get_file() (*telebot.async_telebot.AsyncTeleBot* method), 211

get_file() (*telebot.TeleBot* method), 126

get_file_url() (*telebot.async_telebot.AsyncTeleBot* method), 211

get_file_url() (*telebot.TeleBot* method), 126

get_forum_topic_icon_stickers() (*telebot.async_telebot.AsyncTeleBot* method), 212

get_forum_topic_icon_stickers() (*telebot.TeleBot* method), 126

get_game_high_scores() (*telebot.async_telebot.AsyncTeleBot* method), 212

get_game_high_scores() (*telebot.TeleBot* method), 126

get_me() (*telebot.async_telebot.AsyncTeleBot* method), 212

get_me() (*telebot.TeleBot* method), 127

get_my_commands() (*telebot.async_telebot.AsyncTeleBot* method), 212

get_my_commands() (*telebot.TeleBot* method), 127

get_my_default_administrator_rights() (*telebot.async_telebot.AsyncTeleBot* method), 213

get_my_default_administrator_rights() (*telebot.TeleBot* method), 127

get_my_description() (*telebot.async_telebot.AsyncTeleBot* method), 213

get_my_description() (*telebot.TeleBot* method), 127

get_my_name() (*telebot.async_telebot.AsyncTeleBot* method), 213

get_my_name() (*telebot.TeleBot* method), 128

get_my_short_description() (*telebot.async_telebot.AsyncTeleBot* method), 213

get_my_short_description() (*telebot.TeleBot* method), 128

get_state() (*telebot.async_telebot.AsyncTeleBot* method), 214

get_state() (*telebot.TeleBot* method), 128

get_sticker_set() (*telebot.async_telebot.AsyncTeleBot* method), 214

get_sticker_set() (*telebot.TeleBot* method), 128

get_updates() (*telebot.async_telebot.AsyncTeleBot* method), 214

get_updates() (*telebot.TeleBot* method), 128

get_user_chat_boosts() (*telebot.async_telebot.AsyncTeleBot* method), 215

get_user_chat_boosts() (*telebot.TeleBot* method), 129

get_user_profile_photos() (*telebot.async_telebot.AsyncTeleBot* method), 215

get_user_profile_photos() (*telebot.TeleBot* method), 129

- get_webhook_info() (telebot.async_telebot.AsyncTeleBot method), 215
- get_webhook_info() (telebot.TeleBot method), 130
- Giveaway (class in telebot.types), 34
- GiveawayCompleted (class in telebot.types), 34
- GiveawayCreated (class in telebot.types), 35
- GiveawayWinners (class in telebot.types), 35
- ## H
- handle() (telebot.async_telebot.ExceptionHandler method), 265
- handle() (telebot.ExceptionHandler method), 98
- Handler (class in telebot), 98
- Handler (class in telebot.async_telebot), 265
- hbold() (in module telebot.formatting), 277
- hcite() (in module telebot.formatting), 278
- hcode() (in module telebot.formatting), 278
- hide_general_forum_topic() (telebot.async_telebot.AsyncTeleBot method), 215
- hide_general_forum_topic() (telebot.TeleBot method), 130
- hide_link() (in module telebot.formatting), 278
- hitalic() (in module telebot.formatting), 278
- hlink() (in module telebot.formatting), 279
- hpre() (in module telebot.formatting), 279
- hspoiler() (in module telebot.formatting), 279
- hstrikethrough() (in module telebot.formatting), 279
- html_caption (telebot.types.Message property), 74
- html_text (telebot.types.Message property), 74
- html_text (telebot.types.TextQuote property), 90
- hunderline() (in module telebot.formatting), 280
- ## I
- InaccessibleMessage (class in telebot.types), 35
- infinity_polling() (telebot.async_telebot.AsyncTeleBot method), 216
- infinity_polling() (telebot.TeleBot method), 130
- inline_handler() (telebot.async_telebot.AsyncTeleBot method), 216
- inline_handler() (telebot.TeleBot method), 131
- InlineKeyboardButton (class in telebot.types), 36
- InlineKeyboardMarkup (class in telebot.types), 37
- InlineQuery (class in telebot.types), 38
- InlineQueryResultArticle (class in telebot.types), 39
- InlineQueryResultAudio (class in telebot.types), 39
- InlineQueryResultBase (class in telebot.types), 40
- InlineQueryResultCachedAudio (class in telebot.types), 41
- InlineQueryResultCachedBase (class in telebot.types), 41
- InlineQueryResultCachedDocument (class in telebot.types), 41
- InlineQueryResultCachedGif (class in telebot.types), 42
- InlineQueryResultCachedMpeg4Gif (class in telebot.types), 43
- InlineQueryResultCachedPhoto (class in telebot.types), 43
- InlineQueryResultCachedSticker (class in telebot.types), 44
- InlineQueryResultCachedVideo (class in telebot.types), 45
- InlineQueryResultCachedVoice (class in telebot.types), 45
- InlineQueryResultContact (class in telebot.types), 46
- InlineQueryResultDocument (class in telebot.types), 47
- InlineQueryResultGame (class in telebot.types), 48
- InlineQueryResultGif (class in telebot.types), 48
- InlineQueryResultLocation (class in telebot.types), 49
- InlineQueryResultMpeg4Gif (class in telebot.types), 50
- InlineQueryResultPhoto (class in telebot.types), 51
- InlineQueryResultsButton (class in telebot.types), 54
- InlineQueryResultVenue (class in telebot.types), 52
- InlineQueryResultVideo (class in telebot.types), 53
- InlineQueryResultVoice (class in telebot.types), 53
- InputContactMessageContent (class in telebot.types), 55
- InputFile (class in telebot.types), 55
- InputInvoiceMessageContent (class in telebot.types), 56
- InputLocationMessageContent (class in telebot.types), 57
- InputMedia (class in telebot.types), 58
- InputMediaAnimation (class in telebot.types), 58
- InputMediaAudio (class in telebot.types), 59
- InputMediaDocument (class in telebot.types), 59
- InputMediaPhoto (class in telebot.types), 60
- InputMediaVideo (class in telebot.types), 61
- InputSticker (class in telebot.types), 61
- InputTextMessageContent (class in telebot.types), 62
- InputVenueMessageContent (class in telebot.types), 62
- Invoice (class in telebot.types), 63
- is_animated (telebot.types.StickerSet property), 88
- is_bytes() (in module telebot.util), 273
- is_command() (in module telebot.util), 273
- is_dict() (in module telebot.util), 273
- is_pil_image() (in module telebot.util), 273
- is_string() (in module telebot.util), 274
- is_video (telebot.types.StickerSet property), 88
- IsAdminFilter (class in telebot.asyncio_filters), 266
- IsAdminFilter (class in telebot.custom_filters), 181

IsDigitFilter (class in telebot.asyncio_filters), 266
 IsDigitFilter (class in telebot.custom_filters), 182
 IsReplyFilter (class in telebot.asyncio_filters), 266
 IsReplyFilter (class in telebot.custom_filters), 182

J

JsonDeserializable (class in telebot.types), 63
 JsonSerializerizable (class in telebot.types), 63

K

key (telebot.asyncio_filters.AdvancedCustomFilter attribute), 266
 key (telebot.asyncio_filters.ChatFilter attribute), 266
 key (telebot.asyncio_filters.ForwardFilter attribute), 266
 key (telebot.asyncio_filters.IsAdminFilter attribute), 266
 key (telebot.asyncio_filters.IsDigitFilter attribute), 266
 key (telebot.asyncio_filters.IsReplyFilter attribute), 267
 key (telebot.asyncio_filters.LanguageFilter attribute), 267
 key (telebot.asyncio_filters.SimpleCustomFilter attribute), 267
 key (telebot.asyncio_filters.StateFilter attribute), 267
 key (telebot.asyncio_filters.TextContainsFilter attribute), 268
 key (telebot.asyncio_filters.TextMatchFilter attribute), 268
 key (telebot.asyncio_filters.TextStartsFilter attribute), 268
 key (telebot.custom_filters.AdvancedCustomFilter attribute), 181
 key (telebot.custom_filters.ChatFilter attribute), 181
 key (telebot.custom_filters.ForwardFilter attribute), 181
 key (telebot.custom_filters.IsAdminFilter attribute), 181
 key (telebot.custom_filters.IsDigitFilter attribute), 182
 key (telebot.custom_filters.IsReplyFilter attribute), 182
 key (telebot.custom_filters.LanguageFilter attribute), 182
 key (telebot.custom_filters.SimpleCustomFilter attribute), 182
 key (telebot.custom_filters.StateFilter attribute), 183
 key (telebot.custom_filters.TextContainsFilter attribute), 183
 key (telebot.custom_filters.TextMatchFilter attribute), 184
 key (telebot.custom_filters.TextStartsFilter attribute), 184
 KeyboardButton (class in telebot.types), 63
 KeyboardButtonPollType (class in telebot.types), 64
 KeyboardButtonRequestChat (class in telebot.types), 65
 KeyboardButtonRequestUser (class in telebot.types), 66
 KeyboardButtonRequestUsers (class in telebot.types), 66

kick_chat_member() (telebot.async_telebot.AsyncTeleBot method), 216
 kick_chat_member() (telebot.TeleBot method), 131

L

LabeledPrice (class in telebot.types), 66
 LanguageFilter (class in telebot.asyncio_filters), 267
 LanguageFilter (class in telebot.custom_filters), 182
 leave_chat() (telebot.async_telebot.AsyncTeleBot method), 216
 leave_chat() (telebot.TeleBot method), 131
 LinkPreviewOptions (class in telebot.types), 67
 load_next_step_handlers() (telebot.TeleBot method), 131
 load_reply_handlers() (telebot.TeleBot method), 131
 Location (class in telebot.types), 67
 log_out() (telebot.async_telebot.AsyncTeleBot method), 217
 log_out() (telebot.TeleBot method), 132
 LoginUrl (class in telebot.types), 68

M

MaskPosition (class in telebot.types), 68
 max_row_keys (telebot.types.InlineKeyboardMarkup attribute), 38
 max_row_keys (telebot.types.ReplyKeyboardMarkup attribute), 83
 mbold() (in module telebot.formatting), 280
 mcite() (in module telebot.formatting), 280
 mcode() (in module telebot.formatting), 280
 MenuButton (class in telebot.types), 69
 MenuButtonCommands (class in telebot.types), 69
 MenuButtonDefault (class in telebot.types), 69
 MenuButtonWebApp (class in telebot.types), 69
 Message (class in telebot.types), 70
 message_handler() (telebot.async_telebot.AsyncTeleBot method), 217
 message_handler() (telebot.TeleBot method), 132
 message_reaction_count_handler() (telebot.async_telebot.AsyncTeleBot method), 218
 message_reaction_count_handler() (telebot.TeleBot method), 133
 message_reaction_handler() (telebot.async_telebot.AsyncTeleBot method), 218
 message_reaction_handler() (telebot.TeleBot method), 133
 MessageAutoDeleteTimerChanged (class in telebot.types), 75
 MessageEntity (class in telebot.types), 75
 MessageID (class in telebot.types), 75

- MessageOrigin (class in telebot.types), 76
 MessageOriginChannel (class in telebot.types), 76
 MessageOriginChat (class in telebot.types), 76
 MessageOriginHiddenUser (class in telebot.types), 76
 MessageOriginUser (class in telebot.types), 77
 MessageReactionCountUpdated (class in telebot.types), 77
 MessageReactionUpdated (class in telebot.types), 77
 middleware_handler() (telebot.TeleBot method), 133
 mitalic() (in module telebot.formatting), 280
 mlink() (in module telebot.formatting), 281
 module
 telebot, 98
 telebot.async_telebot, 186
 telebot.asyncio_filters, 265
 telebot.asyncio_handler_backends, 269
 telebot.callback_data, 270
 telebot.custom_filters, 181
 telebot.formatting, 276
 telebot.handler_backends, 184
 telebot.types, 3
 telebot.util, 271
 mspoiler() (in module telebot.formatting), 281
 mstrikethrough() (in module telebot.formatting), 281
 munderline() (in module telebot.formatting), 281
 my_chat_member_handler() (telebot.async_telebot.AsyncTeleBot method), 218
 my_chat_member_handler() (telebot.TeleBot method), 134
- ## N
- new() (telebot.callback_data.CallbackData method), 270
 new_chat_member (telebot.types.Message property), 74
- ## O
- OrderInfo (class in telebot.types), 78
- ## P
- parse() (telebot.callback_data.CallbackData method), 271
 parse_chat() (telebot.types.Message class method), 74
 parse_entities() (telebot.types.Game class method), 33
 parse_entities() (telebot.types.Message class method), 74
 parse_photo() (telebot.types.Game class method), 33
 parse_photo() (telebot.types.Message class method), 74
 parse_web_app_data() (in module telebot.util), 274
 PhotoSize (class in telebot.types), 78
 pil_image_to_file() (in module telebot.util), 274
 pin_chat_message() (telebot.async_telebot.AsyncTeleBot method), 218
 pin_chat_message() (telebot.TeleBot method), 134
 Poll (class in telebot.types), 78
 poll_answer_handler() (telebot.async_telebot.AsyncTeleBot method), 219
 poll_answer_handler() (telebot.TeleBot method), 134
 poll_handler() (telebot.async_telebot.AsyncTeleBot method), 219
 poll_handler() (telebot.TeleBot method), 134
 PollAnswer (class in telebot.types), 79
 polling() (telebot.async_telebot.AsyncTeleBot method), 219
 polling() (telebot.TeleBot method), 135
 PollOption (class in telebot.types), 80
 post_process() (telebot.asyncio_handler_backends.BaseMiddleware method), 269
 post_process() (telebot.handler_backends.BaseMiddleware method), 184
 pre_checkout_query_handler() (telebot.async_telebot.AsyncTeleBot method), 220
 pre_checkout_query_handler() (telebot.TeleBot method), 135
 pre_process() (telebot.asyncio_handler_backends.BaseMiddleware method), 269
 pre_process() (telebot.handler_backends.BaseMiddleware method), 185
 PreCheckoutQuery (class in telebot.types), 80
 process_new_updates() (telebot.async_telebot.AsyncTeleBot method), 220
 process_new_updates() (telebot.TeleBot method), 136
 promote_chat_member() (telebot.async_telebot.AsyncTeleBot method), 220
 promote_chat_member() (telebot.TeleBot method), 136
 ProximityAlertTriggered (class in telebot.types), 81
- ## Q
- quick_markup() (in module telebot.util), 274
- ## R
- ReactionCount (class in telebot.types), 81
 ReactionType (class in telebot.types), 81
 ReactionTypeCustomEmoji (class in telebot.types), 81
 ReactionTypeEmoji (class in telebot.types), 82
 register_business_connection_handler() (telebot.async_telebot.AsyncTeleBot method), 222

`register_business_connection_handler()` (*telebot.TeleBot* method), 137
`register_business_message_handler()` (*telebot.async_telebot.AsyncTeleBot* method), 222
`register_business_message_handler()` (*telebot.TeleBot* method), 137
`register_callback_query_handler()` (*telebot.async_telebot.AsyncTeleBot* method), 222
`register_callback_query_handler()` (*telebot.TeleBot* method), 138
`register_channel_post_handler()` (*telebot.async_telebot.AsyncTeleBot* method), 223
`register_channel_post_handler()` (*telebot.TeleBot* method), 138
`register_chat_boost_handler()` (*telebot.async_telebot.AsyncTeleBot* method), 223
`register_chat_boost_handler()` (*telebot.TeleBot* method), 138
`register_chat_join_request_handler()` (*telebot.async_telebot.AsyncTeleBot* method), 223
`register_chat_join_request_handler()` (*telebot.TeleBot* method), 138
`register_chat_member_handler()` (*telebot.async_telebot.AsyncTeleBot* method), 223
`register_chat_member_handler()` (*telebot.TeleBot* method), 139
`register_chosen_inline_handler()` (*telebot.async_telebot.AsyncTeleBot* method), 224
`register_chosen_inline_handler()` (*telebot.TeleBot* method), 139
`register_deleted_business_messages_handler()` (*telebot.async_telebot.AsyncTeleBot* method), 224
`register_deleted_business_messages_handler()` (*telebot.TeleBot* method), 139
`register_edited_business_message_handler()` (*telebot.async_telebot.AsyncTeleBot* method), 224
`register_edited_business_message_handler()` (*telebot.TeleBot* method), 140
`register_edited_channel_post_handler()` (*telebot.async_telebot.AsyncTeleBot* method), 225
`register_edited_channel_post_handler()` (*telebot.TeleBot* method), 140
`register_edited_message_handler()` (*telebot.async_telebot.AsyncTeleBot* method), 225
`register_edited_message_handler()` (*telebot.TeleBot* method), 140
`register_for_reply()` (*telebot.TeleBot* method), 141
`register_for_reply_by_message_id()` (*telebot.TeleBot* method), 141
`register_inline_handler()` (*telebot.async_telebot.AsyncTeleBot* method), 226
`register_inline_handler()` (*telebot.TeleBot* method), 141
`register_message_handler()` (*telebot.async_telebot.AsyncTeleBot* method), 226
`register_message_handler()` (*telebot.TeleBot* method), 142
`register_message_reaction_count_handler()` (*telebot.async_telebot.AsyncTeleBot* method), 226
`register_message_reaction_count_handler()` (*telebot.TeleBot* method), 142
`register_message_reaction_handler()` (*telebot.async_telebot.AsyncTeleBot* method), 227
`register_message_reaction_handler()` (*telebot.TeleBot* method), 142
`register_middleware_handler()` (*telebot.TeleBot* method), 143
`register_my_chat_member_handler()` (*telebot.async_telebot.AsyncTeleBot* method), 227
`register_my_chat_member_handler()` (*telebot.TeleBot* method), 143
`register_next_step_handler()` (*telebot.TeleBot* method), 143
`register_next_step_handler_by_chat_id()` (*telebot.TeleBot* method), 144
`register_poll_answer_handler()` (*telebot.async_telebot.AsyncTeleBot* method), 227
`register_poll_answer_handler()` (*telebot.TeleBot* method), 144
`register_poll_handler()` (*telebot.async_telebot.AsyncTeleBot* method), 227
`register_poll_handler()` (*telebot.TeleBot* method), 144
`register_pre_checkout_query_handler()` (*telebot.async_telebot.AsyncTeleBot* method), 228
`register_pre_checkout_query_handler()` (*telebot.TeleBot* method), 144
`register_removed_chat_boost_handler()` (*telebot.async_telebot.AsyncTeleBot* method), 228

- 228
 - register_removed_chat_boost_handler() (*telebot.TeleBot* method), 145
 - register_shipping_query_handler() (*telebot.async_telebot.AsyncTeleBot* method), 228
 - register_shipping_query_handler() (*telebot.TeleBot* method), 145
 - remove_webhook() (*telebot.async_telebot.AsyncTeleBot* method), 228
 - remove_webhook() (*telebot.TeleBot* method), 145
 - removed_chat_boost_handler() (*telebot.async_telebot.AsyncTeleBot* method), 229
 - removed_chat_boost_handler() (*telebot.TeleBot* method), 145
 - reopen_forum_topic() (*telebot.async_telebot.AsyncTeleBot* method), 229
 - reopen_forum_topic() (*telebot.TeleBot* method), 146
 - reopen_general_forum_topic() (*telebot.async_telebot.AsyncTeleBot* method), 229
 - reopen_general_forum_topic() (*telebot.TeleBot* method), 146
 - replace_sticker_in_set() (*telebot.async_telebot.AsyncTeleBot* method), 229
 - replace_sticker_in_set() (*telebot.TeleBot* method), 146
 - REPLY_MARKUP_TYPES (in module *telebot*), 98
 - reply_to() (*telebot.async_telebot.AsyncTeleBot* method), 230
 - reply_to() (*telebot.TeleBot* method), 146
 - ReplyKeyboardMarkup (class in *telebot.types*), 82
 - ReplyKeyboardRemove (class in *telebot.types*), 83
 - ReplyParameters (class in *telebot.types*), 84
 - reset_data() (*telebot.async_telebot.AsyncTeleBot* method), 230
 - reset_data() (*telebot.TeleBot* method), 147
 - restrict_chat_member() (*telebot.async_telebot.AsyncTeleBot* method), 230
 - restrict_chat_member() (*telebot.TeleBot* method), 147
 - retrieve_data() (*telebot.async_telebot.AsyncTeleBot* method), 231
 - retrieve_data() (*telebot.TeleBot* method), 148
 - revoke_chat_invite_link() (*telebot.async_telebot.AsyncTeleBot* method), 231
 - revoke_chat_invite_link() (*telebot.TeleBot* method), 148
 - row() (*telebot.types.InlineKeyboardMarkup* method), 38
 - row() (*telebot.types.ReplyKeyboardMarkup* method), 83
 - run_webhooks() (*telebot.async_telebot.AsyncTeleBot* method), 232
 - run_webhooks() (*telebot.TeleBot* method), 148
- ## S
- send_animation() (*telebot.async_telebot.AsyncTeleBot* method), 232
 - send_animation() (*telebot.TeleBot* method), 149
 - send_audio() (*telebot.async_telebot.AsyncTeleBot* method), 234
 - send_audio() (*telebot.TeleBot* method), 150
 - send_chat_action() (*telebot.async_telebot.AsyncTeleBot* method), 235
 - send_chat_action() (*telebot.TeleBot* method), 152
 - send_contact() (*telebot.async_telebot.AsyncTeleBot* method), 236
 - send_contact() (*telebot.TeleBot* method), 152
 - send_dice() (*telebot.async_telebot.AsyncTeleBot* method), 237
 - send_dice() (*telebot.TeleBot* method), 153
 - send_document() (*telebot.async_telebot.AsyncTeleBot* method), 238
 - send_document() (*telebot.TeleBot* method), 154
 - send_game() (*telebot.async_telebot.AsyncTeleBot* method), 239
 - send_game() (*telebot.TeleBot* method), 155
 - send_invoice() (*telebot.async_telebot.AsyncTeleBot* method), 240
 - send_invoice() (*telebot.TeleBot* method), 156
 - send_location() (*telebot.async_telebot.AsyncTeleBot* method), 241
 - send_location() (*telebot.TeleBot* method), 158
 - send_media_group() (*telebot.async_telebot.AsyncTeleBot* method), 243
 - send_media_group() (*telebot.TeleBot* method), 159
 - send_message() (*telebot.async_telebot.AsyncTeleBot* method), 243
 - send_message() (*telebot.TeleBot* method), 160
 - send_photo() (*telebot.async_telebot.AsyncTeleBot* method), 245
 - send_photo() (*telebot.TeleBot* method), 161
 - send_poll() (*telebot.async_telebot.AsyncTeleBot* method), 246
 - send_poll() (*telebot.TeleBot* method), 162
 - send_sticker() (*telebot.async_telebot.AsyncTeleBot* method), 247
 - send_sticker() (*telebot.TeleBot* method), 163
 - send_venue() (*telebot.async_telebot.AsyncTeleBot* method), 248
 - send_venue() (*telebot.TeleBot* method), 164

send_video() (*telebot.async_telebot.AsyncTeleBot method*), 249
 send_video() (*telebot.TeleBot method*), 165
 send_video_note() (*telebot.async_telebot.AsyncTeleBot method*), 250
 send_video_note() (*telebot.TeleBot method*), 166
 send_voice() (*telebot.async_telebot.AsyncTeleBot method*), 252
 send_voice() (*telebot.TeleBot method*), 167
 SentWebAppMessage (*class in telebot.types*), 85
 set_chat_administrator_custom_title() (*telebot.async_telebot.AsyncTeleBot method*), 253
 set_chat_administrator_custom_title() (*telebot.TeleBot method*), 168
 set_chat_description() (*telebot.async_telebot.AsyncTeleBot method*), 253
 set_chat_description() (*telebot.TeleBot method*), 169
 set_chat_menu_button() (*telebot.async_telebot.AsyncTeleBot method*), 253
 set_chat_menu_button() (*telebot.TeleBot method*), 169
 set_chat_permissions() (*telebot.async_telebot.AsyncTeleBot method*), 254
 set_chat_permissions() (*telebot.TeleBot method*), 169
 set_chat_photo() (*telebot.async_telebot.AsyncTeleBot method*), 254
 set_chat_photo() (*telebot.TeleBot method*), 170
 set_chat_sticker_set() (*telebot.async_telebot.AsyncTeleBot method*), 254
 set_chat_sticker_set() (*telebot.TeleBot method*), 170
 set_chat_title() (*telebot.async_telebot.AsyncTeleBot method*), 255
 set_chat_title() (*telebot.TeleBot method*), 170
 set_custom_emoji_sticker_set_thumbnail() (*telebot.async_telebot.AsyncTeleBot method*), 255
 set_custom_emoji_sticker_set_thumbnail() (*telebot.TeleBot method*), 171
 set_game_score() (*telebot.async_telebot.AsyncTeleBot method*), 255
 set_game_score() (*telebot.TeleBot method*), 171
 set_message_reaction() (*telebot.async_telebot.AsyncTeleBot method*), 256
 set_message_reaction() (*telebot.TeleBot method*), 171
 set_my_commands() (*telebot.async_telebot.AsyncTeleBot method*), 256
 set_my_commands() (*telebot.TeleBot method*), 172
 set_my_default_administrator_rights() (*telebot.async_telebot.AsyncTeleBot method*), 257
 set_my_default_administrator_rights() (*telebot.TeleBot method*), 172
 set_my_description() (*telebot.async_telebot.AsyncTeleBot method*), 257
 set_my_description() (*telebot.TeleBot method*), 173
 set_my_name() (*telebot.async_telebot.AsyncTeleBot method*), 257
 set_my_name() (*telebot.TeleBot method*), 173
 set_my_short_description() (*telebot.async_telebot.AsyncTeleBot method*), 258
 set_my_short_description() (*telebot.TeleBot method*), 173
 set_state() (*telebot.async_telebot.AsyncTeleBot method*), 258
 set_state() (*telebot.TeleBot method*), 173
 set_sticker_emoji_list() (*telebot.async_telebot.AsyncTeleBot method*), 258
 set_sticker_emoji_list() (*telebot.TeleBot method*), 174
 set_sticker_keywords() (*telebot.async_telebot.AsyncTeleBot method*), 258
 set_sticker_keywords() (*telebot.TeleBot method*), 174
 set_sticker_mask_position() (*telebot.async_telebot.AsyncTeleBot method*), 259
 set_sticker_mask_position() (*telebot.TeleBot method*), 174
 set_sticker_position_in_set() (*telebot.async_telebot.AsyncTeleBot method*), 259
 set_sticker_position_in_set() (*telebot.TeleBot method*), 175
 set_sticker_set_thumb() (*telebot.async_telebot.AsyncTeleBot method*), 259
 set_sticker_set_thumb() (*telebot.TeleBot method*), 175
 set_sticker_set_thumbnail() (*telebot.async_telebot.AsyncTeleBot method*), 259
 set_sticker_set_thumbnail() (*telebot.TeleBot method*), 175

- method*), 175
 - set_sticker_set_title() (*telebot.async_telebot.AsyncTeleBot method*), 260
 - set_sticker_set_title() (*telebot.TeleBot method*), 175
 - set_update_listener() (*telebot.async_telebot.AsyncTeleBot method*), 260
 - set_update_listener() (*telebot.TeleBot method*), 176
 - set_webhook() (*telebot.async_telebot.AsyncTeleBot method*), 260
 - set_webhook() (*telebot.TeleBot method*), 176
 - setup_middleware() (*telebot.async_telebot.AsyncTeleBot method*), 261
 - setup_middleware() (*telebot.TeleBot method*), 177
 - SharedUser (*class in telebot.types*), 85
 - shipping_query_handler() (*telebot.async_telebot.AsyncTeleBot method*), 261
 - shipping_query_handler() (*telebot.TeleBot method*), 177
 - ShippingAddress (*class in telebot.types*), 85
 - ShippingOption (*class in telebot.types*), 86
 - ShippingQuery (*class in telebot.types*), 86
 - SimpleCustomFilter (*class in telebot.asyncio_filters*), 267
 - SimpleCustomFilter (*class in telebot.custom_filters*), 182
 - skip_updates() (*telebot.async_telebot.AsyncTeleBot method*), 262
 - SkipHandler (*class in telebot.asyncio_handler_backends*), 270
 - SkipHandler (*class in telebot.handler_backends*), 185
 - smart_split() (*in module telebot.util*), 275
 - split_string() (*in module telebot.util*), 275
 - State (*class in telebot.asyncio_handler_backends*), 270
 - State (*class in telebot.handler_backends*), 185
 - state_list() (*telebot.asyncio_handler_backends.StatesGroup class method*), 270
 - state_list() (*telebot.handler_backends.StatesGroup class method*), 185
 - StateFilter (*class in telebot.asyncio_filters*), 267
 - StateFilter (*class in telebot.custom_filters*), 183
 - StatesGroup (*class in telebot.asyncio_handler_backends*), 270
 - StatesGroup (*class in telebot.handler_backends*), 185
 - Sticker (*class in telebot.types*), 87
 - StickerSet (*class in telebot.types*), 88
 - stop_bot() (*telebot.TeleBot method*), 177
 - stop_message_live_location() (*telebot.async_telebot.AsyncTeleBot method*), 262
 - stop_message_live_location() (*telebot.TeleBot method*), 177
 - stop_poll() (*telebot.async_telebot.AsyncTeleBot method*), 262
 - stop_poll() (*telebot.TeleBot method*), 178
 - stop_polling() (*telebot.TeleBot method*), 178
 - Story (*class in telebot.types*), 88
 - SuccessfulPayment (*class in telebot.types*), 88
 - SwitchInlineQueryChosenChat (*class in telebot.types*), 89
- ## T
- telebot
 - module, 98
 - TeleBot (*class in telebot*), 99
 - telebot.async_telebot
 - module, 186
 - telebot.asyncio_filters
 - module, 265
 - telebot.asyncio_handler_backends
 - module, 269
 - telebot.callback_data
 - module, 270
 - telebot.custom_filters
 - module, 181
 - telebot.formatting
 - module, 276
 - telebot.handler_backends
 - module, 184
 - telebot.types
 - module, 3
 - telebot.util
 - module, 271
 - TextContainsFilter (*class in telebot.asyncio_filters*), 267
 - TextContainsFilter (*class in telebot.custom_filters*), 183
 - TextFilter (*class in telebot.asyncio_filters*), 268
 - TextFilter (*class in telebot.custom_filters*), 183
 - TextMatchFilter (*class in telebot.asyncio_filters*), 268
 - TextMatchFilter (*class in telebot.custom_filters*), 183
 - TextQuote (*class in telebot.types*), 89
 - TextStartsFilter (*class in telebot.asyncio_filters*), 268
 - TextStartsFilter (*class in telebot.custom_filters*), 184
 - thumb (*telebot.types.Animation property*), 4
 - thumb (*telebot.types.Audio property*), 5
 - thumb (*telebot.types.Document property*), 29
 - thumb (*telebot.types.InputMediaAnimation property*), 59
 - thumb (*telebot.types.InputMediaAudio property*), 59
 - thumb (*telebot.types.InputMediaDocument property*), 60
 - thumb (*telebot.types.InputMediaVideo property*), 61
 - thumb (*telebot.types.Sticker property*), 88
 - thumb (*telebot.types.StickerSet property*), 88

- thumb (*telebot.types.Video* property), 95
thumb (*telebot.types.VideoNote* property), 96
thumb_height (*telebot.types.InlineQueryResultArticle* property), 39
thumb_height (*telebot.types.InlineQueryResultContact* property), 47
thumb_height (*telebot.types.InlineQueryResultDocument* property), 48
thumb_height (*telebot.types.InlineQueryResultLocation* property), 50
thumb_height (*telebot.types.InlineQueryResultVenue* property), 52
thumb_mime_type (*telebot.types.InlineQueryResultGif* property), 49
thumb_mime_type (*telebot.types.InlineQueryResultMpeg4Gif* property), 51
thumb_url (*telebot.types.InlineQueryResultArticle* property), 39
thumb_url (*telebot.types.InlineQueryResultContact* property), 47
thumb_url (*telebot.types.InlineQueryResultDocument* property), 48
thumb_url (*telebot.types.InlineQueryResultGif* property), 49
thumb_url (*telebot.types.InlineQueryResultLocation* property), 50
thumb_url (*telebot.types.InlineQueryResultMpeg4Gif* property), 51
thumb_url (*telebot.types.InlineQueryResultPhoto* property), 52
thumb_url (*telebot.types.InlineQueryResultVenue* property), 52
thumb_url (*telebot.types.InlineQueryResultVideo* property), 53
thumb_width (*telebot.types.InlineQueryResultArticle* property), 39
thumb_width (*telebot.types.InlineQueryResultContact* property), 47
thumb_width (*telebot.types.InlineQueryResultDocument* property), 48
thumb_width (*telebot.types.InlineQueryResultLocation* property), 50
thumb_width (*telebot.types.InlineQueryResultVenue* property), 52
to_list_of_dicts() (*telebot.types.MessageEntity* static method), 75
- ## U
- unban_chat_member() (*telebot.async_telebot.AsyncTeleBot* method), 263
unban_chat_member() (*telebot.TeleBot* method), 178
unban_chat_sender_chat() (*telebot.async_telebot.AsyncTeleBot* method), 263
unban_chat_sender_chat() (*telebot.TeleBot* method), 178
unhide_general_forum_topic() (*telebot.async_telebot.AsyncTeleBot* method), 263
unhide_general_forum_topic() (*telebot.TeleBot* method), 179
unpin_all_chat_messages() (*telebot.async_telebot.AsyncTeleBot* method), 263
unpin_all_chat_messages() (*telebot.TeleBot* method), 179
unpin_all_forum_topic_messages() (*telebot.async_telebot.AsyncTeleBot* method), 264
unpin_all_forum_topic_messages() (*telebot.TeleBot* method), 179
unpin_all_general_forum_topic_messages() (*telebot.async_telebot.AsyncTeleBot* method), 264
unpin_all_general_forum_topic_messages() (*telebot.TeleBot* method), 179
unpin_chat_message() (*telebot.async_telebot.AsyncTeleBot* method), 264
unpin_chat_message() (*telebot.TeleBot* method), 180
Update (class in *telebot.types*), 90
update_sensitive (*telebot.asyncio_handler_backends.BaseMiddleware* attribute), 269
update_sensitive (*telebot.handler_backends.BaseMiddleware* attribute), 185
update_types (in module *telebot.util*), 275
upload_sticker_file() (*telebot.async_telebot.AsyncTeleBot* method), 264
upload_sticker_file() (*telebot.TeleBot* method), 180
User (class in *telebot.types*), 92
user (*telebot.async_telebot.AsyncTeleBot* property), 265
user (*telebot.TeleBot* property), 180
user_id (*telebot.types.UsersShared* property), 93
user_link() (in module *telebot.util*), 275
user_shared (*telebot.types.Message* property), 74
UserChatBoosts (class in *telebot.types*), 92
UserProfilePhotos (class in *telebot.types*), 93
UsersShared (class in *telebot.types*), 93
- ## V
- validate_web_app_data() (in module *telebot.util*), 276

Venue (*class in telebot.types*), 93
Video (*class in telebot.types*), 94
VideoChatEnded (*class in telebot.types*), 95
VideoChatParticipantsInvited (*class in telebot.types*), 95
VideoChatScheduled (*class in telebot.types*), 95
VideoChatStarted (*class in telebot.types*), 95
VideoNote (*class in telebot.types*), 95
Voice (*class in telebot.types*), 96
voice_chat_ended (*telebot.types.Message* property), 74
voice_chat_participants_invited (*telebot.types.Message* property), 74
voice_chat_scheduled (*telebot.types.Message* property), 74
voice_chat_started (*telebot.types.Message* property), 74
VoiceChatEnded (*class in telebot.types*), 96
VoiceChatParticipantsInvited (*class in telebot.types*), 96
VoiceChatScheduled (*class in telebot.types*), 96
VoiceChatStarted (*class in telebot.types*), 97

W

WebAppData (*class in telebot.types*), 97
WebAppInfo (*class in telebot.types*), 97
webhook_google_functions() (*in module telebot.util*), 276
WebhookInfo (*class in telebot.types*), 97
WriteAccessAllowed (*class in telebot.types*), 98